OKE lab completion sheet

Record core observations; leave optional HPA sections blank if skipped.

Keep credentials, kubeconfig contents, and tokens out of this sheet.

Name: _____ Date: _____ Tested repository revision: _____

Core success checks

- ☐ Preflight passed for my cluster's current context; two workers are Ready with numeric resource metrics.
- ☐ My public app returned my customized message; two app pods showed 2/2 Ready.
- ☐ I identified web and istio-proxy and found hello-oke-traffic -> hello-oke in Kiali.
- ☐ Manual scaling changed app replicas 2 -> 4 -> 2; worker count and Service IP stayed unchanged.

My customized response message:

Core observations

Use Grafana's Last 30 minutes range and p95 latency for each row. Use kubectl -n oke-lab get pods -l app=hello-oke for Ready app pods. Proxy count can lag and does not measure readiness. Record no data for an empty panel. HPA stays disabled in the core lab.

Phase	Ready app pods	Requests/s	Success %	p95 latency (ms)	App proxies up
Baseline (2 replicas)	___	___	___	___	___
Manual (4 replicas)	___	___	___	___	___
Restored (2 replicas)	___	___	___	___	___

The baseline generator keeps the same request interval during manual scaling; more replicas do not create more traffic. Your manual curl requests may briefly increase the observed rate.

Optional HPA observations - not required

HPA extension: skipped / completed / blocked. Leave this section blank if skipped; it is not required for core completion. Run kubectl -n oke-lab get hpa hello-oke only after enabling HPA in step 6.

Phase	HPA replicas / Ready app pods	Requests/s	Success %	p95 latency (ms)	App proxies up
HPA baseline (/)	___ / ___	___	___	___	___
During load (/work)	___ / ___	___	___	___	___
After scale-in (/)	___ / ___	___	___	___	___

OKE lab completion sheet

Core debrief and optional extension notes.

Name: _____ Date: _____

Core debrief

Review these three questions on your own using your lab observations:

1. What changed when you scaled from two to four pods?

My evidence (question 1): App pods before/during/after: ____ / ____ / ____

Worker names: _____ Service IP before/after: _____

2. How do Kiali and Grafana help you understand the application?

My evidence (question 2): Kiali traffic edge: _____ Grafana metric/value: _____

3. What is the difference between a pod and a worker node?

Optional HPA final checks

- ☐ HPA CPU utilization became numeric before load.
- ☐ I observed scale-out above two and scale-in back to two Ready app pods.
- ☐ I explicitly reset traffic.loadEnabled=false, even if the extension was interrupted.

Peak HPA replica count observed: ___ Time load started: ___ Time scale-in finished: ___

Six replicas is a limit, not a required peak. The two endpoints do different work; this comparison does not isolate autoscaling's effect on latency.

HPA scale-in: Final HPA replicas: ____ Ready app pods: ____ Load reset: _____

Optional pod recovery

Pod recovery: skipped / completed / blocked. HPA is not a prerequisite.

Recovery evidence: Old/new pod names: _____ Service IP before/after: _____

Core result: completed / needs instructor help / demonstration only. Skipped extensions do not affect this result.

If blocked, record the step, symptom, and last observed state:

Leave releases for Luna's cleanup. Reset any HPA burst before leaving. Stop watches and port-forwards; these do not stop in-cluster traffic. Report unfinished steps to the instructor.