


Note:

PIO\_A7 is used for PHY interrupt.

PIO\_C13 is used for 5V detection when plugged into a USB host port.

ſ			Ethernet 10/100 & DBGU/Serial				
			& USB Host/Device				
	TITLE		GPLv3				
	FILE:			REVISION:			
	PAGE	OF		DRAWN BY:	Saritha Kalyanam		



Note:

Clock: TK0 and RK0 are connected together, with RK0 configured as an input. FSYNC: TF0 and RF0 are connected together, with RF0 configured as an input.

TITLE		SSC interface (for GPLv3	or FXS Si321x)	
FILE:			REVISION:	Saritha Kalyanam
PAGE	OF		DRAWN BY:	


AT91SAM9260	U1			
	PA4/RTS2/MCDB2	183	SW1	
	PA5/CTS2/MCDB1	184	SW2	
P	B28/RTS1/ISI_PCK	175	LED1	
PB2	9/CTS1/ISI_VSYNC	176	LED2	/

TITLE		User Interface (LEDs and Interrupts) GPLv3			
FILE:		REVISION:			
PAGE	OF		DRAWN BY:	Saritha Kalyanam	


U1 AT91SAM9260 185 PA6/MCDA0 NC 185 PA6/MCDA0
189 PA8/MCCK
190 PA9/MCDA1
1 PA24/TWCK/ETX3
17 PB6/TXD1/TCLK1
18 PB7/RXD1/TCLK2
19 PB8/TXD2
20 PB9/RXD2
161 PB10/TXD3/ISL\_D8 PB30/PCK0/ISI\_HSYNC 177 PB31/PCK1/ISI\_MCK 178 NRD/CFOE 069
NWR0/NWE/CFWE 070 NWR0/NWE/CFWE 0/0
NCS0 0/68
A12 0/55
A15 0/72
A18 0/76
A20 0/75
PC5/A24/SPI1\_NPCS1 67 162 PB11/RXD3/ISI\_D9 165 PB22/DSR0/ISI\_D2 166 PB23/CDC0/ISI\_D3 167 PB24/DTR0/ISI\_D4 168 PB25/RI0/ISI\_D5 158 PC0 159 PC1 62 PC4/A23/SPI1\_NPCS2 63 PC6/TIOB2/CFCE1 64 PC7/TIOB1/CFCE2 61 PC8/NCS4/CFCS0/RTS3 60 PC9/NCS5/CFCS1/TIOB0 58 PC10/A25/CFRNW/CTS3

127 PC15/NWAIT/IRQ1


TITLE		Unconnected GPLv3	pins	
FILE:			REVISION:	
PAGE	OF		DRAWN BY:	Saritha Kalyanam












JTAG/ICE interfa			ace	
FILE:			REVISION:	
PAGE	OF		DRAWN BY:	Saritha Kalyanam



TITLE		SDRAM 32 MB (16-bit m	node)		
FILE:			REVISION:	Saritha Kalyanam	
PAGE	OF		DRAWN BY:	GPLv3	







		UI		
TITLE		GPLv3		
FILE:			REVISION:	Saritha Kalyanam
PAGE	OF		DRAWN BY:	

