








AT91SAM9260 based Telephone ATA Design (GPL v3)		
TITLE		
FILE:		REVISION:
PAGE	OF	DRAWN BY: Saritha Kalyanam




Power		
GPLv3		
TITLE		
FILE:		REVISION:
PAGE	OF	Saritha Kalyanam
		DRAWN BY:



Clock and JTAG/ICE		
GPLv3		
TITLE		
FILE:		REVISION:
PAGE	OF	Saritha Kalyanam
		DRAWN BY:




SDRAM & NAND flash	
GPLv3	
TITLE	
FILE:	REVISION:
PAGE	DRAWN BY: Sariitha Kalyanam



AT91SAM9260


U?



TITLE			SSC interface (for FXS Si321x) GPLv3		
FILE:		REVISION:		Saritha Kalyanam	
PAGE		OF		DRAWN BY:	

AT91SAM9260

U?




TITLE		User Interface (LEDs and Interrupts)	
FILE:		REVISION:	
PAGE		DRAWN BY:	
OF		Saritha Kalyanam	
		GPLv3	


U?

AT91SAM9260		
183	PA4/RTS2/MCDB2	NC 152
184	PA5/CTS2/MCDB1	NRD/CFOE 69
185	PA6/MCDA0	NWR0/NWE/CFWE 70
208	PA23/TWD/ETX2	NCS0 68
1	PA24/TWCK/ETX3	A12 85
17	PB6/TXD1/TCLK1	A15 82
18	PB7/RXD1/TCLK2	A18 79
19	PB8/TXD2	A19 76
20	PB9/RXD2	A20 75
161	PB10/TXD3/ISL_D8	
162	PB11/RXD3/ISL_D9	
165	PB22/DSR0/ISL_D2	
166	PB23/CDC0/ISL_D3	
167	PB24/DTR0/ISL_D4	
168	PB25/RIO/ISL_D5	
175	PB28/RTS1/ISL_PCK	
176	PB29/CTS1/ISL_VSYNC	
158	PC0	
159	PC1	
62	PC4/A23/SPI1_NPCS2	
63	PC6/TIOB2/CFCE1	
64	PC7/TIOB1/CFCE2	
61	PC8/NCS4/CFCS0/RTS3	
60	PC9/NCS5/CFCS1/TIOB0	
58	PC10/A25/CFRNW/CTS3	
57	PC11/NCS2/SPI0_NPCS1	
127	PC15/NWAIT/IRQ1	


Unconnected pins		
GPLv3		
TITLE		
FILE:	REVISION:	
PAGE	OF	Saritha Kalyanam
		DRAWN BY:




Ethernet 10/100 GPLv3		
TITLE		
FILE:		REVISION:
PAGE	OF	DRAWN BY: Sariitha Kalyanam




TITLE			SPI Dataflash (128KB) and NAND Flash (32MB)		
FILE:			GPLv3		
PAGE			OF		
REVISION:			DRAWN BY: Saritha Kalyanam		








TITLE		JTAG/ICE interface GPLv3	
FILE:		REVISION:	
PAGE	OF	DRAWN BY:	Saritha Kalyanam




TITLE		SDRAM 32 MB (16-bit mode)	
FILE:		REVISION:	Saritha Kalyanam
PAGE	OF	DRAWN BY:	GPLv3





SDRAM			
32 MB (32-bit mode)			
TITLE			
FILE:			REVISION: Saritha Kalyanam
PAGE	OF		DRAWN BY: GPLv3




Power Supply		
GPLv3		
TITLE		
FILE:		REVISION:
PAGE	OF	DRAWN BY: Saritha Kalyanam







Serial Port (RS232 and DBGU)		
GPL v3		
TITLE		
FILE:		REVISION:
PAGE	OF	DRAWN BY: Sariitha Kalyanam



TITLE		UI GPLv3	
FILE:		REVISION:	Saritha Kalyanam
PAGE	OF	DRAWN BY:	



USB Host and Device	
GPLv3	
TITLE	
FILE:	REVISION:
PAGE	OF
	Saritha Kalyanam
	DRAWN BY:



USB Host and Device		
GPLv3		
TITLE		
FILE:		REVISION: Saritha Kalyanam
PAGE	OF	DRAWN BY: