




|  |    |                            |
|--|----|----------------------------|
| AT91SAM9260 based Telephone ATA Design<br>(GPL v3) |    |                            |
| TITLE  |    |                            |
| FILE:  |    | REVISION:                  |
| PAGE   | OF | DRAWN BY: Saritha Kalyanam |




|       |    |                |                  |
|-------|----|----------------|------------------|
| TITLE |    | Power<br>GPLv3 |                  |
| FILE: |    | REVISION:      | Saritha Kalyanam |
| PAGE  | OF | DRAWN BY:      |                  |



Note:

REMAP=0, BMS=1 to boot using AT91SAM9260's internal ROM boot program.  
 OSCSEL=1, external slow clock (32.768 KHz)

| Clock and JTAG/ICE |                  |
|--------------------|------------------|
| GPLv3              |                  |
| TITLE              |                  |
| FILE:              | REVISION:        |
| PAGE               | OF               |
| DRAWN BY:          | Saritha Kalyanam |




Note:

PIO\_C11 is used for RDY\_BSY interrupt from the NAND flash.

| SDRAM & Serial SPI Data flash & NAND flash |    |           |                  |
|--|----|-----------|------------------|
| GPLv3                                      |    |           |                  |
| TITLE                                      |    |           |                  |
| FILE:                                      |    |           | REVISION:        |
| PAGE                                       | OF | DRAWN BY: | Saritha Kalyanam |


AT91SAM9260

U1




AT91SAM9260

U1



AT91SAM9260

U1



Note:

PIO\_A7 is used for PHY interrupt.

PIO\_C13 is used for 5V detection when plugged into a USB host port.

Ethernet 10/100 & DBGU/Serial  
& USB Host/Device

TITLE

GPLv3

FILE:


REVISION:

PAGE

OF

DRAWN BY:

Saritha Kalyanam




Note:

Clock: TK0 and RK0 are connected together, with RK0 configured as an input.  
FSYNC: TF0 and RF0 are connected together, with RF0 configured as an input.

|       |    |   |                  |
|-------|----|---|------------------|
| TITLE |    | SSC interface (for FXS Si321x)<br>GPLv3 |                  |
| FILE: |    | REVISION:                               | Saritha Kalyanam |
| PAGE  | OF | DRAWN BY:                               |                  |

AT91SAM9260

U1




|       |  |                                      |  |
|-------|--|--------------------------------------|--|
| TITLE |  | User Interface (LEDs and Interrupts) |  |
| FILE: |  | REVISION:                            |  |
| PAGE  |  | DRAWN BY:                            |  |
| OF    |  | Saritha Kalyanam                     |  |
| GPLv3 |  |                                      |  |



|                  |                            |
|------------------|----------------------------|
| Unconnected pins |                            |
| GPLv3            |                            |
| TITLE            |                            |
| FILE:            | REVISION:                  |
| PAGE             | DRAWN BY: Saritha Kalyanam |
| OF               |                            |







|                 |    |                             |
|-----------------|----|-----------------------------|
| Ethernet 10/100 |    |                             |
| GPLv3           |    |                             |
| TITLE           |    |                             |
| FILE:           |    | REVISION:                   |
| PAGE            | OF | DRAWN BY: Sariitha Kalyanam |




|       |  |  |   |                            |
|-------|--|--|---|----------------------------|
| TITLE |  |  | SPI Dataflash (128KB) and NAND Flash (32MB) |                            |
| FILE: |  |  | GPLv3                                       |                            |
| PAGE  |  |  | OF  | REVISION:                  |
|       |  |  |   | DRAWN BY: Saritha Kalyanam |







|       |    |                         |                  |
|-------|----|-------------------------|------------------|
| TITLE |    | Mounting holes<br>GPLv3 |                  |
| FILE: |    | REVISION:               | Saritha Kalyanam |
| PAGE  | OF | DRAWN BY:               |                  |




|       |    |                             |                  |
|-------|----|-----------------------------|------------------|
| TITLE |    | JTAG/ICE interface<br>GPLv3 |                  |
| FILE: |    | REVISION:                   |                  |
| PAGE  | OF | DRAWN BY:                   | Saritha Kalyanam |



|       |    |                              |                  |
|-------|----|------------------------------|------------------|
| TITLE |    | SDRAM<br>32 MB (16-bit mode) |                  |
| FILE: |    | REVISION:                    | Saritha Kalyanam |
| PAGE  | OF | DRAWN BY:                    | GPLv3            |










|       |    |             |                  |
|-------|----|-------------|------------------|
| TITLE |    | UI<br>GPLv3 |                  |
| FILE: |    | REVISION:   | Saritha Kalyanam |
| PAGE  | OF | DRAWN BY:   |                  |



|                     |                  |
|---------------------|------------------|
| USB Host and Device |                  |
| GPLv3               |                  |
| TITLE               |                  |
| FILE:               | REVISION:        |
| PAGE                | OF               |
|                     | Saritha Kalyanam |
|                     | DRAWN BY:        |