





AT91SAM9260 based Telephone ATA Design (GPL v3)		
FILE:		REVISION:
PAGE	OF	DRAWN BY: Saritha Kalyanam



Power		
GPLv3		
TITLE		
FILE:	REVISION:	Saritha Kalyanam
PAGE	OF	DRAWN BY:



Note:

REMAP=0, BMS=1 to boot using AT91SAM9260's internal ROM boot program.
OSCSEL=1, external slow clock (32.768 KHz)

Clock and JTAG/ICE
GPLv3

FILE:


PAGE

OF

REVISION:

DRAWN BY:

Saritha Kalyanam




Note:

PIO_C11 is used for RDY_BSY interrupt from the NAND flash.

SDRAM & Serial SPI Data flash & NAND flash	
GPLv3	
TITLE	
FILE:	REVISION:
PAGE	DRAWN BY: Sariitha Kalyanam
OF	


AT91SAM9260

U1




AT91SAM9260

U1



AT91SAM9260

U1



Note:

PIO_A7 is used for PHY interrupt.

PIO_C13 is used for 5V detection when plugged into a USB host port.

Ethernet 10/100 & DBGU/Serial
& USB Host/Device

TITLE

GPLv3

FILE:


REVISION:

PAGE

OF

DRAWN BY:

Saritha Kalyanam




Note:

Clock: TK0 and RK0 are connected together, with RK0 configured as an input.
FSYNC: TF0 and RF0 are connected together, with RF0 configured as an input.

TITLE		SSC interface (for FXS Si321x) GPLv3	
FILE:		REVISION:	Saritha Kalyanam
PAGE	OF	DRAWN BY:	

AT91SAM9260


U1



TITLE		User Interface (LEDs and Interrupts)	
FILE:		REVISION:	
PAGE		DRAWN BY:	
OF		Saritha Kalyanam	
		GPLv3	




Unconnected pins	
GPLv3	
TITLE	
FILE:	REVISION:
PAGE	DRAWN BY: Saritha Kalyanam
OF	







TITLE			SPI Dataflash (128KB) and NAND Flash (32MB)		
FILE:			GPLv3		
PAGE			OF		
REVISION:			DRAWN BY: Saritha Kalyanam		




TITLE		Mounting holes GPLv3	
FILE:		REVISION:	Saritha Kalyanam
PAGE	OF	DRAWN BY:	






SDRAM			
32 MB (16-bit mode)			
TITLE			
FILE:			REVISION: Saritha Kalyanam
PAGE	OF		DRAWN BY: GPLv3





TITLE		UI GPLv3	
FILE:		REVISION:	Saritha Kalyanam
PAGE	OF	DRAWN BY:	



USB Host and Device	
GPLv3	
TITLE	
FILE:	REVISION:
PAGE	OF
	Saritha Kalyanam
	DRAWN BY: