AXI4 Protocol over AIB Latency Reference Guide Revision 1.0

24 FEBRUARY 2023

Contents

1. Background

There are 2 critical latency paths in AXI4 protocol:

A) End-to-End latency – from TX to RX
B) Credit return latency – from RX to TX

For AXI4 without flow control (AXI4-Stream without ready) B is not relevant for other AXI4 protocols with flow control both A and B play an important role as discussed below.

AXI4 protocol over AIB uses credit mechanism to manage flow control between follower and leader chiplet. This credit mechanism also allows to manage the multiple clock cycle handshake between chiplets.

To avoid stalling in the traffic (bubbles) the recommendation is to size the RX credit FIFO to match A+B+k where k is an additional buffer. RX FIFO size is parameter for IP generation.

2. Simulation Parameters

Below is a table of measured latency in simulation and RX FIFO buffer size recommendation for AXI4-Stream and AXI4 based on the following parameters.

AXI4 Mode	Freq (Ghz)
Half (Gen1)	0.5
Full (Gen1)	1
Quarter (Gen2)	0.5
Half (Gen2)	1
Full (Gen2)	2

3. AXI4-Stream Latency and FIFO Buffer

Config No	Leader AIB Mode	Follower AIB Mode	FIFO Mode (TX→RX)	A (normalized to AIB Fwd clk)	B (normalized to AIB Fwd clk)	k	Freq Factor between AXI and AIB (F)	RX FIFO Size = Ceiling ((A+B+k)/F)
1	AIB2.0 (Gen1)	AIB 1.0	Half→Half	44	40	2	2	43
2	AIB2.0 (Gen1)	AIB1.0	Full→Half	40	26	2	1	68
3	AIB2.0 (Gen1)	AIB1.0	Half→Full	30	40	2	1	72
4	AIB2.0 (Gen2)	AIB2.0 (Gen2)	Half→Half	50	38	2	2	45
5	AIB2.0 (Gen2)	AIB2.0 (Gen2)	Full→Full	31	28	2	1	61
6	AIB2.0 (Gen2)	AIB2.0 (Gen2)	Quarter→Quarter	88	66	2	4	39
7	AIB2.0 (Gen2)	AIB2.0 (Gen2)	Full→Half	48	29	2	1	79
8	AIB2.0 (Gen2)	AIB2.0 (Gen2)	Full→Quarter	84	31	2	1	117
9	AIB2.0 (Gen2)	AIB2.0 (Gen2)	Half→Full	34	38	2	1	74
10	AIB2.0 (Gen2)	AIB2.0 (Gen2)	Half→Quarter	84	40	2	1	126
11	AIB2.0 (Gen2)	AIB2.0 (Gen2)	Quarter→Full	39	65	2	1	106
12	AIB2.0 (Gen2)	AIB2.0 (Gen2)	Quarter→Half	58	66	2	1	126

4. AXI4 Latency and FIFO Buffer

Si No	Leader AIB Mode	Follower AIB Mode	FIFO Mode (TX→RX)	A (normalized to AIB Fwd clk)	B (normalized to AIB Fwd clk)	k	Freq Factor between AXI and AIB (F)	RX FIFO Size = Ceiling ((A+B+k)/F)
1	AIB2.0 (Gen1)	AIB 1.0	Half→Half	50	32	2	2	42
2	AIB2.0 (Gen2)	AIB2.0 (Gen2)	Half→Half	50	40	2	2	46
3	AIB2.0 (Gen2)	AIB2.0 (Gen2)	Full→Full	31	24	2	1	57
4	AIB2.0 (Gen2)	AIB2.0 (Gen2)	Quarter→Quarter	88	68	2	4	40

5. How to Specify RX FIFO Buffer Size

Can be specified as a configuration parameter in IP configuration file. Here are examples for AXI4-Stream and AXI4-MM

5.1. AXI4-Stream

```
MODULE axi_st
// PHY and AIB Configuration
NUM_CHAN                        7
CHAN_TYPE                       Gen1Only  //Gen1Only, Gen2Only, Gen2, AIBO
// Channel Alignment Strobe Configuration
TX_ENABLE_STROBE                True        // If False, all strobe functionality is removed.
RX_ENABLE_STROBE                True        // If False, all strobe functionality is removed.
TX_PERSISTENT_STROBE            True        // If True strobes are persistent (always there). If false, they are recoverable and can be
reused for data
RX_PERSISTENT_STROBE            True        // If True strobes are persistent (always there). If false, they are recoverable and can be
reused for data
TX_USER_STROBE          True    // If True, then we input user generated signal

RX_USER_STROBE          True    // If True, then we input user generated signal
TX_STROBE_GEN1_LOC              8           // Location of Strobe when in Gen1 Mode
RX_STROBE_GEN1_LOC              8           // Location of Strobe when in Gen1 Mode

// Word Marker Configuration
TX_ENABLE_MARKER                True        // If False, all Marker functionality is removed.
RX_ENABLE_MARKER                True        // If False, all Marker functionality is removed.
TX_PERSISTENT_MARKER            True        // If True Markers are persistent (always there). If false, they are recoverable and can be
reused for data
RX_PERSISTENT_MARKER            True        // If True Markers are persistent (always there). If false, they are recoverable and can be
reused for data//
TX_USER_MARKER                  True
RX_USER_MARKER                  True
TX_MARKER_GEN1_LOC              39          // Location of Marker when in Gen1 Mode
RX_MARKER_GEN1_LOC              39          // Location of Marker when in Gen1 Mode
```

```
TX_REG_PHY          False
RX_REG_PHY          False

SUPPORT_ASYMMETRIC                    True        // Support Asymmetric Gearboxing (e.g. Full to Half)
llink ST
{
  TX_FIFO_DEPTH     1
  RX_FIFO_DEPTH     68 # for Full→Half

  output user_tdata  256
  input user_tready  ready
  output user_tvalid valid
}
```

5.2.   AXI4-MM

```
MODULE axi_mm


// PHY and AIB Configuration
NUM_CHAN                              2
CHAN_TYPE                             Gen1Only         //Gen1Only, Gen2Only, Gen2, AIBO
TX_RATE                               Half             // Full, Half, Quarter
RX_RATE                               Half             // Full, Half, Quarter

// Channel Alignment Strobe Configuration
TX_ENABLE_STROBE        True         // If False, all strobe functionality is removed.
RX_ENABLE_STROBE        True         // If False, all strobe functionality is removed.
TX_PERSISTENT_STROBE             True       // If True strobes are persistent (always there). If false, they are recoverable and can
be reused for data
RX_PERSISTENT_STROBE             True       // If True strobes are persistent (always there). If false, they are recoverable and can
be reused for data
TX_USER_STROBE                   False      // If True, then we input user generated signal
RX_USER_STROBE                   False      // If True, then we input user generated signal
TX_STROBE_GEN1_LOC               7          // Location of Strobe when in Gen1 Mode
RX_STROBE_GEN1_LOC               7          // Location of Strobe when in Gen1 Mode

// Word Marker Configuration
TX_ENABLE_MARKER        True         // If False, all Marker functionality is removed.
RX_ENABLE_MARKER        True         // If False, all Marker functionality is removed.
TX_PERSISTENT_MARKER             True       // If True Markers are persistent (always there). If false, they are recoverable and can
be reused for data
RX_PERSISTENT_MARKER             True       // If True Markers are persistent (always there). If false, they are recoverable and can
be reused for data//
TX_USER_MARKER                   False
RX_USER_MARKER                   False
TX_MARKER_GEN1_LOC               39         // Location of Marker when in Gen1 Mode
RX_MARKER_GEN1_LOC               39         // Location of Marker when in Gen1 Mode
TX_REG_PHY        False
RX_REG_PHY        False

// Packetization
TX_ENABLE_PACKETIZATION                  True
RX_ENABLE_PACKETIZATION                  True
TX_PACKET_MAX_SIZE                       0          // Number of bits to packetize to. 0 means all available data.
RX_PACKET_MAX_SIZE                       0          // Number of bits to packetize to. 0 means all available data.
PACKETIZATION_PACKING_EN         False      // If True, enable packing which makes better use of the BW

llink AR
{
  TX_FIFO_DEPTH     1
```

```
  RX_FIFO_DEPTH      8

  output user_arid    4
  output user_arsize  3
  output user_arlen   8
  output user_arburst 2
  output user_araddr  32
  output user_arvalid  valid
  input  user_arready  ready
}

llink AW
{
  TX_FIFO_DEPTH      1
  RX_FIFO_DEPTH      8

  output user_awid    4
  output user_awsize  3
  output user_awlen   8
  output user_awburst 2
  output user_awaddr  32
  output user_awvalid  valid
  input  user_awready  ready
}

llink W
{
  TX_FIFO_DEPTH      1
  RX_FIFO_DEPTH      42

  output user_wid    4
  output user_wdata   128
  output user_wstrb   16
  output user_wlast
  output user_wvalid   valid
  input  user_wready   ready
}

llink AW
{
  TX_FIFO_DEPTH      1
  RX_FIFO_DEPTH      8

  output user_awid    4
  output user_awsize  3
  output user_awlen   8
  output user_awburst 2
  output user_awaddr  32
  output user_awvalid  valid
  input  user_awready  ready
}

llink W
{
  TX_FIFO_DEPTH      1
  RX_FIFO_DEPTH      42

  output user_wid    4
  output user_wdata   128
  output user_wstrb   16
  output user_wlast
  output user_wvalid   valid
  input  user_wready   ready
```

6. Latency Optimization

These latencies reported here are out of the box. Here are some tips to improve latency with system knowledge:

a) Lane to lane to skew modeled in testbench as delay between AIB and CA. This delay is worst cased at 5 clock cycle this can be optimized for your interface and system once you have the system parameters extracted.

b) Improve RX/TX phasecomp RD delay with the knowledge of AIB write vs read clock wander margin. These values can be programmed to AIB CSR 0x208/0x218.

7. Addendum: Example waveform capture for Parameters A and B (Config 2 for AXI4-ST)

7.1. Latency A

Sum of valid to valid + push to pop on RX FIFO Buffer

7.2. Latency B

Credit return from follower to leader