

LINNEA-60

~60° + 90° beam optimized for 1.0 mm metal sheet or profile. Variant made from PC.



TECHNICAL SPECIFICATIONS:


Dimensions	285.0 x 40.0 mm
Height	9.5 mm
Fastening	clips
ROHS compliant	yes ⓘ

MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
LINNEA-60	Linear lens	PC	clear	

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
F15524_LINNEA-60 » Box size: 398 x 298 x 265 mm	153	36	36	7.7





See also our general installation guide: www.ledil.com/installation_guide


PHOTOMETRIC DATA (MEASURED):




LED CALOSNU405-M7W1
 FWHM 96.0 + 55.0°
 Efficiency 84 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED CALOSNU410-M7W1
 FWHM 95.0 + 55.0°
 Efficiency 84 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:








LED Tridino 1ft 1100lm xxxHE 1R HV
 FWHM 96.0 + 58.0°
 Efficiency 86 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED XP-E
 FWHM 96.0 + 54.0°
 Efficiency 83 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



PHOTOMETRIC DATA (MEASURED):



Helvar	<p>LED L-iC-282-827-865-011A FWHM 97.0 + 58.0° Efficiency 84 % Peak intensity 0.6 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
Helvar	<p>LED LP-282-840-009A 60/300 FWHM 97.0 + 58.0° Efficiency 84 % Peak intensity 0.6 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
Helvar	<p>LED LS-282-840-011A FWHM 97.0 + 58.0° Efficiency 84 % Peak intensity 0.6 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
Helvar	<p>LED LX-282-840-023A FWHM 96.0 + 59.0° Efficiency 85 % Peak intensity 0.6 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		

PHOTOMETRIC DATA (MEASURED):




Your solutions


LED	LinLED 280x24mm 1100lm 8x0 4C 30V Opt G1
FWHM	96.0 + 59.0°
Efficiency	85 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	





LED	NF2x757G
FWHM	96.0 + 54.0°
Efficiency	84 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



LED	NFSW757H
FWHM	96.0 + 60.0°
Efficiency	86 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	





LED	NFSx757G
FWHM	96.0 + 59.0°
Efficiency	83 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



PHOTOMETRIC DATA (MEASURED):



OSRAM

LED PL-LIN-IND-Z1 2800 560x24
 FWHM 96.0 + 60.0°
 Efficiency 88 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





OSRAM

LED PL-LIN-Z5 1100 280x20
 FWHM 97.0 + 58.0°
 Efficiency 84 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




OSRAM

LED PL-LIN-Z5 2000 280x20
 FWHM 97.0 + 58.0°
 Efficiency 84 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OSRAM

Opto Semiconductors
 LED Duris S5 (2 chip)
 FWHM 95.0 + 57.0°
 Efficiency 85 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





PHOTOMETRIC DATA (MEASURED):

OSRAM


Opto Semiconductors

LED Duris S5 (Single chip)
FWHM 96.0 + 57.0°
Efficiency 86 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHILIPS

LED Fortimo LED Strip 1ft 1100lm FC HV4 & LV4
FWHM 95.0 + 59.0°
Efficiency 85 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHILIPS

LED Fortimo LED Strip 1ft 650lm FC HV4 & LV4
FWHM 95.0 + 59.0°
Efficiency 84 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



SAMSUNG


LED LM28xB Series
FWHM 95.0 + 53.0°
Efficiency 84 %
Peak intensity 0.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):


SAMSUNG

LED LM561B Plus
 FWHM 96.0 + 59.0°
 Efficiency 85 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SAMSUNG

LED LT-H282C
 FWHM 96.0 + 55.0°
 Efficiency 85 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SAMSUNG

LED LT-H562C
 FWHM 96.0 + 55.0°
 Efficiency 85 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SAMSUNG



LED LT-Q282B
 FWHM 95.0 + 54.0°
 Efficiency 85 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



PHOTOMETRIC DATA (MEASURED):



SAMSUNG

LED LT-S282H
 FWHM 96.0 + 54.0°
 Efficiency 85 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SAMSUNG

LED LT-S562H
 FWHM 96.0 + 54.0°
 Efficiency 85 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





SAMSUNG

LED LT-V282E
 FWHM 96.0 + 54.0°
 Efficiency 86 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:










SAMSUNG

LED LT-V562E
 FWHM 96.0 + 54.0°
 Efficiency 86 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





PHOTOMETRIC DATA (MEASURED):

 SEOUL SEMICONDUCTOR	LED SEOUL 5630D FWHM 73.0° Efficiency 84 % Peak intensity 0.6 cd/lm LEDs/each optic 1 Light colour White Required components:		
 SEOUL SEMICONDUCTOR	LED SEOUL DC 3030 FWHM 96.0 + 57.0° Efficiency 86 % Peak intensity 0.6 cd/lm LEDs/each optic 1 Light colour White Required components:		
 TRIDONIC	LED LLE G4 24x280mm 1250lm FWHM 96.0 + 58.0° Efficiency 85 % Peak intensity 0.6 cd/lm LEDs/each optic 1 Light colour White Required components:		
 TRIDONIC	LED LLE G4 24x280mm 2000lm ADV FWHM 95.0 + 60.0° Efficiency 85 % Peak intensity 0.6 cd/lm LEDs/each optic 1 Light colour White Required components:		

PHOTOMETRIC DATA (MEASURED):

TRIDONIC


LED LLE G4 24x280mm 650lm
FWHM 95.0 + 59.0°
Efficiency 85 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (SIMULATED):



LED LUXEON 3030 2D (Round LES)
 FWHM 89.0 + 60.0°
 Efficiency 84 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED SEOUL DC 3030C
 FWHM 92.0 + 60.0°
 Efficiency 85 %
 Peak intensity 0.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Ledil:

[F15524_LINNEA-60](#)