More Info | Instructions | Get Quote

For Use with Model 3001/3002/3250/3500

DataGrabber™ 5

Model 3001

The Model 3001 DataGrabber 5 provides an inexpensive, and very portable option for Solinst datalogger users to download data directly to a USB flash drive key.

How the DataGrabber 5 Works

The DataGrabber 5 connects to a Levelogger's direct read cable; alternatively, an L5 Threaded or Slipfit Adaptor allows you to connect it directly to a Levelogger 5. The DataGrabber connects to an AquaVent 5 Wellhead using a Connector Cable, or directly to a LevelVent 5 Wellhead. The USB flash drive key is plugged into the socket on the front of the DataGrabber.

A push-button on the DataGrabber 5 starts the downloading process. All of the data in the datalogger's memory is transferred to the USB device. The DataGrabber comes with a 2 GB USB flash drive key with a second connection for a USB-C device, if required. It is also compatible with most other USB flash drives. The datalogger is not interrupted if it is still logging. The data in the datalogger memory is not erased.


A light changes colour to indicate when the DataGrabber 5 is properly connected, when the data transfer is taking place, and when the data has been successfully downloaded. The DataGrabber uses one 9 volt alkaline or lithium battery that is easy to replace when required.

Materials:	ABS black, 316 stainless steel
Operating Temperature:	-20°C to +50°C
IP Rating:	IP64 (dust and splash resistant)
Battery:	9V replaceable alkaline or lithium battery
Battery Life:	Up to 60 full datalogger downloads @21°C (alkaline)
Size:	ø 45.7 mm x 99.3 mm (ø 1.80" x 3.91")
Weight:	5.79 oz. (180 grams)
Compatible With:	Levelogger 5 Series dataloggers, LevelVent 5 and AquaVent 5, as well as Levelogger Edge and Gold Series dataloggers, LevelVent and AquaVent.



Features of the DataGrabber 5

- One push-button to download data
- Inexpensive and easy to transport
- Compatible with most USB flash drive keys
- Connects to a Levelogger's L5 Direct Read Cable/ Adaptor or LevelVent/AquaVent 5 Wellhead
- Uses separate, replaceable 9V battery
- LED light to indicate operation
- Data transfer does not interrupt running datalogger





Levelogger 5 App Interface

A smart alternative to the DataGrabber 5, is the Levelogger 5 App Interface that uses *Bluetooth*® technology to connect all Solinst dataloggers to your smart device using the Solinst Levelogger App (see Model 3001 Solinst Levelogger 5 App Interface data sheets).





The Apple logo is a trademark of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Google Play is a trademark of Google Inc.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Solinst Canada Ltd. is under license.

