

Quick Start Guide

Levellogger 5 App Interface for Android™



[More Info](#) | [Instructions](#) | [Get Quote](#)



Introduction

The Levellogger® 5 App Interface uses *Bluetooth®* wireless technology to connect a Solinst datalogger to an Android™ smart device running Android 9.0 or higher. Please see the list of tested devices on the last page of this quick start guide.

Once the connection is made, you can use the Solinst Levellogger App to interact with the datalogger. The Solinst Levellogger App allows you to view real time data from the connected datalogger, as well as view, download, and e-mail logged readings. You can also program the dataloggers or apply a saved settings file.

The Levellogger 5 App Interface is compatible with the Levellogger 5 series of dataloggers, LevelVent 5, AquaVent 5, as well as previous Levellogger Edge series dataloggers, and LevelVent and AquaVent using their most current firmware versions.

Levellogger 5 App Interface

Connection

The Levellogger 5 App Interface connects to the top end of a Levellogger's L5 Direct Read Cable or L5 Optical Adaptor, LevelVent 5 Wellhead, or AquaVent 5 Wellhead Connector Cable.

To connect the Levellogger 5 App Interface, simply hold onto the top end of the Direct Read/Connector Cable/Wellhead, and thread the coupling of the Levellogger 5 App Interface onto the connection. The threaded connection is designed to be stable when installed on a Direct Read Cable or LevelVent Wellhead in a Solinst 2" Well Cap Assembly.

Alternatively, you can use a L5 Threaded or Slip Fit Adaptor, when a Direct Read Cable is not being used. Simply thread or slip the Levellogger into the optical end, and thread the Levellogger App Interface into the other connection.

Battery Access



L5 Direct
Read Cable

L5
Threaded
Adaptor

LevelVent 5
Wellhead

AquaVent 5 Wellhead and
App Connector Cable

Connection to
Direct Read/
Connector
Cable, Adaptor
or Wellhead

Levellogger 5 App Interface Quick Start Guide



Batteries

The Levellogger 5 App Interface operates using four 1.5V AA replaceable lithium batteries (alkaline batteries can also be used). To install or replace the batteries:

- 1) Unscrew the top cap of the Levellogger 5 App Interface to access the battery holder.
- 2) Slowly remove the battery holder from the Levellogger 5 App Interface housing.
- 3) Ensure proper installation (polarity) when replacing the batteries.
- 4) Insert the battery holder back into the Levellogger 5 App Interface housing. Ensure it is lined-up properly.
- 5) Screw the top cap of the Levellogger 5 App Interface firmly back onto the housing.

Power Button and LED Light

Press and hold the power button for 1 second to turn the Levellogger 5 App Interface on. Press and hold the power button for 3 seconds to turn the Levellogger 5 App Interface off. The App Interface will automatically turn off after 10 minutes of inactivity.

The LED indicates the status of the Levellogger 5 App Interface:

- Green light flashing every second: Ready/waiting for a Bluetooth connection to be made from your smartphone device.
- Blue light flashing every 3 seconds: Bluetooth connected/device paired (App is open).
- Yellow light: Levellogger 5 App Interface is turning off while the button is held pressed.
- Red light flashing every 10 seconds: Batteries are low, need replacing.

Using the Levellogger 5 App Interface

- 1) Download the Solinst Levellogger App for your smart device on Google Play™.
- 2) Connect the Levellogger 5 App Interface to the top end of your Levellogger's Direct Read Cable or Adaptor, LevelVent Wellhead, or AquaVent Wellhead Connector Cable. Press the power button to turn the App Interface on.
- 3) Enable (turn on) Bluetooth on your smart device by going to Settings > Bluetooth. Scan for devices. Pair the Levellogger 5 App Interface to your smart device by selecting it from the list of Bluetooth devices.
- 4) Launch the Solinst Levellogger App and connect to your datalogger.
- 5) Once you are finished programming or downloading your datalogger, disconnect the Levellogger 5 App Interface, and connect to a datalogger at your next monitoring location. The App Interface is not intended for dedicated applications.



*Tested on the following devices:
Samsung S9 - Model SM-G960W
Google Pixel 3 - Model G013A*

Android and Google Play are trademarks of Google Inc.

The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Solinst Canada Ltd. is under license.

Solinst and Levellogger are registered trademarks of Solinst Canada Ltd.

(#115002) Printed in Canada September 1, 2020 ®Solinst is a registered trademark of Solinst Canada Ltd.

Solinst Canada Ltd. 35 Todd Road, Georgetown, Ontario Canada L7G 4R8
Tel: +1 (905) 873-2255; (800) 661-2023 Fax: +1 (905) 873-1992
E-mail: instruments@solinst.com www.solinst.com

Solinst®