

Code:

```
#include <stdio.h>
#include <string.h>
int main() {
    char nums[13][256] = {
        "ZERO", "ONE", "TWO", "THREE", "FOUR", "FIVE", "SIX",
        "SEVEN", "EIGHT", "NINE", "TEN", "ELEVEN", "TWELVE"
    };
    int input_nums[100];
    int count = 0;
    int val;
    while (scanf("%d", &val) == 1) {
        input_nums[count++] = val;
        if (val == 999) {
            break;
        }
    }
    // Print the numbers exactly as read
    for (int i = 0; i < count; i++) {
        if (i > 0) printf(" ");
        printf("%d", input_nums[i]);
    }
    printf(". ");
    // Max frequency of each letter needed for any single jersey number
    int max_freq[26] = {0};
    for (int i = 0; i < count - 1; i++) {
        int num = input_nums[i];
        if (num >= 0 && num <= 12) {
            int current_freq[26] = {0};
            for (int j = 0; nums[num][j] != '\0'; j++) {
                current_freq[nums[num][j] - 'A']++;
            }
            for (int k = 0; k < 26; k++) {
                if (current_freq[k] > max_freq[k]) {
                    max_freq[k] = current_freq[k];
                }
            }
        }
    }
    // Print the required letters in alphabetical order
    int n;
    for (n = 0; n < 26; n++) {
        for (int j = 0; j < max_freq[n]; j++) {
            printf("%c", 'A' + n);
        }
    }
    printf("\n");
    return 0;
}
```

Input:

2 3 0 999

Output:

2 3 0 999. EEH0RTTW