

Code:

```
#include <stdio.h> #include <string.h> #include <stdlib.h>

typedef struct { char name[15]; long long spends[1005]; int count; } Festival;

int cmp_desc(const void *a, const void *b) { long long x = (long long)a; long long y = (long long)b; if (x > y) return -1; if (x < y) return 1; return 0; }

int main() { int t; if (scanf("%d", &t) != 1) return 0;

while (t--) {
    int n;
    if (scanf("%d", &n) != 1) break;

    Festival fest[105];
    int fest_cnt = 0;

    for (int i = 0; i < n; i++) {
        char s[15];
        long long x;
        scanf("%s %lld", s, &x);

        int idx = -1;
        for (int j = 0; j < fest_cnt; j++) {
            if (strcmp(fest[j].name, s) == 0) {
                idx = j;
                break;
            }
        }

        if (idx == -1) {
            idx = fest_cnt++;
            strcpy(fest[idx].name, s);
            fest[idx].count = 0;
        }

        fest[idx].spends[fest[idx].count++] = x;
    }

    char best_name[15] = "";
    long long max_sum = -1;
```

```

        for (int i = 0; i < fest_cnt; i++) {
            qsort(fest[i].spends, fest[i].count, sizeof(long long),
cmp_desc);
            long long cur_sum = 0;
            for (int j = 0; j < 3 && j < fest[i].count; j++) {
                cur_sum += fest[i].spends[j];
            }

            if (cur_sum > max_sum) {
                max_sum = cur_sum;
                strcpy(best_name, fest[i].name);
            } else if (cur_sum == max_sum) {
                if (strcmp(fest[i].name, best_name) < 0) {
                    strcpy(best_name, fest[i].name);
                }
            }
        }

        printf("%s %lld\n", best_name, max_sum);
    }

    return 0;

}

```

Input:

```

2
6
B 20
A 2
A 10
A 10
B 30

```

A 30
3
abc 10
xyz 15
oop 8

Output:

A 50
xyz 15