

Code:

```
#include <stdio.h> #include <stdlib.h>

int cmp_ll(const void *a, const void *b) { long long x = (long long)a; long long y = (long long)b; if (x < y) return -1; if (x > y) return 1; return 0; }

int main() { int N; if (scanf("%d", &N) != 1) return 0;

int NA[N];
for (int i = 0; i < N; i++) {
    scanf("%d", &NA[i]);
}

int total_subs = N * (N + 1) / 2;
long long *max_sums = (long long*)malloc(total_subs * sizeof(long long));
int count = 0;

// Kadane's on every subarray [i..j]
for (int i = 0; i < N; i++) {
    long long current_sum = 0;
    long long max_so_far = -1e18;
    for (int j = i; j < N; j++) {
        if (current_sum + NA[j] > NA[j]) {
            current_sum += NA[j];
        } else {
            current_sum = NA[j];
        }
        if (current_sum > max_so_far) {
            max_so_far = current_sum;
        }
        max_sums[count++] = max_so_far;
    }
}

qsort(max_sums, count, sizeof(long long), cmp_ll);

long long total_unique_sum = 0;
for (int i = 0; i < count; i++) {
    if (i == 0 || max_sums[i] != max_sums[i - 1]) {
        total_unique_sum += max_sums[i];
    }
}
```

```
}  
  
printf("%lld\n", total_unique_sum);  
free(max_sums);  
return 0;  
  
}
```

Input:

```
4  
5 -2 7 -3
```

Output:

```
17
```