

Code:

```
#include <stdio.h>
#include <stdbool.h>

int A[309][309];
bool ok[309][309][309];

int min_val(int a, int b) { return a < b ? a : b; }
int max_val(int a, int b) { return a > b ? a : b; }

void solve() {
    int R, C, L;
    if (scanf("%d %d %d", &R, &C, &L) != 3) return;

    for (int i = 0; i < R; i++) {
        for (int j = 0; j < C; j++) {
            scanf("%d", &A[i][j]);
        }
    }

    for (int i = 0; i < R; i++) {
        for (int c1 = 0; c1 < C; c1++) {
            int mn = A[i][c1], mx = A[i][c1];
            for (int c2 = c1; c2 < C; c2++) {
                mn = min_val(mn, A[i][c2]);
                mx = max_val(mx, A[i][c2]);
                ok[i][c1][c2] = (mx - mn <= L);
            }
        }
    }

    int ans = 0;
    for (int c1 = 0; c1 < C; c1++) {
        for (int c2 = c1; c2 < C; c2++) {
            int width = c2 - c1 + 1;
            int current_h = 0;
            for (int r = 0; r < R; r++) {
                if (ok[r][c1][c2]) {
                    current_h++;
                    int area = current_h * width;
                    if (area > ans) ans = area;
                }
            }
        }
    }
}
```

```

        } else {
            current_h = 0;
        }
    }
}

printf("%d\n", ans);
}

int main() {
    int T;
    if (scanf("%d", &T) == 1) {
        while (T--) {
            solve();
        }
    }
    return 0;
}

```

Input:

```

3
1 4 0
3 1 3 3
2 3 0
4 4 5
7 6 6
4 5 0
2 2 4 4 2 0
8 3 3 3 1 2
6 6 3 3 3
1 6 8 6 4

```

Output:

2

2

6