

Code:

```
#include <stdio.h>
#include <stdlib.h>

struct node {
    int data;
    struct node *next;
};

struct node *front = NULL;
struct node *rear = NULL;

void enqueue(int d) {
    struct node* new_n;
    new_n = (struct node*)malloc(sizeof(struct node));
    new_n->data = d;
    new_n->next = NULL;

    if (front == NULL && rear == NULL) {
        front = rear = new_n;
        return;
    }
    rear->next = new_n;
    rear = new_n;
}

void dequeue() {
    if (front == NULL) return;
    struct node *temp = front;
    front = front->next;
    if (front == NULL) rear = NULL;
    free(temp);
}

void print() {
    if (front == NULL) {
        printf("No data in the queue.\n");
        return;
    }
    struct node *temp = front;
    while (temp != NULL) {
```

```
        printf("%d", temp->data);
        if (temp->next != NULL) printf(" ");
        temp = temp->next;
    }
    printf("\n");
}

int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;

    for (int i = 0; i < n; i++) {
        int val;
        scanf("%d", &val);
        enqueue(val);
    }

    print();
    dequeue();
    print();

    return 0;
}
```

Input:

```
5
9 1 5 3 5
```

Output:

```
9 1 5 3 5
1 5 3 5
```