

Code:

```
#include <stdio.h>
#include <stdlib.h>

void insertionSort(long int *p, long int n) {
    int i, j;
    long int key;
    for (i = 1; i < n; i++) {
        key = p[i];
        j = i - 1;
        while (j >= 0 && p[j] > key) {
            p[j + 1] = p[j];
            j = j - 1;
        }
        p[j + 1] = key;
    }
}

int main() {
    int q;
    if (scanf("%d", &q) != 1) return 0;

    while (q--) {
        int n;
        if (scanf("%d", &n) != 1) break;

        long int rowSum[105] = {0};
        long int colSum[105] = {0};
        int i, j;

        for (i = 0; i < n; i++) {
            for (j = 0; j < n; j++) {
                long long val;
                scanf("%lld", &val);
                rowSum[i] += val;
                colSum[j] += val;
            }
        }

        insertionSort(rowSum, n);
        insertionSort(colSum, n);
    }
}
```

```
int possible = 1;
for (i = 0; i < n; i++) {
    if (rowSum[i] != colSum[i]) {
        possible = 0;
        break;
    }
}

if (possible) {
    printf("Possible\n");
} else {
    printf("Impossible\n");
}

return 0;
}
```

Input:

```
2
2
1 1
1 1
2
0 2
1 1
```

Output:

```
Possible
Impossible
```

