

Code:

```
#include <stdio.h>
#include <stdlib.h>

#define MAXN 100005

typedef struct {
    int to, next;
} Edge;

Edge edges[2 * MAXN];
int head[MAXN], edge_cnt;
char s[MAXN];
int cnt[MAXN][26];

void add_edge(int u, int v) {
    edges[++edge_cnt] = (Edge){v, head[u]};
    head[u] = edge_cnt;
}

void dfs(int u, int p) {
    cnt[u][s[u] - 'a'] = 1;
    for (int e = head[u]; e; e = edges[e].next) {
        int v = edges[e].to;
        if (v != p) {
            dfs(v, u);
            for (int c = 0; c < 26; c++) {
                cnt[u][c] += cnt[v][c];
            }
        }
    }
}

int main() {
    int N, Q;
    if (scanf("%d %d", &N, &Q) != 2) return 0;

    scanf("%s", s);

    int i;
    for (i = 0; i < N - 1; i++) {
```

```
    int u, v;  
    scanf("%d %d", &u, &v);  
    add_edge(u, v);  
    add_edge(v, u);  
}  
  
dfs(1, 0);  
  
while (Q--) {  
    int u;  
    char c;  
    scanf("%d %c", &u, &c);  
    printf("%d\n", cnt[u][c - 'a']);  
}  
  
return 0;  
}
```

Input:

```
3 1  
aba  
1 2  
1 3  
1 a
```

Output:

```
2
```