

Code:

```
#include <stdio.h> #include <stdlib.h>

struct Node { int data; struct Node *next; };

void sortedInsert(struct Node** head_ref, struct Node* new_node) { struct Node*
current = *head_ref;

if (current == NULL) {
    new_node->next = new_node;
    *head_ref = new_node;
} else if (current->data >= new_node->data) {
    while (current->next != *head_ref) {
        current = current->next;
    }
    current->next = new_node;
    new_node->next = *head_ref;
    *head_ref = new_node;
} else {
    while (current->next != *head_ref && current->next->data <
new_node->data) {
        current = current->next;
    }
    new_node->next = current->next;
    current->next = new_node;
}

}

int main() { int n; if (scanf("%d", &n) != 1) return 0;

struct Node* head = NULL;
for (int i = 0; i < n; i++) {
    int val;
    scanf("%d", &val);
    struct Node* new_node = (struct Node*)malloc(sizeof(struct
Node));
    new_node->data = val;
    new_node->next = NULL;
    sortedInsert(&head, new_node);
}
```

```
if (head != NULL) {  
    struct Node* temp = head;  
    do {  
        printf("%d", temp->data);  
        temp = temp->next;  
        if (temp != head) printf(" ");  
    } while (temp != head);  
}  
printf("\n");  
  
return 0;  
  
}
```

Input:

```
6  
10 20 30 45 34 56
```

Output:

```
10 20 30 34 45 56
```