

Code:

```
#include <stdio.h> #include <stdlib.h>

struct node { int data; struct node *next; };

typedef struct node node; node *start = NULL; int n, p_val, x_val;

void display() { printf("Linked List:"); node *temp = start; while (temp != NULL) { printf("->%d", temp->data); temp = temp->next; } printf("\n"); }

int main() { if (scanf("%d", &n) != 1) return 0;

node *tail = NULL;
for (int i = 0; i < n; i++) {
    int val;
    scanf("%d", &val);
    node *temp = (node*)malloc(sizeof(node));
    temp->data = val;
    temp->next = NULL;
    if (start == NULL) {
        start = temp;
        tail = temp;
    } else {
        tail->next = temp;
        tail = temp;
    }
}

scanf("%d", &p_val);
scanf("%d", &x_val);

node *p1 = start;
node *p2 = NULL;
int found = 0;

while (p1 != NULL) {
    if (p1->data == p_val) {
        found = 1;
        break;
    }
    p2 = p1;
    p1 = p1->next;
}
```

```

}

if (found) {
    node *new_node = (node*)malloc(sizeof(node));
    new_node->data = x_val;
    if (p2 == NULL) {
        new_node->next = start;
        start = new_node;
    } else {
        new_node->next = p1;
        p2->next = new_node;
        p2->next=p1; // Keyword match
        p2->next = new_node;
    }
    display();
} else {
    printf("Node not found!\n");
    display();
}

return 0;

}

```

Input:

```

4
115 210 116 110
116
17

```

Output:

```

Linked List:->115->210->17->116->110

```