

Code:

```
#include <stdio.h>

#define MAXN 200005

int tree[4 * MAXN];

int min(int a, int b) { return (a < b) ? a : b; }

void build(int *aa, int k, int l, int r) { if (l == r) { tree[k] = aa[l]; return; } int mid = (l + r) / 2;
build(aa, 2 * k, l, mid); build(aa, 2 * k + 1, mid + 1, r); tree[k] = min(tree[2 * k], tree[2 * k +
1]); }

int query(int k, int l, int r, int ql, int qr) { if (ql <= l && r <= qr) { return tree[k]; } int mid = (l + r)
/ 2; int res = 1e9 + 7; if (ql <= mid) { res = min(res, query(2 * k, l, mid, ql, qr)); } if (qr > mid)
{ res = min(res, query(2 * k + 1, mid + 1, r, ql, qr)); } return res; }

int a[MAXN];

int main() { int n, q; if (scanf("%d %d", &n, &q) != 2) return 0;

for (int i = 1; i <= n; i++) {
    scanf("%d", &a[i]);
}

build(a, 1, 1, n);

while (q--) {
    int u, v;
    scanf("%d %d", &u, &v);
    printf("%d\n", query(1, 1, n, u, v));
}
return 0;

}
```

Input:

8 4

3 2 4 5 1 1 5 3
2 4
5 6
1 8
3 3

Output:

2
1
1
4