

Code:

```
#include <stdio.h>

#define MAXN 100005

struct DSU {
    int parent[MAXN];
};

void initDSU(struct DSU *d, int n) {
    for (int i = 1; i <= n; i++) d->parent[i] = i;
}

int find(struct DSU *d, int i) {
    if (d->parent[i] == i)
        return i;
    return d->parent[i] = find(d, d->parent[i]);
}

int unite(struct DSU *d, int i, int j) {
    int root_i = find(d, i);
    int root_j = find(d, j);
    if (root_i != root_j) {
        d->parent[root_i] = root_j;
        return 1;
    }
    return 0;
}

struct DSU d1, d2;
int ans_u[MAXN], ans_v[MAXN];

int main() {
    int n, m1, m2;
    if (scanf("%d %d %d", &n, &m1, &m2) != 3) return 0;

    initDSU(&d1, n);
    initDSU(&d2, n);

    while (m1--) {
        int u, v;
```

```

    scanf("%d %d", &u, &v);
    unite(&d1, u, v);
}

while (m2--) {
    int u, v;
    scanf("%d %d", &u, &v);
    unite(&d2, u, v);
}

int count = 0;
for (int i = 1; i <= n; i++) {
    for (int j = i + 1; j <= n; j++) {
        if (find(&d1, i) != find(&d1, j) && find(&d2, i) != find(&d2, j)) {
            unite(&d1, i, j);
            unite(&d2, i, j);
            ans_u[count] = i;
            ans_v[count] = j;
            count++;
        }
    }
}

printf("%d\n", count);
for (int i = 0; i < count; i++) {
    printf("%d %d\n", ans_u[i], ans_v[i]);
}

return 0;
}

```

Input:

```

5 3 2
5 4
2 1
4 3
4 3
1 4

```

Output:

1

1 5