

Code:

```
#include <stdio.h>
#include <string.h>
#include <stdbool.h>
#define MAX 1000
char stack[MAX];
int top = -1;
void push(char c) {
    if (top < MAX - 1) {
        stack[++top] = c;
    }
}
char pop() {
    if (top >= 0) {
        return stack[top--];
    }
    return '\0';
}
bool empty() {
    return top == -1;
}
int isMatching(char a, char b) {
    if (a == '(' && b == ')') return 1;
    if (a == '{' && b == '}') return 1;
    if (a == '[' && b == ']') return 1;
    return 0;
}
int main() {
    char exp[MAX];
    if (scanf("%s", exp) != 1) {
        return 0;
    }
    int balanced = 1; for (int i = 0; exp[i] != '\0'; i++) {
        char ch = exp[i];
        if (ch == '(' || ch == '{' || ch == '[') {
            push(ch);
        } else if (ch == ')' || ch == '}' || ch == ']') {
            if (empty()) {
                balanced = 0;
                break;
            }
            char popped = pop();
            if (!isMatching(popped, ch)) {
                balanced = 0;
                break;
            }
        }
    }
    if (balanced && empty()) {
        printf("Balanced\n");
    } else {
        printf("Not Balanced\n");
    }
    return 0;
}
```

Input:

{()}[]

Output:

Balanced