

Computer Networks

Computer networks are a group of interconnected devices that can communicate with each other and share resources. These devices can include computers, servers, printers, and other peripherals. The purpose of a computer network is to allow for the easy sharing of data and resources among its users.

Some key concepts in computer networks include:

1. **Topology:** This refers to the physical and logical arrangement of the devices in a network. Common topologies include bus, star, ring, and mesh.
2. **Protocols:** These are the rules and standards that govern the communication between devices on a network. Some common protocols include TCP/IP, HTTP, FTP, and SMTP.
3. **Transmission media:** This refers to the physical means by which data is transmitted between devices on a network. Common transmission media include copper cables, fiber optic cables, and wireless signals.
4. **Network devices:** These are the hardware components that make up a network, such as routers, switches, and hubs.
5. **Network security:** This refers to the measures taken to protect a network and its data from unauthorized access and malicious attacks.

A mnemonic to remember the OSI model layers is: “**Please Do Not Throw Sausage Pizza Away**”. It stands for Physical, Data Link, Network, Transport, Session, Presentation, and Application.

An example of a computer network is the Internet, which is a global network of interconnected devices that allows for the sharing of information and resources on a massive scale. Other examples include local area networks (LANs) and wide area networks (WANs).

Computer networks have numerous applications, including in business, education, and government. They allow for the efficient sharing of information and resources, and can improve productivity and collaboration. However, they also present security risks, and measures must be taken to protect against unauthorized access and attacks.

Unit 1 - Introductory Concepts of Computer Networks and Physical Layer

1. **Computer Networks** are a group of interconnected devices that can communicate with each other and share resources.
2. The **Physical Layer** is the first layer of the OSI model and is responsible for transmitting raw data bits over a physical medium.

3. The Physical Layer defines the electrical, mechanical, procedural, and functional specifications for activating, maintaining, and deactivating the physical link between communicating network systems.
4. Some common physical layer transmission mediums include copper wire, fiber optic cable, and wireless transmission.
5. The Physical Layer is also responsible for converting digital data into signals that can be transmitted over the physical medium.
6. Some common Physical Layer protocols include Ethernet, Wi-Fi, and Bluetooth.
7. A **Mnemonic** to remember the OSI model layers is “Please Do Not Throw Sausage Pizza Away” (Physical, Data Link, Network, Transport, Session, Presentation, Application).
8. A **learning trick** for the Physical Layer is to remember that it is the first layer and is responsible for the physical transmission of data. Think of it as the foundation of a building, without which the upper layers cannot function.

Introductory Concepts of Computer Networks

1. **Computer Networks:** A computer network is a group of interconnected computers and other devices that are capable of communicating with each other and sharing resources.
2. **Types of Networks:** There are several types of computer networks, including Local Area Networks (LANs), Wide Area Networks (WANs), Metropolitan Area Networks (MANs), and Personal Area Networks (PANs).
3. **Network Topologies:** The physical and logical arrangement of the devices in a network is known as the network topology. Common topologies include bus, star, ring, and mesh.
4. **Network Protocols:** A protocol is a set of rules and standards that govern the communication between devices on a network. Some common network protocols include TCP/IP, HTTP, FTP, and SMTP.
5. **OSI Model:** The Open Systems Interconnection (OSI) model is a conceptual framework that describes the functions of a networking system. It consists of seven layers: Physical, Data Link, Network, Transport, Session, Presentation, and Application.
6. **IP Addressing:** An IP address is a numerical label assigned to each device on a network that uses the Internet Protocol for communication. It serves two main functions: host or network interface identification and location addressing.
7. **Routing:** Routing is the process of selecting a path for traffic in a network, or between or across multiple networks. Routers are devices that perform this function by using routing tables and algorithms to determine the best path for forwarding packets.

A mnemonic to remember the OSI model layers is “**Please Do Not Throw**

Sausage Pizza Away”, where each first letter represents a layer: Physical, Data Link, Network, Transport, Session, Presentation, and Application.

Goals and applications of networks and protocols

- Networks and protocols are designed to facilitate communication between devices and systems.
- The primary goal of networks and protocols is to enable the exchange of data and information between devices and systems.
- Networks and protocols are used to connect devices and systems, allowing them to communicate and share resources.
- Networks and protocols are used to provide reliable and secure communication between devices and systems.
- Networks and protocols are used to manage and control the flow of data and information between devices and systems.
- Networks and protocols are used to ensure that data and information are transmitted and received accurately and efficiently.
- Networks and protocols are used to provide access to shared resources, such as printers, files, and databases.
- Networks and protocols are used to support a wide range of applications, including email, file sharing, web browsing, and online gaming.
- Networks and protocols are used to support the development and deployment of new technologies, such as the Internet of Things (IoT) and cloud computing.
- Networks and protocols are used to support the growth and expansion of businesses and organizations, by enabling them to connect with customers, partners, and suppliers.

Categories of networks in computer networks

Computer networks can be categorized based on their size, geographical area, and the number of devices connected. Here are the main categories of computer networks:

1. **Local Area Network (LAN):** A LAN is a network that connects computers and devices within a limited geographical area, such as a home, school, or office building. LANs are typically owned, controlled, and managed by a single person or organization.
2. **Wide Area Network (WAN):** A WAN is a network that covers a large geographical area, such as a city, country, or even the entire world. WANs are typically owned and operated by large corporations or telecommunications companies.
3. **Metropolitan Area Network (MAN):** A MAN is a network that connects multiple LANs within a metropolitan area, such as a city or a large campus. MANs are typically owned and operated by a single entity, such as a government or a large corporation.

4. **Personal Area Network (PAN):** A PAN is a network that connects devices within the close proximity of a single person, such as a smartphone, smartwatch, and wireless headphones. PANs can be either wired or wireless.
5. **Storage Area Network (SAN):** A SAN is a network that provides access to consolidated, block-level data storage. SANs are primarily used to enhance storage devices' accessibility to servers so that the devices appear as locally attached devices to the operating system.
6. **Enterprise Private Network (EPN):** An EPN is a network that is built, owned, and operated by an enterprise, and is used to securely connect various company locations, such as branch offices and data centers.
7. **Virtual Private Network (VPN):** A VPN is a network that uses a public network, such as the internet, to provide remote users with secure access to their organization's network.

A helpful mnemonic to remember these categories is **Lucy Wants More Pancakes So Everyone Volunteers**.

Each of these categories of networks has its own advantages, disadvantages, and applications. For example, LANs are typically faster and more secure than WANs, but WANs can cover a much larger geographical area. SANs are used to improve storage performance and availability, while VPNs are used to provide secure remote access to a network. It is important to understand the differences between these categories when designing and implementing a computer network.

Organization of the Internet

The Internet is a global network of interconnected computer networks that use the standard Internet protocol suite (TCP/IP) to link devices worldwide. It is organized in a hierarchical structure, with several levels of organization.

1. At the top level, the Internet is managed by a group of organizations responsible for the overall coordination and management of the Internet's infrastructure. These organizations include the Internet Corporation for Assigned Names and Numbers (ICANN), the Internet Engineering Task Force (IETF), and the Internet Society (ISOC).
2. Below this top level, the Internet is divided into several interconnected networks, known as Autonomous Systems (AS). Each AS is managed by a single organization, such as an Internet Service Provider (ISP), and is responsible for routing traffic within its network and exchanging traffic with other ASes.
3. Within each AS, there are several levels of organization, including backbone networks, regional networks, and local networks. Backbone networks are high-speed networks that connect regional networks, which in turn connect local networks.

4. At the local level, individual devices, such as computers and smartphones, connect to the Internet through a local network, such as a home network or a corporate network.
5. The Domain Name System (DNS) is a hierarchical and decentralized naming system for computers, services, or other resources connected to the Internet or a private network. It associates various information with domain names assigned to each of the participating entities.
6. The Internet also has a layered architecture, with different protocols operating at different layers. The most commonly used model for this architecture is the OSI (Open Systems Interconnection) model, which divides the communication process into seven layers: Physical, Data Link, Network, Transport, Session, Presentation, and Application.
7. The Internet also relies on a number of supporting organizations and technologies, such as the World Wide Web Consortium (W3C), which develops standards for the Web, and the Border Gateway Protocol (BGP), which is used to exchange routing information between ASes.

Overall, the organization of the Internet is complex and involves multiple levels of hierarchy and coordination. However, this structure allows for the efficient routing of traffic and the effective management of the global network.

ISP

ISP stands for Internet Service Provider. An ISP is a company that provides internet access to customers. Here are some key points to remember about ISPs:

- ISPs provide internet access to customers through various means, such as cable, DSL, or fiber-optic connections.
- ISPs may offer different plans with varying speeds and data allowances.
- Some ISPs may also offer additional services, such as email, web hosting, or virtual private networks (VPNs).
- To connect to the internet, a customer typically needs a modem and a router. The modem connects to the ISP's network, while the router allows multiple devices to share the internet connection.
- ISPs may have peering agreements with other ISPs to exchange traffic and improve connectivity.
- Net neutrality is a principle that ISPs should treat all internet traffic equally, without blocking or slowing down certain content.

A helpful mnemonic to remember the key functions of an ISP is **I**nternet **S**ervice **P**rovider = **I**nternet **S**peed and **P**lans.

Network structure with reference to Computer Networks

- A computer network is a group of interconnected devices that can communicate with each other and share resources.

- The structure of a computer network refers to the way in which the devices are connected and the protocols used for communication.
- There are several common network structures, including:
 - **Bus:** In a bus network, all devices are connected to a central cable, called the bus. Data is transmitted along the bus and all devices can receive it, but only the intended recipient processes it.
 - **Star:** In a star network, all devices are connected to a central hub or switch. Data is transmitted from the sender to the hub, which then forwards it to the intended recipient.
 - **Ring:** In a ring network, all devices are connected in a closed loop. Data is transmitted from one device to the next until it reaches its destination.
 - **Mesh:** In a mesh network, each device is connected to multiple other devices. Data can be transmitted along multiple paths to reach its destination.
- Each network structure has its own advantages and disadvantages. For example, a bus network is simple and inexpensive to set up, but can become slow and congested as the number of devices increases. A star network is more scalable, but requires more cabling and a central hub or switch.
- The choice of network structure depends on factors such as the size of the network, the amount of data being transmitted, and the need for reliability and security.
- A mnemonic to remember the different network structures is **BSRM** (Bus, Star, Ring, Mesh).

Network architecture with reference to Computer Networks

Network architecture refers to the design of a computer network, including its physical components, their functional organization and configuration, and the principles and protocols governing their operation. It provides a framework for communication between devices on the network.

- **Types of Network Architecture:**
 - **Client-Server:** In this architecture, a central server provides services to multiple client devices. The server manages resources and data, while the clients request and receive information from the server.
 - **Peer-to-Peer (P2P):** In this architecture, all devices on the network act as both clients and servers, sharing resources and data with each other without the need for a central server.
- **OSI Model:** The Open Systems Interconnection (OSI) model is a conceptual framework that describes the functions of a networking system. It divides the communication process into seven layers, with each layer performing a specific function and providing services to the layer above it.

The layers are, from top to bottom: Application, Presentation, Session, Transport, Network, Data Link, and Physical.

- **TCP/IP Model:** The Transmission Control Protocol/Internet Protocol (TCP/IP) model is a simpler, four-layer model that is widely used in modern networks. It consists of the Application, Transport, Internet, and Network Access layers.
- **Protocols:** Network protocols are sets of rules and standards that govern the communication between devices on a network. Some common protocols include TCP, IP, HTTP, FTP, and SMTP.
- **Topologies:** Network topology refers to the arrangement of devices on a network and the connections between them. Common topologies include bus, star, ring, and mesh.
- **Devices:** Common network devices include routers, switches, hubs, and modems. These devices facilitate the communication between devices on a network.
- **Advantages of Network Architecture:**
 - Facilitates communication and resource sharing between devices.
 - Allows for centralized management and control of the network.
 - Provides a framework for the development and implementation of network protocols and standards.
- **Disadvantages of Network Architecture:**
 - Can be complex and difficult to design and implement.
 - May require specialized knowledge and expertise to manage and maintain.
 - Can be vulnerable to security threats and attacks.
- **Mnemonics:** A useful mnemonic for remembering the seven layers of the OSI model is “All People Seem To Need Data Processing” (Application, Presentation, Session, Transport, Network, Data Link, Physical).
- **Learning Trick:** To better understand the different layers of the OSI and TCP/IP models, try visualizing them as a stack of building blocks, with each layer providing a foundation for the layer above it. This can help you remember the order and function of each layer.

Layering principles with reference to Network Architecture in Computer Networks

Layering is a design principle that is used to structure computer networks into multiple layers, each of which provides a specific set of services to the layer above it. This approach simplifies the design, implementation, and maintenance of complex network systems.

1. **Abstraction:** Each layer provides an abstraction that hides the details of the underlying layer from the layers above it. This allows each layer to focus on providing a specific set of services without worrying about the details of how those services are implemented.
2. **Modularity:** The use of layers allows for modularity in the design of network systems. Each layer can be designed, implemented, and tested independently of the other layers. This makes it easier to develop, maintain, and upgrade complex network systems.
3. **Encapsulation:** Each layer adds its own header and/or trailer to the data it receives from the layer above it. This encapsulation of data allows each layer to add its own control information to the data, which is used to provide the services of that layer.
4. **Hierarchy:** The layers in a network system are arranged in a hierarchy, with the lowest layer providing services to the layer above it, and so on. This hierarchy of layers allows for a structured approach to the design of network systems.

A mnemonic to remember the layering principles is **All Men Eat Hamburgers**, where the first letter of each word represents the first letter of each principle: **A**bstraction, **M**odularity, **E**ncapsulation, and **H**ierarchy.

An example of a layered network architecture is the OSI (Open Systems Interconnection) model, which consists of seven layers: Physical, Data Link, Network, Transport, Session, Presentation, and Application. Each layer provides a specific set of services to the layer above it, and the layers work together to provide end-to-end communication between network devices.

In summary, layering is a design principle that is used to structure computer networks into multiple layers, each of which provides a specific set of services to the layer above it. This approach simplifies the design, implementation, and maintenance of complex network systems. The key principles of layering are abstraction, modularity, encapsulation, and hierarchy. An example of a layered network architecture is the OSI model. A mnemonic to remember the layering principles is **All Men Eat Hamburgers**.

Services in Networks Architecture in Computer Networks

In computer networks, the architecture refers to the design and structure of the system, including the hardware, software, and protocols used to enable communication between devices. The services provided by the network architecture are the capabilities and features that the network offers to its users.

Some of the services provided by network architecture include:

1. **Connection-oriented and connectionless services:** Connection-oriented services establish a dedicated connection between devices before

data transmission, while connectionless services transmit data without establishing a dedicated connection.

2. **Reliability:** Networks can provide reliable data transmission through error detection and correction mechanisms, retransmission of lost or corrupted data, and acknowledgement of successful data transmission.
3. **Quality of Service (QoS):** QoS refers to the ability of a network to provide improved service to certain network traffic. This can include prioritizing certain types of traffic, reserving bandwidth, and minimizing latency and jitter.
4. **Security:** Network architecture can provide security services such as authentication, encryption, and access control to protect data transmission and prevent unauthorized access.
5. **Addressing and routing:** Networks use addressing and routing mechanisms to determine the path that data takes from the source to the destination. This can include the use of IP addresses and routing protocols.
6. **Multicasting:** Multicasting is the transmission of data to multiple destinations simultaneously. This can be useful for applications such as video conferencing and online gaming.

These are some of the services provided by network architecture in computer networks. Understanding these services can help in the design and implementation of efficient and effective networks.

Protocols and standards in networks architecture in Computer Networks

- **Protocols** are a set of rules and standards that define how data is transmitted and received over a network. They ensure that devices can communicate with each other and exchange information in a standardized way.
- **Standards** are technical specifications that define how different components of a network should operate and interact with each other. They are developed by organizations such as the International Organization for Standardization (ISO) and the Institute of Electrical and Electronics Engineers (IEEE).
- Some common protocols used in computer networks include:
 - **Transmission Control Protocol (TCP):** This protocol is responsible for establishing connections between devices and ensuring that data is transmitted reliably and in the correct order.
 - **Internet Protocol (IP):** This protocol is responsible for routing data packets between devices on a network. It assigns unique addresses to each device, allowing data to be sent to the correct destination.

- **User Datagram Protocol (UDP)**: This protocol is used for transmitting data that does not require reliable delivery, such as streaming media or online gaming.
- **Hypertext Transfer Protocol (HTTP)**: This protocol is used for transmitting web pages and other data over the internet.
- Some common standards used in computer networks include:
 - **Ethernet**: This is a standard for transmitting data over a local area network (LAN). It defines the physical and data link layers of the network.
 - **Wi-Fi**: This is a standard for transmitting data wirelessly over a local area network. It is based on the IEEE 802.11 family of standards.
 - **Bluetooth**: This is a standard for short-range wireless communication between devices.
- A mnemonic to remember the OSI model layers is “**Please Do Not Throw Sausage Pizza Away**”, which stands for Physical, Data Link, Network, Transport, Session, Presentation, and Application.
- A learning trick to remember the difference between TCP and UDP is that **TCP** is like making a **phone call** where you have to establish a connection before communicating, while **UDP** is like sending a **postcard** where you just send the message without establishing a connection.
- It is important to follow protocols and standards in network architecture to ensure interoperability between different devices and systems. This allows for seamless communication and data exchange, improving the efficiency and reliability of the network.

The OSI reference model in Computer Networks

The Open Systems Interconnection (OSI) reference model is a conceptual framework that describes the functions of a networking or telecommunication system. The model partitions the flow of data in a communication system into seven abstraction layers, from the physical implementation of transmitting bits across a communications medium to the highest-level representation of data and interactions with application software.

Here are the seven layers of the OSI model, along with their functions and protocols:

1. **Physical Layer (Layer 1)**: This layer is responsible for the transmission and reception of raw, unstructured data between devices. It converts digital data into electrical, radio, or optical signals and vice versa. Some common protocols and standards associated with this layer include Ethernet, USB, and Bluetooth.
2. **Data Link Layer (Layer 2)**: This layer provides reliable data transfer between two directly connected nodes by detecting and possibly correcting

errors that may occur in the Physical layer. It also defines the protocol for accessing the physical medium. Some common protocols associated with this layer include Ethernet, PPP, and ATM.

3. **Network Layer (Layer 3):** This layer is responsible for routing data packets between networks. It also handles the logical addressing of devices and the fragmentation and reassembly of data packets. Some common protocols associated with this layer include IP, ICMP, and OSPF.
4. **Transport Layer (Layer 4):** This layer provides end-to-end communication services, such as connection-oriented data stream support, reliability, flow control, and multiplexing. Some common protocols associated with this layer include TCP, UDP, and SCTP.
5. **Session Layer (Layer 5):** This layer establishes, manages, and terminates connections between applications. It also provides services such as authentication and authorization. Some common protocols associated with this layer include RPC, SQL, and NFS.
6. **Presentation Layer (Layer 6):** This layer is responsible for the representation of data, including character encoding, data compression, and encryption/decryption. Some common standards associated with this layer include ASCII, JPEG, and MPEG.
7. **Application Layer (Layer 7):** This layer provides services to the user, such as file transfer, email, and web browsing. Some common protocols associated with this layer include HTTP, FTP, and SMTP.

A mnemonic to remember the seven layers of the OSI model is “Please Do Not Throw Sausage Pizza Away”, where the first letter of each word represents the first letter of each layer, starting from the bottom (Physical) to the top (Application).

The OSI model is useful for understanding the flow of data in a network and for troubleshooting network issues. However, it is important to note that not all protocols fit neatly into the seven layers, and some protocols operate at multiple layers. Additionally, the OSI model is not the only model for network communication, and other models, such as the TCP/IP model, are also widely used.

TCP/IP protocol suite in Computer Networks

- TCP/IP stands for Transmission Control Protocol/Internet Protocol.
- It is a suite of communication protocols used to interconnect network devices on the internet.
- The suite is named after its two most important protocols: Transmission Control Protocol (TCP) and Internet Protocol (IP).
- TCP/IP provides end-to-end connectivity specifying how data should be formatted, addressed, transmitted, routed, and received at the destination.

- The TCP/IP model has four layers: Application, Transport, Internet, and Network Interface.

Application Layer

- The Application Layer is the topmost layer of the TCP/IP model.
- It provides services to the user and includes protocols such as HTTP, FTP, SMTP, and DNS.
- This layer is responsible for providing user interfaces and support for services such as email, remote file access, and transfer.

Transport Layer

- The Transport Layer is responsible for providing end-to-end communication services.
- It includes protocols such as TCP and UDP.
- TCP is a connection-oriented protocol that provides reliable data transfer, flow control, and error recovery.
- UDP is a connectionless protocol that provides unreliable data transfer and is used for applications that do not require reliability, such as online gaming or streaming media.

Internet Layer

- The Internet Layer is responsible for routing data packets across the network.
- It includes the IP protocol, which is responsible for routing data packets between hosts.
- The Internet Layer also includes the ICMP protocol, which is used for error reporting and control messages.

Network Interface Layer

- The Network Interface Layer is responsible for the physical transmission of data.
- It includes protocols such as Ethernet and Wi-Fi.
- This layer is responsible for transmitting data over the physical network and for providing access to the network.

Mnemonics and Learning Tricks

- A mnemonic to remember the layers of the TCP/IP model is “All People Seem To Need Data Processing” (Application, Transport, Internet, Network Interface).
- Another mnemonic to remember the layers is “Armadillos Take In New Ants” (Application, Transport, Internet, Network Interface).

Network devices in Computer Networks

Network devices are the components used to connect computers or other electronic devices together so that they can share files or resources like printers or fax machines. Devices used to setup a Local Area Network (LAN) are the most common type of network devices used by the public. Here are some common network devices and their functions:

1. **Router:** A router is a device that forwards data packets between computer networks. It is connected to two or more data lines from different networks and uses routing tables in its operating system to determine the best path for forwarding the packets.
2. **Switch:** A switch is a device that filters and forwards packets between LAN segments. Switches operate at the data link layer (layer 2) and sometimes the network layer (layer 3) of the OSI Reference Model and therefore support any packet protocol.
3. **Hub:** A hub is a common connection point for devices in a network. Hubs are commonly used to connect segments of a LAN. A hub contains multiple ports. When a packet arrives at one port, it is copied to the other ports so that all segments of the LAN can see all packets.
4. **Modem:** A modem modulates outgoing digital signals from a computer or other digital device to analog signals for a conventional copper twisted pair telephone line and demodulates the incoming analog signal and converts it to a digital signal for the digital device.
5. **Firewall:** A firewall is a network security system that monitors and controls incoming and outgoing network traffic based on predetermined security rules. A firewall typically establishes a barrier between a trusted internal network and untrusted external network, such as the Internet.
6. **Repeater:** A repeater is an electronic device that receives a signal and retransmits it. Repeaters are used to extend transmissions so that the signal can cover longer distances or be received on the other side of an obstruction.
7. **Bridge:** A network bridge is a computer networking device that creates a single aggregate network from multiple communication networks or network segments. This function is called network bridging. Bridging is distinct from routing, which allows multiple different networks to communicate independently while remaining separate.

A mnemonic to remember these devices is “**Randy Saw His Mom’s Face Red and Blue**” which stands for **R**outer, **S**witch, **H**ub, **M**odem, **F**irewall, **R**epeater, and **B**ridge.

Network Components in Computer Networks

Computer networks are made up of various components that work together to enable communication and data transfer between devices. Some of the main components of a computer network include:

1. **Nodes:** Nodes are devices that are connected to the network and can send and receive data. Examples of nodes include computers, printers, and servers.
2. **Network Interface Cards (NICs):** A network interface card is a hardware component that connects a device to the network. It provides a physical connection between the device and the network medium.
3. **Switches:** Switches are used to connect multiple devices on a network. They receive data from one device and forward it to the appropriate destination device.
4. **Routers:** Routers are used to connect multiple networks and route data between them. They use routing tables to determine the best path for data to travel between networks.
5. **Cables:** Cables are used to physically connect devices on a network. There are various types of cables, including Ethernet, coaxial, and fiber optic.
6. **Wireless Access Points (WAPs):** Wireless access points are used to connect wireless devices to a wired network. They broadcast a wireless signal that devices can connect to.
7. **Firewalls:** Firewalls are used to protect networks from unauthorized access. They monitor incoming and outgoing network traffic and block or allow data based on a set of predefined rules.
8. **Modems:** Modems are used to connect a network to the internet. They modulate and demodulate signals to enable data transfer over telephone or cable lines.
9. **Hubs:** Hubs are used to connect multiple devices on a network. They receive data from one device and broadcast it to all other connected devices.
10. **Repeaters:** Repeaters are used to extend the range of a network by regenerating and amplifying the signal.

These are some of the main components of a computer network. Each component plays a specific role in enabling communication and data transfer between devices.

Physical Layer in Computer Networks

The Physical Layer is the first and lowest layer of the OSI (Open Systems Interconnection) model. It is responsible for the transmission and reception of

unstructured raw data between a device and a physical transmission medium. It converts the digital bits into electrical, radio, or optical signals.

Some of the functions of the Physical Layer include: - Defining the physical characteristics of the transmission medium, such as the type of cable, connectors, and signaling methods. - Establishing and terminating connections between devices. - Modulating and demodulating signals. - Encoding and decoding data. - Controlling the transmission rate and synchronizing the bit streams.

Some common Physical Layer standards include: - Ethernet - Wi-Fi - Bluetooth - USB - DSL

A mnemonic to remember the functions of the Physical Layer is “Please Do Not Throw Sausage Pizza Away”, where the first letter of each word represents the first letter of each layer of the OSI model, with the Physical Layer being the first “P”.

An example of the Physical Layer in action is when a computer sends data to a printer. The data is first converted into electrical signals by the computer’s network interface card (NIC) and then transmitted over a cable to the printer. The printer’s NIC receives the signals, converts them back into digital data, and sends the data to the printer’s processor for printing.

In summary, the Physical Layer is responsible for the physical transmission of data between devices and is the foundation upon which all other layers of the OSI model are built. It is essential for establishing and maintaining reliable communication between devices in a computer network.

Network topology design in Computer Networks

Network topology is used to describe the physical and logical structure of a network. It maps the way different nodes on a network, including switches and routers, are placed and interconnected, as well as how data flows. Diagramming the locations of endpoints and service requirements helps determine the best placement for each node to optimize traffic flows.

Network topology is how participating computers, antennas, sensors, and other devices are arranged and interact in a network. Several types of topology can be used to organize and direct the flow of data within networks. Selection of the most appropriate topology is a critical part of network design and takes into consideration various factors.

The two major categories of topology are physical and logical. A Network Topology is the arrangement with which computer systems or network devices are connected to each other. Topologies may define both physical and logical aspect of the network. Both logical and physical topologies could be same or different in a same network.

Types of connections in Computer Networks

There are three basic types of network connections that exist:

1. **Point-to-point connections** allow one device to communicate with one other device. For example, two phones may pair with each other to exchange data.
2. **Broadcast/multicast connections** allow a device to send one message out to the network and have copies of that message delivered to multiple recipients.
3. **Multipoint connections** allow one device to connect and deliver messages to multiple devices in parallel.

These connections allow devices in a network to communicate and share information and resources. Networks follow protocols, which define how communications are sent and received.

Transmission media in Computer Networks

Transmission media refers to the physical pathways that carry data signals between devices in a computer network. There are two main types of transmission media: guided and unguided.

1. **Guided media:** Guided media, also known as wired or bounded transmission media, use a physical conductor to transmit data signals. Examples of guided media include:
 - **Twisted pair cable:** Consists of two insulated copper wires twisted together to reduce interference.
 - **Coaxial cable:** Consists of a central copper conductor surrounded by an insulating layer, a braided shield, and an outer insulating layer.
 - **Fiber optic cable:** Uses light to transmit data signals through a glass or plastic core surrounded by a cladding layer.
2. **Unguided media:** Unguided media, also known as wireless or unbounded transmission media, use air or space as the transmission medium. Examples of unguided media include:
 - **Radio waves:** Electromagnetic waves that can travel through the air and are commonly used for wireless communication.
 - **Microwaves:** Electromagnetic waves with a higher frequency than radio waves, commonly used for long-distance communication.
 - **Infrared:** Electromagnetic waves with a higher frequency than microwaves, commonly used for short-range communication.

Each type of transmission media has its own advantages and disadvantages. For example, guided media generally offer higher data rates and are more secure, but are limited by the physical constraints of the conductor. Unguided media offer more flexibility and mobility, but are more susceptible to interference and have lower data rates.

Mnemonics: - Guided media can be remembered as “Twisted Coaxial Fiber”

(TCF). - Unguided media can be remembered as “Radio Microwave Infrared” (RMI).

Signal transmission and encoding in Computer Networks

Signal transmission is the process of transmitting data from one point to another in a computer network. Encoding is the process of converting data into a format that can be transmitted over a communication channel.

1. **Analog and Digital Signals:** Signals can be either analog or digital. Analog signals are continuous and can take on any value within a range, while digital signals are discrete and can only take on a finite number of values.
2. **Modulation:** Modulation is the process of varying one or more properties of a carrier signal, such as its amplitude, frequency, or phase, in order to encode information onto it. This is commonly used in analog transmission.
3. **Encoding Schemes:** There are several encoding schemes used in digital transmission, including Non-Return-to-Zero (NRZ), Manchester, and 4B/5B. These schemes define how the digital data is represented as a sequence of voltage levels or light pulses.
4. **Error Detection and Correction:** Transmission errors can occur due to noise or interference on the communication channel. Error detection and correction techniques, such as parity checking and cyclic redundancy check (CRC), can be used to detect and correct these errors.
5. **Multiplexing:** Multiplexing is the process of combining multiple signals into a single signal for transmission over a shared communication channel. This allows multiple users to share the same channel, increasing the efficiency of the network.

A mnemonic to remember the OSI model layers is “**All People Seem To Need Data Processing**” which stands for Application, Presentation, Session, Transport, Network, Data Link, and Physical.

Network performance and transmission impairments in Computer Networks

Network performance refers to the level of quality of service of a telecommunications product as seen by the customer. It should not be seen merely as an attempt to get “more through” the network. Performance can also be modeled in terms of the availability of network resources.

Transmission impairments are factors that degrade the quality of a transmitted signal. These impairments can be caused by a variety of factors, including attenuation, delay distortion, and noise.

- **Attenuation:** Attenuation is the loss of signal strength as it travels through a medium. This can be caused by the absorption of the signal by the medium, as well as by scattering and reflection. Attenuation is measured in decibels (dB) and is typically greater at higher frequencies.
- **Delay distortion:** Delay distortion occurs when different frequency components of a signal arrive at the receiver at different times. This can cause the signal to become distorted, as the different frequency components are no longer in phase with one another. Delay distortion is typically caused by the dispersion of the signal as it travels through the medium.
- **Noise:** Noise is any unwanted signal that interferes with the transmission of the desired signal. There are many sources of noise, including thermal noise, intermodulation noise, and crosstalk. Noise can cause errors in the received signal, which can result in a degradation of the quality of the transmitted information.

Mnemonics and learning tricks: - **A**ttenuation **D**elay distortion **N**oise: **ADN** (like DNA, but with an A instead of a D). - **A**ttenuation is the **A**bsorption of the signal. - **D**elay **D**istortion is caused by **D**ispersion of the signal. - **N**oise is any u**N**wanted signal.

Switching techniques and multiplexing in Computer Networks

Switching techniques are methods used to connect multiple devices in a network to communicate with each other. There are three main types of switching techniques: Circuit Switching, Message Switching, and Packet Switching.

1. **Circuit Switching:** In Circuit switching, two nodes communicate with each other over a dedicated communication path.
2. **Message Switching:** In message switching, the whole message is treated as a data unit.
3. **Packet Switching:** The packet switching technique is derived from message switching where the message is broken down into smaller chunks called Packets.

Multiplexing is a method by which multiple analog or digital signals are combined into one signal over a shared medium. It is a technique through which low-speed signals are converted into high-speed signals. Multiplexing is the set of techniques that allows the simultaneous transmission of multiple signals across a single data link.

Statistical Multiplexing is a communication link sharing technique, which is used in packet switching. The shared linking is variable in statistical multiplexing, whereas it is fixed in TDM or FDM. This is a strategic application for maximizing the utilization of bandwidth. This can increase the efficiency of the network, as well.

A **Multiplexer/MUX** is the device which does all this function (many to one)

i.e., at source end. A **Demultiplexer/DEMUX** is a device which performs functions reverse to that of MUX (one to many) i.e., at destination end.

Unit 2 - Link layer in Computer Networks and Medium Access Control and Local Area Networks

The link layer is the lowest layer in the OSI model of computer networking. It is responsible for the transmission of data between two directly connected nodes. The link layer is responsible for the following tasks:

1. Framing: The link layer takes the packets from the network layer and encapsulates them into frames. Each frame contains a header, payload, and trailer. The header contains the source and destination addresses, while the trailer contains error detection and correction information.
2. Error detection and correction: The link layer is responsible for detecting and correcting errors that may occur during transmission. This is done using techniques such as parity checking, checksums, and cyclic redundancy checks (CRC).
3. Flow control: The link layer is responsible for regulating the flow of data between two nodes. This is done to prevent the receiver from being overwhelmed by the sender.
4. Medium access control: The link layer is responsible for controlling access to the shared communication medium. This is done using techniques such as time division multiple access (TDMA), frequency division multiple access (FDMA), and carrier sense multiple access with collision detection (CSMA/CD).

Local Area Networks (LANs) are computer networks that are designed to operate over a small geographical area, such as a home, office, or campus. LANs are typically used to connect computers and other devices within a single building or group of buildings.

The most common type of LAN is the Ethernet LAN. Ethernet LANs use the CSMA/CD protocol for medium access control. In an Ethernet LAN, all devices are connected to a shared communication medium, such as a coaxial cable or twisted pair cable. When a device wants to transmit data, it listens to the medium to see if it is free. If the medium is free, the device transmits its data. If the medium is busy, the device waits for a random amount of time before trying again.

Mnemonics and learning tricks: - **F**raming, **E**rror detection and correction, **F**low control, **M**edium access control: **F**our **E**ssential **F**unctions of the **M**edium access control sublayer. - **C**arrier **S**ense **M**ultiple **A**ccess with **C**ollision **D**etection: **C**ats **S**ee **M**ice **A**nd **C**hase **D**own.

Link layer in Computer Networks

The link layer is the lowest layer in the OSI (Open Systems Interconnection) model of computer networking. It is responsible for the transmission of data between two directly connected nodes. The link layer is also responsible for error detection and correction, flow control, and framing.

Some of the key functions of the link layer include:

1. **Framing:** The link layer takes the packets from the network layer and encapsulates them into frames. Each frame contains a header, payload, and trailer. The header contains information such as the source and destination addresses, while the trailer contains error detection and correction information.
2. **Error detection and correction:** The link layer is responsible for detecting and correcting errors that may occur during transmission. This is done using techniques such as parity checking and checksums.
3. **Flow control:** The link layer is responsible for regulating the flow of data between two nodes. This is done to prevent the receiver from being overwhelmed by data.
4. **Media access control:** The link layer is responsible for controlling access to the shared transmission medium. This is done using techniques such as CSMA/CD (Carrier Sense Multiple Access with Collision Detection) and token passing.

Some common link layer protocols include Ethernet, Wi-Fi, and Bluetooth.

A mnemonic to remember the functions of the link layer is **FEMM** - **F**raming, **E**rror detection and correction, **M**edia access control, and **M**edia access control.

An example of the link layer in action is when a computer sends data to a printer over a wired connection. The link layer on the computer takes the data from the network layer, encapsulates it into frames, and sends it to the printer. The link layer on the printer receives the frames, checks for errors, and passes the data to the network layer for further processing.

In summary, the link layer is responsible for the transmission of data between two directly connected nodes. It performs functions such as framing, error detection and correction, flow control, and media access control. Common link layer protocols include Ethernet, Wi-Fi, and Bluetooth. A mnemonic to remember the functions of the link layer is FEMM. An example of the link layer in action is when a computer sends data to a printer over a wired connection.

Framing in link layer in Computer Networks

Framing is a function of the link layer in computer networks. It is the process of encapsulating data into frames for transmission over the network. Here are some key points to remember about framing in the link layer:

1. The link layer is responsible for providing a reliable connection between two directly connected nodes in a network.
2. Framing is the process of dividing the data stream into smaller units called frames for transmission over the network.
3. Each frame contains a header, payload, and trailer. The header contains information such as the source and destination addresses, while the trailer contains error-detection information.
4. The link layer uses various framing methods to encapsulate data into frames. Some common framing methods include character counting, byte stuffing, and bit stuffing.
5. The link layer is also responsible for error detection and correction. It uses techniques such as checksums and cyclic redundancy checks to detect errors in the transmitted frames.
6. Once the frames are received at the destination, the link layer decapsulates the data and passes it to the upper layers for further processing.

Error Detection and Correction in link layer in Computer Networks

Error detection and correction are techniques used in the link layer of computer networks to ensure the integrity of data transmitted over a communication channel. These techniques are used to detect and correct errors that may occur during transmission due to noise, interference, or other factors.

1. **Error Detection:** Error detection techniques are used to detect errors in the transmitted data. Some common error detection techniques include parity check, checksum, and cyclic redundancy check (CRC).
 - **Parity Check:** Parity check is a simple error detection technique that adds an extra bit, called the parity bit, to the data. The parity bit is set to 1 or 0 to make the total number of 1s in the data (including the parity bit) even or odd. The receiver checks the parity of the received data and if it is incorrect, an error is detected.
 - **Checksum:** Checksum is another error detection technique that calculates a value based on the data and sends it along with the data. The receiver recalculates the checksum and compares it with the received checksum. If the two values do not match, an error is detected.
 - **Cyclic Redundancy Check (CRC):** CRC is a more complex error detection technique that uses polynomial division to calculate a value based on the data. This value is sent along with the data and the receiver recalculates the value and compares it with the received value. If the two values do not match, an error is detected.
2. **Error Correction:** Error correction techniques are used to correct errors in the transmitted data. Some common error correction techniques include Hamming code, Reed-Solomon code, and convolutional code.
 - **Hamming Code:** Hamming code is an error correction technique that adds extra bits, called check bits, to the data. These check bits

are calculated based on the data and are used to detect and correct errors. Hamming code can detect and correct single-bit errors and detect double-bit errors.

- **Reed-Solomon Code:** Reed-Solomon code is an error correction technique that is widely used in applications such as CDs, DVDs, and data transmission. Reed-Solomon code can correct multiple errors and is well suited for correcting burst errors (errors that occur in a consecutive sequence of bits).
- **Convolutional Code:** Convolutional code is an error correction technique that is widely used in wireless communication. Convolutional code adds redundancy to the data by encoding it using a convolutional encoder. The receiver uses a Viterbi decoder to decode the data and correct errors.

Mnemonics and learning tricks: - **Error Detection:** Parity Check, Checksum, Cyclic Redundancy Check (CRC) can be remembered as **PCC**. - **Error Correction:** Hamming Code, Reed-Solomon Code, Convolutional Code can be remembered as **HRC**.

These techniques are essential for ensuring the reliability of data transmission in computer networks. They are widely used in various applications and are an important part of the link layer of computer networks.

Flow control in link layer in Computer Networks


Flow control is a mechanism used in the link layer of computer networks to prevent the sender from overwhelming the receiver with data. This is achieved by regulating the rate at which data is transmitted from the sender to the receiver.

There are two main methods of flow control in the link layer: stop-and-wait and sliding window.

1. **Stop-and-wait:** In this method, the sender sends a single frame and then waits for an acknowledgment from the receiver before sending the next frame. If the acknowledgment is not received within a certain time period, the sender retransmits the frame. This method is simple to implement but can result in low throughput due to the time spent waiting for acknowledgments.
2. **Sliding window:** In this method, the sender is allowed to transmit multiple frames without waiting for acknowledgments. The receiver sends an acknowledgment for each frame received, and the sender uses this information to determine which frames have been successfully received and which need to be retransmitted. This method can result in higher throughput than stop-and-wait, but it is more complex to implement.

Both methods have their advantages and disadvantages, and the choice of method depends on the specific requirements of the network.

Here is an example of a sliding window protocol:



In this example, the sender is allowed to transmit up to four frames (the window size) without waiting for an acknowledgment. The receiver sends an acknowledgment for each frame received, and the sender uses this information to slide the window forward and transmit new frames.

Advantages of flow control in the link layer: - Prevents the sender from overwhelming the receiver with data. - Can improve the efficiency of data transmission by regulating the rate at which data is transmitted.

Disadvantages of flow control in the link layer: - Can add complexity to the link layer protocol. - Can reduce the throughput of the link if not implemented correctly.

Mnemonic: **Stop-and-Wait**, **Sliding Window** - **SWSW** (pronounced “swiss”) for the two main methods of flow control in the link layer.

Elementary Data Link Protocols in link layer in Computer Networks

The data link layer is responsible for providing reliable data transfer between two adjacent nodes in a network. This layer is responsible for framing, flow control, error control, and media access control. The data link layer is divided into two sublayers: the Logical Link Control (LLC) and the Media Access Control (MAC).

Elementary Data Link Protocols are the basic protocols used in the data link layer to provide reliable data transfer. Some of the commonly used Elementary Data Link Protocols are:

1. **Stop-and-Wait ARQ**: This protocol uses a stop-and-wait mechanism for flow control and error control. In this protocol, the sender sends a frame and waits for an acknowledgment from the receiver before sending

the next frame. If the acknowledgment is not received within a specified time, the sender retransmits the frame.

2. **Go-Back-N ARQ:** This protocol uses a sliding window mechanism for flow control and error control. In this protocol, the sender can send multiple frames without waiting for an acknowledgment, but the number of unacknowledged frames cannot exceed the window size. If an error is detected, the sender retransmits all the frames starting from the erroneous frame.
3. **Selective Repeat ARQ:** This protocol also uses a sliding window mechanism for flow control and error control. In this protocol, the sender can send multiple frames without waiting for an acknowledgment, but the number of unacknowledged frames cannot exceed the window size. If an error is detected, the sender only retransmits the erroneous frame.

These protocols have their own advantages and disadvantages. For example, the Stop-and-Wait ARQ protocol is simple to implement but has low efficiency due to the waiting time. The Go-Back-N ARQ protocol has higher efficiency but may result in the retransmission of correctly received frames. The Selective Repeat ARQ protocol has the highest efficiency but is more complex to implement.

A mnemonic to remember these protocols is “**Stop, Go back, Selectively Repeat**”. This can help you remember the order and names of the protocols.

These protocols are used in various applications such as wireless networks, satellite communication, and computer networks. They are essential for providing reliable data transfer in these networks.

Sliding Window protocols in link layer in Computer Networks

Sliding Window protocols are a method of flow control for network data transfers at the link layer. They are used to ensure that data is transmitted reliably and efficiently over a network.

1. **How it works:** The sender maintains a window of packets that it is allowed to send. The receiver also maintains a window of packets that it is allowed to receive. The size of the window determines the number of packets that can be sent or received at any given time. The sender sends packets within its window and waits for acknowledgements from the receiver. The receiver sends acknowledgements for the packets it receives and slides its window to allow for more packets to be received. The sender slides its window when it receives acknowledgements, allowing it to send more packets.
2. **Advantages:** Sliding Window protocols provide a reliable and efficient method of transmitting data over a network. They ensure that packets are not lost or duplicated and that they are transmitted in the correct order.

They also allow for efficient use of network bandwidth by controlling the flow of data.

3. **Disadvantages:** Sliding Window protocols can be complex to implement and may require significant processing power and memory. They may also be less efficient in networks with high latency or packet loss.
4. **Examples:** Some examples of Sliding Window protocols include the Transmission Control Protocol (TCP) and the High-Level Data Link Control (HDLC) protocol.
5. **Applications:** Sliding Window protocols are commonly used in computer networks for reliable data transfer. They are used in a wide range of applications, including file transfers, email, and web browsing.
6. **Mnemonics and learning tricks:** One way to remember the basic concept of Sliding Window protocols is to think of a physical window that slides along a track. The window represents the range of packets that can be sent or received at any given time. As packets are sent or received, the window slides along the track to allow for more packets to be transmitted.

Medium Access Control and Local Area Networks

- Medium Access Control (MAC) is a sublayer of the Data Link Layer in the OSI model.
- MAC is responsible for controlling how devices in a network gain access to a shared medium and transmit data.
- In Local Area Networks (LANs), the shared medium is typically a cable or wireless connection.
- MAC protocols are used to ensure that only one device transmits data at a time, to avoid collisions and maximize network efficiency.
- Some common MAC protocols used in LANs include:
 - Carrier Sense Multiple Access with Collision Detection (CSMA/CD): used in Ethernet networks.
 - Carrier Sense Multiple Access with Collision Avoidance (CSMA/CA): used in wireless networks.
 - Token Ring: used in some older LANs.
- A mnemonic to remember the difference between CSMA/CD and CSMA/CA is “CD = Collision Detection, CA = Collision Avoidance”.
- LANs are networks that connect devices in a limited geographical area, such as a home, office, or campus.
- LANs can be connected to other LANs or to Wide Area Networks (WANs) to form larger networks.
- LANs can use various technologies, including Ethernet, Wi-Fi, and Bluetooth.
- Advantages of LANs include:
 - High-speed data transfer.
 - Resource sharing, such as printers and storage devices.

- Centralized management and security.
- Disadvantages of LANs include:
 - Limited geographical range.
 - Potential for congestion and reduced network performance.
 - Cost of equipment and maintenance.

Channel allocation in medium access control

Channel allocation in medium access control refers to the process of assigning communication channels to devices in a network. This is necessary to avoid interference and ensure efficient use of the available bandwidth. There are several methods for channel allocation, including:

1. **Fixed Channel Allocation (FCA):** In this method, channels are permanently assigned to devices or cells. This can result in inefficient use of the available channels if the traffic is not evenly distributed.
2. **Dynamic Channel Allocation (DCA):** In this method, channels are assigned to devices or cells on demand. This can result in more efficient use of the available channels, but requires more complex algorithms and control mechanisms.
3. **Hybrid Channel Allocation (HCA):** This method combines elements of both FCA and DCA, with some channels permanently assigned and others dynamically allocated.

A mnemonic to remember these three methods is “**FDH**” - Fixed, Dynamic, Hybrid.

Advantages of channel allocation in medium access control include:

- Reduced interference between devices
- More efficient use of the available bandwidth
- Improved network performance

Disadvantages of channel allocation in medium access control include:

- Increased complexity of the network control mechanisms
- Potential for suboptimal allocation of channels if the traffic is not evenly distributed

Examples of applications that use channel allocation in medium access control include cellular networks, wireless local area networks (WLANs), and satellite communication systems.

In summary, channel allocation in medium access control is an important process that helps to ensure efficient use of the available bandwidth and reduce interference between devices in a network. There are several methods for channel allocation, including fixed, dynamic, and hybrid, each with its own advantages and disadvantages. Mnemonics and learning tricks such as “FDH” can help to remember the different methods. Channel allocation is used in a variety of

applications, including cellular networks, WLANs, and satellite communication systems.

Multiple access protocols in medium access control

Multiple access protocols are used in medium access control (MAC) to coordinate the access of multiple devices to a shared communication medium. These protocols are essential in networks where multiple devices share a common channel, such as in wireless networks or local area networks (LANs).

There are several types of multiple access protocols, including:

1. **Frequency Division Multiple Access (FDMA):** This protocol assigns a unique frequency band to each device on the network. Each device transmits its data using its assigned frequency band, avoiding interference with other devices.
2. **Time Division Multiple Access (TDMA):** This protocol divides the channel into time slots and assigns each device a unique time slot for transmission. Each device transmits its data during its assigned time slot, avoiding interference with other devices.
3. **Code Division Multiple Access (CDMA):** This protocol assigns a unique code to each device on the network. Each device transmits its data using its assigned code, and the receiver uses the same code to extract the data from the received signal.
4. **Carrier Sense Multiple Access (CSMA):** This protocol allows devices to sense the carrier signal on the channel before transmitting. If the channel is busy, the device waits for a random time before attempting to transmit again.
5. **Carrier Sense Multiple Access with Collision Detection (CSMA/CD):** This protocol is an extension of CSMA, where devices can detect collisions on the channel. If a collision is detected, the device waits for a random time before attempting to transmit again.
6. **Carrier Sense Multiple Access with Collision Avoidance (CSMA/CA):** This protocol is another extension of CSMA, where devices use a handshake mechanism to avoid collisions on the channel.

Each of these protocols has its advantages and disadvantages, and the choice of protocol depends on the specific requirements of the network.

A mnemonic to remember the different types of multiple access protocols is “FTC3”: Frequency, Time, Code, Carrier Sense, Collision Detection, Collision Avoidance.

LAN standards in local area network

A local area network (LAN) is a computer network that interconnects computers within a limited area such as a residence, school, laboratory, university campus or office building. LAN standards define the protocols and technologies used to create and maintain a LAN.

Some of the most common LAN standards include:

1. **Ethernet (IEEE 802.3):** Ethernet is the most widely used LAN technology. It uses a bus or star topology and supports data transfer rates of 10 Mbps, 100 Mbps, 1 Gbps, and 10 Gbps.
2. **Token Ring (IEEE 802.5):** Token Ring is a LAN technology that uses a ring topology. It supports data transfer rates of 4 Mbps and 16 Mbps.
3. **Fiber Distributed Data Interface (FDDI):** FDDI is a LAN technology that uses a dual-ring topology and supports data transfer rates of 100 Mbps.
4. **Wireless LAN (IEEE 802.11):** Wireless LAN, also known as Wi-Fi, is a LAN technology that uses radio waves to transmit data. It supports data transfer rates of up to 1.3 Gbps.

Each of these standards has its own advantages and disadvantages, and the choice of which standard to use depends on the specific needs and requirements of the network.

A mnemonic to remember the LAN standards is “**E.T. Found Wi-Fi**” which stands for **E**thernet, **T**oken **R**ing, **F**DDI, and **W**ireless **L**AN.

Link layer switches & bridges in local area network

- Link layer switches and bridges are networking devices that operate at the data link layer (layer 2) of the OSI model.
- They are used to connect multiple devices on a local area network (LAN) and to filter and forward data packets between them.
- Switches and bridges work by learning the MAC addresses of the devices connected to them and forwarding data packets to the appropriate destination based on the destination MAC address.
- Switches are more advanced than bridges and can have multiple ports, allowing them to connect multiple devices simultaneously.
- Bridges, on the other hand, typically have only two ports and are used to connect two separate LANs or to divide a larger LAN into smaller segments.
- Both switches and bridges can improve network performance by reducing the number of unnecessary data transmissions and collisions.
- A mnemonic to remember the difference between switches and bridges is: **S**witches have multiple **S**ockets, while **B**ridges **B**ridge two LANs.
- An example of a switch in a LAN is a home router that connects multiple devices such as computers, smartphones, and smart home devices to the

internet.

- An example of a bridge in a LAN is a wireless bridge that connects two separate LANs, such as two buildings on a campus, using a wireless link.

Learning bridge algorithms in local area network

A bridge is a device that connects two or more local area networks (LANs) or segments of the same LAN. A bridge operates at the data link layer (layer 2) of the OSI model and uses MAC addresses to determine where to forward traffic.

Bridge algorithms are used to determine the best path for forwarding traffic between different segments of a LAN. Some common bridge algorithms include:

1. **Transparent Bridging:** This is the most common type of bridging used in Ethernet networks. In transparent bridging, the bridge learns the MAC addresses of the devices connected to each of its ports by examining the source addresses of incoming frames. The bridge then uses this information to build a forwarding table, which it uses to determine where to forward traffic.
2. **Source Route Bridging:** This type of bridging is used in Token Ring networks. In source route bridging, the source device specifies the entire path that the frame should take through the network. The bridge uses this information to forward the frame to its destination.
3. **Spanning Tree Protocol (STP):** This is a protocol used to prevent loops in a network with redundant paths. STP is used in conjunction with transparent bridging to ensure that there is only one active path between any two network segments.

Mnemonics and learning tricks: - To remember the three types of bridge algorithms, you can use the acronym **TSS**: **T**ransparent Bridging, **S**ource Route Bridging, **S**panning Tree Protocol. - To remember the order of the OSI model layers, you can use the mnemonic **Please Do Not Throw Sausage Pizza Away**: **P**hysical, **D**ata Link, **N**etwork, **T**ransport, **S**ession, **P**resentation, **A**pplication.

Spanning Tree Algorithms in Local Area Network

- Spanning Tree Protocol (STP) is a network protocol that ensures a loop-free topology for any bridged Ethernet local area network.
- STP was invented by Dr. Radia Perlman while working for Digital Equipment Corporation.
- The basic function of STP is to prevent bridge loops and the broadcast radiation that results from them.
- STP creates a spanning tree within a mesh network of connected layer-2 bridges, and disables those links that are not part of the spanning tree, leaving a single active path between any two network nodes.

- STP uses the Spanning Tree Algorithm (STA) to determine the best path between network nodes.
- STA assigns a numerical value called a Bridge Protocol Data Unit (BPDU) to each bridge in the network. The bridge with the lowest BPDU is elected as the root bridge.
- The root bridge is responsible for generating BPDUs and sending them to other bridges in the network.
- Each bridge uses the received BPDUs to determine the shortest path to the root bridge and disables all other paths.
- If a link fails, STP recalculates the spanning tree and activates a previously disabled path to maintain network connectivity.
- STP can take up to 50 seconds to converge on a new topology after a link failure, which can cause temporary network outages.
- Rapid Spanning Tree Protocol (RSTP) is an evolution of STP that provides faster convergence times.
- RSTP can converge on a new topology in less than 10 seconds, reducing the impact of link failures on network availability.
- RSTP is backward compatible with STP and can be used in mixed networks.

Mnemonics and Learning Tricks: - Remember the acronym STP for Spanning Tree Protocol. - Remember that STP prevents loops in a network by creating a spanning tree. - Remember that the root bridge is the bridge with the lowest BPDU. - Remember that RSTP is an evolution of STP that provides faster convergence times.

Unit 3 - Network Layer in Computer Networks

The network layer is responsible for routing data packets from the source to the destination. It is the third layer of the OSI model and is also known as the Internet layer in the TCP/IP model.

1. **Routing:** The network layer is responsible for finding the best path for data packets to travel from the source to the destination. This is done through the use of routing algorithms and protocols such as OSPF, RIP, and BGP.
2. **Logical Addressing:** The network layer uses logical addresses, such as IP addresses, to identify devices on the network. These addresses are used by the routing algorithms to determine the best path for data packets.
3. **Fragmentation and Reassembly:** The network layer is responsible for breaking down large data packets into smaller packets, known as fragments, for transmission. It is also responsible for reassembling the fragments at the destination.
4. **Error Control and Flow Control:** The network layer is responsible for detecting and correcting errors that may occur during transmission. It

also manages the flow of data to prevent congestion and ensure reliable delivery.

A mnemonic to remember the functions of the network layer is “**Real Friends Fight Everytime**”, where each letter stands for Routing, Logical Addressing (Friends), Fragmentation and Reassembly (Fight), and Error Control and Flow Control (Everytime).

An example of the network layer in action is when you send an email from your computer to a friend’s computer. The network layer on your computer determines the best path for the data packets to travel, assigns a logical address to the destination, breaks down the data into smaller packets, and manages the flow of data to ensure reliable delivery. At the destination, the network layer reassembles the packets and delivers the email to your friend’s inbox.

In summary, the network layer is responsible for routing, logical addressing, fragmentation and reassembly, and error and flow control. It plays a crucial role in ensuring reliable and efficient communication on a computer network.

Point-to-point networks in network layer

- Point-to-point networks are a type of network topology in which each connection is a direct link between two endpoints.
- In the network layer, point-to-point networks are used to establish direct connections between two devices, such as two routers or a router and a host.
- Point-to-point networks are commonly used in Wide Area Networks (WANs) to connect remote locations.
- Point-to-point networks can be implemented using various technologies, such as leased lines, Frame Relay, or Asynchronous Transfer Mode (ATM).
- In a point-to-point network, data is transmitted directly from one endpoint to the other, without the need for intermediate devices such as switches or hubs.
- Point-to-point networks are generally considered to be more reliable and secure than other types of networks, as there are fewer points of failure.
- However, point-to-point networks can be more expensive to implement and maintain, as each connection requires a dedicated link.
- A mnemonic to remember the characteristics of point-to-point networks is “Direct, WAN, Various, No intermediate, Reliable, Expensive” (DWNRE).

Logical addressing in network layer

- Logical addressing is used to provide a universal addressing scheme for identifying hosts on a network.
- It is used to route data between networks and to identify devices on different networks.

- The most common logical addressing scheme is the Internet Protocol (IP) addressing scheme.
- IP addresses are hierarchical and consist of two parts: the network ID and the host ID.
- The network ID identifies the network to which the host belongs, while the host ID identifies the specific host on that network.
- IP addresses are assigned to devices by the network administrator or by a Dynamic Host Configuration Protocol (DHCP) server.
- IP addresses can be either static or dynamic. Static IP addresses are manually assigned and do not change, while dynamic IP addresses are assigned by a DHCP server and can change over time.
- The network layer uses logical addresses to route data between networks. Routers use routing tables to determine the best path for forwarding data based on the destination IP address.
- Logical addressing is essential for communication between devices on different networks and is a key component of the network layer.

Mnemonic: **Logical Addressing Identifies Hosts On Networks - L.A.I.H.O.N.**

Basic internetworking in network layer

The network layer is responsible for routing data packets from the source to the destination. It is the third layer of the OSI model and is responsible for logical addressing and routing. The following are some key points to remember about basic internetworking in the network layer:

1. The network layer uses logical addresses, such as IP addresses, to identify devices on the network. These addresses are used to route data packets to their destination.
2. Routers are the primary devices used in the network layer to route data packets between networks. They use routing tables to determine the best path for a packet to take to reach its destination.
3. The network layer is responsible for fragmentation and reassembly of data packets. If a packet is too large to be transmitted over a particular link, it is broken into smaller packets, transmitted, and then reassembled at the destination.
4. The network layer is also responsible for error handling and congestion control. If a packet is lost or corrupted during transmission, the network layer can request that it be retransmitted. It can also implement congestion control mechanisms to prevent network congestion.
5. The Internet Protocol (IP) is the most widely used protocol in the network layer. It is responsible for routing data packets across the Internet.
6. There are two versions of IP in use today: IPv4 and IPv6. IPv6 was developed to address the limitations of IPv4, including the limited address

space.

7. The network layer can use both connection-oriented and connectionless services. In a connection-oriented service, a virtual circuit is established between the source and destination before data transmission begins. In a connectionless service, data packets are sent without establishing a connection first.
8. The network layer can also provide Quality of Service (QoS) guarantees, such as guaranteed bandwidth or low latency, for certain types of traffic.

A mnemonic to remember the functions of the network layer is **“RIFE”** - **R**outing, **I**nternetworking, **F**ragmentation and reassembly, and **E**rror handling and congestion control.

IP

- IP stands for Internet Protocol.
- It is a set of rules that govern the format of data sent over the internet or other networks.
- IP is a connectionless protocol, which means that it does not establish a connection before sending data.
- IP is responsible for routing data packets between devices on a network.
- IP is the primary protocol in the Internet Layer of the Internet Protocol Suite.
- The current version of IP is IPv4, but IPv6 is gradually being adopted to replace it.
- IPv4 addresses are 32-bit numbers, while IPv6 addresses are 128-bit numbers.
- IP addresses are written in dotted decimal notation for IPv4 and in hexadecimal notation for IPv6.
- A mnemonic to remember the difference between IPv4 and IPv6 is: “IPv4 has 4 numbers, IPv6 has 6 groups of numbers”.
- IP provides a best-effort delivery service, which means that it does not guarantee that packets will be delivered or that they will arrive in the same order they were sent.
- IP can be used in conjunction with other protocols, such as TCP and UDP, to provide reliable data transmission.
- Some advantages of IP include its scalability, flexibility, and ability to support multiple network architectures.
- Some disadvantages of IP include its susceptibility to security threats and the limited number of available IPv4 addresses.
- IP is used in a wide range of applications, including web browsing, email, file transfer, and online gaming.

CIDR

CIDR stands for Classless Inter-Domain Routing. It is a method for allocating

IP addresses and routing Internet Protocol packets. CIDR notation is a compact representation of an IP address and its associated routing prefix. It is expressed using the format **address/prefix**, where **address** is the IP address and **prefix** is the number of leading 1 bits in the subnet mask.

- CIDR allows for more efficient use of IP address space and routing table memory.
- CIDR notation makes it easier to aggregate routes, reducing the size of routing tables.
- CIDR is used by Internet Service Providers (ISPs) to allocate IP addresses to customers.
- CIDR can help reduce the number of routing table entries by allowing multiple, contiguous IP address ranges to be represented by a single routing table entry.

A mnemonic to remember CIDR notation is “Slash the Mask.” The slash (/) separates the IP address from the prefix, and the prefix represents the subnet mask.

For example, the CIDR notation 192.168.1.0/24 represents the IP address 192.168.1.0 with a subnet mask of 255.255.255.0. The prefix /24 indicates that the first 24 bits of the IP address are the network portion, while the remaining 8 bits are the host portion.

Advantages of CIDR: - More efficient use of IP address space. - Reduced size of routing tables. - Easier route aggregation.

Disadvantages of CIDR: - Can be more complex to understand and implement than traditional IP addressing and routing.

Applications of CIDR: - Used by ISPs to allocate IP addresses to customers. - Used in enterprise networks to efficiently route traffic.

Example: - An ISP has been allocated the IP address range 203.0.113.0/24. Using CIDR notation, the ISP can allocate smaller blocks of IP addresses to customers, such as 203.0.113.0/25 and 203.0.113.128/25. These smaller blocks can be further subdivided and allocated to individual customers. This allows for more efficient use of the IP address space and reduces the size of routing tables.

ARP

ARP stands for Address Resolution Protocol. It is a protocol used to map an IP address to a physical address, also known as a MAC address, on a local network. Here are some key points to remember about ARP:

1. ARP operates at the Data Link layer of the OSI model.
2. ARP is used to find the MAC address of a device on the local network, given its IP address.

- A helpful mnemonic to remember the function of ARP is: **A**ddress **R**esolution **P**rotocol resolves an **A**ddress to a **R**eal **P**hysical address.

```
Device A (IP: 192.168.1.1)                                Device B (IP: 192.168.1.2)
```

```
|                                                           |
```

```
| ARP Request:                                             |
```

```
| Who has IP 192.168.1.2?                                 |
```

```
| Tell 192.168.1.1                                        |
```

```
|                                                           |
```

```
|                                                           |
```

```
|                                                           |
```

```
|                                                           |
```

```
|                                                           |
```

```
|                                                           |
```

```
|                                                           |
```

```
|                                                           |
```

```
|                                                           |
```

```
|                                                           |
```

```
|                                                           |
```

```
| ARP Reply:                                              |
```

```
| 192.168.1.2 is at                                       |
```

```
| MAC: 00:11:22:33:44:55                                  |
```

- It allows devices on a local network to communicate with each other without the need for manual configuration of MAC addresses.
- It is simple and efficient, as it only requires a single broadcast and reply to resolve an IP address to a MAC address.

- It is not secure, as it is vulnerable to ARP spoofing attacks, where an attacker can send false ARP replies to redirect traffic to their device.
- It is not scalable, as it relies on broadcasts, which can cause congestion on large networks.

ARP is commonly used in local area networks (LANs) to enable communication between devices on the same network. It is an essential protocol for the functioning of the Internet and other IP-based networks.

RARP

RARP stands for Reverse Address Resolution Protocol. It is a protocol used to map a MAC address to an IP address. It is used in situations where a device knows its own MAC address but does not know its IP address.

- RARP operates at the Data Link Layer of the OSI model.
- RARP is used by diskless workstations to obtain an IP address from a RARP server.
- RARP uses the same message format as ARP, but with different operation codes.
- RARP is not widely used anymore and has been replaced by other protocols such as BOOTP and DHCP.

A mnemonic to remember the difference between ARP and RARP is that ARP is used to find the MAC address when the IP address is known, while RARP is used to find the IP address when the MAC address is known. You can remember this by thinking of the “R” in RARP as standing for “Reverse”.

DHCP

- DHCP stands for Dynamic Host Configuration Protocol.
- It is a network management protocol used to dynamically assign IP addresses to devices on a network.
- DHCP operates on a client-server model, where a DHCP server assigns IP addresses to DHCP clients.
- The DHCP server maintains a pool of available IP addresses and assigns them to clients on a lease basis.
- When a client connects to the network, it sends a broadcast message requesting an IP address.
- The DHCP server receives the request and assigns an available IP address to the client.
- The server also provides the client with additional network configuration information, such as the subnet mask, default gateway, and DNS server addresses.
- The client uses the assigned IP address for a specified period of time, known as the lease time.
- When the lease time expires, the client must request a new IP address from the DHCP server.
- DHCP can simplify network management by automatically assigning IP addresses to devices, reducing the need for manual configuration.
- A mnemonic to remember the steps of the DHCP process is DORA: Discover, Offer, Request, Acknowledge.

- Discover: The client sends a broadcast message to discover available DHCP servers.
- Offer: The DHCP server sends an offer message to the client, offering an IP address and other network configuration information.
- Request: The client sends a request message to the server, requesting the offered IP address.
- Acknowledge: The server sends an acknowledgement message to the client, confirming the assignment of the IP address.

ICMP

ICMP stands for Internet Control Message Protocol. It is a network layer protocol used by network devices to send error messages and operational information. ICMP is mainly used to report error conditions and diagnose network issues.

Some of the key features of ICMP are: - ICMP messages are encapsulated within IP datagrams. - ICMP messages are typically generated by network devices, such as routers, to indicate error conditions or provide other information about the state of the network. - ICMP messages are not typically used to exchange data between hosts.

Some common ICMP message types are: - Echo Request and Echo Reply (Ping): Used to test the reachability of a network host. - Destination Unreachable: Indicates that a destination host or network is unreachable. - Time Exceeded: Indicates that a datagram has been discarded because its time to live (TTL) value has reached zero. - Redirect: Used by routers to inform hosts of a better route to a destination.

A mnemonic to remember the ICMP message types is: **E**cho **R**equest, **D**estination **U**nreachable, **T**ime **E**xceeded, **R**edirect (ERDUTER).

ICMP can be useful for diagnosing network issues and ensuring the proper functioning of the network. However, it can also be used for malicious purposes, such as in denial-of-service (DoS) attacks. It is important for network administrators to monitor ICMP traffic and take appropriate measures to secure their networks.

Routing in network layer

Routing is the process of selecting a path for traffic in a network or between or across multiple networks. It is performed by a special device called a router. The network layer is responsible for routing packets from the source to the destination.

1. **Routing algorithms:** There are several routing algorithms used in the network layer, such as shortest path, flooding, distance vector, and link state. These algorithms determine the best path for a packet to take based on various factors such as the number of hops, cost, and congestion.

2. **Routing tables:** Routers maintain routing tables that contain information about the network topology and the best path to reach each destination. These tables are updated periodically or when there is a change in the network.
3. **Routing protocols:** Routing protocols are used to exchange routing information between routers. Some common routing protocols include RIP, OSPF, and BGP.
4. **Static and dynamic routing:** Static routing is when the routing table is manually configured by the network administrator. Dynamic routing is when the routing table is automatically updated using routing protocols.
5. **Advantages of routing in the network layer:** Routing in the network layer provides several advantages such as load balancing, fault tolerance, and scalability.
6. **Mnemonics:** A mnemonic to remember the OSI model layers in order is “Please Do Not Throw Sausage Pizza Away” where the first letter of each word represents a layer: Physical, Data Link, Network, Transport, Session, Presentation, Application.
7. **Learning trick:** To remember the difference between static and dynamic routing, think of static as something that does not change, like a statue, while dynamic is something that changes, like the weather. Static routing is manually configured and does not change unless the network administrator changes it, while dynamic routing automatically updates based on changes in the network.

Forwarding and Delivery in Network Layer

1. The network layer is responsible for forwarding and delivering data packets from the source to the destination.
2. Forwarding refers to the process of moving a packet from one network element to another, while delivery refers to the process of delivering the packet to the final destination.
3. The network layer uses routing algorithms to determine the best path for forwarding packets.
4. The network layer also handles congestion control, which is the process of managing network traffic to prevent congestion and ensure efficient data transmission.
5. The network layer can use various techniques for forwarding and delivery, such as virtual circuit switching, datagram switching, and source routing.
6. Virtual circuit switching involves establishing a dedicated path between the source and destination before data transmission begins.
7. Datagram switching, on the other hand, involves forwarding packets on a hop-by-hop basis, with each network element making independent forwarding decisions.

8. Source routing involves the source specifying the entire path for the packet to follow.
9. Each technique has its advantages and disadvantages, and the choice of technique depends on the specific requirements of the network and the data being transmitted.
10. A helpful mnemonic to remember the functions of the network layer is “Please Do Not Throw Sausage Pizza Away”, where the first letter of each word corresponds to the first letter of the layers of the OSI model, with the network layer being the third layer represented by the letter “N” for “Not”.

Static and dynamic routing in cn

Static and dynamic routing are two types of routing methods used in computer networks.

1. **Static routing** is a method of routing in which the network administrator manually configures the routing table on each router in the network. The routing table contains information about the network topology and the best path to reach each destination network. Static routing is simple to implement and works well in small networks with a simple topology. However, it can be difficult to manage in large networks with complex topologies, as any changes to the network require manual updates to the routing table on each router.
2. **Dynamic routing**, on the other hand, is a method of routing in which routers automatically exchange information about the network topology and the best path to reach each destination network. This information is used to update the routing table on each router. Dynamic routing is more complex to implement than static routing, but it is easier to manage in large networks with complex topologies, as changes to the network are automatically propagated to all routers.

Advantages of static routing: - Simple to implement - Works well in small networks with a simple topology - No overhead from routing protocol messages

Disadvantages of static routing: - Difficult to manage in large networks with complex topologies - Any changes to the network require manual updates to the routing table on each router - Not scalable

Advantages of dynamic routing: - Easier to manage in large networks with complex topologies - Changes to the network are automatically propagated to all routers - Scalable

Disadvantages of dynamic routing: - More complex to implement than static routing - Overhead from routing protocol messages

Mnemonics and learning tricks: - Static routing is like a **S**tatic map, where the routes are fixed and do not change. - Dynamic routing is like a **D**ynamic GPS,

where the routes are updated in real-time based on the current traffic conditions.

Routing algorithms and protocols in cn

Routing algorithms and protocols are used in computer networks to determine the best path for data packets to travel from their source to their destination. There are several types of routing algorithms and protocols, each with its own advantages and disadvantages.

1. **Distance Vector Routing:** This algorithm calculates the best path based on the distance between nodes. Each node maintains a routing table that contains the distance to all other nodes in the network. The table is updated periodically by exchanging information with neighboring nodes. The main advantage of this algorithm is its simplicity. However, it can take a long time for the routing tables to converge, and it is not suitable for large networks.
2. **Link State Routing:** This algorithm calculates the best path based on the state of the links between nodes. Each node maintains a database of the entire network topology and uses a shortest-path algorithm to determine the best path. The main advantage of this algorithm is its ability to quickly adapt to changes in the network. However, it requires more processing power and memory than distance vector routing.
3. **Path Vector Routing:** This algorithm is similar to distance vector routing, but it also includes the path information in the routing table. This allows the algorithm to avoid routing loops and to support more complex routing policies. The main advantage of this algorithm is its flexibility. However, it requires more processing power and memory than distance vector routing.

Some common routing protocols include:

- **RIP (Routing Information Protocol):** This is a distance vector routing protocol that is commonly used in small networks.
- **OSPF (Open Shortest Path First):** This is a link state routing protocol that is commonly used in large networks.
- **BGP (Border Gateway Protocol):** This is a path vector routing protocol that is commonly used to route traffic between autonomous systems on the Internet.

Mnemonics and learning tricks:

- **“Please Do Not Throw Sausage Pizza Away”** can be used to remember the OSI model layers: Physical, Data Link, Network, Transport, Session, Presentation, Application.
- **“All People Seem To Need Data Processing”** can also be used to remember the OSI model layers in reverse order: Application, Presentation, Session, Transport, Network, Data Link, Physical.

These mnemonics are easy to remember and can be helpful in remembering the OSI model layers, which is an important concept in computer networking. However, there are no easy-to-remember mnemonics for routing algorithms and protocols specifically. It is recommended to understand the concepts and their applications to effectively learn and remember them.

Congestion control algorithms in cn

Congestion control algorithms are used in computer networks to prevent congestion collapse by controlling the rate at which data is transmitted. There are several congestion control algorithms used in computer networks, including:

1. **Additive Increase Multiplicative Decrease (AIMD):** This algorithm increases the transmission rate linearly until congestion is detected, at which point the rate is decreased multiplicatively. This algorithm is used in TCP.
2. **Slow Start:** This algorithm starts with a low transmission rate and increases it exponentially until congestion is detected or a threshold is reached. This algorithm is also used in TCP.
3. **Congestion Avoidance:** This algorithm is used in conjunction with Slow Start. Once the threshold is reached, the transmission rate is increased linearly to avoid congestion.
4. **Fast Retransmit:** This algorithm is used to quickly retransmit lost packets when multiple duplicate acknowledgements are received.
5. **Fast Recovery:** This algorithm is used in conjunction with Fast Retransmit to quickly recover from packet loss without reducing the transmission rate as much as other algorithms.

These algorithms can be used in combination to provide effective congestion control in computer networks. It is important to note that different algorithms may be more effective in different network conditions and scenarios.

A mnemonic to remember these algorithms is “**A Smart Cat Finds Fish**”, where each letter represents the first letter of each algorithm: **A**dditive Increase Multiplicative Decrease, **S**low Start, **C**ongestion Avoidance, **F**ast Retransmit, and **F**ast Recovery. This mnemonic is easy to remember and can be helpful when studying for exams.

IPv6 in cn

- Internet Protocol version 6 (IPv6) is the replacement for version 4 (IPv4).
- China’s Central Cyberspace Affairs Commission and Cyberspace Administration have set out a plan for massive adoption of IPv6.

- A Notice on Accelerating the Large-scale Deployment and Application of IPv6 calls for China to have 700 million active IPv6 users by 2023, plus 200 million Internet of Things devices using the protocol .
- The overall bulk of IPv6 addresses allocated to Chinese entities were allocated in the period 2011 to 2015 .
- More recently, a /21 was allocated in late 2017 (to CBN, China Broadcasting Network Corporation), and a /20 in 2018 (to SINOPEC, the China Petroleum & Chemical Corporation) .
- IPv6 and v4 protocol support in China is evolving over time .

Unit 4 - Transport Layer in Computer Networks

The transport layer is the fourth layer in the OSI model of computer networks. It is responsible for providing end-to-end communication services for applications. Some of the key functions of the transport layer include:

1. **Connection-oriented communication:** The transport layer can establish a logical connection between the sending and receiving hosts to ensure reliable data transfer.
2. **Reliable data transfer:** The transport layer can provide reliable data transfer by implementing error control mechanisms such as retransmission of lost or corrupted packets.
3. **Flow control:** The transport layer can regulate the flow of data between the sending and receiving hosts to prevent network congestion.
4. **Multiplexing:** The transport layer can multiplex multiple application-layer connections onto a single transport-layer connection.
5. **Segmentation and reassembly:** The transport layer can divide long messages into smaller segments for transmission and reassemble them at the receiving end.

Two of the most commonly used transport layer protocols are the Transmission Control Protocol (TCP) and the User Datagram Protocol (UDP). TCP provides connection-oriented, reliable data transfer, while UDP provides connectionless, unreliable data transfer.

Process-to-process delivery in transport layer

- The transport layer is responsible for process-to-process delivery of the entire message.
- A process is an application program running on a host.
- The transport layer provides logical communication between processes running on different hosts.
- The transport layer protocols are implemented in the end systems but not in the network routers.

- The transport layer provides two types of services: connection-oriented and connectionless.
- Connection-oriented service involves three phases: connection establishment, data transfer, and connection termination.
- Connectionless service does not involve any connection establishment or termination. Data is transferred between processes in the form of independent packets.
- The transport layer is responsible for flow control, error control, and congestion control.
- Flow control is the process of adjusting the rate of data transmission between two nodes to prevent a fast sender from overwhelming a slow receiver.
- Error control is the process of detecting and correcting errors that may occur during transmission.
- Congestion control is the process of preventing network congestion by regulating the rate of data transmission.
- The transport layer uses port numbers to identify different processes running on a host.
- Port numbers are 16-bit numbers ranging from 0 to 65535.
- Well-known port numbers are used by standard services such as HTTP (80), FTP (21), and Telnet (23).
- The transport layer uses a combination of the IP address and the port number to uniquely identify a process running on a host.
- The transport layer uses sockets to establish a connection between processes.
- A socket is a combination of an IP address and a port number.
- The transport layer uses the Transmission Control Protocol (TCP) for connection-oriented service and the User Datagram Protocol (UDP) for connectionless service.
- TCP provides reliable, in-order delivery of data while UDP provides unreliable, unordered delivery of data.
- TCP is used by applications that require reliability, such as email and file transfer, while UDP is used by applications that can tolerate some data loss, such as online gaming and video streaming.

Transport layer protocols

The transport layer is the fourth layer in the OSI model and is responsible for end-to-end communication between devices. The two most common transport layer protocols are the Transmission Control Protocol (TCP) and the User Datagram Protocol (UDP).

1. **Transmission Control Protocol (TCP):** TCP is a connection-oriented protocol that provides reliable, ordered, and error-checked delivery of data between applications. It is used by applications that require a high degree of reliability, such as web browsing, email, and file transfers. Some of the

key features of TCP include:

- Three-way handshake: Before data transmission, TCP establishes a connection between the sender and receiver using a three-way handshake.
- Flow control: TCP uses a sliding window mechanism to control the flow of data and prevent the receiver from being overwhelmed.
- Error checking: TCP uses checksums to detect errors in the transmitted data and retransmits corrupted packets.
- Congestion control: TCP uses various algorithms to avoid network congestion and ensure fair allocation of bandwidth.

2. **User Datagram Protocol (UDP)**: UDP is a connectionless protocol that provides fast and lightweight data transmission. It is used by applications that can tolerate some data loss, such as online gaming, voice over IP, and video streaming. Some of the key features of UDP include:

- No connection setup: UDP does not establish a connection before data transmission, which reduces latency.
- No error checking: UDP does not provide error checking or retransmission of lost packets, which reduces overhead.
- No flow control: UDP does not provide flow control, which allows for faster data transmission.

A mnemonic to remember the difference between TCP and UDP is: “TCP is for applications that require **T**ransportation with **C**are, while UDP is for applications that can handle **U**nreliable **D**ata **P**ackets.”


In summary, the transport layer provides end-to-end communication between devices using protocols such as TCP and UDP. TCP is a connection-oriented protocol that provides reliable data transmission, while UDP is a connectionless protocol that provides fast and lightweight data transmission. The choice of protocol depends on the requirements of the application.

UDP Transport layer protocol

- UDP stands for User Datagram Protocol.
- It is a transport layer protocol used for transmitting data over the internet.
- UDP is a connectionless protocol, meaning it does not establish a connection before transmitting data.
- It is a simple protocol that does not provide error checking or flow control.
- UDP is faster than TCP because it does not have the overhead of error checking and flow control.
- UDP is used for applications that require fast transmission of data, such as online gaming, voice over IP, and video streaming.
- A mnemonic to remember the characteristics of UDP is “Unreliable, Datagram, Protocol”.
- UDP packets are called datagrams.
- Each datagram contains a header and a payload.
- The header contains information such as the source and destination port

numbers, the length of the datagram, and a checksum.

- The payload contains the data being transmitted.
- UDP is not suitable for applications that require reliable transmission of data, such as file transfers.
- Advantages of UDP:
 - Faster transmission of data
 - Lower overhead
 - Suitable for real-time applications
- Disadvantages of UDP:
 - No error checking
 - No flow control
 - Not suitable for reliable transmission of data
- Example applications that use UDP:
 - Online gaming
 - Voice over IP
 - Video streaming
 - DNS queries
- ASCII diagram of a UDP datagram:



TCP Transport layer protocol

- TCP stands for Transmission Control Protocol.
- It is one of the main protocols in the Internet Protocol Suite.
- It is a connection-oriented protocol, which means that a connection is established and maintained until the application programs at each end have finished exchanging messages.
- TCP provides reliable, ordered, and error-checked delivery of data between applications running on different devices.
- TCP achieves this reliability by assigning a sequence number to each byte transmitted and requiring a positive acknowledgment (ACK) from the receiving device. If the ACK is not received within a certain time, the data is retransmitted.
- TCP also includes a flow control mechanism, which ensures that the sender does not overwhelm the receiver with data.
- TCP is used by many common applications such as the World Wide Web,

email, and file transfer.

Mnemonic: **T**ransmission **C**ontrol **P**rotocol - **T**ransfers **C**ontent **P**roperly

Multiplexing in transport layer

Multiplexing is the process of combining multiple data streams into a single physical connection. In the transport layer, multiplexing is used to allow multiple applications to share a single network connection.

1. **Process:** The transport layer receives data from multiple applications, each with its own port number. The transport layer adds a header to each data segment, which includes the source and destination port numbers. The data segments are then sent to the network layer, which transmits them over the network. At the destination, the transport layer uses the port numbers in the header to demultiplex the data and deliver it to the correct application.
2. **Advantages:** Multiplexing in the transport layer has several advantages. It allows multiple applications to share a single network connection, reducing the need for multiple physical connections. This can save on hardware and infrastructure costs. It also allows for more efficient use of network resources, as multiple data streams can be transmitted over a single connection.
3. **Examples:** An example of multiplexing in the transport layer is when a user opens multiple tabs in a web browser. Each tab represents a different application, and each application sends and receives data over the network. The transport layer multiplexes the data from each application and sends it over a single network connection. At the destination, the data is demultiplexed and delivered to the correct application.
4. **Applications:** Multiplexing in the transport layer is used in many different applications, including web browsing, email, file transfer, and online gaming. It is an essential part of the transport layer protocol and is used in both TCP and UDP.

There are no easy to remember Mnemonics or learning tricks for Multiplexing in transport layer. However, understanding the process, advantages, examples, and applications can help in remembering the concept.

Connection management in transport layer

Connection management in the transport layer is responsible for establishing, maintaining, and terminating connections between two or more devices. This is done through a process known as a three-way handshake.

1. The first step in the three-way handshake is the SYN (synchronize) message, which is sent from the initiating device to the receiving device. This

message contains information about the initial sequence number and other connection parameters.

2. The second step is the SYN-ACK (synchronize-acknowledge) message, which is sent from the receiving device to the initiating device. This message acknowledges the receipt of the SYN message and contains information about the initial sequence number and other connection parameters of the receiving device.
3. The third and final step is the ACK (acknowledge) message, which is sent from the initiating device to the receiving device. This message acknowledges the receipt of the SYN-ACK message and confirms that the connection has been established.

Once the connection has been established, data can be transmitted between the two devices. The transport layer is responsible for ensuring that the data is transmitted reliably and in the correct order.

When the connection is no longer needed, it can be terminated through a process known as the four-way handshake. This involves the exchange of FIN (finish) and ACK (acknowledge) messages between the two devices.

A mnemonic to remember the steps of the three-way handshake is “SYN, SYN-ACK, ACK” or “Synchronize, Synchronize-Acknowledge, Acknowledge”.

Connection management in the transport layer is important because it ensures that data is transmitted reliably and in the correct order. It also allows for the efficient use of network resources by establishing and terminating connections as needed. Some examples of transport layer protocols that use connection management are TCP (Transmission Control Protocol) and SCTP (Stream Control Transmission Protocol).

Flow control in transport layer

Flow control is a mechanism used in the transport layer of the OSI model to regulate the flow of data between two devices. It ensures that the sender does not overwhelm the receiver by sending too much data too quickly.

1. Flow control is implemented using a sliding window protocol. The receiver sends a window size to the sender, indicating how many bytes of data it can receive before it needs to send an acknowledgment.
2. The sender then sends data up to the window size and waits for an acknowledgment from the receiver before sending more data.
3. If the receiver is unable to process the data quickly enough, it can reduce the window size, signaling the sender to slow down.
4. If the receiver is able to process the data quickly, it can increase the window size, allowing the sender to send more data.

5. This mechanism allows the receiver to control the rate at which data is sent, preventing buffer overflow and ensuring reliable data transfer.
6. Flow control is used in both TCP and UDP protocols, although the implementation differs between the two.
7. In TCP, flow control is implemented using a sliding window protocol, where the receiver sends a window size to the sender, indicating how many bytes of data it can receive before it needs to send an acknowledgment.
8. In UDP, flow control is implemented using a rate control mechanism, where the receiver sends feedback to the sender indicating the rate at which it can receive data.
9. Flow control is an important mechanism for ensuring reliable data transfer and preventing buffer overflow in the transport layer.
10. A mnemonic to remember the steps of flow control in the transport layer is “Sliding Window Regulates Data Flow” (SWRDF). The first letters of each word represent the steps of flow control: Sliding window, Window size, Receiver, Data, Flow.
11. An example of flow control in action is when downloading a large file from the internet. The receiver (your computer) sends a window size to the sender (the server), indicating how much data it can receive. The sender then sends data up to the window size and waits for an acknowledgment from the receiver before sending more data. If the receiver is unable to process the data quickly enough, it can reduce the window size, signaling the sender to slow down. This ensures that the data is transferred reliably and without overwhelming the receiver.

etransmission in transport layer

The transport layer is responsible for end-to-end communication between two devices on a network. It is the fourth layer in the OSI model and the third layer in the TCP/IP model. The transport layer is responsible for the following functions:

1. **Segmentation and reassembly:** The transport layer divides the data into smaller segments that can be transmitted over the network. At the receiving end, the transport layer reassembles the segments into the original data.
2. **Connection control:** The transport layer can establish, maintain, and terminate connections between two devices on a network.
3. **Flow control:** The transport layer can control the flow of data between two devices to prevent the receiver from being overwhelmed by the sender.
4. **Error control:** The transport layer can detect and correct errors that may occur during transmission.

5. **Reliable transmission:** The transport layer can provide reliable transmission of data by using techniques such as error correction and retransmission of lost or corrupted data.

In the context of data transmission, the transport layer is responsible for ensuring that the data is transmitted reliably and efficiently. This is achieved through the use of protocols such as TCP (Transmission Control Protocol) and UDP (User Datagram Protocol).

TCP is a connection-oriented protocol that provides reliable transmission of data. It establishes a connection between two devices before transmitting data and uses techniques such as error correction and retransmission to ensure that the data is transmitted reliably.

UDP, on the other hand, is a connectionless protocol that provides fast but unreliable transmission of data. It does not establish a connection before transmitting data and does not provide error correction or retransmission. As a result, UDP is typically used for applications where speed is more important than reliability, such as online gaming or video streaming.

In summary, the transport layer is responsible for ensuring reliable and efficient transmission of data between two devices on a network. It achieves this through the use of protocols such as TCP and UDP and by providing functions such as segmentation and reassembly, connection control, flow control, error control, and reliable transmission.

Window management in transport layer

Window management is a flow control mechanism used in the transport layer of the OSI model. It is used to control the amount of data that can be sent by a sender before receiving an acknowledgment from the receiver. This mechanism helps to prevent network congestion and ensures reliable data transmission.

- The sender maintains a sending window, which is the maximum amount of data that can be sent without receiving an acknowledgment from the receiver.
- The receiver maintains a receiving window, which is the maximum amount of data that can be received before sending an acknowledgment to the sender.
- The size of the sending and receiving windows can be adjusted dynamically based on network conditions.
- The sender can only send data within the sending window and must wait for an acknowledgment from the receiver before sending more data.
- The receiver can only receive data within the receiving window and must send an acknowledgment to the sender before receiving more data.

Advantages of window management: - It helps to prevent network congestion by controlling the amount of data that can be sent by the sender. - It ensures reliable data transmission by requiring the sender to wait for an acknowledgment

from the receiver before sending more data. - It allows for dynamic adjustment of the window size based on network conditions, which can improve the efficiency of data transmission.

Disadvantages of window management: - It can add complexity to the transport layer protocol. - It can increase the latency of data transmission if the window size is too small.

Example of window management: - The Transmission Control Protocol (TCP) uses window management as part of its flow control mechanism. The sender and receiver negotiate the initial window size during the connection establishment phase, and the window size is adjusted dynamically during data transmission based on network conditions.

Mnemonic for remembering the concept of window management: - **W**indow management **I**s **N**ecessary to **D**ecrease **O**verflow of data and **W**ait for **A**cknowledgment before **S**ending more data. (WINDOW WAS)

TCP Congestion control in transport layer

TCP congestion control is a mechanism used by the transport layer protocol, TCP, to control the flow of data in a network and prevent congestion. It is an essential part of the TCP protocol and is used to ensure that the network is used efficiently and fairly.

1. **Slow Start:** When a TCP connection is first established, the sender starts by sending a small amount of data, typically one or two segments. The sender then waits for an acknowledgement from the receiver before sending more data. This process is repeated, with the sender doubling the amount of data sent each time until the receiver's advertised window is reached or packet loss occurs.
2. **Congestion Avoidance:** Once the slow start phase is complete, the sender enters the congestion avoidance phase. In this phase, the sender increases the amount of data sent by one segment for each round trip time (RTT). This allows the sender to gradually increase the amount of data sent until the network becomes congested.
3. **Fast Retransmit:** If the sender detects that a segment has been lost, it will immediately retransmit the lost segment without waiting for the retransmission timer to expire. This is known as fast retransmit.
4. **Fast Recovery:** After fast retransmit, the sender enters the fast recovery phase. In this phase, the sender reduces the congestion window by half and continues to transmit data at a reduced rate. This allows the sender to quickly recover from the lost segment and resume transmitting data at a high rate.

A mnemonic to remember the four phases of TCP congestion control is “**Start Avoiding Fast Recovery**”.

TCP congestion control is an important mechanism that helps to ensure that the network is used efficiently and fairly. By controlling the flow of data, TCP congestion control can prevent congestion and improve the overall performance of the network. It is an essential part of the TCP protocol and is used by all TCP-based applications.

Quality of service in transport layer

Quality of Service (QoS) refers to the ability of a network to provide improved service to certain network traffic. The primary goal of QoS is to provide priority including dedicated bandwidth, controlled jitter and latency, and improved loss characteristics to specific flows of data in a network.

In the transport layer, QoS can be achieved through several mechanisms:

1. **Resource Reservation:** The transport layer can reserve resources such as bandwidth and buffer space to ensure that the desired QoS is achieved for a particular flow of data.
2. **Traffic Shaping:** The transport layer can shape the traffic by controlling the rate at which data is sent into the network. This can help to prevent congestion and ensure that the desired QoS is achieved.
3. **Admission Control:** The transport layer can implement admission control mechanisms to determine whether a new flow of data can be admitted into the network based on the current network conditions and the desired QoS for the new flow.
4. **Packet Scheduling:** The transport layer can implement packet scheduling algorithms to determine the order in which packets are transmitted. This can help to ensure that high priority packets are transmitted before lower priority packets.
5. **Error and Flow Control:** The transport layer can implement error and flow control mechanisms to ensure that data is transmitted reliably and that the desired QoS is achieved.

A mnemonic to remember these mechanisms is **Resource Reservation, Traffic Shaping, Admission Control, Packet Scheduling, Error and Flow Control: RTACPEF**.

These mechanisms can be used individually or in combination to achieve the desired QoS for a particular flow of data in the transport layer. It is important to note that the effectiveness of these mechanisms depends on the underlying network conditions and the desired QoS for the flow of data. Therefore, it is important to carefully design and implement QoS mechanisms in the transport layer to ensure that the desired QoS is achieved.

Unit 5 - Application Layer in Computer Networks

The application layer is the topmost layer in the OSI model of computer networks. It provides services to the user and interacts with the user directly. Some of the common protocols used in the application layer are:

- **HTTP (Hypertext Transfer Protocol):** Used for transmitting web pages over the internet.
- **FTP (File Transfer Protocol):** Used for transferring files between computers.
- **SMTP (Simple Mail Transfer Protocol):** Used for sending and receiving emails.
- **DNS (Domain Name System):** Used for resolving domain names to IP addresses.

A mnemonic to remember these protocols is **How Far Shall Dave Swim**.

The application layer is responsible for providing a user-friendly interface for the user to interact with the network. It also provides services such as data formatting, data compression, and encryption.

Advantages of the application layer: - Provides a user-friendly interface for the user to interact with the network. - Provides services such as data formatting, data compression, and encryption. - Allows for the development of custom applications to meet specific user needs.

Disadvantages of the application layer: - Can be resource-intensive, as it requires additional processing power to provide its services. - Can be a potential security risk, as it is the layer that interacts directly with the user.

Examples of application layer protocols in use: - Web browsers use HTTP to transmit web pages over the internet. - Email clients use SMTP to send and receive emails. - File sharing applications use FTP to transfer files between computers.

Applications of the application layer: - Web browsing - Email - File sharing - Online gaming - Video conferencing

In summary, the application layer is the topmost layer in the OSI model of computer networks, providing services to the user and interacting with the user directly. It uses common protocols such as HTTP, FTP, SMTP, and DNS, and provides services such as data formatting, data compression, and encryption. It has advantages such as providing a user-friendly interface and allowing for the development of custom applications, but can also be resource-intensive and a potential security risk. It is used in applications such as web browsing, email, file sharing, online gaming, and video conferencing. A mnemonic to remember the common protocols used in the application layer is **How Far Shall Dave Swim**.

Domain Name System

- The Domain Name System (DNS) is a hierarchical and decentralized naming system for computers, services, or other resources connected to the Internet or a private network.
- It associates various information with domain names assigned to each of the participating entities.
- Most prominently, it translates more readily memorized domain names to the numerical IP addresses needed for locating and identifying computer services and devices with the underlying network protocols.
- By providing a worldwide, distributed directory service, the Domain Name System is an essential component of the functionality of the Internet.
- The Domain Name System is maintained by a distributed database system, which uses the client-server model.
- The nodes of this database are the name servers.
- Each domain has at least one authoritative DNS server that publishes information about that domain and the name servers of any domains subordinate to it.
- The top of the hierarchy is served by the root name servers, the servers to query when looking up (resolving) a top-level domain name.
- A DNS resolver is responsible for initiating and sequencing the queries that ultimately lead to a full resolution of the resources sought, e.g., translation of a human-readable domain name into the IP address of a host computer.
- A mnemonic to remember the DNS hierarchy is “All People Seem To Need Data Processing” which represents the order of the DNS hierarchy: Application, Presentation, Session, Transport, Network, Data Link, Physical.

World Wide Web

- The World Wide Web (WWW or Web) is an information space where documents and other web resources are identified by Uniform Resource Locators (URLs), interlinked by hypertext links, and can be accessed via the Internet.
- The Web was invented by British scientist Tim Berners-Lee in 1989 while working at CERN, the European Organization for Nuclear Research.
- The Web is not the same as the Internet. The Internet is a global network of interconnected computer networks, while the Web is a way of accessing information over the Internet.
- The Web uses the Hypertext Transfer Protocol (HTTP) to transmit data.
- Web pages are written in Hypertext Markup Language (HTML) and are displayed in a web browser.
- The Web has had a profound impact on society, enabling the sharing of information and knowledge on a global scale.
- A useful mnemonic to remember the difference between the Web and the Internet is that the Web is a service that runs on the Internet.

Hyper Text Transfer Protocol

Hyper Text Transfer Protocol (HTTP) is an application-layer protocol used for transmitting hypermedia documents, such as HTML. It is the foundation of data communication for the World Wide Web.

- HTTP is a request-response protocol between a client and a server.
- A client sends an HTTP request to the server, and the server responds with an HTTP response.
- HTTP is a stateless protocol, meaning that the server does not retain any information about the client between requests.
- HTTP uses a reliable transport protocol, typically TCP, to establish a connection between the client and server.
- HTTP requests and responses use a well-defined message format with headers and a message body.
- HTTP defines a set of request methods, such as GET, POST, PUT, DELETE, and others, to indicate the desired action to be performed on the identified resource.
- HTTP also defines a set of response status codes, such as 200 OK, 404 Not Found, and others, to indicate the outcome of the request.

A mnemonic to remember the common HTTP methods is **GPOD**: - **GET**: Retrieve a resource. - **POST**: Submit data to be processed to a specified resource. - **OPTIONS**: Returns the HTTP methods that the server supports for the specified URL. - **DELETE**: Deletes the specified resource.

HTTP has several advantages, including: - It is simple and easy to implement. - It is platform-independent and can be used by any device or operating system. - It is extensible, allowing new functionality to be added without breaking existing implementations.

HTTP also has some disadvantages, including: - It is not secure by default, and data transmitted over HTTP can be intercepted and read by attackers. - It is not efficient for transmitting large amounts of data, as each request and response includes a significant amount of overhead.

HTTP is used in a wide range of applications, including web browsing, web services, and API communication. It is an essential protocol for the modern internet.

Electronic mail in application layer

Electronic mail (email) is a method of exchanging messages between people using electronic devices. It operates across the internet or other computer networks. Email is one of the protocols included in the application layer of the OSI model and the TCP/IP protocol suite.

1. Email works by sending messages from the sender's email client to the recipient's email server, and then from the server to the recipient's email

client.

2. The Simple Mail Transfer Protocol (SMTP) is the standard protocol for sending email messages between servers.
3. The Post Office Protocol (POP) and the Internet Message Access Protocol (IMAP) are two of the most common protocols for retrieving email messages from a server.
4. Email messages are typically composed of three main parts: the header, the body, and the attachments.
5. The header contains information about the sender, recipient, subject, and other metadata.
6. The body contains the actual message content, which can be in plain text or HTML format.
7. Attachments are additional files that are sent along with the email message, such as images, documents, or audio files.

A mnemonic to remember the email retrieval protocols is “PIMP” - Post Office Protocol (POP), Internet Message Access Protocol (IMAP).

Advantages of using email include: - Speed: Email messages can be sent and received almost instantly. - Convenience: Email can be accessed from anywhere with an internet connection. - Cost-effective: Sending an email is typically free or very low cost. - Record keeping: Email provides a written record of communication.

Disadvantages of using email include: - Spam: Unsolicited email messages can clutter up an inbox. - Security: Email messages can be intercepted and read by unauthorized parties. - Miscommunication: The tone of an email message can be easily misinterpreted.

In summary, email is a widely used method of communication that operates at the application layer of the OSI model and the TCP/IP protocol suite. It has several advantages and disadvantages, and there are several protocols involved in sending and retrieving email messages. A mnemonic to remember the email retrieval protocols is “PIMP” - Post Office Protocol (POP), Internet Message Access Protocol (IMAP).

File Transfer Protocol in application layer

- File Transfer Protocol (FTP) is a standard network protocol used to transfer files from one host to another over a TCP-based network, such as the Internet.
- FTP is built on a client-server architecture and uses separate control and data connections between the client and the server.
- FTP users may authenticate themselves with a clear-text sign-in protocol, normally in the form of a username and password, but can connect anonymously if the server is configured to allow it.
- FTP is defined by RFC 959, which was published in October 1985.

- FTP is an application layer protocol, which means it operates at the top layer of the OSI model, the application layer.
- FTP is commonly used to transfer files between a local computer and a remote server, or between two remote servers.
- FTP can be used to transfer files of any size and type, including text, binary, and multimedia files.
- FTP can be used in active or passive mode. In active mode, the client opens a port and listens, and the server actively connects to it. In passive mode, the server opens a port and listens, and the client actively connects to it.
- FTP can be secured with SSL/TLS, which adds a layer of encryption to the data being transferred.
- FTP has several commands, including **USER** (to specify the username), **PASS** (to specify the password), **CWD** (to change the working directory), **RETR** (to retrieve a file), **STOR** (to store a file), and **LIST** (to list the contents of a directory).
- FTP has some limitations, including the fact that it is not firewall-friendly, it sends login credentials in clear text, and it does not support file synchronization or delta transfers.
- FTP can be used with a variety of FTP clients, including command-line clients, graphical clients, and web-based clients.
- FTP is still widely used, but has largely been replaced by more secure and versatile protocols such as SFTP (Secure File Transfer Protocol) and SCP (Secure Copy Protocol).

Remote login in application layer

Remote login is a process that allows a user to log in to a computer or a network from a remote location. This is typically done using a remote login protocol, such as Telnet or Secure Shell (SSH), which operates at the application layer of the OSI model.

1. **Telnet** is a protocol that allows a user to remotely log in to a computer over a network. It is a simple, text-based protocol that is used to send commands to a remote computer and receive the output. Telnet is not secure, as the data transmitted between the client and server is not encrypted.
2. **Secure Shell (SSH)** is a protocol that provides a secure way to remotely log in to a computer over a network. SSH uses encryption to secure the data transmitted between the client and server, making it much more secure than Telnet.
3. **Advantages of remote login:**
 - Allows users to access resources on a remote computer or network from anywhere with an internet connection.
 - Can be used to perform administrative tasks on a remote computer without physically being present.

- Can be used to transfer files between computers.

4. Disadvantages of remote login:

- Can be a security risk if not properly secured, as it provides a potential entry point for attackers.
- Can be slower than working directly on the remote computer, as data must be transmitted over the network.

5. Examples of remote login:

- A system administrator using SSH to log in to a server to perform maintenance tasks.
- A user using Telnet to log in to a remote computer to run a program.

6. Applications of remote login:

- Remote system administration.
- Remote technical support.
- Remote file transfer.

7. Mnemonics and learning tricks:

- To remember the difference between Telnet and SSH, think of Telnet as “Tell-All” because it is not secure and sends data in plain text, while SSH is “Secure Shell” because it uses encryption to secure the data transmitted between the client and server.

Network management in application layer

- Network management refers to the activities, methods, procedures, and tools that pertain to the operation, administration, maintenance, and provisioning of networked systems.
- The application layer is the topmost layer of the OSI model and is responsible for providing services to the user.
- In the context of network management, the application layer provides a user interface for managing the network.
- Some common network management tasks that can be performed at the application layer include:
 - Monitoring network performance
 - Configuring network devices
 - Managing network security
 - Troubleshooting network issues
- Network management protocols such as SNMP (Simple Network Management Protocol) operate at the application layer.
- SNMP is an application layer protocol that allows network administrators to manage network performance, find and solve network problems, and plan for network growth.
- An example of network management in the application layer is the use of a web-based interface to monitor and configure network devices.

- Advantages of network management in the application layer:
 - Provides a user-friendly interface for managing the network
 - Allows for remote management of network devices
 - Can provide a centralized view of the network
- Disadvantages of network management in the application layer:
 - Can be less efficient than lower-layer management protocols
 - May require additional software or hardware to implement
- A mnemonic to remember the tasks that can be performed at the application layer is “MCTM” (Monitoring, Configuring, Troubleshooting, Managing security).

Data compression in application layer

Data compression is the process of encoding information using fewer bits than the original representation. It is used to reduce the amount of data that needs to be transmitted or stored. In the application layer, data compression is used to improve the performance of network applications by reducing the amount of data that needs to be transmitted over the network.

There are two main types of data compression: lossless and lossy. Lossless compression algorithms reduce the size of the data without losing any information, while lossy compression algorithms reduce the size of the data by discarding some information.

Some common lossless compression algorithms used in the application layer include: - Huffman coding - Lempel-Ziv-Welch (LZW) - Deflate

Some common lossy compression algorithms used in the application layer include: - JPEG (Joint Photographic Experts Group) - MP3 (MPEG-1 Audio Layer III) - MPEG (Moving Picture Experts Group)

Advantages of using data compression in the application layer include: - Reduced bandwidth usage - Faster data transmission - Reduced storage requirements

Disadvantages of using data compression in the application layer include: - Additional processing time required for compression and decompression - Potential loss of data quality with lossy compression

Examples of applications that use data compression in the application layer include: - File transfer applications (e.g. FTP, HTTP) - Email applications (e.g. SMTP, POP3, IMAP) - Streaming media applications (e.g. RTP, RTSP)

Mnemonic for remembering the types of data compression: **LossLess** compression **Loses Less** information, while **Lossy** compression **Loses** some information.

In conclusion, data compression in the application layer is an important technique for improving the performance of network applications by reducing the amount of data that needs to be transmitted over the network. It is important

to carefully choose the appropriate compression algorithm for the specific application and data type to balance the trade-off between data size reduction and data quality.

Cryptography in application layer

Cryptography in the application layer refers to the use of cryptographic techniques to secure data and communication at the application level. This is in contrast to lower-level cryptographic techniques, such as those used in the transport or network layers.

Some common examples of application layer cryptography include:

- Secure email: Email messages can be encrypted and digitally signed to ensure confidentiality and authenticity.
- Secure messaging: Instant messaging and chat applications can use end-to-end encryption to secure messages between users.
- Secure file storage: Cloud storage services can use encryption to protect user data at rest.
- Digital signatures: Digital signatures can be used to verify the authenticity and integrity of electronic documents.

Advantages of using cryptography in the application layer include:

- Flexibility: Application layer cryptography can be tailored to the specific needs of the application and its users.
- Control: Users have more control over the security of their data and communication, as they can choose which cryptographic techniques to use and how to use them.
- End-to-end security: Application layer cryptography can provide end-to-end security, meaning that data is protected from the moment it leaves the sender until it reaches the intended recipient.

Disadvantages of using cryptography in the application layer include:

- Complexity: Implementing cryptographic techniques at the application layer can be more complex than using lower-level techniques.
- User responsibility: Users are responsible for managing their own cryptographic keys and ensuring the security of their data and communication.

Mnemonic: A helpful mnemonic to remember the advantages of application layer cryptography is “FCE”: Flexibility, Control, and End-to-end security.

Basic Concepts of Cryptography in Application Layer

Cryptography is the practice of securing communication in the presence of third parties. It involves techniques for secure communication, data integrity, and authentication. In the application layer, cryptography is used to secure data transmitted over the network.

1. **Encryption and Decryption:** Encryption is the process of converting plaintext into ciphertext, which is unreadable without the key. Decryption is the reverse process, converting ciphertext back into plaintext. There are two types of encryption: symmetric and asymmetric. Symmetric encryption uses the same key for encryption and decryption, while asymmetric encryption uses different keys for encryption and decryption.

2. **Hashing:** Hashing is the process of converting data into a fixed-size string of characters, called a hash value. Hashing is used to ensure data integrity, as any change to the data will result in a different hash value.
3. **Digital Signatures:** Digital signatures are used to verify the authenticity of a message. The sender signs the message with their private key, and the recipient can verify the signature with the sender's public key.
4. **Key Exchange:** Key exchange is the process of securely exchanging cryptographic keys between two parties. This is necessary for secure communication, as the keys are used for encryption and decryption.
5. **Certificates and Public Key Infrastructure (PKI):** Certificates are used to verify the identity of a party. They are issued by a trusted third party, called a Certificate Authority (CA). Public Key Infrastructure (PKI) is a system for managing certificates and keys.

Mnemonic for remembering the basic concepts: **Every Happy Dog Knows Commands** (Encryption, Hashing, Digital Signatures, Key Exchange, Certificates).

These are some of the basic concepts of cryptography in the application layer. Understanding these concepts is essential for securing communication and ensuring data integrity in the application layer.