DS-203 Assignment 8

Chirag Garg 190100042 Electrical Engineering, Dual Degree

Ans 1.)

	Questi	on 1		
Part No.	Input Variables	Output Variables	Type of Problem	
a.)	Grades of 50 courses	5 numbers (mentioned in the question)	PCA	
b.)	Students' Performance in courses and extra curriculars	Personality group of students	Clustering	
c.)	Performance; 1st job type; extra curricular activities	Salary after 2 years	Regression	
d.)	Performance in courses and extra curricular activities	Best job type for person	Classification	

Ans 2.)

		Target		Question 2	
Problem	Framework	output variable	Parameters	Hyperparameters and their typical value range	Scikit-learn commands for their defining training and testing
Classification	SVM-C with Gaussian kernel	ОНЕ	Support Vectors, their coefficients and intercepts	C(regularisation)[0.5-2], gamma(kernel coefficient)['scale'/'auto'], tol(tolerance)[10^-5 - 10^-3]	svmClass = sklearn.svm.SVC(); svmClass.fit(x, y) svmClass.predict(X_)
	NN with one hidden layer	ОНЕ	Weights and biases	hidden_layer_size[20-1000], activation['relu'/'tanh'/'sigmoid'] , solver['sgd'/'adam'], alpha[0.001(default)-1]	mlpClass = MLPClassifier(); mlpClass.fit(x, y); mlpClass.predict(X_)
	Random Forest	ОНЕ	No. of decision trees, No. of features considered by each tree when splitting a node	n_estimators[10-1000], orientation['gini'/'entropy'], max_depth[2-10], bootstrap[True/False]	rfc =sklearn.ensemble.RandomForestClassifier(); rfc.fit(x, y); rfc.predict(X_)
Regression	SVM-R with Gaussian kernel	Float	Support Vectors, their coefficients and intercepts	C(regularisation)[0.5-2], gamma(kernel coefficient)['scale'/'auto'], tol(tolerance)[10^-5 - 10^-3], epsilon[0.01-0.1]	<pre>svmReg = sklearn.svm.SVR(); svmReg.fit(x, y); svmReg.predict(X_)</pre>
	NN with one hidden layer	Float	Weights and biases	hidden_layer_size[20-1000], activation['relu'/'tanh'/'sigmoid'] , solver['sgd'/'adam'], alpha[0.001(default)-1]	mlpReg = MLPClassifier(); mlpReg.fit(x, y); mlpReg.predict(X_)
	Random Forest	Float	No. of decision trees, No. of features considered by each tree when splitting a node	n_estimators[10-1000], orientation['gini'/'entropy'], max_depth[2-10], bootstrap[True/False]	rfr =sklearn.ensemble.RandomForestRegressor(); rfr.fit(x, y); rfr.predict(X_)
Clustering	k-means	Integer	Cluster Centers	n_clusters[4-12], init['k- means++'/'random'], max_iter[100-1000], tol(tolerance)[10^-5 - 10^-3]	kmeansClass = sklearn.cluster.Kmeans(); kmeansClass.fit(x); kmeansClass.predict(X_)
	DBSCAN	Integer	Core Points	eps[0.1-0.9], min_samples[default: 5], algorithm['auto'/'kd- tree'/'brute']	dbs = sklearn.cluster.DBSCAN(); dbs.fit(x); dbs.predict(X_)
Dimension	PCA	None	Vectors along which data is to be projected	n_components[1-no. of features], copy[True/False], svd-solver['auto'/'full'/'randomized']	<pre>pca = sklearn.decomposition.PCA(); pca.fit(X);</pre>
Reduction	Kernel PCA	None	Vectors along which data is to be projected	<pre>n_components[1-no. of features], gamma[~1/no. of features], degree[2-4]</pre>	<pre>kpca = sklearn.decomposition.KernelPCA(); kpca.fit(X); kpca.fit_transform(X_)</pre>