

PLC Splitter

Tray Type PLC Splitter



DESCRIPTION

Welltech Enterprises PLC splitter is based on silicon dioxide waveguides, which is used to connect main equipment and terminal equipment in EPON, BPON and GPON network.

FEATURES

- Qualified with CE certificate and ROHS certificate.
- Comply with GR-1209-CORE, GR-1221-CORE, YD/T 2000.1-2014 and IEC criterion.



T3.1 Tray type PLC Splitter dimension

| Dimension | nx2, nx4, nx8, nX16 | 1X32, 2X32 | 1X64, 2X64 | |
|----------------|---------------------|------------|-------------|--|
| L x W x H (mm) | 288×180×25 | 288×180×50 | 288×180×100 | |

OPTICAL PARAMETER:

T4.1 1×N (N≥2)PLC splitter optical parameter

| | Parameter | 1X2 | 1x4 | 1x8 | 1x16 | 1x32 | 1x64 |
|---------------------------|--------------------|-------------------|------|-------|-------|-------|-------|
| Wavelength (nm) | | 1260 ~ 1650 | | | | | |
| | IL (dB) | ≤4.1 | ≤7.4 | ≤10.5 | ≤13.8 | ≤17.1 | ≤20.4 |
| Uniformity (dB) | | ≤0.6 | ≤0.7 | ≤0.8 | ≤1.0 | ≤1.5 | ≤2.0 |
| RL (dB) | | ≥50(PC); ≥55(APC) | | | | | |
| PDL (dB) | | ≤0.15 | ≤0.2 | ≤0.2 | ≤0.3 | ≤0.3 | ≤0.3 |
| Directivity (dB) | | ≥55 | ≥55 | ≥55 | ≥55 | ≥55 | ≥55 |
| | Operating temp(°C) | -40~85℃ | | | | | |
| Storage temp(°C) -40~85°C | | | | | | | |



| ment | Humidity | ≤95% (+40℃) | | | |
|--------------|----------------------|--------------------------------|--|--|--|
| mem | Atmospheric pressure | 62~106kPa | | | |
| Fiber | | SM G657A or customized | | | |
| Connector | | SC, FC, LC | | | |
| Pigtail (mm) | | 1000, 1500, 2000 or customized | | | |

T4.2 2×N (N≥2) PLC splitter optical parameter

| Parameter | 2X2 | 2x4 | 2x8 | 2x16 | 2x32 | 2x64 |
|--------------------|-------------------|------|-------|--------|-------|-------|
| Wavelength (nm) | 1260 ~ 1650 | | | | | |
| IL (dB) | ≤4.4 | ≤7.7 | ≤10.8 | ≤14.1 | ≤17.4 | ≤20.7 |
| Uniformity (dB) | ≤0.8 | ≤1.0 | ≤1.0 | ≤1.5 | ≤1.8 | ≤2.0 |
| RL (dB) | ≥50(PC); ≥55(APC) | | | | | |
| PDL (dB) | ≤0.2 | ≤0.2 | ≤0.3 | ≤0.3 | ≤0.3 | ≤0.4 |
| Directivity (dB) | ≥55 | ≥55 | ≥55 | ≥55 | ≥55 | ≥55 |
| Operating temp(°C) | | | -4 | l0~85℃ | | |

WELLTECH ENTERPRISES



| Fro direct | Storage temp(°C) | -40~85℃ |
|--------------|------------------|--------------------------------|
| Environ | Humidity | ≤95% (+40℃) |
| ment | Atmospheric | 62∼106kPa |
| | pressure | 02~100KFa |
| Fiber | | SM G657A or customized |
| Connector | | SC, FC, LC |
| Pigtail (mm) | | 1000, 1500, 2000 or customized |