

FTTH Components

Fast Connector

Welltech Enterprises fast connector with embedded structure can be used repeatedly. It can be used to drop Cable and 3 mm single-mode optical fiber. Its easy and convenient installation process takes only 2 minutes.



FEATURES	APPLICATIONS				
11					
On-site installation, less tools;	Optical fiber transmission lines				
•The back end of the inside box set can be spun open, benefit	for optical fiber •ODF				
inletting;	•Fiber optic test instruments				
Perfect optical performance;					
Can repeat operation at least 5 times					
●Tensile strength: 30N;					
●Total length of SC type fast connector(include tail-cuff methods)≤ 60mm					
Connector Type	XDQAC-SC/PC(APC)-A				
Fiber Type	Single mode				
Optical Cable Type	Figure 8 Cable				
Insertion Loss	< 0.5dB				
Mari American Marina Devendo					

Phone +91 9871650366 Email : sales@welltechenterprises.in



Return Loss	>40dB(PC) >50dB(APC)		
Tensile Strength	30N (Figure 8 Cable)		
Operating Temperature	-40°C~+85°C		

		I			
	1 SC type Fast Connector	XDQAC-SC/PC-A	рс	1	
1		XDQAC-SC/APC-A	рс	1	
2	2 Fixed length cutting slice (Slice)	XDQAC-DQG	рс	1	10pcs Fast connector with 1pc Fixed length cutting
			F-5	·	slice
2	Fiber cleaver	OFC-1	set	1	Optional
3	Rubber-insulated wire stripping	PKBQ	рс	1	Optional
	pliers	T NOQ	ρo	•	Cpriorial
4	Fiber Optical Stripper	CFS-2	рс	1	Optional
5	Red laser pointer	AVL720S	рс	1	Optional

Phone +91 9871650366 Email : sales@welltechenterprises.in