

ODF Series

Splice Closure

Welltech Enterprises vertical splice closure is made by CNC with quality engineering plastics material (PC). The locking fastener is made of stainless steel, the sealing accessory is made of elastic sealing materials. The box is reusable in service. Installation ways are overhead, pipes or directly buried for different connections. It also meets the requirements of box type splitters in the FTTX.



		FEATURES			APPLICATIONS				
						,			
•Ou	Outdoor Wall mounted or pole mounted,IP66.				Cable connection				
•Mo	●Modular design, easy to install or expansion.				Optical splitting(split ratio:1X2~X2)				
•FC	•FC、SC、LC adapters could match the installation bar								

Phone +91 9871650366 Email : sales@welltechenterprises.in



Parameters	Conditions				
Wavelength	850nm,1310nm,1550nm				
Insertion Loss	≤0.2dB				
Return Loss	SC/PC≥50dB SC/UPC≥50dB SC/APC≥60dB				
Operating Temperature	-40℃~+65℃				
Storage Temperature	-25℃ ~ +60℃				
Environment humility	≤95% (+40°C)				
Atmosphere Pressure	70kPa ~ 106kPa				
Connector Lifetime	After 1000 times repeat plug, variation<0.1 dB;				
Insulation resistance between wiring unit and cabinet > 20000MΩ/500V(DC)					
Voltage resistance between wiring unit and cabinet > 15000V(DC)/1min,no spark-through and no flash-over					

Material	Name	Туре	Dimensions mm (H×W×L)±3mm	Capacity	Remark
	96c Fiber Optic Splice Closure	GPX311-JX1-96(H1)	400X200X120	Max. 96c	3 in 3 out
Horizontal	192c Fiber Optic Splice Closure	GPX311-JX1-192(H3)	450X216X160	Max. 192	3 in 3 out

WELLTECH ENTERPRISES

Phone +91 9871650366 Email : sales@welltechenterprises.in



18c Fiber Optic Splice			With two pcs of1x8 blockness	2 in 2 out
	GPX311-JX1-18(H6)	600x135x78		
Closure			fiber splitters Max.52c	

Phone +91 9871650366 Email : sales@welltechenterprises.in