

Introduction to Scientific Computing for Biologists

ISCB20.09 - Introduction to R

Md. Jubayer Hossain
<https://jhossain.me/>
jubayer@hdrobd.org

Founder
Health Data Research Organization
Lead Organizer
Scientific Computing for Biologists

01 February 2021

Section-2: Getting Started


Installing R

- ▶ Installing R on Windows - <https://cran.r-project.org/bin/windows/base/>
- ▶ Installing R on Linux -
<https://cran.r-project.org/bin/linux/ubuntu/README.html>
- ▶ Installing R on Mac - <https://cran.r-project.org/bin/macosx/>

Installing RStudio

- ▶ RStudio is an Integrated Development Environment(IDE) available for R that is built by RStudio.
- ▶ Download and Install
<https://rstudio.com/products/rstudio/download/#download>

The RStudio Interface



Section-3: Variables and Reserved Keywords

Variables(Identifiers) in R

- ▶ Variables are used to **store data**, whose value can be changed according to our need.

Variables(Identifiers) in R

- ▶ Variables are used to **store data**, whose value can be changed according to our need.
- ▶ A variable is a name given to a memory location, which is used to store values in a computer program.

Variables(Identifiers) in R

- ▶ Variables are used to **store data**, whose value can be changed according to our need.
- ▶ A variable is a name given to a memory location, which is used to store values in a computer program.
- ▶ Variables in R programming can be used to store numbers (real and complex), words, matrices, and even tables.

Variables(Identifiers) in R

- ▶ Variables are used to **store data**, whose value can be changed according to our need.
- ▶ A variable is a name given to a memory location, which is used to store values in a computer program.
- ▶ Variables in R programming can be used to store numbers (real and complex), words, matrices, and even tables.
- ▶ R is a dynamically programmed language which means that unlike other programming languages, we do not have to declare the data type of a variable before we can use it in our program.

Variables(Identifiers) in R

- ▶ Variables are used to **store data**, whose value can be changed according to our need.
- ▶ A variable is a name given to a memory location, which is used to store values in a computer program.
- ▶ Variables in R programming can be used to store numbers (real and complex), words, matrices, and even tables.
- ▶ R is a dynamically programmed language which means that unlike other programming languages, we do not have to declare the data type of a variable before we can use it in our program.
- ▶ Unique name given to variable (function and objects as well) is **identifier**.

Rules for writing Identifiers in R

- ▶ Identifiers can be a combination of letters, digits, period (.) and underscore (_).

Rules for writing Identifiers in R

- ▶ Identifiers can be a combination of letters, digits, period (.) and underscore (_).
- ▶ It must start with a letter or a period. If it starts with a period, it cannot be followed by a digit.

Rules for writing Identifiers in R

- ▶ Identifiers can be a combination of letters, digits, period (.) and underscore (_).
- ▶ It must start with a letter or a period. If it starts with a period, it cannot be followed by a digit.
- ▶ It should not start with a number (e.g:- 2x)

Rules for writing Identifiers in R

- ▶ Identifiers can be a combination of letters, digits, period (.) and underscore (_).
- ▶ It must start with a letter or a period. If it starts with a period, it cannot be followed by a digit.
- ▶ It should not start with a number (e.g:- 2x)
- ▶ It should not start with a dot followed by a number (e.g:- .2x)

Rules for writing Identifiers in R

- ▶ Identifiers can be a combination of letters, digits, period (.) and underscore (_).
- ▶ It must start with a letter or a period. If it starts with a period, it cannot be followed by a digit.
- ▶ It should not start with a number (e.g:- 2x)
- ▶ It should not start with a dot followed by a number (e.g:- .2x)
- ▶ It should not start with an underscore (e.g:- _x)

Rules for writing Identifiers in R

- ▶ Identifiers can be a combination of letters, digits, period (.) and underscore (_).
- ▶ It must start with a letter or a period. If it starts with a period, it cannot be followed by a digit.
- ▶ It should not start with a number (e.g:- 2x)
- ▶ It should not start with a dot followed by a number (e.g:- .2x)
- ▶ It should not start with an underscore (e.g:- _x)
- ▶ Reserved words in R cannot be used as identifiers(e.g: TRUE, FALSE)

Rules for writing Identifiers in R

- ▶ Identifiers can be a combination of letters, digits, period (.) and underscore (_).
- ▶ It must start with a letter or a period. If it starts with a period, it cannot be followed by a digit.
- ▶ It should not start with a number (e.g:- 2x)
- ▶ It should not start with a dot followed by a number (e.g:- .2x)
- ▶ It should not start with an underscore (e.g:- _x)
- ▶ Reserved words in R cannot be used as identifiers(e.g: TRUE, FALSE)

Basically, there are 5 naming conventions

- ▶ alllowercase: e.g. myname
- ▶ period.separated: e.g. new.name
- ▶ underscore_separated: e.g. my_name
- ▶ lowerCamelCase: e.g. myName
- ▶ UpperCamelCase: e.g. MyName

Creating Variables

Using equal(=) operator

```
x = 10
```

Using leftward(<-) operator

```
y <- 15
```

Using rightward(->) operator

```
z <- 20
```

Reserved Keywords in R

- ▶ Don't use any reserved keyword as variable name. List all of reserved words in R by using `(?Reserved)`.
- ▶ The reserved words in R's parser are - `if` `else` `repeat` `while` `function` `for` `in` `next` `break` - `TRUE` `FALSE` `NULL` `Inf` `NaN` `NA` `NA_integer_` `NA_real_` `NA_complex_` `NA_character_`

Entering Input

At the R prompt/console we type expressions.

```
num <- 10
```

The <- symbol is the **assignment** operator.

The grammar of the language determines whether an expression is complete or not.

Evaluation

When a complete expression is entered at the R console, it is evaluated and the result of evaluated expression is returned. The result may be auto-printed.

```
x <- 10
```

```
x
```

```
## [1] 10
```

```
x <- 10
```

```
print(x)
```

```
## [1] 10
```

```
x <- 10
```

```
cat(x)
```

```
## 10
```

Comments in R

The `#` character indicates a comment.

```
x <- 10 # This is a comment
```

Anything to the right of the `#` (including the `#` itself) is ignored.

This is only comment character in R.

R does not support multi-line comments or comment block.