


% Introduction to the Unix shell for biologists % original by Konrad U. Förstner % modified by Markus J. Ankenbrand and Alexander Keller



The original work by Konrad Förstner is licensed under a [Creative Commons Attribution 4.0 International License](#) so is this modified version by Markus J. Ankenbrand and Alexander Keller.

The source code can be found at:

- original: [https://github.com/konrad/Introduction\\_to\\_the\\_Unix\\_Shell\\_for\\_biologists/](https://github.com/konrad/Introduction_to_the_Unix_Shell_for_biologists/)
- modified: [https://github.com/chiras/Introduction\\_to\\_the\\_Unix\\_Shell\\_for\\_biologists](https://github.com/chiras/Introduction_to_the_Unix_Shell_for_biologists)

## Motivation and background

---

In this course you will learn the basics of how to use the Unix shell. Unix is a class of operating systems with many different flavors including well-known ones like GNU/Linux and the BSDs. The development of Unix and its shell (also known as command line interface) dates back to the late 1960s. Still, their concepts lead to very powerful tools. In the command line you can easily combine different tools into pipelines, avoid repetitive work and make your workflow reproducible. Knowing how to use the shell will also enable you to run programs that are only developed for this environment which is the case for many bioinformatical tools.

## Work environment and test files

---

During this course all of you are working on Ubuntu (version 24.04) which is a widely used GNU/Linux distribution or Mac OSX. To get started execute the following command in a terminal:

```
$ git clone  
https://github.com/iimog/Introduction_to_the_Unix_Shell_for_biologists/
```

Do not type the \$ sign it just indicates the beginning of user input. This command will clone the repository with everything you need for this tutorial.

## The basic anatomy of a command line call

---

Running a tool in the command line interface follows a simple pattern. At first you have to write the name of the command (if it is not globally installed it's precise location needs to be given - we will get to this later). Some programs additionally require parameters and arguments. Parameters usually start with a dash (-). The common pattern looks like this (<> indicates obligatory items, [] indicates optional items):

```
<program name> [parameters] [arguments]
```

An example is calling the program `ls` which lists the content of a directory. You can simply call it without any parameter

```
$ ls
```

or with one or more parameters

```
$ ls -l  
$ ls -lh
```

or with one or more arguments

```
$ ls test_folder
```

or with one or more parameters and arguments

```
$ ls -l test_folder
```

The result of a command is written usually to the so called *standard output* of the shell which is the screen shown to you. We will later learn how to redirect this e.g. to the *standard input* of another program.

## How to get help and documentation

---

Especially in the beginning you will have a lot of questions what a command does and which arguments and parameters need to be given. One rule before using a command or before asking somebody about it is called **RTFM** (please check the meaning yourself). Maybe the most important command is `man` which stands for *manual*. Most commands offer a manual and with `man` you can read those. To get the documentation of `ls` type

```
$ man ls
```

To close the manual use `q`. Additionally or alternatively many tools offer some help via the parameter `-h`, `-help` or `--help`. For example `ls`:

```
$ ls --help
```

Other tools present this help if they are called without any parameters or arguments.

# Bash keyboard shortcuts

---

There are different implementations of the Unix shell. You are currently working with Bash (**B**ourne-**a**gain **s**hell). Bash has several keyboard shortcuts that improve the interaction. Here is a small selection:

- Ctrl-c - Stop the command
- Tab - extend commands and file/folder names
- Ctrl-↑ - Go backward in command history
- Ctrl-↓ - Go forward in command history
- Ctrl-r - Search in command history

## Files, folders, locations

---

Topics:

- `ls`
- `pwd`
- `cd`
- `mkdir`

In this part you will learn how to navigate through the file system, explore the content of folders and create folders.

At first we need to know where we are. If you open a new terminal you should be in your home directory (we will explain this below). To test this, call the program `pwd` which stands for **p**rint **w**orking **d**irectory.

```
$ pwd
/home/ubuntu
```

Instead of `ubuntu` there will be your username after `/home/`. This is your personal home directory. In general each user has a folder with its user name located inside the folder `home`. The next command we need and which has been already mentioned above is `ls`. It simply lists the content of a folder. If you call it without any arguments it will output the content of the current folder. Using `ls` we want to get a rough overview of what a common Unix file system tree looks like and learn how to address files and folders. The root folder of a systems starts with `/`. Call

```
$ ls /
```

to see the content of the root folder. You should see something like

```
bin    data  etc   lib    lost+found  mnt  proc  run   srv  tmp  var
boot  dev   home  lib64  media      opt  root  sbin  sys  usr
```

There are several subfolders in the so-called root folder (and yes, to make it a little bit confusing there is even a folder called `root` in the root folder). Those are more important if you are the administrator of the system. Normal users do not have the permission to make changes here. Currently your home directory is your little universe in which you can do whatever you want. In here we will learn how to work with paths. A file or folder can be addressed either with its *absolute* or *relative path*.

Assuming you are in this folder (`/home/ubuntu/`) the relative path to the folder you cloned earlier is simply `introduction_to_the_unix_shell_for_biologists`. You can get the content of the folder listed by calling `ls` like this:

```
$ ls introduction_to_the_unix_shell_for_biologists
```

This is the so called *relative path* as it is relative to the current work directory `/home/ubuntu/`. The *absolute path* would start with a `/` and is `/home/ubuntu/introduction_to_the_unix_shell_for_biologists`. Call `ls` like this:

```
$ ls /home/ubuntu/introduction_to_the_unix_shell_for_biologists
```

There are some conventions regarding *relative* and *absolute paths*. One is that a dot (`.`) represents the current folder. The command

```
$ ls ./
```

should return the same as simply calling

```
$ ls
```

Two dots (`..`) represent the parent folder. If you call

```
$ ls ../
```

you should see the content of `/home`. If you call

```
$ ls ../../
```

you should see the content of the parent folder of the parent folder which is the root folder (`/`) assuming you are in `/home/ubuntu/`. Another convention is that `~/` represents the home directory of the user. The command

```
$ ls ~/
```

should list the content of your home directory independent of your current location in the file system.

Now as we know where we are and what is there we can start to change our location. For this we use the command `cd` (change directory). If you are in your home directory `/home/ubuntu/` you can go into the folder `introduction_to_the_unix_shell_for_biotologists` by typing

```
$ cd introduction_to_the_unix_shell_for_biotologists
```

After that call `pwd` to make sure that you are in the correct folder.

```
$ pwd
/home/ubuntu/introduction_to_the_unix_shell_for_biotologists
```

To go back into your home directory you have different options. Use the *absolute path*

```
$ cd /home/ubuntu/
```

or the above mentioned convention for the home directory `~/`:

```
$ cd ~/
```

or the *relative path*, in this case the parent directory of `/home/ubuntu/unix_course_files`:

```
$ cd ../
```

As the home directory is such an important place `cd` uses this as default argument. This means if you call `cd` without argument you will go to the home directory. Test this behavior by calling

```
$ cd
```

Try now to go to different locations in the file system and list the files and folders located there.

Now we will create our first folder using the command `mkdir` (*make directory*). Go into the home directory and type:

```
$ mkdir my_first_folder
```

Here we can discuss the implementation of another Unix philosophy: "No news is good news." The command successfully created the folder `my_first_folder`. You can check this by calling `ls`, but `mkdir` did not tell you this. If you do not get a message this usually means everything went fine. If you call the above `mkdir` command again you should get an error message like this:

```
$ mkdir my_first_folder
mkdir: cannot create directory 'my_first_folder': File exists
```

So if a command does not complain you can usually assume there was no error.

## Manipulating files and folder

---

Topics:

- `touch`
- `cp`
- `mv`
- `rm`

Next we want to manipulate files and folders. We create some dummy files using `touch` which is usually used to change the time stamps of files. But you can also create empty files with it easily. Let's create a file called `test_file_1.txt`:

```
$ touch test_file_1.txt
```

Use `ls` to check that it was created.

The command `cp` (*copy*) can be used to copy files. For this it requires at least two arguments: the source and the target file. In the following example we generate a copy of the file `test_file_1.txt` called `a_copy_of_test_file.txt`.

```
$ cp test_file_1.txt a_copy_of_test_file.txt
```

Use `ls` to confirm that this worked. We can also copy the file in the folder `my_first_folder` which we have created above:

```
$ cp test_file_1.txt my_first_folder
```

Now there should be also a file `test_file_1.txt` in the folder `my_first_folder`. If you want to copy a folder and its content you have to use the parameter `-r`.

```
$ cp -r my_first_folder a_copy_of_my_first_folder
```

You can use the command `mv` (move) to rename or relocate files or folders. To rename the file `a_copy_of_test_file.txt` to `test_file_with_new_name.txt` call

```
$ mv a_copy_of_test_file.txt test_file_with_new_name.txt
```

With `mv` you can also move a file into a folder. For this the second argument has to be a folder. For example, to move the file now named `test_file_with_new_name.txt` into the folder `my_first_folder` use

```
$ mv test_file_with_new_name.txt my_first_folder
```

You are not limited to one file if you want to move them into a folder. Let's create and move two files `file1` and `file2` into the folder `my_first_folder`.

```
$ touch file1 file2  
$ mv file1 file2 my_first_folder
```

At this point we can introduce another handy feature most shells offer which is called *globbing*. Let us assume you want to apply the same command to several files. Instead of explicitly writing all the file names you can use a *globbing pattern* to address them. There are different wildcards that can be used for these patterns. The most important one is the asterisk (`*`). It can replace none, one or more characters. Let us explore this with a small example:

```
$ touch file1.txt file2.txt file3  
$ ls *txt  
$ mv *txt my_first_folder
```

The `ls` shows the two files matching the given pattern (i.e. `file1.txt` and `file2.txt`) while dismissing the one not matching (i.e. `file3`). Same for `mv` - it will only move the two files ending with `txt`.

We accumulated several test files that we do not need anymore. Time to clean up a little bit. With the command `rm` (remove) you can delete files and folders. Please be aware that there is no such thing as a trash bin if you remove items this way. They will be gone for good and without further notice.

To delete a file in `my_first_folder` call:

```
$ rm my_first_folder/file1.txt
```

To remove a folder use the parameter `-r` (*recursive*):

```
$ rm -r my_first_folder
```

## File content - part 1

---

Topics:

- `less`
- `cat`
- `echo`
- `head`
- `tail`
- `cut`

Until now we did not care about the content of the files. This will change now. Please go into the folder `unix_course_files`:

```
$ cd unix_course_files
```

There should be some files waiting for you. To read the content with the possibility to scroll around we need a so called pager program. Most Unix systems offer the programs `more` and `less` which have very similar functionalities ("more or less are more or less the same"). We will use the later one here. Let's open the file `origin_of_species.txt`

```
$ less origin_of_species.txt
```

The file contains Charles Darwin's *Origin of species* in plain text. You can scroll up and down line-wise using the arrow keys or page-wise using the page-up/page-down keys. To quit use the key `q`. With pager programs you can read file content interactively, but sometimes you just want to have the content of a file given to you (i.e. on the *standard output*). The command `cat` (*concatenate*) does that for one or more files. Let us use it to see what is in the example file `two_lines.txt`. Assuming you are in the folder `unix_course_files` you can call

```
$ cat two_lines.txt
```



The content of the file is shown to you. You can apply the command to two files and the content is concatenated and returned:

```
$ cat two_lines.txt three_lines.txt
```

This is a good time to introduce the *standard input* and *standard output* and what you can do with it. Above I wrote the output is given to you. This means it is written to the so called *standard output*. You can redirect the *standard output* into a file by using `>`. Let us use the call above to generate a new file that contains the combined content of both files:

```
$ cat two_lines.txt three_lines.txt > five_lines.txt
```

Please have a look at the content of this file:

```
$ cat five_lines.txt
```

The *standard output* can also be redirected to other tools as *standard input*. More about this below. With `cat` we can reuse the existing file content. To create something new we use the command `echo` which writes a given string to the standard output.

```
$ echo "Something very creative"
```

To redirect the output into a target file use `>`.

```
$ echo "Something very creative." > creative.txt
```

Be aware that this can be dangerous. You will overwrite the content of an existing file. For example if you call now

```
$ echo "Something very uncreative." > creative.txt
```

there will be only the latest string written to the file and the previous one will be overwritten. To append the output of a command to a file without overwriting the content use `>>`.

```
$ echo "Something very creative." > creative.txt  
$ echo "Something very uncreative." >> creative.txt
```

Now `creative.txt` should contain two lines.

Sometimes you just want to get an excerpt of a file e.g. just the first or last lines of it. For this the commands `head` and `tail` can be used. Per default 10 lines are shown. You can use the parameter `-n <NUMBER>` (e.g. `-n 20` or just `-<NUMBER>` (e.g. `-20`) to specify the number of lines to be displayed. Test the tools with the file `origin_of_species.txt`:

```
$ head origin_of_species.txt
$ tail origin_of_species.txt
```

You cannot only select vertically but also horizontally using the command `cut`. Let us extract only the first 10 characters of each line in the file `origin_of_species.txt`:

```
$ cut -c 1-10 origin_of_species.txt
```

The tool `cut` can be very useful to extract certain columns from CSV files (*comma/character separated values*). Have a look at the content of the file `genes.csv`. You see that it contains different columns that are tabular-separated. You can extract selected columns with `cut`:

```
$ cut -f 1,4 genes.csv
```

## File content - part 1

---

Topics:

- `wc`
- `sort`
- `uniq`
- `grep`
- `cut`
- `tr`

There are several tools that let you manipulate the content of a plain text file or return information about it. If you want for example some statistics about the number of character, words and lines use the command `wc`. Let us count the number of lines in the file `origin_of_species.txt`:

```
$ wc -l origin_of_species.txt
```

You can use the command `sort` to sort a file alpha-numerically. Test the following calls

```
$ sort unsorted_numbers.txt
$ sort -n unsorted_numbers.txt
$ sort -rn unsorted_numbers.txt
```

and try to understand the output.

The tool **uniq** takes a sorted list of lines and removes line-wise the redundancy. Please have a look at the content of the file **redundant.txt**. Then use **uniq** to generate a non-redundant list:

```
$ uniq redundant.txt
```

If you call **uniq** with **-c** you get the number of occurrence for each remaining entry:

```
$ uniq -c redundant.txt
```

With the tool **grep** you can extract lines that match a given pattern. For instance, if you want to find all lines in **origin\_of\_species.txt** that contain the word **species** call

```
$ grep species origin_of_species.txt
```

As you can see we only get the lines that contain **species** but not the ones that contain **Species**. To make the search case-insensitive use the parameter **-i**.

```
$ grep -i species origin_of_species.txt
```

If you are only interested in the number of lines that match the pattern use **-c**:

```
$ grep -ic species origin_of_species.txt
```

The program **tr** (*translate*) exchanges one character by another. It reads from the *standard input* and performs the replacement. To direct the content of a file as *standard input* into a program **<** is applied. Have a quick look at the content of the file **DNA.txt**.

```
$ cat DNA.txt
```

We now want to replace all **T**s in the file by **U**s. For this we call:

```
$ tr T U < DNA.txt
```

## Connecting tools

---

Another piece of the Unix philosophy is to build small tools that do one thing optimally and use the standard input and standard output. The real power of Unix builds on the capability to easily connect tools. For this so-called *pipes* are used. To use the *standard output* of one tool as *standard input* of another tool the vertical bar `|` is used. For example, in order to extract the first 1000 lines from `origin_of_species.txt`, search for lines that contain `species`, then search in those lines the ones which contain `wild` and finally replace the `ws` by `ms` call (Please write this in one line in the shell and remove the `\`):

```
$ head -n 1000 origin_of_species.txt | grep species \  
  | grep wild | tr w m
```

## Examples analysis

---

Equipped with a fine selection of useful programs and basic understanding of how to combine them, we will now apply them to analyze real biological data.

### Retrieving data

You have used the tool `wget` above to download the example files. It is very useful, especially, if you want to retrieve large data sets. We download the fasta file of the *Salmonella* Typhimurium SL1344 chromosome by calling (in this document the URL is split into three lines. Please write it in one line in the shell and remove the `\`).

```
wget ftp://ftp.ncbi.nih.gov/genomes/archive/old_refseq/Bacteria/  
  Salmonella_enterica_serovar_Typhimurium_SL1344_uid86645/  
  NC_016810.fna
```

### Calculate the GC content of a genome

Let us assume the GC content of the genome is not known to us. We can use a handful of commands to calculate this quickly. We can gain the number of nucleotides in the following manner.

```
grep -v ">" NC_016810.fna | grep -o "A" | wc -l  
  
grep -v ">" NC_016810.fna | grep -o "C" | wc -l  
  
grep -v ">" NC_016810.fna | grep -o "G" | wc -l
```

```
grep -v ">" NC_016810.fna | grep -o "T" | wc -l
```

As we only need to get the sum of As and Ts as well as Cs and Gs we can use an extended pattern for grep. The `|` means or:

```
grep -v ">" NC_016810.fna | grep -Eo "A|T" | wc -l
```

```
grep -v ">" NC_016810.fna | grep -Eo "C|G" | wc -l
```

Once we have the number we can calculate the GC content by piping a formula into the calculator `bc`.

```
echo "scale=5; 2332503/(2332503+2545509)*100" | bc
```

## Quality control with fastqc

We cannot only work with the default tools of the Unix shell but additionally have now access to a plethora of command line tools. Let's assume we want to perform a quality control analysis of multiple sequencing files. We choose `fastqc` for this purpose. On the current machine this tool is already installed. Try:

```
$ fastqc --help
```

To get some example data change into your home directory and clone the course files:

```
$ git clone /workshop/analysis-script.git
```

Now you can run fastqc on a real sequencing file:

```
$ fastqc analysis-script/PoJ118_S214_L001_R1_001.fastq.gz
```

The results will be in `analysis-script/PoJ118_S214_L001_R1_001_fastqc.html` Open with:

```
$ firefox analysis-script/PoJ118_S214_L001_R1_001_fastqc.html
```

## Very, very basic scripting

---

One huge advantage of the Unix shell is that you can script actions. For example you can write the command for the multiple alignment into a file e.g. using `echo`:

```
$ echo "fastqc analysis-script/PoJ118_S214_L001_R1_001.fastq.gz" >
run_me.sh
$ echo "firefox analysis-script/PoJ118_S214_L001_R1_001_fastqc.html" >>
run_me.sh
```

If you want to run the commands in that script you can call the script in the following manner:

```
$ bash run_me.sh
```

Shell scripting offers very powerful options to program workflows. Due to time restriction we will not cover this here.

## What's next

---

Here we just covered a small selection of tools and possibilities and hope that you can extend your Unix skills based on this knowledge yourself. There are many basic tools we have not covered but which could be important, e.g., archiving and compression tools like `tar`, `bzip2` and `gzip`. For more powerful text manipulation `sed` and `awk` are good choices. We also recommend to get familiar with text editors which can be used to interactively modify text files. Classic Unix environment editors are `vi` (and derivatives like `vim`) or `Emacs`. While they are very powerful they have a steep learning curve. For beginners `gedit` that offers a graphical user interface could be another option.