## **Sky-Frame 1**

www.sky-frame.ch

INQUIRY:	PROJECT:
<ul><li>☐ In accordance with drawing no.</li><li>☐ In accordance with diagram: (from outside)</li></ul>	Date of inquiry:/ / Project no:
	Item:   Piece(s):   Page:   /
	☐ Standard ☐ Pool (T,min > 5°C) ☐ Position monitoring (P)
Insect-screen	□ Deadbolt surveillance (R) □ Electric drive, amount: pce. (no R, VR) □ Required classifications: (water tightness, air permeability □ Special: powder coated: (RAL / NCS / DB /) □ E6 EV1
Accessories:  Gutter Sun-Box Weatherboard	Statics:  Wind load: [kN/m²]
Sketch:	
Notes:	Stamp: Signature:
	Order fax: +41 52 724 94 95

09.02.2015 10.2.2.1

## **Sky-Frame 2**

www.sky-frame.ch

INQUIRY:	PROJECT:
<ul><li>□ In accordance with drawing no.</li><li>□ In accordance with diagram: (from outside)</li></ul>	Date of inquiry:/ / Project no:
	Item: Piece(s): Page:    2-track   3-track   4-track
★   ★   ★   ★   ★     □   Axis size defined	☐ Standard ☐ Pool (T,min > 0°C)
All panels same width (recommendation)  Insect-screen to right "Fly" to left 45  Handle height: — mm  Standard = 1050mm RC2: must 1050mm min: RV=200 MVv=750  Width = mm  KABA (22) DPZ / Euro (17)	□ Increased burglary RC2 (WK2) □ Position monitoring (P) □ Deadbolt surveillance (R) □ Glass breakage sensor (G) □ Electric drive, amount: pce. (no R, G, VR) □ Required classifications: (water tightness, air permeability □ Special: powder coated: (RAL / NCS / DB /) □ E6 EV1
Accessories:  Gutter Sun-Box Weatherboard	Statics: ☐ Wind load: [kN/m²]
Sketch:	
Notes:	Stamp: Signature:
Pressure compensating valve (>800m)	Order fax: +41 52 724 94 95

## **Sky-Frame 3**

www.sky-frame.ch

INQUIRY:	PROJECT:
<ul><li>In accordance with drawing no.</li><li>In accordance with diagram: (from outside)</li></ul>	Date of inquiry:/ / Project no:
	Item:
Axis size defined All panels same width (recommendation)  Insect-screen to right "Fly" to left  Width =	□ Standard □ Pool □ Increased burglary RC2 (WK2) □ Sound insulation (special case) □ Position monitoring (P) □ MINERGIE Modul □ Deadbolt surveillance (R) □ MINERGIE-P Modul □ Glass breakage sensor (G) □ Gun □ Electric drive, amount: pce. (no R, G, VR) □ Required classifications: (water tightness, air permeabilit □ Special: powder coated: (RAL / NCS / DB /) □ E6 EV1 □ (80-120my, gloss standard 70±10%) □ 20 my (Standard) □ powder coated: □ 1 □ 2 □ 25 my (Pool / near sea) □ + pre-anodizing (Pool / near sea) □ Glass-Type: SG = "Sky-Glass" □ SG (Ug= / Lt = / g =) □ Swisspacer-U black □ Swisspacer-U grey □ Special: Swisspacer-U grey
Accessories:  Gutter Sun-Box Weatherboard	Statics: ☐ Wind load: [kN/m²]
Sketch:	
Notes:  Pressure compensating valve (>800m)	Stamp: Signature:
Yes • No	Order fax: +41 52 724 94 95

09.02.2015