

# A Unified View of Frequency Estimation and their Attacks on Local Differential Privacy

Al Mehdi Saadat Chowdhury, Dhaval Pankaj Tanna, Deepak Vellanki, Chirag Manjeshwar  
School of Computing and Augmented Intelligence  
Arizona State University

# Outline



## Introduction:


- Differential Privacy
- Local Differential Privacy
- Pure LDP Framework
- Attack Problem



## Attacks:

- General Attack Formulation
- Attacking kRR
- Attacking OUE
- Attacking OLH

## Frequency Estimation Techniques:

- RAPPOR
  - K Randomized Response (kRR)
  - Optimized Unary Encoding (OUE)
  - Optimized Local Hashing (OLH)
- 

## Evaluation:


- Comparison between Estimators
- Gain from Attacks
- Impacts of Parameters on Attacks

## Conclusion:



# Introductory Concepts

# Differential Privacy




$$\Pr \left[ \mathcal{M} \left( \begin{array}{c} x \\ \text{sample}_1 \\ \text{sample}_2 \\ \text{sample}_3 \\ \text{sample}_4 \\ \text{sample}_5 \end{array} \right) \in S \right] \leq e^{\epsilon} \Pr \left[ \mathcal{M} \left( \begin{array}{c} y \\ \text{sample}_1 \\ \text{sample}_2 \\ \text{sample}_3 \\ \text{sample}_4 \\ \text{sample}_{11} \end{array} \right) \in S \right] + \delta$$

# Local Differential Privacy


$$\Pr \left[ \mathcal{M} \left( \begin{array}{c} x \\ \text{sample}_1 \end{array} \right) \in y \right] \leq e^\epsilon \Pr \left[ \mathcal{M} \left( \begin{array}{c} y \\ \text{sample}_{11} \end{array} \right) \in y \right]$$

# Protocols for Local Differential Privacy


## Encode



## Perturb



## Aggregate



Frequency Estimation Problem

# Pure Differential Privacy

- A unified framework --- Can be used to define all frequency protocols.
- Defined based on two fixed probabilities  $p^*$  and  $q^*$

$$\begin{aligned}\Pr[PE(v_1) \in \{y \mid v_1 \in \text{Support}(y)\}] &= p^* \\ \Pr[PE(v_2) \in \{y \mid v_1 \in \text{Support}(y)\}] &= q^*\end{aligned}$$

- Based on this framework, we will describe 4 protocols – RAPPOR, kRR, OUE, OLH.

# Attacking Estimators – Problem Formulation

- Assume:  $n$  real users
- Inject:  $m$  fake users
- To increase frequency of  $r$  items:  $T = \{t_1, t_2, \dots, t_r\}$

- Goal:

$$\Delta \tilde{f}_t = \tilde{f}_{t,after} - \tilde{f}_{t,before} \quad \forall t \in T$$
$$\max_Y \sum_{\{t \in T\}} \mathbb{E}[\Delta \tilde{f}_t]$$




# Foundational Work

# Google's RAPPOR

## Encode

$$\mathcal{H} = \{H_1, H_2, \dots, H_m\}$$



0	1	0	0	0	0
---	---	---	---	---	---

$$B_0[i] = 1 \quad \text{if } \exists H \in \mathcal{H}, s.t., H(v) = i$$

## Perturb

0	1	0	0	0	0
---	---	---	---	---	---



0	1	0	0	1	0
---	---	---	---	---	---

$$\Pr[B_1[i]] = 1 = \begin{cases} p = 1 - \frac{f}{2} & \text{if } B_0[i] = 1 \\ q = \frac{f}{2} & \text{if } B_0[i] = 0 \end{cases}$$

## Aggregate

- Using Linear Regression
- Using LASSO Regression

# Limitations of RAPPOR

- Use of Bloom filter reduced communication cost


However,

- Accuracy decreased significantly
- Computation cost of the aggregation step increased significantly


# SOTA Frequency Estimators

# K Randomized Response

## Encode



## Perturb



$$\Pr[PE(v) = i] = \begin{cases} p = \frac{e^\epsilon}{e^\epsilon + d - 1} & \text{if } i = v \\ q = \frac{1}{e^\epsilon + d - 1} & \text{otherwise} \end{cases}$$

## Aggregate


$$\tilde{f}_v = \frac{\frac{1}{n} \sum_{i=1}^n \mathbb{I}_{\{Support(y_i)\}}(v) - q^*}{p^* - q^*}$$

For kRR,


$$Support(y_i) = \{y\}$$

# Optimal Unary Encoding

## Encode



## Perturb



$$\Pr[PE(v) = 1] = \begin{cases} p = \frac{1}{2} & \text{if } i = v \\ q = \frac{1}{e^\epsilon + 1} & \text{otherwise} \end{cases}$$

## Aggregate

$$\tilde{f}_v = \frac{\frac{1}{n} \sum_{i=1}^n \mathbb{I}_{\{Support(y_i)\}}(v) - q^*}{p^* - q^*}$$

For OUE,

$$Support(y_i) = \{v \mid v \in [d] \text{ and } y_v = 1\}$$

# Optimal Local Hashing

## Encode

$$\mathcal{H} = \{H_1, H_2, \dots, H_m\}$$



$H_3$



0	0	1	0	0	0
---	---	---	---	---	---

## Perturb

0	0	1	0	0	0
---	---	---	---	---	---



0	0	0	0	0	0
---	---	---	---	---	---

$$\Pr[y = \langle H, x \rangle] = \begin{cases} p = \frac{e^\epsilon}{e^\epsilon + d - 1} & \text{if } x = i \\ q = \frac{1}{e^\epsilon + d - 1} & \text{otherwise} \end{cases}$$

## Aggregate

$$\tilde{f}_v = \frac{\frac{1}{n} \sum_{i=1}^n \mathbb{I}_{\{\text{Support}(y_i)\}}(v) - q^*}{p^* - q^*}$$

For OLH,

$$\begin{aligned} \text{Support}(y_i) \\ = \{v \mid v \in [d] \text{ and } H(v) = x\} \end{aligned}$$

# Maximum Gain Attacks on Frequency Estimators



# Frequency Estimators Under Attack




Illustration: Apple introduced LDP to estimate popular emojis in 2016

# Frequency Gain from an Attack

General Formula:

$$G = \frac{\sum_{\{i=n+1\}}^{\{n+m\}} \mathbb{E}[\mathbb{I}_{\text{Support}(y_i)}(t)]}{(n+m)(p^* - q^*)} - \frac{m \sum_{\{i=1\}}^{\{n\}} \mathbb{E}[\mathbb{I}_{\text{Support}(y_i)}(t)]}{n(n+m)(p^* - q^*)}$$

(Accounts for Fake  
Users' Impact)

(Accounts for Genuine Users'  
Impact Dilution)

MGA tries to maximize this gain

# Maximum Gain Attack: Overview




Illustration: MGA attack on the OUE protocol

# Attacking kRR

- The support set is:

$$\sum_{\{t \in T\}} \mathbb{I}_{\text{Support}(y_i)}(t) = 1$$

- Gain becomes:

$$G = \frac{m}{(n + m)(p^* - q^*)} - c$$

- Plugging in  $p^*$  and  $q^*$  gives:

$$G = \beta(1 - f_T) + \frac{\beta(d - r)}{e^\epsilon - 1}$$

# Attacking OUE

- The support set is:

$$\sum_{\{t \in T\}} \mathbb{I}_{\text{Support}(y_i)}(t) = r$$

- Gain becomes:

$$G = \frac{rm}{(n+m)(p^* - q^*)} - c$$

- Plugging in  $p^*$  and  $q^*$  gives:

$$G = \beta(2r - f_T) + \frac{2\beta r}{e^\epsilon - 1}$$

# Attacking OLH

- The support set is:

$$\sum_{\{t \in T\}} \mathbb{I}_{\text{Support}(y_i)}(t) = r$$

- Gain becomes:

$$G = \frac{rm}{(n+m)(p^* - q^*)} - c$$

- Plugging in  $p^*$  and  $q^*$  gives:

$$G = \beta(2r - f_T) + \frac{2\beta r}{e^\epsilon - 1}$$

# Evaluation

# Estimators: Utility vs. Security

	kRR	OUE	OLH
Communication Cost	$\theta(\log d)$	$\theta(d)$	$\theta(\log n)$
Variance	$n \cdot \frac{d - 2 + e^\epsilon}{(e^\epsilon - 1)^2}$	$n \cdot \frac{4e^\epsilon}{(e^\epsilon - 1)^2}$	$n \cdot \frac{4e^\epsilon}{(e^\epsilon - 1)^2}$
Gain of MGA	$\beta(1 - f_T) + \frac{\beta(d - r)}{e^\epsilon - 1}$	$\beta(2r - f_T) + \frac{2\beta r}{e^\epsilon - 1}$	$\beta(2r - f_T) + \frac{2\beta r}{e^\epsilon - 1}$

$n$  = number of real users

$m$  = number of fake users

$\beta = \frac{m}{n+m}$  = fraction of fake users

$d$  = domain size


$T$  = set of target items

$r = |T|$

$$f_T = \sum_{t \in T} f_t$$



# MGA Comparison



# Conclusion

# Summary and Open Questions

- Different Frequency Estimation Protocols under LDP
- Attacks on Estimators
  - kRR performs poorly when the domain size increases
  - OUE, OLH perform poorly when the target items increases
- Open Question:
  - Large domain, Large target items
  - How to handle complex data types
  - Utility – Privacy trade-offs

Thank You