

DBT Assignment-6

1. Write two different queries that would produce all orders taken on October 3rd or 4th, 1990.

```
select * from orders
where odate between '1990-10-03' and '1990-10-04';
```

```
select * from orders
where odate in ('1990-10-03', '1990-10-04');
```

```
mysql> select * from orders
      -> where odate between '1990-10-03' and '1990-10-04';
+-----+-----+-----+-----+-----+
| Onum | Amt   | Odate   | Cnum | Snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
+-----+-----+-----+-----+-----+
```

```
mysql> select * from orders
      -> where odate in ('1990-10-03', '1990-10-04');
+-----+-----+-----+-----+-----+
| Onum | Amt   | Odate   | Cnum | Snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
+-----+-----+-----+-----+-----+
```

2. Write a query that selects all of the customers serviced by Peel or Motika.
(Hint: the snum field relates the two tables to one another).

```
select c.* from customers c
join salespeople s on c.snum = s.snum
where s.sname in ('Peel', 'Motika');
```

```
mysql> select c.* from customers c
      -> join salespeople s on c.snum = s.snum
      -> where s.sname in ('Peel', 'Motika');
+-----+-----+-----+-----+-----+
| Cnum | Cname  | City   | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2001 | Hoffman | London | 100    | 1001 |
| 2006 | Clemens | London | 100    | 1001 |
| 2007 | Pereira | Rome   | 100    | 1004 |
+-----+-----+-----+-----+-----+
```

3. Write a query that will produce all the customers whose names begin with a letter from 'A' to 'G'.

```
select * from customers
where cname >= 'A' and cname < 'H';
```

```
mysql> select * from customers
      -> where cname >= 'A' and cname < 'H';
+-----+-----+-----+-----+-----+
| Cnum | Cname    | City    | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome    | 200    | 1003 |
| 2004 | Grass    | Berlin  | 300    | 1002 |
| 2006 | Clemens  | London  | 100    | 1001 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
+-----+-----+-----+-----+-----+
```

4. Write a query that selects all customers whose names begin with the letter 'C'.

```
mysql> select * from customers
      -> where cname like 'C%';
+-----+-----+-----+-----+-----+
| Cnum | Cname    | City    | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2006 | Clemens  | London  | 100    | 1001 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
+-----+-----+-----+-----+-----+
```

5. Write a query that selects all orders except those with zeroes or NULLs in the amt field.

```
select * from orders
where amt != null or amt != 0;
```

```
mysql> select * from orders
      -> where amt != null or amt != 0;
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002
3008	4723.00	1990-10-05	2006	1001
3010	1309.95	1990-10-06	2004	1002
3011	9891.88	1990-10-06	2006	1001