



Week 3 Quiz



4/5 questions
correct

Quiz passed!

[Continue Course \(/learn/r-programming/peer/tNy8H/programming-assignment-2-lexical-scoping\)](/learn/r-programming/peer/tNy8H/programming-assignment-2-lexical-scoping)

[Back to Week 3 \(/learn/r-programming/home/week/3\)](/learn/r-programming/home/week/3)



1.

Take a look at the 'iris' dataset that comes with R. The data can be loaded with the code:

```
library(datasets)  
data(iris)
```

A description of the dataset can be found by running

```
?iris
```

There will be an object called 'iris' in your workspace. In this dataset, what is the mean of 'Sepal.Length' for the species *virginica*? **Please round your answer to the nearest whole number.**

(Only enter the numeric result and nothing else.)

7

Well done!

To get the answer here, you can use 'tapply' to calculate the mean of 'Sepal.Length' within each species.

✖ 2.

Continuing with the 'iris' dataset from the previous Question, what R code returns a vector of the means of the variables 'Sepal.Length', 'Sepal.Width', 'Petal.Length', and 'Petal.Width'?

- ☐ `apply(iris, 1, mean)`
- ☒ `apply(iris[, 1:4], 1, mean)`

Sorry, that's incorrect.

this takes the row means of the dataset.

- ☐ `apply(iris, 2, mean)`
- ☐ `apply(iris[, 1:4], 2, mean)`
- ☐ `rowMeans(iris[, 1:4])`
- ☐ `colMeans(iris)`

✔ 3.

Load the 'mtcars' dataset in R with the following code

```
library(datasets)
data(mtcars)
```

There will be an object names 'mtcars' in your workspace. You can find some information about the dataset by running

```
?mtcars
```

How can one calculate the average miles per gallon (mpg) by number of cylinders in the car (cyl)? Select all that apply.

- ☒ `with(mtcars, tapply(mpg, cyl, mean))`

Well done!

☐ `lapply(mtcars, mean)`

Well done!

this calculates the mean of each column and returns them in a list

☐ `split(mtcars, mtcars$cyl)`

Well done!

this just splits the data frame by number of cylinders

☐ `tapply(mtcars$cyl, mtcars$mpg, mean)`

Well done!

this computes the mean number of cylinders by mpg.

☒ `sapply(split(mtcars$mpg, mtcars$cyl), mean)`

Well done!

☐ `apply(mtcars, 2, mean)`

Well done!

this computes the mean of each column.

☐ `mean(mtcars$mpg, mtcars$cyl)`

Well done!

this returns an error in R.

☐ `sapply(mtcars, cyl, mean)`

Well done!

this returns an error in R.

☐ `tapply(mtcars$mpg, mtcars$cyl, mean)`

Well done!



4.

Continuing with the 'mtcars' dataset from the previous Question, what is the absolute difference between the average horsepower of 4-cylinder cars and the average horsepower of 8-cylinder cars?

(Please round your final answer to the nearest whole number. Only enter the numeric result and nothing else.)

127

Well done!



5.

If you run

`debug(ls)`

what happens when you next call the 'ls' function?

- ☐ The 'ls' function will execute as usual.
- ☐ Execution of 'ls' will suspend at the beginning of the function and you will be in the browser.

Well done!

- ☐ You will be prompted to specify at which line of the function you would like to suspend execution and enter the browser.
- ☐ The 'ls' function will return an error.

