Namespace Locator

Classes

Locator

Class Locator

Namespace: Locator

Assembly: Locator.dll

```
public class Locator
```

Inheritance

object ← Locator

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

Locator(string, string, string, string, string, string)

```
public Locator(string locatorDbConnectionString, string auth0Url, string
auth0ClientId, string auth0ClientSecret, string apiId, string apiIdentifier)
```

Parameters

`locatorDbConnectionString` string

`auth0Url` string

`auth0ClientId` string

`auth0ClientSecret` string

`apiId` string

`apiIdentifier` string

Methods

AddClient(string, string, Status)

Add client to locator database

```
public Task<int> AddClient(string clientName, string clientCode,
Status clientStatus)
```

Parameters

`clientName` string

`clientCode` string

`clientStatus` Status

Returns

Task<int>

AddClientUser(int, int)

Add user to a client in locator database

```
public Task<int> AddClientUser(int clientId, int userId)
```

Parameters

`clientId` int

`userId` int

Returns

Task<int>

AddConnection(int, int)

Add connection to locator database

```
public Task<int> AddConnection(int clientUserId, int databaseId)
```

Parameters

`clientUserId` int

`databaseId` int

Returns

Task<int>

AddDatabase(string, string, int, byte, Status)

Add new database on specified server and insert record in locator database

```
public Task<int> AddDatabase(string databaseName, string databaseUser, int
databaseServerId, byte databaseTypeId, Status databaseStatus)
```

Parameters

`databaseName` string

`databaseUser` string

`databaseServerId` int

`databaseTypeId` byte

`databaseStatus` Status

Returns

Task<int>

AddDatabaseServer(string, string)

Add existing database server information to locator database. (This will not create spin up a database server for you)

```
public Task<int> AddDatabaseServer(string databaseServerName,
string databaseServerIpAddress)
```

Parameters

`databaseServerName` string

`databaseServerIpAddress` string

Returns

Task<int>

AddDatabaseType(string)

Add database type to locator database

```
public Task<int> AddDatabaseType(string name)
```

Parameters

`name` string

Returns

Task<int>

AddPermission(string, string)

Add permission to locator database and to Auth0 API

```
public Task AddPermission(string permissionName, string permissionDescription)
```

Parameters

`permissionName` string

`permissionDescription` string

Returns

Task

AddRole(string, string)

Add role to locator database and Auth0 tenant

```
public Task<int> AddRole(string roleName, string roleDescription)
```

Parameters

`roleName` string

`roleDescription` string

Returns

Task<int>

AddRolePermission(int, int)

Add permission to a role in locator database and Auth0 API

```
public Task<int> AddRolePermission(int roleId, int permissionId)
```

Parameters

`roleId` int

`permissionId` int

Returns

Task<int>

AddUser(string, string, string, string, Status)

Add user to locator database and Auth0 tenant

```
public Task<int> AddUser(string firstName, string lastName, string emailAddress,
string password, Status userStatus)
```

Parameters

`firstName` string

`lastName` string

`emailAddress` string

`password` string

`userStatus` Status

Returns

Task<int>

AddUserRole(int, int)

Add user to a role in locator database and Auth0 tenant

```
public Task<int> AddUserRole(int userId, int roleId)
```

Parameters

`userId` int

`roleId` int

Returns

Task<int>

DeleteClient(int)

Delete client from locator database

```
public Task DeleteClient(int clientId)
```

Parameters

`clientId` int

Returns

Task

DeleteClientUser(int, int)

Remove user from a client in locator database

```
public Task DeleteClientUser(int clientId, int userId)
```

Parameters

`clientId` int

`userId` int

Returns

Task

DeleteConnection(int)

Delete connection from locator database

```
public Task DeleteConnection(int connectionId)
```

Parameters

`connectionId` int

Returns

Task

DeleteDatabase(int)

Delete database information from locator database and on server it lives on

```
public Task DeleteDatabase(int databaseId)
```

Parameters

`databaseId` int

Returns

Task

DeleteDatabaseServer(int)

Delete database server information from locator database

```
public Task DeleteDatabaseServer(int databaseServerId)
```

Parameters

`databaseServerId` int

Returns

Task

DeleteDatabaseType(int)

Delete database type from locator database

```
public Task DeleteDatabaseType(int databaseTypeId)
```

Parameters

`databaseTypeId` int

Returns

Task

DeletePermission(int)

Delete permission in locator database and Auth0 API

```
public Task DeletePermission(int permissionId)
```

Parameters

`permissionId` int

Returns

Task

DeleteRole(int)

Delete role from locator database and Auth0 tenant

```
public Task DeleteRole(int roleId)
```

Parameters

`roleId` int

Returns

Task

DeleteRolePermission(int, int)

Delete permission from a role in locator database and Auth0 API

```
public Task DeleteRolePermission(int roleId, int permissionId)
```

Parameters

`roleId` int

`permissionId` int

Returns

Task

DeleteUser(int)

Delete user from locator database and Auth0 tenant

```
public Task DeleteUser(int userId)
```

Parameters

`userId` int

Returns

Task

DeleteUserRole(int, int)

Remove user from a role in locator database and Auth0 tenant

```
public Task DeleteUserRole(int userId, int roleId)
```

Parameters

`userId` int

`roleId` int

Returns

Task

GeneratePasswordChangeTicket(string, string)

Generate Url for user to go update their password in Auth0

```
public Task<string> GeneratePasswordChangeTicket(string auth0Id, string redirectUrl)
```

Parameters

`auth0Id` string

`redirectUrl` string

Returns

Task<string>

GetAuth0Id(HttpContext)

Get a user's Auth0Id from an authenticated http request

```
public string GetAuth0Id(HttpContext httpContext)
```

Parameters

`httpContext` HttpContext

Returns

string

GetClients(string, int, int)

Gets clients from locator database with search text and pagination

```
public Task<PagedList<Client>> GetClients(string searchText, int page, int pageSize)
```

Parameters

`searchText` string

`page` int

`pageSize` int

Returns

Task<PagedList<Client>>

GetConnection(string, int, int)

Create SQL connection based on user, client and database type

```
public Task<SqlConnection> GetConnection(string auth0Id, int clientId,
int databaseTypeId)
```

Parameters

`auth0Id` string

`clientId` int

`databaseTypeId` int

Returns

Task<SqlConnection>

GetDatabaseServers()

Get database servers from locator database

```
public Task<List<DatabaseServer>> GetDatabaseServers()
```

Returns

Task<List<DatabaseServer>>

GetDatabaseTypes()

Get database types from locator database

```
public Task<List<DatabaseType>> GetDatabaseTypes()
```

Returns

Task<List<DatabaseType>>

GetDatabases(string, int, int)

Get databases from locator database with search text and pagination

```
public Task<PagedList<Database>> GetDatabases(string searchText, int page,
int pageSize)
```

Parameters

`searchText` string

`page` int

`pageSize` int

Returns

Task<PagedList<Database>>

GetPermissions()

Get permission information in locator database

```
public Task<List<Permission>> GetPermissions()
```

Returns

Task<List<Permission>>

GetRoles()

Get roles from locator database

```
public Task<List<Role>> GetRoles()
```

Returns

Task<List<Role>>

GetUsers(string, int, int)

Get users from locator database

```
public Task<PagedList<User>> GetUsers(string keyWord, int pageNumber, int pageSize)
```

Parameters

`keyWord` string

`pageNumber` int

`pageSize` int

Returns

Task <PagedList<User>>

UpdateClient(int, string, string, Status)

Update client information in locator database

```
public Task UpdateClient(int clientId, string clientName, string clientCode,
Status clientStatus)
```

Parameters

`clientId` int

`clientName` string

`clientCode` string

`clientStatus` Status

Returns

Task

UpdateDatabase(int, string, string, int, byte, Status)

Update database information in locator database and make updates on database server

```
public Task UpdateDatabase(int databaseId, string databaseName, string databaseUser,
int databaseServerId, byte databaseTypeId, Status databaseStatus)
```

Parameters

`databaseId` int

`databaseName` string

`databaseUser` string

`databaseServerId` int

`databaseTypeId` byte

`databaseStatus` Status

Returns

Task

UpdateDatabaseServer(int, string, string)

Update database server information in locator database

```
public Task UpdateDatabaseServer(int databaseServerId, string databaseServerName,
string databaseServerIpAddress)
```

Parameters

`databaseServerId` int

`databaseServerName` string

`databaseServerIpAddress` string

Returns

Task

UpdateDatabaseType(int, string)

Update database type information in locator database

```
public Task UpdateDatabaseType(int databaseTypeId, string name)
```

Parameters

`databaseTypeId` int

`name` string

Returns

Task

UpdatePermission(int, string, string)

Update permission information in locator database and to Auth0 API

```
public Task UpdatePermission(int permissionId, string permissionName,
string permissionDescription)
```

Parameters

`permissionId` int

`permissionName` string

`permissionDescription` string

Returns

Task

UpdateRole(int, string, string)

Update role information in locator database and Auth0 tenant

```
public Task UpdateRole(int roleId, string roleName, string roleDescription)
```

Parameters

`roleId` int

`roleName` string

`roleDescription` string

Returns

Task

UpdateUser(int, string, string, string, string, Status)

Update user information in locator database and Auth0 tenant

```
public Task UpdateUser(int userId, string firstName, string lastName, string
emailAddress, string password, Status userStatus)
```

Parameters

`userId` int

`firstName` string

`lastName` string

`emailAddress` string

`password` string

`userStatus` Status

Returns

Task

UpdateUserPassword(string, string)

Update user password in Auth0

```
public Task UpdateUserPassword(string auth0, string password)
```

Parameters

`auth0` string

`password` string

Returns

Task

Namespace Locator.Common.Models

Classes

PagedList<T>

Class PagedList<T>

Namespace: Locator.Common.Models

Assembly: Locator.dll

```
public class PagedList<T>
```

Type Parameters

T

Inheritance

object ← PagedList<T>

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

PagedList(IEnumerable<T>, int, int, int, int)

```
public PagedList(IEnumerable<T> items, int rowCount, int pageNumber, int pageSize,
int totalPages)
```

Parameters

items IEnumerable<T>

rowCount int

pageNumber int

pageSize int

totalPages int

Properties

Items

```
public IEnumerable<T> Items { get; set; }
```

Property Value

IEnumerable<T>

PageNumber

```
public int PageNumber { get; }
```

Property Value

int

PageSize

```
public int PageSize { get; }
```

Property Value

int

RowCount

```
public int RowCount { get; set; }
```

Property Value

int

TotalPages

```
public int TotalPages { get; }
```

Property Value

int

Namespace Locator.Domain

Classes

Client

Connection

Database

DatabaseServer

DatabaseType

Permission

Role

User

Enums

Status

Class Client

Namespace: Locator.Domain

Assembly: Locator.dll

```
public class Client
```

Inheritance

object ← Client

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

Client(int, string, string, Status)

```
public Client(int id, string name, string code, Status status)
```

Parameters

`id` int

`name` string

`code` string

`status` Status

Properties

Code

```
public string Code { get; init; }
```

Property Value

string

Id

```
public int Id { get; init; }
```

Property Value

int

Name

```
public string Name { get; init; }
```

Property Value

string

Status

```
public Status Status { get; init; }
```

Property Value

Status

Class Connection

Namespace: Locator.Domain

Assembly: Locator.dll

```
public class Connection
```

Inheritance

object ← Connection

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

Connection(int, int, int)

```
public Connection(int id, int databaseId, int clientUserId)
```

Parameters

`id` int

`databaseId` int

`clientUserId` int

Properties

ClientUserId

```
public int ClientUserId { get; set; }
```

Property Value

int

DatabaseId

```
public int DatabaseId { get; set; }
```

Property Value

int

Id

```
public int Id { get; init; }
```

Property Value

int

Class Database

Namespace: Locator.Domain

Assembly: Locator.dll

```
public class Database
```

Inheritance

object ← Database

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

Database(int, string, string, int, Status)

```
public Database(int id, string name, string user, int databaseServerId,
Status status)
```

Parameters

`id` int

`name` string

`user` string

`databaseServerId` int

`status` Status

Properties

DatabaseServerId

```
public int DatabaseServerId { get; init; }
```

Property Value

int

Id

```
public int Id { get; init; }
```

Property Value

int

Name

```
public string Name { get; init; }
```

Property Value

string

Status

```
public Status Status { get; set; }
```

Property Value

Status

User

```
public string User { get; set; }
```

Property Value

string

Class DatabaseServer

Namespace: Locator.Domain

Assembly: Locator.dll

```
public class DatabaseServer
```

Inheritance

object ← DatabaseServer

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

DatabaseServer(int, string, string)

```
public DatabaseServer(int id, string name, string ipAddress)
```

Parameters

`id` int

`name` string

`ipAddress` string

Properties

Id

```
public int Id { get; init; }
```

Property Value

int

IpAddress

```
public string IpAddress { get; init; }
```

Property Value

string

Name

```
public string Name { get; init; }
```

Property Value

string

Class DatabaseType

Namespace: Locator.Domain

Assembly: Locator.dll

```
public class DatabaseType
```

Inheritance

object ← DatabaseType

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

DatabaseType(int, string)

```
public DatabaseType(int id, string name)
```

Parameters

`id` int

`name` string

Properties

Id

```
public int Id { get; init; }
```

Property Value

int

Name

```
public string Name { get; init; }
```

Property Value

string

Class Permission

Namespace: Locator.Domain

Assembly: Locator.dll

```
public class Permission
```

Inheritance

object ← Permission

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

Permission(int, string, string)

```
public Permission(int id, string name, string description)
```

Parameters

`id` int

`name` string

`description` string

Properties

Description

```
public string Description { get; set; }
```

Property Value

string

Id

```
public int Id { get; init; }
```

Property Value

int

Name

```
public string Name { get; set; }
```

Property Value

string

Class Role

Namespace: Locator.Domain

Assembly: Locator.dll

```
public class Role
```

Inheritance

object ← Role

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

Role(int, string, string, string)

```
public Role(int id, string auth0RoleId, string name, string description)
```

Parameters

`id` int

`auth0RoleId` string

`name` string

`description` string

Properties

Auth0RoleId

```
public string Auth0RoleId { get; init; }
```

Property Value

string

Description

```
public string Description { get; init; }
```

Property Value

string

Id

```
public int Id { get; init; }
```

Property Value

int

Name

```
public string Name { get; init; }
```

Property Value

string

Enum Status

Namespace: Locator.Domain

Assembly: Locator.dll

```
[Flags]
public enum Status
```

Fields

`Active = 1`

`Inactive = 2`

Class User

Namespace: Locator.Domain

Assembly: Locator.dll

```
public class User
```

Inheritance

object ← User

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

User(int, string, string, string, string, Status)

```
public User(int id, string auth0Id, string firstName, string lastName, string
emailAddress, Status userStatus)
```

Parameters

`id` int

`auth0Id` string

`firstName` string

`lastName` string

`emailAddress` string

`userStatus` Status

Properties

Auth0Id

```
public string Auth0Id { get; init; }
```

Property Value

string

EmailAddress

```
public string EmailAddress { get; init; }
```

Property Value

string

FirstName

```
public string FirstName { get; init; }
```

Property Value

string

Id

```
public int Id { get; init; }
```

Property Value

int

LastName

```
public string LastName { get; init; }
```

Property Value

string

Status

```
public Status Status { get; init; }
```

Property Value

Status