
VULTR AGENT RUSH · CHALLENGE 1: BLAST RADIUS ZERO

ProofCell

Sandboxed AI agents with a verifiable record of every step.
Contained by design. Every step on the record.



Prototype build - designed for Vultr Cloud Compute + Serverless Inference; Vultr deployment pending account verification.

THE PROBLEM

Agents that execute are useful - and dangerous

An agent that can write and run code can also wipe a disk, read your keys, or exfiltrate your data.

Teams won't hand real work to agents they can't contain - and can't audit after the fact.

WHAT PROOFCELL DOES

Plan → Screen → Record

1 · Plan

A planner on Vultr Serverless Inference is designed to break your task into concrete steps. When a step fails, the error feeds back and the plan repairs itself.

→

2 · Screen

Every planned step is screened by a policy engine before it runs - refused outright, gated for human approval, or allowed. Execution is built for a fresh, locked-down Docker sandbox on a Vultr VM.

→

3 · Record

Every decision, command, output and artifact lands in a ledger that links entries with SHA-256 hashes, with a verifier that checks the chain for internal consistency.

CONTAINMENT ARCHITECTURE

Two walls, then a receipt

Designed blast radius: the workspace, and nothing else.

Wall 1 · Policy engine

Static screening of every planned step before it runs: refuse destructive patterns outright, gate exfiltration-shaped actions for human approval. Demonstrated in the prototype.

Wall 2 · Disposable sandbox

Designed: non-root, all capabilities dropped, read-only root filesystem, no credentials inside, CPU / memory / PID / wall-clock caps, network disabled - force-destroyed when the run ends. Awaits deployment testing.

The receipt · Proof ledger

The ledger links entries with SHA-256 hashes and includes a verifier that checks the chain for internal consistency. Demonstrated in the prototype.

THE CONTAINMENT MOMENT


Watch the walls work

REFUSED




`rm -rf /` refused by the policy engine before anything executes.

GATED · NEVER APPROVED



`curl --data @secret.txt` held for human approval; it never runs.

REFUSED




Reading the host account database refused by policy.

Prototype recording, scripted drill plans: policy checks, approval gate and ledger are the real app paths. No container runtime in this recording - Docker isolation awaits deployment testing.

PROOF YOU CAN VERIFY

A receipt for every step



- Each event links to the previous by SHA-256.
- The verifier checks the chain for internal consistency.
- Refusals, gates and executions all land on the same record.
- Artifacts carry content hashes.

BUILT FOR VULTR

Vultr is the control plane, not a host

Cloud Compute

A single regular-performance VM is designed to run the whole control layer and the sandbox pool - planning, dispatch, sandbox lifecycle, ledger, UI.

Serverless Inference

OpenAI-compatible endpoint designed to power the planner and its error-feedback repair loop - no GPU, no model ops.

Vultr API

Sandbox lifecycle is disposable by design; the same API path scales to throwaway-per-task instances.

Intended architecture - Vultr deployment is pending account verification; policy, gate and ledger paths demonstrated locally.

WHAT'S NEXT

From drill to default

- Policy engine that learns new refuse/gate patterns from drill outcomes.
- Multi-step approval chains for long-running agent workflows.
- Hosted verifier: paste a ledger, get an independent verdict.

Links

Live demo: `pending Vultr account verification`

Source (MIT): `github.com/chkanubhav09/proofcell`