


- **Functional Dependency:**

- **Definition:** Functional dependency is a relation that exists between two attributes. It typically exists between the primary key and non key attribute within a table.



- **$X \rightarrow Y$:** The left side of FD is known as determinant; the right side of the production is known as a dependent.

- **Types of functional Dependency:**

1. Trivial FD
2. Non-Trivial FD
3. Multivalued FD
4. Transitive FD
5. Fully FD

6. Partial FD

- **Trivial functional dependency:** $A \rightarrow B$ has trivial functional dependency if B is a subset of A. A dependent is always a subset of the determinant.
- **Non-trivial Functional Dependency:** $A \rightarrow B$ is non-trivial dependency if B is not a subset of A. The dependent is strictly not a subset of the determinant.
- **Multivalued functional dependency:** If $A \twoheadrightarrow \{B, C\}$ and there exists no functional dependency between B and C. Entities of the dependent set are not dependent on each other.
- **Transitive Functional Dependency:** If $A \rightarrow B$ & $B \rightarrow C$ then $A \rightarrow C$. Dependent is indirectly dependent on the determinant.
- **Fully Functional Dependency:** An attribute or a set of attributes uniquely determines another attribute or set of attributes. A relation R has attributes X, Y, Z with dependencies $X \rightarrow Y$ and $X \rightarrow Z$.
- **Partial Functional Dependency:** a non-key attribute depends on a part of the composite keys, rather than the whole key. If a relation R has attributes X, Y, Z where X and Y are the composite key and Z is non key attribute. Then $X \twoheadrightarrow Z$ is a partial functional dependency in RDBMS.

- **Armstrong's Axioms:** Armstrong's axioms are used to test the logical implication of functional dependencies.

- **Axiom of Reflexivity:** If Y is a subset of X, then $X \rightarrow Y$. Any subset of the attribute is functionally dependent on the whole set of attributes.
- **Axiom of Augmentation:** If $X \rightarrow Y$, then $XZ \rightarrow YZ$ for any attribute set Z. Adding attributes to both sides of a functional dependency maintains its validity.
- **Axiom of Transitivity:** If $X \rightarrow Y$ and $Y \rightarrow Z$, then $X \rightarrow Z$. If a functional dependency can be derived indirectly, it can be inferred directly.
- **Interference Rules:** These rules are derived from the above axioms:
 - **Union:** If $X \rightarrow Y$ and $X \rightarrow Z$ then $X \rightarrow YZ$.

- **Composition:** If $A \rightarrow B$ and $X \rightarrow Y$ hold, then $AX \rightarrow BY$ holds.
 - **Decomposition:** If $X \rightarrow YZ$ then $X \rightarrow Y$ and $X \rightarrow Z$.
 - **Pseudo Transitivity:** If $X \rightarrow Y$ and $YZ \rightarrow W$ then $XZ \rightarrow W$.
- **Normalization:** A database design technique used to eliminate data redundancy and improve data integrity by organizing data in a structured and efficient manner.
Involves breaking down a relational database into multiple related tables while adhering to specific rules.
 - **Benefits of normalization:**
 - **Data integrity:** normalisation minimizes data duplication and inconsistencies, ensuring accurate and reliable information.
 - **Efficiency:** Smaller, more focused tables improve query performance and reduce storage requirements.
 - **Flexibility:** Normalised structures allow for easier data manipulation, updates, and maintenance.
 - **Normal Forms:**
 1. **First normal form (1NF):**
 - a. Each table should hold a single atomic value.
 - b. Consider a "Customers" table with column "Phone Numbers" containing multiple phone numbers. To achieve 1NF, create a separate "Phone Numbers" table with a customer Id and Phone Number.
 2. **Second normal form (2NF):**
 - a. Meets 1NF requirements.
 - b. No partial dependencies: Non-key attributes depend on the entire primary key, not just part of it.
 - c. In a "Sales" tables with "Order ID", "Product ID" and "Quantity" where "Product ID" depends only on part of the primary key, create a separate "Products" table.
 3. **Third Normal Form(3NF):**
 - a. Meets 2NF requirements.
 - b. No Transitive dependencies: Non-key attributes depend only on the primary key, not on other non-key attributes.
 - c. In a "Students" table with "Student ID," "Course ID," and "Instructor," where "Instructor" depends on "Course ID," move "Instructor" to a separate "Courses" table.
 4. **Boyce-Codd Normal Form (BCNF):**
 - a. Meets 3NF requirements.
 - b. Every determinant (attributes that uniquely determine other attributes) must be a candidate key.
 - c. Example: In an "Employees" table with "Employee ID," "Project ID," and "Project Manager," where "Project Manager" depends on "Project ID," separate "Project Managers" from "Projects."
 - **Database security:**
 1. Database security refers to the protection of data stored in database from unauthorised access, tampering, and other malicious activities.
 2. **Threats to database security:**
 - **Unauthorised Access:** Unauthorised users gaining access to the database, either by exploiting vulnerabilities or using stolen credentials.

- **Data leakage:** Sensitive information being leaked to unauthorized parties, often due to poor access controls or misconfigurations.
- **SQL injection:** Malicious SQL statements are injected into user input to manipulate or access the database.
- **Malware and Ransomware:** Malicious software can inject databases, steal data, or hold it ransom.
- **Insider threats:** Authorised individuals with malicious intent accessing, manipulating, or leaking data.
- **Data Tampering:** Unauthorised modification of data to manipulate records or disrupt business operations.
- **Denial of service:** Attackers overwhelm the database with excessive requests, leading to a slowdown or complete outage.
- **Weak authentication and authorization:** Poorly managed user access privileges that can lead to unauthorized actions within the database.
- **Insecure Configurations:** Poorly configured databases with default settings or unnecessary services enabled.
- **Lack of encryption:** Data transmission and storage without encryption can lead to data interception and theft.

3. Counter measures:

1. Access Control:

- a. Implement strong authentication mechanisms like multi-factor authentication (MFA).
- b. Use role-based access control (RBAC) to assign specific privileges based on user roles.
- c. Regularly review and update access permissions.

2. Encryption:

- a. Employ encryption for the data at rest and data in transit using protocols like TLS/SSL.
- b. Implement encryption mechanisms for sensitive fields within the database.

3. Patch Management:

- a. Keep database management systems and software up to date with the latest security patches.
- b. Regularly review and apply security updates to the operating system and related software.

4. Intrusion Detection and Prevention:

- a. Implement intrusion detection and prevention systems to monitor databases activities and detect suspicious behaviour.
- b. Set up alerts for potential security breaches or anomalies.

5. SQL injection Prevention:

- a. Input validation and parameterized queries to prevent SQL injections attacks.
- b. Use web application firewalls (WAFs) to detect and block malicious SQL queries.

6. Backup and recovery:

- a. Regularly back up the database and test data restoration procedures.
- b. Store backups in secure locations to mitigate data loss due to attacks.

7. Auditing and monitoring:

- a. Implement auditing to track user activities and changes to the database.
- b. Monitor logs and set up alerts for unusual or suspicious activities.

8. Training and awareness:

- a. Educate employees about best practices in database security and potential risks of data breaches.
- b. Promote a security-conscious culture within the organization.

9. Vendor security assessment:

- a. Assess the security practices of third-party vendors providing database-related services.

10. Data masking and reduction:

- a. Mask sensitive data so that it remains confidential even to authorised users who don't need to see the full information.
- b. Implement data redaction to selectively show parts of sensitive data.

- **Control Structure:** A set of statements that control the flow of execution of a program.

There are three types of control structures in MySQL:

1. **Sequences:** A sequence is a set of statements that are executed one after the other.

2. Conditional Statements:

A statement that executes one set of statements if a certain condition is met.

3. Loop statements:

A statement that repeats a set of statements until a certain condition is met.

- **Trigger:**

- A set of SQL statements that are executed automatically when a specified change operation (SQL, INSERT, UPDATE, or DELETE statement) is performed on a specified table.
- Useful for tasks such as enforcing business rules, validating input data, and keeping an audit trail.

- **View:**

- A virtual table that is created from a select statement. Views are not stored in the database, but they are dynamically created when they are referenced.
- Used to simplify complex queries, to hide sensitive data, and to provide a consistent view of data to different users.