# Database Recovery

- Database recovery is a critical aspect of database management, ensuring that data remains consistent and available even in the face of system failures or human errors.

Here are detailed notes on database recovery:

What is Database Recovery?

- Database recovery is the process of restoring a database to a consistent and reliable state after a system failure or data corruption event.

Key Concepts in Database Recovery:

Transaction:

- A transaction is a sequence of one or more SQL statements treated as a single unit of work.

- Transactions are either completed successfully (committed) or undone (rolled back) in case of failure.

Commit:
- A commit is an operation that signifies the successful completion of a transaction, making its changes permanent in the database.

Rollback:
- A rollback is an operation that reverses the changes made by a transaction, returning the database to its state before the transaction started.

Checkpoint / Savepoint:
- A checkpoint is a predefined point in the database log that indicates a consistent state of the database.
- It is used as a reference for crash recovery.

Write-Ahead Logging (WAL):
- In this approach, the DBMS writes both the data modification and the corresponding log entry to the transaction log before making any changes to the data.
- This ensures durability and aids in recovery.

Types of Database Recovery:

Crash Recovery:
- In crash recovery, the goal is to restore the database to a consistent state after a system crash or unexpected shutdown.
- The main components involved are the transaction log and checkpoint information.
- The recovery process consists of three phases: analysis, redo, and undo.

Point-in-Time Recovery:

- This type of recovery allows you to restore a database to a specific point in time.
- It's useful for recovering from data corruption, accidental deletions, or user errors.
- It typically involves restoring a full database backup and then applying transaction logs up to the desired point in time.

Transaction Logs:

- Transaction logs are crucial for recovery.

- They contain a record of all changes made to the database.

- Write-Ahead Logging (WAL) is a common technique where the DBMS writes changes to the log before making the corresponding changes to the data.
- Log records contain information about the type of operation (insert, update, delete), the affected data, and a unique transaction identifier.

- Types of logs:

  redo logs (used during crash recovery)

  undo logs (used during point-in-time recovery).

Recovery Phases in Detail

Analysis Phase:

- During crash recovery, this phase identifies the last checkpoint and active transactions at the time of the failure.

- It helps establish a recovery point and identifies which transactions were committed and which weren't.

Redo Phase:

- In this phase, the DBMS applies changes from the transaction log to the database to bring it to a consistent state.
- It applies committed transactions and any uncommitted changes up to the point of failure.
- This phase ensures durability and brings the database to a state as close as possible to what it was before the crash.

Undo Phase:

- This phase is necessary to roll back any changes made by transactions that were uncommitted at the time of failure.
- It ensures that the database is left in a consistent state and that no partial or erroneous changes are retained.

Recovery Tools and Technologies:

- Various database management systems have specialized tools for recovery.

For example:

- Oracle Recovery Manager (RMAN):
  A comprehensive tool for backup and recovery in Oracle databases.
- SQL Server Management Studio (SSMS):
  Offers a range of recovery features for SQL Server databases.

- pgBackRest for PostgreSQL:
  A popular tool for PostgreSQL backup and recovery.

Best Practices for Database Recovery:

- Implement a robust backup strategy with regular full and transaction log backups.

- Store backups offsite to protect against disasters like fires or floods.

- Maintain detailed documentation of recovery procedures.

- Test recovery procedures periodically to ensure they work as expected.

- Consider high availability solutions such as database replication and clustering to minimize downtime.

Challenges in Database Recovery:

- Large databases may require extended recovery times.

- Ensuring that transaction logs are not lost or corrupted is essential.

- Maintaining compliance with data protection regulations can be challenging during recovery.

Legal and Compliance Considerations:

- Compliance with data protection laws (e.g., GDPR, HIPAA) requires secure and reliable backup and recovery processes.

- Ensure that recovery activities are in line with any legal requirements for data retention and privacy.

Summary:
- Database recovery is a complex and critical aspect of database management.
- It involves multiple phases, requires careful planning and documentation, and is essential for data consistency and business continuity.
- Understanding the specific recovery tools and techniques for your chosen database management system is crucial for successful recovery operations.