

Linear Upper Confidence Bound Algorithm for Contextual Bandit Problem with Piled Rewards


Kuan-Hao Huang and Hsuan-Tien Lin

Department of Computer Science & Information Engineering
National Taiwan University




April 20, 2016 (PAKDD)


Contextual Bandit Problem (example)




Contextual Bandit Problem (example)




Contextual Bandit Problem (example)



Contextual Bandit Problem (example)



Contextual Bandit Problem (example)



Contextual Bandit Problem (traditional)

Notation

- ▶ user: context $\mathbf{x} \in \mathbb{R}^d$
- ▶ ad: action $a \in \{1, 2, \dots, K\}$
- ▶ feedback: reward $r \in [0, 1]$

Contextual Bandit Problem (traditional)

Notation

- ▶ user: context $\mathbf{x} \in \mathbb{R}^d$
- ▶ ad: action $a \in \{1, 2, \dots, K\}$
- ▶ feedback: reward $r \in [0, 1]$

Contextual bandit problem (traditional setting)

for round $t = 1, 2, \dots, T$

- ▶ algorithm \mathcal{A} receives a context \mathbf{x}_t
- ▶ algorithm \mathcal{A} selects an action a_t based on the context \mathbf{x}_t
- ▶ algorithm \mathcal{A} receives the reward r_{t,a_t}

algorithm \mathcal{A} tries to maximize the cumulative rewards $\sum_{t=1}^T r_{t,a_t}$

Contextual Bandit Problem (traditional)

Notation

- ▶ user: context $\mathbf{x} \in \mathbb{R}^d$
- ▶ ad: action $a \in \{1, 2, \dots, K\}$
- ▶ feedback: reward $r \in [0, 1]$

Contextual bandit problem (traditional setting)

for round $t = 1, 2, \dots, T$


- ▶ algorithm \mathcal{A} receives a context \mathbf{x}_t
- ▶ algorithm \mathcal{A} selects an action a_t based on the context \mathbf{x}_t
- ▶ algorithm \mathcal{A} receives the reward r_{t,a_t}

algorithm \mathcal{A} tries to maximize the cumulative rewards $\sum_{t=1}^T r_{t,a_t}$


Challenge for contextual bandit problem

- ▶ partial feedback: **exploitation** vs. **exploration**

Contextual Bandit Problem (piled-reward example)



Contextual Bandit Problem (piled-reward example)



Contextual Bandit Problem (piled-reward)

Notation

- ▶ user: context $\mathbf{x} \in \mathbb{R}^d$
- ▶ ad: action $a \in \{1, 2, \dots, K\}$
- ▶ feedback: reward $r \in [0, 1]$

Contextual bandit problem (piled-reward setting)

for round $t = 1, 2, \dots, T$

- ▶ for $i = 1, 2, \dots, n$
 - ▶ algorithm \mathcal{A} receives a context \mathbf{x}_{t_i}
 - ▶ algorithm \mathcal{A} selects an action a_{t_i} based on the context \mathbf{x}_t
- ▶ algorithm \mathcal{A} receives n rewards $r_{t_1, a_{t_1}}, r_{t_2, a_{t_2}}, \dots, r_{t_n, a_{t_n}}$

algorithm \mathcal{A} tries to maximize the cumulative rewards $\sum_{t=1}^T \sum_{i=1}^n r_{t_i, a_{t_i}}$

Linear Upper Confidence Bound (LinUCB)

LinUCB [Li et al., 2010]

- ▶ state-of-the-art algorithm for the traditional setting ($n = 1$)
- ▶ for each round t and context \mathbf{x}_t , LinUCB gives every actions a a score
- ▶ selected action $a_t = \operatorname{argmax}_a(\operatorname{score}_{t,a}(\mathbf{x}_t))$

$$\begin{aligned}\operatorname{score}_{t,a}(\mathbf{x}_t) &= \text{estimated reward} + \text{uncertainty} \\ &= \text{estimated reward} + \text{confidence bound} \\ &= \mathbf{w}_{t,a}^\top \mathbf{x} + \alpha \sqrt{\mathbf{x}_t^\top (\mathbf{I} + \mathbf{X}_{t-1,a}^\top \mathbf{X}_{t-1,a})^{-1} \mathbf{x}_t}\end{aligned}$$

- ▶ **estimated reward** for **exploitation**, is obtained by the online regression from previous pairs $(\mathbf{x}_\tau, r_{\tau,a})$ of action a
- ▶ **uncertainty** for **exploration**, estimates how much confident for the estimated reward
- ▶ update the scoring function whenever receiving the reward

Applying LinUCB to Piled-reward setting

LinUCB under the piled-reward setting

for round $t = 1, 2, \dots, T$

- ▶ for $i = 1, 2, \dots, n$
 - ▶ LinUCB receives context \mathbf{x}_{t_i}
 - ▶ LinUCB selects an action a_{t_i} with the same scoring function
- ▶ LinUCB receives n rewards $r_{t_1, a_{t_1}}, r_{t_2, a_{t_2}}, \dots, r_{t_n, a_{t_n}}$
- ▶ LinUCB updates the scoring function with n rewards

Applying LinUCB to Piled-reward setting

LinUCB under the piled-reward setting

for round $t = 1, 2, \dots, T$

- ▶ for $i = 1, 2, \dots, n$
 - ▶ LinUCB receives context \mathbf{x}_{t_i}
 - ▶ LinUCB selects an action a_{t_i} with **the same scoring function**
- ▶ LinUCB receives n rewards $r_{t_1, a_{t_1}}, r_{t_2, a_{t_2}}, \dots, r_{t_n, a_{t_n}}$
- ▶ **LinUCB updates the scoring function with n rewards**

Problem for LinUCB under the piled-reward setting

- ▶ no update for scoring function within the round
- ▶ LinUCB selects action with **high uncertainty** but **low reward risk** for some contexts
- ▶ these contexts come again and again \rightarrow low cumulative reward
- ▶ need **strategic exploration** within the round

Strategic Exploration

Our solution

- ▶ use previous contexts $\mathbf{x}_{t_1}, \mathbf{x}_{t_2}, \dots, \mathbf{x}_{t_{i-1}}$ in this round to help for selecting the next action for \mathbf{x}_{t_i}
- ▶ give each previous context \mathbf{x}_{t_τ} a **pseudo reward** $p_{t_\tau, a_{t_\tau}}$
- ▶ use the pseudo reward to **pretend** the true reward
- ▶ we design two pseudo rewards:
 - ▶ **estimated reward (ER)**: estimated reward
 - ▶ **underestimated reward (UR)**: estimated reward - confidence bound

Strategic Exploration

Our solution

- ▶ use previous contexts $\mathbf{x}_{t_1}, \mathbf{x}_{t_2}, \dots, \mathbf{x}_{t_{i-1}}$ in this round to help for selecting the next action for \mathbf{x}_{t_i}
- ▶ give each previous context \mathbf{x}_{t_τ} a **pseudo reward** $p_{t_\tau, a_{t_\tau}}$
- ▶ use the pseudo reward to **pretend** the true reward
- ▶ we design two pseudo rewards:
 - ▶ **estimated reward (ER)**: estimated reward
 - ▶ **underestimated reward (UR)**: estimated reward - confidence bound

Score after the update with pseudo reward

pseudo reward	estimated reward	uncertainty
estimated reward	no change	become lower
underestimated reward	become lower	become lower

- ▶ achieve **strategic exploration**
- ▶ **underestimated reward** is more aggressive than **estimated reward**

Linear Upper Confidence Bound with Pseudo Reward

A novel algorithm

- ▶ **Linear Upper Confidence Bound with Pseudo Reward (LinUCBPR)**
 - ▶ **LinUCBPR-ER**: estimated reward as the pseudo reward
 - ▶ **LinUCBPR-UR**: underestimated reward as the pseudo reward

LinUCBPR under the piled-reward setting

for round $t = 1, 2, \dots, T$

- ▶ for $i = 1, 2, \dots, n$
 - ▶ LinUCBPR receives context \mathbf{x}_{t_i}
 - ▶ LinUCBPR selects an action a_{t_i} with the scoring function
 - ▶ **LinUCBPR updates the scoring function with the pseudo rewards $p_{t_i, a_{t_i}}$**
- ▶ LinUCBPR receives n true rewards $r_{t_1, a_{t_1}}, r_{t_2, a_{t_2}}, \dots, r_{t_n, a_{t_n}}$
- ▶ LinUCBPR **discards the change** caused by the **pseudo rewards**
- ▶ **LinUCBPR updates the scoring function with n true rewards**

Theoretical Analysis

Regret of algorithm \mathcal{A}

$$\text{Regret}(\mathcal{A}) = \text{perfect reward} - \text{real reward} = \sum_{t=1}^T \sum_{i=1}^n r_{t_i, a_{t_i}^*} - \sum_{t=1}^T \sum_{i=1}^n r_{t_i, a_{t_i}}$$

Theorem

With probability $1 - \delta$, the regret bounds of LinUCB and LinUCBPR-ER under the piled-reward setting are both


$$\mathcal{O} \left(\sqrt{Cn(nT) \ln^3(nT/\delta)} \right)$$

- ▶ when the number of contexts (nT) is constant, the regret bound $\propto \sqrt{n}$
- ▶ LinUCB and LinUCBPR-ER enjoy the same regret bound


Artificial Datasets

Artificial data

- ▶ $\mathbf{u}_1, \mathbf{u}_1, \dots, \mathbf{u}_K \in \mathbb{R}^d$ for K actions
- ▶ $r_{t,a} = \mathbf{u}_a^\top \mathbf{x}_t + \epsilon_t$, where $\epsilon \in [-0.05, 0.05]$



(a) Average cumulative reward




(b) Regret


- ▶ LinUCBPR outperforms others, especially in the early rounds
- ▶ LinUCBPR-ER is better than LinUCBPR-UR

Simple Supervised-to-contextual-bandit Datasets


- ▶ take supervised-to-contextual-bandit transform [Dudík et al., 2011] on 8 multiclass datasets




(a) acoustic




(b) covtype




(c) letter




(d) pendigits




(e) poker



(f) satimage



(g) shuttle




(h) usps

- ▶ LinUCBPR-ER reaches the best again


Real-world Datasets

News recommendation dataset by Yahoo!


- ▶ appearing in ICML 2012 workshop competition
- ▶ the only public dataset for contextual bandit problem
- ▶ dynamic action set



(a) R6A



(b) R6B



(c) R6B-clean

- ▶ LinUCBPR-ER is a stable and promising algorithm

Conclusion

- ▶ formalize the **piled-reward setting** for contextual bandit problem
- ▶ demonstrate how LinUCB can be applied to the piled-reward setting, and prove its **regret bound**
- ▶ propose **LinUCBPR**, and prove the **regret bound** of LinUCBPR-ER
- ▶ use extensive experiments to validate the **promising performance** of LinUCBPR-ER

Thank you! Any question?

