

Nutree Clinic — Patient App Master Spec

Last updated: session 1
Status: In progress
Repo: github.com/chloeghnassiab/nutree-clinic-website

1. Project Overview

A single patient-facing app at `app.nutreeclinic.com`, **separate from the marketing website**, built for Nutree Clinic LLC — a Florida-licensed telehealth practice.

The app has two phases for patients:

- **Onboarding phase** — pre-approval: pre-screen through post-intake confirmation (Section 8)
- **Active phase** — post-approval: dashboard, dosing, messages, progress, account (Section 6.6)

Same app, same URL, same codebase. The distinction is only in the spec for documentation clarity.

The marketing website (Next.js on Vercel) remains separate. No PHI ever touches Vercel.

2. Tech Stack

Layer	Technology	Notes
Frontend — website	Next.js 15 on Vercel Pro	Marketing site only, no PHI
Frontend — app	Next.js or React (TBD)	Hosted on Google Cloud Run or Vercel (no PHI)
Auth	Firebase Auth	Separate roles: patient, clinician, admin
Database	Firestore	All PHI. Free BAA with Google.
File storage	Google Cloud Storage	ID uploads, signed consent PDFs
Backend logic	Firebase Cloud Functions	Notifications, reminders, automation
Payments	Stripe	Subscriptions + one-time. HSA/FSA eligible.

Layer	Technology	Notes
E-signature	DocuSeal	Embedded signing. Signed PDFs → Cloud Storage. Free tier: 100 docs/mo
Pharmacy / Rx	LifeFile API	3 partner pharmacies. Detailed spec TBD.
Calendar / booking	Google Calendar API	Practitioner availability + patient booking
Email	SendGrid	Transactional: confirmations, reminders
Push notifications	Firebase Cloud Messaging	Optional. Mobile only.
AI chat	Anthropic Claude API	Already built. Via /api/chat.
Analytics	Plausible	Marketing site.
Prescription send	LifeFile API	Detailed integration spec to be provided
Shipment tracking	LifeFile API	Live status from 3 partner pharmacies

3. HIPAA Architecture

- Vercel serves HTML/CSS/JS only — **no PHI ever touches Vercel**
- All PHI routes to Google Cloud (Firestore + Cloud Storage)
- Google Cloud BAA must be signed **before any PHI is stored** — blocks go-live
- Audit log of all PHI access is legally required — built into admin platform
- DocuSeal signed PDFs stored in Google Cloud Storage, not Firestore
- **PHI field naming convention:** All Firestore fields containing PHI must be suffixed with `(_phi)` (e.g. `(firstName_phi)`, `(dateOfBirth_phi)`, `(shippingAddress_phi)`). Non-PHI fields use standard naming. This makes PHI fields immediately identifiable in code, queries, logs, and audits.

4. Treatments & Products

Product	Category	Administration route	Notes
GLP-1 Semaglutide	Weight Loss	Subcutaneous injection	Compounded

Product	Category	Administration route	Notes
GLP-1 Tirzepatide	Weight Loss	Subcutaneous injection	Compounded
Sema Microdosing	Weight Loss	Subcutaneous injection	BMI 20-24.9 only
Tirz Microdosing	Weight Loss	Subcutaneous injection	BMI 20-24.9 only
Wegovy®	Weight Loss	Subcutaneous injection	Brand name
Mounjaro®	Weight Loss	Subcutaneous injection	Brand name
Sermorelin	Strength & Performance	Subcutaneous injection	Injection only
NAD+ Injectable	Longevity / Strength & Performance	Subcutaneous injection	
NAD+ Nasal Spray	Longevity / Strength & Performance	Nasal spray	Spec pending
Glutathione	Longevity	TBD	Spec pending
Oxytocin	Well-being	TBD	Spec pending
B12-MIC	Well-being	TBD	Spec pending

Administration routes used in the app:

- `subcutaneous_injection` → syringe SVG shown in patient app dosing view
- `nasal_spray` → nasal spray instructions shown (no syringe)
- `patch` → patch instructions shown (no syringe)
- `oral` → oral instructions shown (no syringe)
- `TBD` → admin must set before product goes live

Categories are for website navigation only — products can appear in multiple categories.

Notes:

- Sermorelin: injection only (no nasal spray, troche, or ODT)
- NAD+ Injectable and NAD+ Nasal Spray both appear in Longevity and Strength & Performance
- Categories are used for website navigation only — products can appear in multiple categories
- NAD+ Nasal Spray: spec pending (protocol, pharmacy, pricing TBD)
- Sema Microdosing and Tirz Microdosing: BMI 20-24.9 only, week-based plans only
- Tirzepatide Microdosing: confirmed product — 10-week plan \$450 via Emerald Pharmacy
- Products sold via Stripe must be **anonymised** (no PHI in Stripe product names)

5. Pricing

Last updated: session 1

Status:  Architecture locked. Plan prices and saving % TBD before launch.

How Pricing Works

Each product has a list of **named plans**. Each plan has:

- A name (e.g. "Athletic recovery", "Starter", "3-month")
- A duration in weeks
- A price — set directly by admin, no formula
- A saving \$ and saving % — calculated vs a reference plan

The **reference plan** is the baseline for saving calculations. Default is the shortest plan for that product. Admin can change it per product.

Saving formula:

```
saving_dollars = (refPlan.price × planWeeks / refPlan.weeks) - plan.price
saving_pct     = saving_dollars / (refPlan.price × planWeeks / refPlan.weeks) × 100
```

Duration display: weeks translate to months when cleanly divisible by 4. 4 weeks → 1 month ·

12 weeks → 3 months · 6 weeks → 6 weeks · 52 weeks → 12 months

What never changes:

- 1 month = 4 weeks, always shown explicitly
- Per-week price is NOT shown
- All Stripe products use anonymous codes — no treatment names
- Admin sets all prices directly — no code deployment needed
- `calcPlan(productCode, planName)` is the single helper used by website and app

Consultation

Item	Price	Notes
Consultation	\$50	Permanent. Credited to first plan. Not a promotion. NTC-CON

Products & Plans

Prices marked \$TBD must be confirmed before launch. Saving % marked TBD must be set by admin in pricing panel before launch. Reference plan shown in **bold**.

Semaglutide NTC-001

Compounded · GLP-1 Weight Loss · BMI ≥ 25 · subcutaneous_injection

Plan name	Weeks	Duration	Price	Saving vs ref
Standard (reference)	4	1 month	\$249	—
3-month	12	3 months	\$TBD	TBD
6-month	24	6 months	\$TBD	TBD
12-month	48	12 months	\$TBD	TBD

Tirzepatide NTC-002

Compounded · GLP-1 Weight Loss · BMI ≥ 25 · subcutaneous_injection

Plan name	Weeks	Duration	Price	Saving vs ref
Standard (reference)	4	1 month	\$349	—
3-month	12	3 months	\$TBD	TBD
6-month	24	6 months	\$TBD	TBD
12-month	48	12 months	\$TBD	TBD

Semaglutide Microdosing NTC-003

Compounded · Weight Loss · BMI 20–24.9 only · Week-based plans only · subcutaneous_injection

Plan name	Weeks	Duration	Price	Saving vs ref
5-week (<i>reference</i>)	5	5 weeks	\$TBD	—
10-week	10	10 weeks	\$350	TBD (vs 2 × 5-week)

Tirzepatide Microdosing NTC-003b

Compounded · Weight Loss · BMI 20–24.9 only · Week-based plans only · subcutaneous_injection

Plan name	Weeks	Duration	Price	Saving vs ref
10-week (<i>reference</i>)	10	10 weeks	\$450	—

 Only one plan confirmed. Additional plans TBD.

Wegovy® NTC-004

Brand name · GLP-1 Weight Loss · subcutaneous_injection

Plan name	Weeks	Duration	Price	Saving vs ref
Standard (<i>reference</i>)	4	1 month	\$1,399	—
3-month	12	3 months	\$TBD	TBD
6-month	24	6 months	\$TBD	TBD
12-month	48	12 months	\$TBD	TBD

Mounjaro® NTC-005

Brand name · GLP-1 Weight Loss · subcutaneous_injection

Plan name	Weeks	Duration	Price	Saving vs ref
Standard <i>(reference)</i>	4	1 month	\$1,069	—
3-month	12	3 months	\$TBD	TBD
6-month	24	6 months	\$TBD	TBD
12-month	48	12 months	\$TBD	TBD

Sermorelin NTC-006

Strength & Performance · Emerald Pharmacy · subcutaneous_injection

Plan name	Weeks	Duration	Price	Saving vs ref
Starter <i>(reference)</i>	10	10 weeks	\$399	—
1-month	4	1 month	\$199	— (shorter than reference, no saving shown)
3-month	12	3 months	\$475	TBD (vs 3 × 1-month)

Note: Sermorelin reference plan is the Starter (10-week) because it is the entry plan. 1-month plan is for returning patients post-starter. Admin should set reference plan to 1-month once Starter is no longer the primary entry point.

NAD+ Injectable NTC-007

Longevity / Strength & Performance · Rush Pharmacy · subcutaneous_injection

Plan name	Weeks	Duration	Price	Saving vs ref
Wellness / Longevity <i>(reference)</i>	4	1 month	\$199	—
Athletic / Injury Recovery	6	6 weeks	\$229	TBD

⚠️ \$139 special price is a promotional coupon — managed in promotions.config.ts, not here.

NAD+ Nasal Spray NTC-007b

Plan name	Weeks	Duration	Price	Saving vs ref
Standard (reference)	4	1 month	\$TBD	—

 Full protocol, pharmacy, and pricing spec pending.

Glutathione NTC-008

Longevity · Pharmacy TBD · TBD

Plan name	Weeks	Duration	Price	Saving vs ref
Standard (reference)	4	1 month	\$TBD	—

Oxytocin NTC-009

Well-being · Pharmacy TBD · TBD

Plan name	Weeks	Duration	Price	Saving vs ref
Standard (reference)	4	1 month	\$TBD	—

B12-MIC NTC-010

Well-being · Pharmacy TBD · TBD

Plan name	Weeks	Duration	Price	Saving vs ref
Standard (reference)	4	1 month	\$TBD	—

Weeks Paid vs Weeks Prescribed — Tracking Rule

Firestore tracks per patient:

- weeksPaid_phi — total weeks covered by the patient's payment
- weeksPrescribed_phi — total weeks sent via LifeFile so far

- $\text{weeksRemaining_phi} = \text{weeksPaid_phi} - \text{weeksPrescribed_phi}$

When clinician enters supplyWeeks_phi :

- $\leq \text{weeksRemaining_phi}$ → allowed
- $> \text{weeksRemaining_phi}$ → warning shown, clinician can override with note (logged to chart)
- $\text{weeksRemaining_phi} = 0$ → blocked until patient pays for more weeks

Admin Price Management

All prices stored in Firestore config/pricing . Admin edits from the pricing panel — no code deployment needed. Every change logged to $\text{config/pricing_history}$ with old price, new price, admin UID, timestamp.

Firestore structure per product:

```
json
{
  "productCode": "NTC-001",
  "displayName": "Semaglutide",
  "referencePlanName": "Standard",
  "administrationRoute": "subcutaneous_injection",
  "plans": [
    { "name": "Standard", "weeks": 4, "price": 249, "stripePriceId": "price_xxx", "a"},
    { "name": "3-month", "weeks": 12, "price": 686, "stripePriceId": "price_xxx", "a"},
  ],
  "updatedAt": "timestamp",
  "updatedBy": "admin_uid"
}
```

Stripe Anonymisation

All Stripe products use anonymous codes. No treatment names in any Stripe field.

NTC-001	→	Semaglutide	NTC-006	→	Sermorelin
NTC-002	→	Tirzepatide	NTC-007	→	NAD+ Injectable
NTC-003	→	Sema Microdosing	NTC-007b	→	NAD+ Nasal Spray
NTC-003b	→	Tirz Microdosing	NTC-008	→	Glutathione
NTC-004	→	Wegovy®	NTC-009	→	Oxytocin
NTC-005	→	Mounjaro®	NTC-010	→	B12-MIC
NTC-CON	→	Consultation			

Each product has one Stripe Product ID. Each plan has its own Stripe Price ID under it.

Pending Before Launch

Item	Status
Sema Microdosing 5-week price	⚠ TBD
Sema / Tirz / Wegovy / Mounjaro 3mo, 6mo, 12mo prices	⚠ TBD — set in admin pricing panel
Sermorelin 3-month saving % vs 1-month	⚠ TBD
Glutathione, Oxytocin, B12-MIC base prices	⚠ TBD
NAD+ Nasal Spray full spec	⚠ TBD
Tirzepatide Microdosing additional plans	⚠ TBD
Glutathione administration route	⚠ Must set before product goes live
Oxytocin administration route	⚠ Must set before product goes live
B12-MIC administration route	⚠ Must set before product goes live
pricing.config.ts vs refill.config.ts — one file or two	⚠ Architecture decision before build

6. Platform Architecture — 4 Platforms

6.1 Onboarding Flow

(See Section 8 for detailed screen specs)

The onboarding flow is configurable in admin — steps, content, and order can be changed without code deployment. See Section 8 for the full flow architecture.

Default GLP-1 flow (flow-glp1-v1) — 9 steps:

Step	Type	Phase	Notes
1	Pre-screen	P1	State + pregnancy for all. BMI + GLP-1 contraindication for GLP-1 track only. No age question — DOB at Step 2.
2	Account creation	P1	Name, email, password, phone, DOB. Age 18–70 validated here.
3	Product + plan select	P1	Product pre-selected from URL param. Patient selects form factor + plan length.
4	Shipping address	P1	Must match a served state
5	Payment	P1	Stripe Payment Element. Card charged immediately. HSA/FSA + BNPL.
6	Intake form	P1	One form per product, built in admin form builder
7	ID upload	P1	Government ID. Google Cloud Storage.
8	Consents + e-signature	P1	HIPAA auth, telehealth consent, ToS via DocuSeal
9	Confirmation	P1	24hr review promise, status tracker
—	Book-a-consult	P1	Separate flow. State + pregnancy pre-screen → account → \$50 payment → calendar → confirmation.

6.2 Patient App — Logged In

(See Section 6.6 for detailed screen specs — *post-approval logged-in experience*)

Screen	Phase	Notes
Dashboard home	P1	Status, next action, messages badge
Shipment tracking	P1	Live status via LifeFile API
Clinician messaging	P1	7/7 direct, threaded per patient
Weight + metrics log	P1	Log weight, see trend chart
Dosing schedule	P1	Current dose, titration schedule, next dose date. Clinician sets, patient reads.
Dosing visual	P1	Interactive syringe SVG showing current dose
Side effect reporting	P1	Via chat or check-in form (not separate screen)
Monthly check-in form	P1	Prompted every 4 weeks. Answers stored as JSON.
Refill status tracker	P1	Cycle: check-in due → clinician review → Rx sent → shipped
My prescriptions	P1	History, status, sent via LifeFile
Subscription management	P1	Pause (1-4 weeks), cancel, upgrade
Treatment pause flow	P2	Reason capture, clinician notified, Stripe billing paused
My documents	P2	Signed consents, any uploaded documents
Account settings	P1	Address, notifications, password

6.3 Clinician Platform

(See Section 6.5 for detailed screen specs)

Screen	Phase	Notes
Dashboard + queue	P1	Intake queue, flagged items, today's appointments
Intake review	P1	Approve, flag, request more info
Patient chart	P1	Full medical history, all prescriptions, all notes
Charting notes	P1	Two types: intake review note, appointment note
Patient metrics view	P1	Weight trend chart, vitals over time
Send prescription	P1	Via LifeFile API. Logged to patient chart.
Patient messaging	P1	All patients, threaded
My schedule	P1	Appointments + availability blocks (Google Calendar)
My activity report	P1	Rx sent, charts reviewed, appointments — exportable
Check-in review	P2	Monthly patient check-ins flagged for review
Urgent / safety flags	P1	Side effect reports surfaced to clinician queue

6.4 Admin / Operations

(See Section 6.7 for detailed screen specs)

Screen	Phase	Notes
Ops dashboard	P1	Revenue, patient counts, Rx volume
Served states config	P1	Toggle states on/off per product or globally
Audit log	P1	All PHI access. Legally required under HIPAA.
Clinician activity export	P1	CSV export for payroll calculation
Pricing panel	P1	One block per product. Named plans, weeks, price, reference plan. See Section 5.
Flow builder	P1	Create / edit onboarding flows. Drag-and-drop steps. Assign flows to products.
Form builder	P1	Build intake forms per product. 5 question types. Conditional logic. Preview mode.
Product → flow assignment	P1	Assign which flow each product uses
Promotions config	P1	Toggle active/inactive. Coupon codes (e.g. NAD+ \$139).
Clinician management	P2	Add, assign state licenses, deactivate
Patient assignment rules	P2	By state license + load queue (auto-assign)
Refill reminder config	P2	Holiday mode toggle. Reminder window override.
Partial refund calculator	P1	For 6-month and 12-month plan refusals. Shows weeks paid, weeks fulfilled, calculated refund amount. Admin confirms → Stripe refund initiated.

6.5 Clinician Platform — Detailed Screen Specs

- Status:  Fully specced
- Auth: Google SSO + 2FA. Role: clinician. Sees assigned patients only.
- Session: 8-hour inactivity timeout with 10-minute warning.

Navigation Structure

Clinician app (app.nutreeclinic.com/clinician)

|—

Queue

(default landing screen)

|—

Patients

(full patient list + search)

|—

Schedule

(appointments + availability)

|—

Messages

(all patient threads)

|—

My Activity

(report + export)

Patient chart is accessed by clicking a patient anywhere — it is not a top-level nav item.

Screen 1 — Queue (default landing)

What the clinician sees on arrival:

Four tabs with unread counts:

Tab	What it contains	Sort order
Intakes	New patient intakes awaiting approval	Oldest first (24hr SLA)
Check-ins	Patient check-ins awaiting refill approval	Days until supply runs out (most urgent first)
Messages	Unread patient messages	Most recent first
Flags	Safety flags, urgent alerts, 48h escalations	Most urgent first

Each tab shows a list of task cards. Each card contains:

- Patient identifier (first name + last initial — never full name in list view for privacy)
- Product code (e.g. NTC-001 — not treatment name in list)
- Task type badge (New intake / Check-in due / Message / Flag)
- Time elapsed since submission
- Urgency indicator: green (>12h remaining), amber (6-12h), red (<6h / overdue)
- "Open" button → opens patient chart at the relevant section

SLA indicators:

- Intake: 24h from submission. Red if overdue.
- Check-in: based on `nextRefillDue_phi` – today. Red if supply runs out in <5 days.
- Flag: always red. Must be actioned immediately.

Firestore query:

```
clinician queue = all tasks where:  
  assignedClinicianId == currentUser.uid  
  AND status IN ['pending_review', 'checkin_submitted', 'safety_flagged']  
  ORDER BY urgencyScore DESC
```

Screen 2 — Patient Chart

Accessed by clicking any patient from Queue, Patients list, or Messages. This is the central clinical screen.

Layout: two-column

- Left column (30%): patient summary sidebar — persistent
- Right column (70%): active section content — changes based on selected tab

Left sidebar — Patient Summary:

- Patient name + photo placeholder
- Age, sex (from intake `_phi` fields)
- Product code + current level (e.g. NTC-001 · Level 2)
- Current dose (e.g. 0.5mg / 0.5mL weekly)
- Weeks remaining on plan (`weeksRemaining_phi`)
- Last check-in date
- Last Rx sent date
- Quick action buttons:
 - Send prescription
 - Add chart note
 - Message patient
 - Flag for review

Right column — tabbed sections:

Tab	Contents
Overview	Timeline of all events (intakes, Rx sent, check-ins, notes, messages) in chronological order
Intake	Full intake form answers. Read-only. Flag individual answers.
Prescriptions	All Rx sent via LifeFile. Date, level, dose, supply weeks, status.
Check-ins	All check-in submissions. Answers + weight at time of check-in.
Metrics	Weight trend chart + any other logged vitals over time
Notes	All charting notes (intake review + appointment types)
Messages	This patient's message thread (same as messaging screen, scoped to patient)
Documents	ID upload, signed consent PDFs

Screen 3 — Intake Review

Opened from Queue → Intakes tab → click task card.

What the clinician sees:

- Full intake form answers rendered clearly (question → answer pairs)
- Patient pre-screen data (state, BMI if GLP-1, pregnancy status)
- ID upload preview (thumbnail, click to enlarge)
- Consent documents signed status (all three — HIPAA, telehealth, ToS)
- Any flags auto-detected (e.g. contraindication answers, safety flag)
- Time elapsed since submission + SLA indicator

Action panel (right side or bottom):

Action	Result
Approve + send prescription	Opens prescription send screen pre-loaded with patient's product
Approve — prescription later	Marks intake approved, clinician sends Rx separately
Request more information	Opens message composer pre-addressed to patient with optional template text
Reject intake	Opens rejection flow — reason required, refund triggered automatically

Firestore write on approval:

```
json
{
  "status": "approved",
  "approvedAt": "timestamp",
  "approvedBy_phi": "clinician_uid",
  "intakeReviewNote_phi": "string"
}
```

Screen 4 — Send Prescription

Opened from: Intake approval, Patient chart → Prescriptions tab, or Quick action button.

Fields:

Field	Type	Notes
Medication level	Dropdown	Levels for this product from <code>medications</code> collection. Shows dose range + vial spec. Level skip blocked.
Exact dose (mg)	Number input	Within level's range. mL auto-calculated in real time.
Calculated volume (mL)	Read-only	<code>calcVolume(dose, medicationId)</code> — shown prominently
Supply weeks	Number input	Default = plan standard. Compared to <code>weeksRemaining_phi</code> . Warning if over.
Titration notes	Free text	Optional. Stored as <code>titrationNotes_phi</code> .
LifeFile order preview	Read-only	"Ordering [vialSpec] from [pharmacy] for [supplyWeeks] weeks to [city, state]" — no full address shown

Confirm & Send:

- Calls LifeFile API
- Writes to `patients/{uid}/prescriptions/{rxId}` with all `_phi` fields
- Updates `weeksPrescribed_phi`, `lastRxSentAt_phi`, `nextRefillDue_phi`
- Patient app updated immediately
- SendGrid: patient notified "Your prescription has been sent to the pharmacy"

Warning states:

- Level skip attempted → blocked with message
 - supplyWeeks > weeksRemaining → amber warning, can override with note
 - weeksRemaining = 0 → blocked, patient must renew
-

Screen 5 — Charting Notes

Two note types. Both use the same screen with different templates.

Note type 1: Intake Review Note Triggered automatically when clinician approves or rejects an intake.

Structured fields:

- Intake reviewed: [date auto-filled]
- Decision: Approved / Rejected / More info requested
- Clinical summary: [free text – smart suggestions shown]

Smart verbiage suggestions (single-click to insert, editable):

"Patient meets clinical criteria for [product]. No contraindications identified."

"Patient history reviewed. Dose titration to start at Level 1."

"Requested clarification on [field] before proceeding."

"Intake rejected due to [contraindication]. Refund initiated."

Note type 2: Appointment / Check-in Note Triggered when clinician reviews a check-in or after an appointment.

Structured fields:

- Date: [auto-filled]
- Type: Check-in review / Appointment / Ad hoc
- Current weight: [number – pulled from latest check-in if available]
- Dose decision: Maintain / Titrate up / Titrate down / Hold
- Next level: [dropdown – only shown if titrating, enforces no-skip]
- Clinical notes: [free text – smart suggestions shown]
- Follow-up: [date picker – optional]

Smart verbiage suggestions:

"Patient tolerating current dose well. No significant side effects reported."

"Weight loss of [X] lbs since last check-in. Progressing as expected."

"Patient reports [side effect]. Dose adjusted to manage tolerability."

"Advancing to Level [N] based on tolerance and progress."

"Dose held at current level pending further monitoring."

Firestore write:

```
json
{
  "noteId": "string",
  "noteType_phi": "intake_review | appointment | checkin",
  "createdAt": "timestamp",
  "createdBy_phi": "clinician_uid",
  "decision_phi": "approved | rejected | more_info",
  "currentWeight_phi": 185.5,
  "doseDecision_phi": "titrate_up",
  "nextLevel_phi": "SEMA-L2",
  "clinicalNotes_phi": "string",
  "followUpDate_phi": "date | null"
}
```

Screen 6 — Check-in Review

Opened from Queue → Check-ins tab → click task card.

What the clinician sees:

- Check-in answers rendered (question → answer pairs)
- Weight logged at check-in vs previous weight → delta shown (e.g. "–4.2 lbs since last check-in")
- Side effects reported (if any) — highlighted
- Current dose and level
- Days until supply runs out — prominent urgency indicator
- weeksRemaining_phi

Action panel:

Action	Result
Approve refill + send prescription	Opens prescription send screen pre-loaded
Approve refill — prescription later	Marks check-in reviewed, clinician sends Rx separately
Request more info	Message composer to patient
Flag for clinical review	Escalates to Flags tab, notifies admin

Firestore write on approval:

```
json
```

```
{
  "checkinId": "string",
  "reviewedAt": "timestamp",
  "reviewedBy_phi": "clinician_uid",
  "status": "reviewed",
  "refillApproved": true
}
```

Screen 7 — Patient Metrics View

Accessed from Patient Chart → Metrics tab.

Weight chart:

- Line chart of all weight entries over time
- Each data point = patient self-reported weight from check-in or manual log
- Overlaid events: Rx sent (dose level markers), level changes
- Timeframe selector: 1 month / 3 months / 6 months / all time
- Current weight shown prominently
- Total weight change since first entry

Other vitals (if logged by patient):

- Any numeric fields from check-in form (configured in form builder)
- Each renders as its own mini chart below the weight chart

Clinician notes on metrics:

- Clinician can add a free-text annotation to any data point
- Annotation stored as `metricNote_phi`

Screen 8 — Patient Messaging

Accessed from: Queue → Messages tab (all patients), or Patient Chart → Messages tab (single patient).

Layout:

- Left panel: patient list sorted by most recent message, unread badge
- Right panel: message thread for selected patient

Message thread:

- Chronological, oldest at top
- Each message shows: sender (patient name or clinician name), timestamp, read status
- Clinician can attach files (e.g. injection instructions PDF)
- Character limit: 2000 per message
- No message deletion — medical record

Sending:

- Text field + send button
- Optional quick-reply templates (admin-configurable):
 - "Your prescription has been sent to the pharmacy."
 - "Please complete your check-in to continue your treatment."
 - "Your intake has been reviewed and approved."

Firestore structure:

```
messages/{threadId}
  threadId = patientUid (one thread per patient-clinician pair)
  messages: [{
    messageId, senderId_phi, senderRole,
    body_phi, sentAt, readAt
  }]
```

Screen 9 — My Schedule

Two views:

Calendar view:

- Week view default (day view available)
- Appointments shown as blocks
- Availability blocks shown in lighter colour
- Click appointment → opens appointment detail

Appointment detail:

- Patient name + product
- Appointment type (consultation / follow-up / check-in call)
- Google Calendar link (opens in Google Calendar for clinician)

- Add appointment note button → opens Charting Notes (Screen 5, type: appointment)

Availability management:

- Clinician sets availability blocks in Google Calendar
 - Nutree reads from Google Calendar API — no separate availability UI needed
 - Patients book via the book-a-consult flow which reads the same calendar
-

Screen 10 — My Activity Report

Purpose: Gives clinician visibility into their own work volume. Also used by admin for payroll CSV export.

Metrics shown (date range selector — default: current month):

Metric	Description
Intakes reviewed	Count of intake approvals + rejections
Prescriptions sent	Count of LifeFile Rx dispatched
Check-ins reviewed	Count of check-in approvals
Appointments completed	Count of calendar appointments in period
Messages sent	Count of outbound messages
Average intake review time	Time from submission to clinician action

Export:

- "Export CSV" button → downloads all metrics for selected date range
- Used by admin for payroll calculation
- CSV columns: date, event type, patient code (anonymised), action taken

Firestore query:

```
clinician_activity where clinicianId == currentUser.uid  
AND date BETWEEN startDate AND endDate
```

Firestore Collections — Clinician Platform

Collection	Contents	PHI fields
<code>clinicians/{uid}</code>	Clinician profile, state licenses, auth status	<code>email_phi</code> , <code>firstName_phi</code> , <code>lastName_phi</code> , <code>stateLicenses_phi</code>
<code>patients/{uid}</code>	Patient record (read by assigned clinician)	All <code>_phi</code> fields
<code>patients/{uid}/prescriptions/{rxId}</code>	Rx history	All <code>_phi</code> fields
<code>patients/{uid}/notes/{noteId}</code>	Charting notes	All <code>_phi</code> fields
<code>patients/{uid}/checkins/{checkinId}</code>	Check-in submissions	All <code>_phi</code> fields
<code>messages/{threadId}</code>	Patient-clinician messages	<code>senderId_phi</code> , <code>body_phi</code>
<code>clinician_activity/{eventId}</code>	Activity log for reporting	<code>clinicianId</code> (uid, not name)
<code>audit_log/{eventId}</code>	All PHI access events	Metadata only

Screen 11 — Internal Comments

Purpose: Informal clinical notes visible to all clinicians and admin. Not shown to patient. Not part of the formal chart. Used for phone call summaries, informal observations, coordination notes between clinicians.

Distinct from charting notes (Screen 5):

- Charting notes = formal clinical record (intake review, appointment note)
- Internal comments = informal, internal-only (phone calls, observations, team coordination)

What the clinician sees:

- Comment feed on the Patient Chart sidebar (below quick action buttons)
- Each comment: clinician name, timestamp, free text
- Add comment button → text field inline, 500 char limit
- Comments are append-only — no editing or deletion after saving

Firestore structure:

```
json
{
  "commentId": "string",
  "body_phi": "Spoke to patient by phone. Confirmed they understand weekly injection",
  "createdBy_phi": "clinician_uid",
  "createdByName_phi": "Dr. A. Smith",
  "createdAt": "timestamp",
  "visibleTo": "all_clinicians"
}
```

Stored at: `patients/{uid}/comments/{commentId}`

Screen 12 — Intake Review — Rejection & Correction Flow

Step 1 — Clinician flags a concern (not a hard reject)

Before rejecting, clinician selects:

- "Flag for correction" → opens message composer pre-addressed to patient
- Clinician selects which question(s) are unclear or potentially incorrect (multi-select from intake question list)
- Adds optional message to patient
- System sends email + SMS to patient (no PHI — see templates below)
- Patient status → `intake_correction_requested`
- Intake appears in patient app with: "Your clinician has a question about your intake. Please review and update."

Step 2 — Patient corrects intake

Patient sees their intake with all answers editable. They can change any answer. On resubmit:

- All answers replaced with new version
- Previous answers archived in `intakeAnswers_history_phi` array (full audit trail)
- Status → `pending_review`
- Clinician queue updated — intake reappears as new task with badge: "Resubmitted"
- SendGrid + SMS: patient confirmation of resubmission (template below)

Step 3 — True rejection (after correction or without)

If clinician confirms rejection after reviewing:

1. Clinician clicks "Reject intake"
2. Popup: "Are you sure? This will cancel the patient's order and trigger an automatic refund."
 - Confirm / Cancel buttons
3. On confirm:
 - Clinician must select a rejection reason (required):
 - Clinical contraindication
 - Incomplete or unclear information
 - Patient does not meet eligibility criteria
 - Other (free text required)
 - Rejection reason stored as `rejectionReason_phi`
 - Status → `rejected`
 - Stripe refund triggered automatically via Firebase Cloud Function
 - SendGrid + SMS to patient (no PHI — template below)

Firestore write on rejection:

```
json
{
  "status": "rejected",
  "rejectedAt": "timestamp",
  "rejectedBy_phi": "clinician_uid",
  "rejectionReason_phi": "clinical_contraindication | incomplete_info | ineligible |",
  "rejectionNote_phi": "free text if other",
  "refundTriggered": true,
  "refundTriggeredAt": "timestamp"
}
```

Screen 13 — Prescription Refusal

Different from intake rejection: Intake rejection = patient never gets a prescription, full refund. Prescription refusal = clinician had approved the intake but refuses to send the Rx at a later point (e.g. after check-in review, or due to new clinical concern).

Trigger: Clinician clicks "Refuse prescription" on the prescription send screen or patient chart.

Flow:

1. Popup: "Are you sure you want to refuse this prescription? This will cancel the patient's current order and trigger an automatic refund."
 - Confirm / Cancel

2. On confirm — clinician must select reason (required):
 - Safety concern based on check-in
 - Patient non-compliant (missed multiple check-ins)
 - Clinical contraindication identified
 - Patient request
 - Other (free text required)
3. Reason stored as `prescriptionRefusalReason_phi`
4. Patient status → `prescription_refused`
5. Stripe refund triggered for current billing period
6. SendGrid + SMS to patient (template below)
7. Internal comment auto-created: "Prescription refused by [clinician]. Reason: [category]."

Firestore write:

```
json
{
  "prescriptionRefusalId": "string",
  "refusedAt": "timestamp",
  "refusedBy_phi": "clinician_uid",
  "reason_phi": "safety_concern | non_compliant | contraindication | patient_request",
  "reasonNote_phi": "free text if other",
  "refundTriggered": true,
  "refundAmount": "number"
}
```

Stored at: `patients/{uid}/prescription_refusals/{id}`

Patient Communication Templates

All templates contain NO PHI. No treatment names, medication names, doses, or diagnosis information.

Patient sees their own name (first name only) in the email subject line only — not in the body.

All templates sent via SendGrid (email) + SMS (body only, shorter version).

Template 1 — Intake submitted confirmation

Trigger: Patient completes onboarding Step 9 (confirmation screen)

Email subject: `Your Nutree Clinic intake is under review`

Hi [firstName],

Thank you for completing your intake. A licensed clinician will review your information and you will hear from us within 24 hours.

If you have any questions in the meantime, you can message your care team directly through your patient app.

The Nutree Clinic Team
nutreeclinic.com

SMS: Nutree Clinic: Your intake has been received. A clinician will review within 24 hours. Questions? Log in to your app.

Template 2 — Intake approved + prescription sent

Trigger: Clinician approves intake and sends Rx

Email subject: Good news — your order is on its way

Hi [firstName],

Your intake has been reviewed and approved. Your order has been placed with our partner pharmacy and will be shipped to your address.

You can track your shipment status in your patient app.

The Nutree Clinic Team

SMS: Nutree Clinic: Great news! Your order has been placed and is on its way. Track it in your app.

Template 3 — Intake correction requested

Trigger: Clinician flags intake for correction

Email subject: Action needed — please review your intake

Hi [firstName],

Our clinical team has reviewed your intake and has a question about one of your responses. Please log in to your patient app to review and update your information.

This won't delay your care – we just want to make sure everything is accurate before proceeding.

The Nutree Clinic Team

SMS: Nutree Clinic: Our team needs clarification on your intake. Please log in to your app to review and update.

Template 4 — Intake resubmitted confirmation

Trigger: Patient resubmits corrected intake

Email subject: Your updated intake is under review

Hi [firstName],

Thank you for updating your intake. Our clinical team will review your updated information and you will hear from us within 24 hours.

The Nutree Clinic Team

SMS: Nutree Clinic: Updated intake received. A clinician will review within 24 hours.

Template 5 — Intake rejected + refund

Trigger: Clinician rejects intake

Email subject: Update on your Nutree Clinic intake

Hi [firstName],

After reviewing your intake, our clinical team has determined that we are unable to proceed with your order at this time.

A full refund of [refundAmount] has been initiated and will appear on your original payment method within 5-7 business days.

If you believe this decision was made in error or would like to speak with a clinician, you can book a consultation at nutreeclinic.com/consult.

The Nutree Clinic Team

SMS: [Nutree Clinic: We're unable to proceed with your intake. A refund of \[refundAmount\] has been initiated \(5-7 business days\). Questions? Book a consult at \[nutreeclinic.com/consult\]\(https://nutreeclinic.com/consult\)](#)

Note: [refundAmount] is the only data point included — it is not PHI. It is a dollar amount only, with no clinical context.

Template 6 — Prescription refused + refund

Trigger: Clinician refuses prescription

Email subject: [Important update about your Nutree Clinic order](#)

Hi [firstName],

Our clinical team has reviewed your case and is unable to proceed with your current order. A refund of [refundAmount] has been initiated and will appear within 5-7 business days.

If you have questions or would like to speak with a clinician, please message us through your patient app or book a consultation.

The Nutree Clinic Team

SMS: [Nutree Clinic: Your clinician has an update about your order. A refund of \[refundAmount\] is being processed. Check your email for details.](#)

Note: [refundAmount] is the only data point included — it is not PHI.

Template 7 — Check-in reminder

Trigger: [refill_due - 10](#) days (standard) or [refill_due - 3](#) days (escalation)

Email subject: `Time for your Nutree Clinic check-in`

Hi `[firstName]`,

It's time to complete your monthly check-in to continue your care.
Your check-in must be completed to ensure your next supply is sent without delay.

Log in to your app to complete it now – it takes less than 5 minutes.

The Nutree Clinic Team

SMS (standard): `Nutree Clinic: Your check-in is due. Complete it in your app to avoid delays with your next supply.` SMS (escalation - 3 days): `Nutree Clinic: Reminder – your check-in is overdue. Complete it now to avoid a delay in your supply.`

Template 8 — Prescription shipped

Trigger: LifeFile API shipment status update → `shipped`

Email subject: `Your Nutree Clinic order has shipped`

Hi `[firstName]`,

Your order is on its way. You can track your shipment in your patient app.

The Nutree Clinic Team

SMS: `Nutree Clinic: Your order has shipped! Track it in your app.`

Updated Patient Status Values

Value	Meaning
<code>onboarding_in_progress</code>	Account created, onboarding not complete
<code>pending_review</code>	Intake submitted, awaiting clinician
<code>intake_correction_requested</code>	Clinician flagged intake for patient correction
<code>approved</code>	Clinician approved intake
<code>active</code>	Rx sent, patient in active care

Value	Meaning
<code>prescription_refused</code>	Clinician refused Rx after approval
<code>rejected</code>	Intake rejected, refund triggered
<code>waitlisted</code>	State not served
<code>safety_flagged</code>	Harm to self/others answer = Yes
<code>paused</code>	Patient paused subscription
<code>cancelled</code>	Patient cancelled

6.6 Patient App — Detailed Screen Specs

Status:  Fully specced

Auth: Email+password or Google SSO. Role: patient. Sees own record only.

This is the same app as onboarding — one Next.js app at app.nutreeclinic.com. Onboarding = pre-approval flow. This section = post-approval logged-in experience.

Session: 30-minute inactivity timeout.

Navigation Structure

Patient app (app.nutreeclinic.com)

Home

(default – status tracker + quick access icons)

My Care

(dosing, prescriptions, refill status, shipment)

Check-in

(monthly check-in form – shown when due)

Messages

(clinician thread)

Progress

(weight log + metrics chart)

Account

(subscription, documents, settings)

Bottom navigation bar on mobile. Sidebar on desktop.
 Check-in tab shows a badge when check-in is due.

Screen 1 — Home (Dashboard)

Purpose: Instant orientation. Patient sees where they are and what needs attention.

Layout: status tracker + quick-access icon row

Status tracker (top, full width): Visual progress pipeline showing current position in care journey:

Intake submitted → Under review → Approved → Rx sent → Shipped → Delivered → Active care

Each stage shows:

- Completed stages: filled, with date
- Current stage: highlighted with label
- Upcoming stages: dimmed

For patients in active care (post-first-delivery), tracker shows refill cycle status:

Supply active → Check-in due [date] → Clinician review → Next Rx → Shipped

Quick-access icon row (below tracker): Four icons — tap to navigate directly:

Icon	Label	Destination	Badge
Message bubble	Messages	Messages screen	Unread count
Clipboard	Check-in	Check-in form	"Due" if overdue
Package	My order	Shipment tracking	"In transit" if shipped
Chart line	Progress	Weight + metrics	—

Context card (below icons): One card showing the single most important next action:

- Pending intake review → "Your clinician is reviewing your intake — within 24 hours"
- Check-in due → "Your check-in is due — complete it to avoid delays"
- Rx in transit → "Your order is on its way — track it here"
- Active, nothing due → "You're on track — next check-in in [X] days"

Firestore reads: `patients/{uid}` status, `weeksPrescribed_phi`, `nextCheckinDue_phi`, `lastRxSentAt_phi`, latest shipment status from LifeFile cache.

Screen 2 — My Care

Tabbed screen with four sub-sections:

Tab 1 — Dosing

- Current product (display name from `pricing.config`) + level label
- Current dose: `dose_phi` mg = `volume_phi` mL

- Administration: route + frequency (from `medications` catalogue)
- Next injection due date (calculated from `lastRxSentAt_phi` + frequency)
- **Interactive syringe SVG (injection products only):**
 - Shown only when `administrationRoute == "subcutaneous_injection"`
 - Syringe barrel drawn to represent a standard 1mL insulin syringe (fixed drawing — not scaled to vial size)
 - Volume to draw calculated as: `mL = dose_phi / concentrationMgPerMl` (uses `calcVolume()` helper)
 - Fill line drawn at the calculated mL position on the syringe barrel
 - Graduation marks shown on barrel (0.1mL increments)
 - Labels clearly shown:
 - "Your weekly dose: `[dose_phi]` mg"
 - "Draw to: `[volume_phi]` mL"
 - "Concentration: `[concentrationMgPerMl]` mg/mL (Level `[levelLabel]`)"
 - Tapping the syringe shows instruction card: "Draw `[volume_phi]` mL into your syringe. This equals `[dose_phi]` mg of your medication."
 - If `concentrationMgPerMl` is missing or zero → syringe hidden, error logged to admin
 - Not shown for: patches, nasal spray, oral medications
- Titration history: collapsible list of all past doses (date, level, mg, mL)

Tab 2 — Prescriptions

Table of all prescriptions sent:

Date	Level	Dose	Supply	Status
Apr 10	Level 2	0.5mg	4 weeks	Delivered
Mar 6	Level 1	0.25mg	4 weeks	Delivered

Tapping a row shows full detail: pharmacy code, vial spec, LifeFile order reference.

Tab 3 — Refill Status

Visual refill cycle tracker (matches what clinician sees):

Check-in submitted → Clinician review → Rx approved → Sent to pharmacy → Shipped → Delivered

Shows:

- Current cycle position
- Days until next check-in due
- `weeksRemaining_phi` displayed as: "X weeks of supply remaining"
- If check-in overdue: amber warning card "Complete your check-in to avoid delays"
- If `weeksRemaining_phi` = 0: red card "Your supply has run out — contact your clinician"

Tab 4 — Shipment

Live shipment tracking:

- Current status (processing / shipped / out for delivery / delivered)
- Estimated delivery date
- Tracking reference number
- Shipping address (from `shippingAddress_phi` — shown masked: "123 Main St, Miami FL")
- Link to carrier tracking page (external)

⚠ LifeFile API has no GET endpoint for tracking in the current spec. Status updates must arrive via LifeFile callback/webhook to Nutree (to be confirmed with LifeFile). Nutree stores the latest status in Firestore `patients/{uid}/prescriptions/{rxId}` and the patient app reads from Firestore — not directly from LifeFile at display time.

If no active shipment: "No active shipment — your next order will appear here once your prescription is sent."

Screen 3 — Check-in Form

When shown: Check-in tab shows badge when `nextCheckinDue_phi` ≤ today. Patient can also access past check-ins from this screen.

Form:

- Rendered dynamically from the product's check-in form (built in admin form builder — same 5 question types as intake)
- Weight entry always first question (number field, lbs or kg toggle)
- Remaining questions per product form config
- Progress indicator within form: "Question X of Y"
- Save draft (auto-saves every question answer)
- Submit button — disabled until all required questions answered

On submit:

- Answers stored as `checkinAnswers_phi` JSON in `patients/{uid}/checkins/{checkinId}`
- Status updated: check-in appears in clinician's Check-ins queue tab
- Patient sees: "Check-in submitted — your clinician will review shortly"
- SendGrid + SMS: clinician notified (internal notification, not a patient template)
- Check-in badge clears from navigation

Past check-ins:

- List of all previous check-ins below the current form
- Each shows: date submitted, weight logged, review status (pending / reviewed)
- Tap to expand and see answers (read-only)

Firestore structure:

```
json
{
  "checkinId": "string",
  "submittedAt": "timestamp",
  "formId": "string",
  "answers_phi": {
    "weight_phi": 182.5,
    "q1": "None of the above",
    "q2": false
  },
  "status": "submitted | reviewed",
  "reviewedAt": "timestamp | null"
}
```

Screen 4 — Messages

Layout: Single thread — patient only ever messages their assigned clinician.

- Chronological thread, oldest at top, newest at bottom
- Each message: sender label (You / Dr. [lastName]), timestamp
- Patient can send text messages up to 2000 characters
- Clinician attachments (e.g. injection guide PDF) shown as downloadable file cards
- No message deletion — append only
- Unread messages from clinician shown with blue dot until read
- "Mark as read" triggered automatically when patient views the thread

Input: Text field + Send button at bottom. No file upload for patients at launch.

If no clinician assigned yet: "Your clinician will be assigned shortly. You'll be able to message them here once your intake is reviewed."

Screen 5 — Progress

Weight chart (top):

- Line chart of all weight entries over time (from check-ins + manual logs)
- X-axis: dates. Y-axis: weight in patient's preferred unit (lbs/kg)
- Timeframe toggle: 1 month / 3 months / All time
- Total change label: "-12 lbs since [start date]"
- Each data point tappable: shows date + weight value
- Empty state: "Log your first weight to start tracking your progress"

Manual weight log (below chart):

- "Log weight" button → simple modal: weight field (number) + date (defaults to today) + optional note
- Logged entries appear on chart immediately
- Past entries listed below chart: date, weight, note
- Patient can delete a manual entry (check-in weights cannot be deleted — they are part of the clinical record)

Other metrics (if configured in check-in form):

- Any numeric question from the check-in form renders as its own mini chart below the weight chart
- E.g. energy level, sleep quality (if using a 1-10 scale question type)

Firestore structure — manual weight logs:

```
json
{
  "logId": "string",
  "loggedAt": "timestamp",
  "weight_phi": 182.5,
  "unit_phi": "lbs",
  "note_phi": "optional string",
  "source": "manual | checkin"
}
```

Stored at: `patients/{uid}/weight_logs/{logId}`

Screen 6 — Account

Three sub-sections:

Sub-section 1 — Subscription

Item	Detail
Current plan	Product display name + plan name + weeks
Plan start date	Date first Rx was sent
Weeks paid	<code>weeksPaid_phi</code>
Weeks remaining	<code>weeksRemaining_phi</code>
Payment method	Last 4 digits of card (from Stripe)

Actions — all require clinician involvement:

- "Request a change to my plan" → opens message composer pre-filled: "I'd like to discuss a change to my plan." Sends to clinician.
- "Request to pause" → opens message composer pre-filled: "I'd like to pause my treatment temporarily."
- "Request to cancel" → opens message composer pre-filled: "I'd like to discuss cancelling my treatment."

No self-service pause, upgrade, or cancel — all go through clinician messaging.
Clinician or admin processes the change after clinical conversation.

Why clinician-gated: This is a medical product. Cancellation or pausing without a clinical conversation could harm the patient (abrupt GLP-1 discontinuation, for example). The friction is intentional and clinically appropriate.

Sub-section 2 — Documents

- Signed consent documents: HIPAA Authorization, Telehealth Consent, Terms of Service
 - Each shows: signed date, "Download PDF" button (reads from Google Cloud Storage)
- Intake form submission (read-only PDF or rendered answers)
- Any documents shared by clinician (injection guides etc.)

Sub-section 3 — Settings

Setting	Options
Name	Editable — triggers clinician notification
Email	Editable — requires re-verification
Phone	Editable
Password	Change password flow (email+password accounts only)
Linked Google account	Connect / disconnect (if using email+password)
Shipping address	Editable — must remain in a served state
Weight unit	lbs / kg toggle
Notification preferences	Email on / off · SMS on / off (per notification type)
Language	English only at launch

Shipping address change: validated against served states in real time. If patient moves to an unserved state → warning: "We don't currently serve [State]. Please contact your clinician before changing your address."

Patient App — Firestore Collections Summary

Collection	Contents	PHI
patients/{uid}	Profile, status, subscription tracking	All <code>_phi</code> fields
patients/{uid}/prescriptions	Rx history	All <code>_phi</code> fields
patients/{uid}/checkins	Check-in submissions + answers	<code>answers_phi</code>
patients/{uid}/weight_logs	Manual weight entries	<code>weight_phi</code> , <code>unit_phi</code> , <code>note_phi</code>
patients/{uid}/notes	Charting notes (read-only for patient — not shown)	—
patients/{uid}/comments	Internal clinician comments (not shown to patient)	—

Collection	Contents	PHI
messages/{uid}	Patient-clinician message thread	body_phi, senderId_phi
patients/{uid}/documents	References to GCS files	storagePath

Patient App — Notification Preferences

Patients can toggle each notification type on/off independently:

Notification	Default	Channel
Check-in reminder	On	Email + SMS
Prescription sent	On	Email + SMS
Shipment update	On	Email + SMS
New message from clinician	On	Email + SMS
Intake status update	On	Email only
Subscription renewal reminder	On	Email + SMS

6.7 Admin Platform — Detailed Screen Specs

Status:  Fully specced

Auth: Google SSO + 2FA. Role: admin. Full access to all screens and all patients.

Session: 8-hour inactivity timeout.

Navigation Structure

```
Admin app (app.nutreeclinic.com/admin)
├─ Dashboard      (default – key metrics + flags)
├─ Patients       (all patients, search, filter)
├─ Clinicians     (manage clinicians)
├─ Configuration
│   ├─ Pricing
│   ├─ Flows
│   ├─ Forms
│   └─ States
```

Screen 1 — Ops Dashboard

Purpose: First thing admin sees on login. Instant orientation on clinic health.

Four metric cards (top row):

Card	Metric	Detail
Revenue	MRR (monthly recurring revenue)	Current month vs previous month, % change
Patients	Active patient count	Total active + new this month
Prescriptions	Rx sent this month	Count + trend vs last month
Flags	Items needing attention	Count of unactioned flags (red if > 0)

Flags panel (below metric cards): List of items requiring admin action, sorted by urgency:

Flag type	Trigger	Action
Safety flag	Patient answered Yes to harm question	Open patient record
Clinician 48h escalation	Clinician did not action a task in 48h	Assign to another clinician or action directly
Refund pending	Prescription refusal on 6/12-month plan	Open partial refund calculator
Overdue intake	Intake not reviewed after 24h	Reassign or action
Failed payment	Stripe payment failure	View in Stripe dashboard
System error	LifeFile API failure, Firestore write error	View error log

Recent activity feed (below flags): Last 20 events across all patients — intakes submitted, Rx sent, check-ins, new signups. Read-only.

Firestore queries:

- Revenue: sum of `pricePaid` from payment documents where `paidAt` within current month
 - Active patients: count of `patients` where `status == "active"`
 - Rx volume: count of `prescriptions` where `sentAt` within current month
 - Flags: query `flags` collection where `resolved == false`
-

Screen 2 — Patients

Patient list:

- Search by name, email, or patient code
- Filter by: status, product, clinician, state
- Columns: patient code, first name, product, status, assigned clinician, last activity
- Click row → opens patient chart (same two-column layout as clinician view, but admin sees everything including internal comments and all clinicians' notes)

Admin-only actions on patient chart:

- Reassign clinician
 - Manually override patient status
 - Process partial refund (links to Finance → Refund calculator)
 - Delete account (HIPAA retention rules apply — soft delete only, data retained per legal requirement)
-

Screen 3 — Clinicians

Clinician list:

- Name, email, active status, state licenses, patients assigned, last login
- "Add clinician" button

Add clinician flow:

1. Enter Google email
2. Confirm 2FA is enabled on their Google account (manual checkbox — admin verifies)
3. Enter NPI number (required — 10 digits)
4. Select state licenses with license number per state
5. Set active = true
6. Firebase Auth custom claim `role: clinician` assigned via Cloud Function

- Clinician receives email (SendGrid template): "You've been added to Nutree Clinic. Log in with your Google account at [url]."

Edit clinician:

- Toggle active / inactive
- Add or remove state licenses
- View activity report for this clinician (same as Screen 10 in clinician platform)

Firestore write:

```
json
{
  "uid": "firebase_uid",
  "email_phi": "clinician@gmail.com",
  "firstName_phi": "string",
  "lastName_phi": "string",
  "phone_phi": "string",
  "role": "clinician",

  "npi_phi": "string (10-digit NPI – required for every LifeFile order)",
  "dea_phi": "string (DEA number – required for controlled substance orders, format",
  "stateLicenses_phi": [
    { "state": "FL", "licenseNumber_phi": "string" },
    { "state": "TX", "licenseNumber_phi": "string" }
  ],

  "address_phi": "string",
  "city_phi": "string",
  "state_phi": "string (primary practice state)",
  "zip_phi": "string",

  "active": true,
  "googleSsoVerified": true,
  "twoFaVerified": true,
  "addedBy": "admin_uid",
  "addedAt": "timestamp",
  "lastLoginAt": "timestamp"
}
```

All fields required before clinician can send any prescription:

- `npi_phi` — mandatory for all LifeFile orders
- `dea_phi` — mandatory for controlled substance orders (confirm which products with LifeFile)

- `stateLicenses_phi` — at least one state + license number; must match patient's shipping state
- `address_phi`, `city_phi`, `state_phi`, `zip_phi` — required in LifeFile prescriber block
- `googleSsoVerified` + `twoFaVerified` — must both be true before clinician can log in

Admin enters all fields in the Clinician Management screen (Section 6.7 Screen 3). The app blocks prescription send if `npi_phi` is null or if no matching state license exists for the patient's state.

Screen 4 — Configuration: Pricing

Already specced in Section 5 and the pricing admin mockup.

Summary:

- One block per product
 - Each block: product name, code, administration route, reference plan selector
 - Each plan row: name, weeks, duration label, price input, saving vs ref (auto-calculated)
 - Add plan / delete plan per product
 - Save per product block → writes to Firestore `config/pricing`
 - Audit trail below: date, product, plan, old price, new price, changed by
-

Screen 5 — Configuration: Flow Builder

Flow list view:

- All flows with name, status (active/inactive), products assigned, last modified
- "New flow" button
- Each flow row: click to edit, toggle active/inactive

Flow editor:

- Flow name input
- Drag-and-drop step list
- Each step shows: step type badge, order number, configured items summary
- "Add step" button → dropdown of available step types
- Delete step button (confirmation required if flow is active)
- "Assign to products" section: multi-select of all products → assigns this flow

Step configurator (opens when clicking a step): Per step type, configurable items:

Step type	Configurable items
prescreen	Checkboxes: state / pregnancy / bmi / glp1_contraindication
intake_form	Select which form (dropdown of forms built in Form Builder)
consents	Checkboxes: hipaa / telehealth / tos
payment	No configuration — BNPL options managed in Stripe dashboard
All others	No configuration

Firestore write:

```
json
{
  "flowId": "flow-glp1-v1",
  "flowName": "GLP-1 standard v1",
  "active": true,
  "steps": [
    { "stepId": "prescreen", "stepType": "prescreen",
      "order": 1, "items": ["state","pregnancy","bmi","glp1_contraindication"] },
    { "stepId": "intake", "stepType": "intake_form",
      "order": 6, "items": ["form-glp1"] }
  ],
  "assignedProducts": ["NTC-001","NTC-002"],
  "updatedAt": "timestamp",
  "updatedBy": "admin_uid"
}
```

Screen 6 — Configuration: Form Builder

Form list view:

- All forms with name, product assigned, question count, last modified
- "New form" button

Form editor:

- Form name input
- Product assignment (dropdown — one form per product)
- Question list (drag to reorder)

- Each question row: type badge, label preview, required toggle, conditional logic badge
- "Add question" button

Question editor (opens inline when clicking a question):

Field	Input
Question type	Dropdown: free_text / number / single_select / multi_select / boolean
Label	Text input — stored as <code>label_phi</code>
Required	Toggle
Options	(single_select / multi_select only) — add/remove option chips
Number unit	(number only) — e.g. "lbs", "mg/dL"
Conditional logic	Show this question only if: [question selector] [operator] [value]

Conditional logic builder:

- "Show if" toggle
- Question selector: dropdown of all previous questions in this form
- Operator: is / is not / contains / is greater than / is less than
- Value: text / number / option depending on parent question type

Preview mode:

- "Preview form" button → renders the form exactly as patient will see it
- Conditional logic is live in preview — toggle answers to see show/hide behaviour

Firestore write: Same structure as already specced in Section 8 (`forms/{formId}`)

Screen 7 — Configuration: Served States

Single screen — clinic-level toggle:

- USA map with states coloured: green = served, grey = not served
- List view alongside map: all 50 states + DC with toggle per state
- "Enable all" / "Disable all" bulk actions
- Each state toggle: click to flip, confirmation modal: "Enable [State]? Patients in [State] will be able to sign up."
- Changes take effect immediately — no deployment needed

Firestore structure:

```
json
{
  "servedStates": ["FL", "TX", "NY", "CA"],
  "updatedAt": "timestamp",
  "updatedBy": "admin_uid"
}
```

Stored at: `config/served_states`

Read by: pre-screen step (state validation), shipping address step, patient settings (address change).

Screen 8 — Configuration: Promotions

Coupon code management:

Field	Detail
Code	Admin-defined string (e.g. NAD139, WELCOME50)
Discount type	Fixed amount (\$) or percentage (%)
Discount value	Number
Applies to	All products / specific product codes (multi-select)
Valid from / until	Date range (optional — leave blank for no expiry)
Max uses	Number (optional — leave blank for unlimited)
Uses so far	Read-only counter
Active	Toggle

How it works:

- Patient enters code at payment step → Stripe validates via Stripe Coupon API
- Stripe applies the discount to the charge
- Coupon code stored in Stripe — admin creates it in Nutree admin, Nutree creates it in Stripe automatically
- Nutree stores a mirror in Firestore `config/promotions` for display and reporting

Firestore structure:

json

```
{
  "code": "NAD139",
  "stripeCouponId": "coup_xxx",
  "discountType": "fixed",
  "discountValue": 60,
  "appliesTo": ["NTC-007"],
  "validFrom": "timestamp",
  "validUntil": null,
  "maxUses": null,
  "usesCount": 14,
  "active": true,
  "createdBy": "admin_uid",
  "createdAt": "timestamp"
}
```

Screen 9 — Finance: Partial Refund Calculator

Shown when: Admin clicks a refund flag from the dashboard, or navigates to Finance → Refunds.

Refund list:

- All pending partial refunds (6-month and 12-month plan prescription refusals)
- Columns: patient code, product, plan, paid, weeks fulfilled, calculated refund, date of refusal

Refund detail (clicking a row):

Field	Value
Patient code	Anonymised UID
Product code	NTC-00X
Plan	e.g. "6-month (24 weeks)"
Price paid	<code>pricePaid</code> at order time
Standard monthly price at order	<code>standardMonthlyPriceAtOrder</code>
Weeks fulfilled	<code>weeksPrescribed_phi</code>
Consumed cost	$\text{weeksPrescribed_phi} \times (\text{standardMonthlyPriceAtOrder} / 4)$
Refund amount	<code>pricePaid - consumed_cost</code>
Stripe payment ref	Link to charge in Stripe dashboard

Admin actions:

- "Process refund" → confirmation modal: "Process refund of \$[amount] to patient? This cannot be undone."
 - On confirm: Stripe refund API called for exact amount
 - Patient notified via Template 6 with `[refundAmount]` filled in
 - Record updated: `refundProcessed: true`, `refundAmount`, `refundProcessedAt`, `refundProcessedBy`
- "Dispute / do not refund" → opens free text reason field, logs to patient record, flags for legal review

Edge case: If `consumed_cost ≥ pricePaid` → refund shown as \$0. "Process refund" disabled. Admin sees: "No refund due — consumed cost equals or exceeds amount paid."

Screen 10 — Finance: Clinician Activity Export

Already specced in clinician platform (Screen 10 — My Activity Report).

Admin version adds:

- View all clinicians in one table (not just current user)
- Filter by clinician, date range, activity type

- Export CSV covering all clinicians or selected subset
 - CSV columns: date, clinician code (anonymised), event type, patient code (anonymised), action
-

Screen 11 — Audit Log

HIPAA requirement. All PHI access events logged and viewable by admin.

Log table columns:

Column	Detail
Timestamp	Date + time
User	UID + role (patient / clinician / admin)
Action	read / write / delete / login / logout
Resource	Collection + document path (e.g. <code>patients/uid123</code>)
IP address	If available
Outcome	success / denied

Filters: date range, user, action type, resource type **Export:** CSV for compliance reporting

Retention: Logs retained for minimum 6 years (HIPAA requirement — confirm with lawyer)

Firestore structure:

```
json
{
  "eventId": "string",
  "timestamp": "timestamp",
  "userId": "uid",
  "userRole": "clinician",
  "action": "read",
  "resource": "patients/uid123/prescriptions/rx456",
  "ipAddress": "string | null",
  "outcome": "success"
}
```

Stored at: `audit_log/{eventId}` — write-only for all roles except admin read.

Admin Platform — Firestore Collections

Collection	Admin access	Notes
<code>config/pricing</code>	Read + write	Product plans and prices
<code>config/served_states</code>	Read + write	Which states are active
<code>config/promotions</code>	Read + write	Coupon codes
<code>config/flows</code>	Read + write	Onboarding flow definitions
<code>config/forms</code>	Read + write	Intake and check-in form definitions
<code>config/pricing_history</code>	Read only	Audit trail of price changes
<code>patients/{uid}</code>	Read + write	All patients
<code>clinicians/{uid}</code>	Read + write	All clinicians
<code>audit_log/{eventId}</code>	Read only	PHI access log
<code>flags/{flagId}</code>	Read + write	Flags needing admin attention

7. Integrations

Integration	Purpose	Status
Firebase Auth	Patient (email+password + Google SSO), Clinician + Admin (Google SSO + 2FA only). RBAC via custom claims.	Decided
Firestore	All PHI storage	Decided
Google Cloud Storage	Files: ID uploads, signed PDFs	Decided
Firebase Cloud Functions	Backend automation	Decided
Google Calendar API	Practitioner availability + booking	Decided
Stripe	Payments, subscriptions, pause/cancel	Decided

Integration	Purpose	Status
LifeFile API (via Keragon)	Rx send + shipment status updates	Accessed via Keragon middleware — Nutree never connects to LifeFile directly
Fullscript	Lab ordering (Quest Diagnostics + at-home kits) + supplement recommendations	Phase 2. REST API + OAuth. BAA available. Contact api@fullscript.com for access.
Keragon	HIPAA-compliant middleware between Nutree and LifeFile	✅ BAA signed. SOC2 Type II, AES-256, 7-day data retention. Nutree sends prescription data to Keragon via webhook; Keragon forwards to LifeFile API and returns response.
DocuSeal	E-signature, embedded, free tier	Decided
SendGrid	Transactional email	Decided
Anthropic Claude API	AI chat widget	Already built

7b. Authentication & Session Management

Status:✅ Fully specced
Implementation: Firebase Auth — handles all three user types with role-based access

Three User Types & Auth Methods

User type	Login method	2FA	Auto-logout
Patient	Email + password OR Google SSO	Not required	30 min inactivity
Clinician	Google SSO only	Required (enforced)	8 hours inactivity
Admin	Google SSO only	Required (enforced)	8 hours inactivity

Patient Authentication

Sign-up (onboarding Step 2):

- Email + password (min 8 chars, 1 number, 1 special char)
- Password confirmation field

- After onboarding completes, patient can link a Google account from account settings

Login (returning patient):

- Email + password
- OR Google SSO — if Google account matches the email used at sign-up, accounts are linked automatically via Firebase Auth
- "Forgot password" → Firebase sends reset email to registered address
- Failed login: 5 attempts → 15-minute logout, patient notified by email

Session:

- Firebase Auth JWT token, auto-refreshed while active
- Auto-logout after 30 minutes of inactivity
- Patient sees: "You've been logged out for security. Please log in again."
- Session persists across browser tabs (same device)
- No concurrent session limit for patients

HIPAA note: 30-minute auto-logout is the HHS recommended timeout for patient-facing health portals. Not legally mandated but strongly recommended and protects Nutree if a patient leaves their app open on a shared device.

Clinician Authentication

Login:

- Google SSO only — no email/password option shown
- Must use a Google account that has been pre-registered by admin (see Clinician Management in Section 6.4)
- 2FA enforced at the Google account level — clinician must have 2FA enabled on their Google account before admin can activate them in Nutree
- If 2FA not enabled on Google account → login blocked with message: "Your Google account requires 2-step verification to access Nutree Clinic. Please enable it at myaccount.google.com."

How 2FA works:

- Firebase Auth + Google SSO delegates 2FA entirely to Google
- Nutree does not manage 2FA codes — Google handles it
- Clinician uses their existing Google Authenticator / SMS / hardware key — whatever they have set up on their Google account

- No Nutree-specific 2FA setup needed

Session:

- Auto-logout after 8 hours of inactivity (full shift)
- Clinician sees warning at 7h50m: "Your session expires in 10 minutes. Click to stay logged in."
- On logout: any unsaved charting note is preserved as a draft in Firestore
- No concurrent sessions — if clinician logs in on a second device, first session is invalidated
- Firebase Auth custom claims store the `role: clinician` and `clinicianId`

Firestore document: `clinicians/{uid}`

```
json
{
  "uid": "firebase_uid",
  "email_phi": "clinician@gmail.com",
  "firstName_phi": "string",
  "lastName_phi": "string",
  "phone_phi": "string",
  "role": "clinician",

  "npi_phi": "string (10-digit NPI – required for every LifeFile order)",
  "dea_phi": "string (DEA number – required for controlled substance orders, format",
  "stateLicenses_phi": [
    { "state": "FL", "licenseNumber_phi": "string" },
    { "state": "TX", "licenseNumber_phi": "string" }
  ],

  "address_phi": "string",
  "city_phi": "string",
  "state_phi": "string (primary practice state)",
  "zip_phi": "string",

  "active": true,
  "googleSsoVerified": true,
  "twoFaVerified": true,
  "addedBy": "admin_uid",
  "addedAt": "timestamp",
  "lastLoginAt": "timestamp"
}
```

All fields required before clinician can send any prescription:

- `npi_phi` — mandatory for all LifeFile orders

- `dea_phi` — mandatory for controlled substance orders (confirm which products with LifeFile)
- `stateLicenses_phi` — at least one state + license number; must match patient's shipping state
- `address_phi`, `city_phi`, `state_phi`, `zip_phi` — required in LifeFile prescriber block
- `googleSsoVerified` + `twoFaVerified` — must both be true before clinician can log in

Admin enters all fields in the Clinician Management screen (Section 6.7 Screen 3). The app blocks prescription send if `npi_phi` is null or if no matching state license exists for the patient's state.

Admin activates a clinician:

1. Admin adds clinician's Google email in Clinician Management screen
2. System checks Google account has 2FA enabled via Google Admin SDK (or manual verification)
3. Admin sets `active: true` and assigns state licenses
4. Firebase Auth custom claim `role: clinician` assigned
5. Clinician can now log in — they will be prompted for Google 2FA automatically

Admin Authentication

Same as clinician — Google SSO + 2FA enforced.

Firestore document: `admins/{uid}`

```
json
{
  "uid": "firebase_uid",
  "email_phi": "admin@nutreeclinic.com",
  "firstName_phi": "string",
  "role": "admin",
  "active": true,
  "addedAt": "timestamp",
  "lastLoginAt": "timestamp"
}
```

Firebase Auth custom claim: `role: admin`

Admin has access to everything clinician can see, plus admin-only screens (pricing, flow builder, form builder, audit log, clinician management).

Role-Based Access Control (RBAC)

Firebase Auth custom claims control access. Checked server-side on every Firestore read/write via Security Rules — not just on the frontend.

Role	Firebase claim	Access
patient	role: patient	Own patient record only. No access to other patients or clinician data.
clinician	role: clinician	Assigned patients only. No admin screens. No pricing. No other clinicians' data.
admin	role: admin	All screens. All patients. All clinicians. Audit log.

Firestore Security Rules principle:

```
// Patient can only read/write their own document
allow read, write: if request.auth.uid == userId && request.auth.token.role == 'patient';

// Clinician can read assigned patients only
allow read: if request.auth.token.role == 'clinician'
    && resource.data.assignedClinicianId == request.auth.uid;

// Admin can read/write everything
allow read, write: if request.auth.token.role == 'admin';
```

Session Architecture — All Users

```
User logs in
  → Firebase Auth issues JWT with custom claims (role, uid)
  → JWT stored in browser (httpOnly cookie preferred over localStorage)
  → Every Firestore request includes JWT automatically
  → Firebase Security Rules validate role on every read/write
  → Inactivity timer runs client-side
  → On timeout → Firebase Auth signOut() called → redirect to login
```

Important: Session tokens are never stored in `localStorage` — use Firebase Auth's built-in session persistence (`browserSessionPersistence` for clinicians/admins, `browserLocalPersistence` for patients who chose "remember me").

Password Reset — Patients Only

- "Forgot password?" link on login screen
 - Patient enters email → Firebase sends reset link (via SendGrid template)
 - Reset link expires after 1 hour
 - On reset: all active sessions invalidated
 - Clinicians and admins have no password — Google account recovery handles this
-

Audit Log — Auth Events

All auth events written to Firestore `audit_log` collection (HIPAA requirement):

Event	Logged
Login success	uid, role, timestamp, IP (if available)
Login failure	email attempted, timestamp, failure reason
Logout	uid, role, timestamp, reason (manual / timeout)
Password reset requested	uid, timestamp
Session invalidated (concurrent login)	uid, timestamp
Role changed	uid, old role, new role, changed by, timestamp
Clinician activated / deactivated	clinician uid, by admin uid, timestamp

8. Onboarding Flow — Detailed Screen Specs

Last updated: session 1
Status:  Architecture locked. Step content TBD per flow configuration.

Flow Architecture — Flexible & Configurable

The onboarding flow is **not hardcoded**. It is driven by a flow configuration stored in Firestore, editable by admin without code deployment. This enables:

- Multiple flows running in parallel (A/B testing, product-specific flows)
- Easy reordering, enabling/disabling steps
- Future experimentation without developer involvement

Each flow consists of:

- A unique `flowId` and `flowName`
- An ordered list of `steps`
- Each step has a `stepType` (from a fixed set) and a list of `items` (configurable content)
- A flow is assigned to one or more products by admin

Flow assignment: Admin assigns a flow to each product individually. One product = one active flow at a time. Multiple flows can exist simultaneously for different products or for A/B testing.

Firestore structure:

```
json
{
  "flowId": "flow-glp1-v1",
  "flowName": "GLP-1 standard onboarding v1",
  "active": true,
  "steps": [
    { "stepId": "prescreen", "stepType": "prescreen", "order": 1, "items": ["state",
    { "stepId": "account", "stepType": "account_creation", "order": 2, "items": []
    { "stepId": "product", "stepType": "product_select", "order": 3, "items": [] }
    { "stepId": "address", "stepType": "shipping_address", "order": 4, "items": []
    { "stepId": "payment", "stepType": "payment", "order": 5, "items": [] },
    { "stepId": "intake", "stepType": "intake_form", "order": 6, "items": ["form-
    { "stepId": "id", "stepType": "id_upload", "order": 7, "items": [] },
    { "stepId": "consents", "stepType": "consents", "order": 8, "items": ["hipaa",
    { "stepId": "confirm", "stepType": "confirmation", "order": 9, "items": [] }
  ]
}
```

Product → flow assignment (Firestore `config/product_flows`):

```
json
{
  "NTC-001": "flow-glp1-v1",
  "NTC-002": "flow-glp1-v1",
  "NTC-006": "flow-sermorelin-v1",
  "NTC-007": "flow-nad-v1"
}
```

Available Step Types

These are the fixed set of step types the flow builder can use. New step types require a developer.

Configuring existing ones does not.

stepType	Description	Configurable items
prescreen	Eligibility gates before account creation	Which checks to include (see below)
account_creation	Name, email, password, phone, DOB	Fixed — not configurable
product_select	Product, form factor, plan length	Fixed — driven by product catalogue
shipping_address	Address + state validation	Fixed
payment	Stripe Payment Element	BNPL options enabled via Stripe dashboard
intake_form	Patient intake questions	Form assigned per product (built in admin form builder)
id_upload	Government ID upload	Fixed
consents	DocuSeal e-signature	Which documents to include
confirmation	Post-submission screen	Fixed

Pre-Screen Items — Configurable per Flow

The pre-screen step checks are individually toggleable. Each check is an item that can be added or removed from the step.

Item key	Shown when	Description
state	All flows	State must be in served states list
pregnancy	All flows	Not pregnant / breastfeeding
bmi	GLP-1 flows only	Height + weight → BMI routing (≥25 full GLP-1, 20-24.9 microdosing, <20 ineligible)
glp1_contraindication	GLP-1 flows only	MEN2/ Medullary thyroid cancer — patient or blood relative

DOB is collected at account creation (Step 2) — age 18-70 validation runs there. No separate age question in pre-screen.

Product Selection — Pre-Selection & Form Factor

When a patient arrives from a product page on the website, the product is pre-selected via URL param (e.g. `?product=NTC-001`). The product selection step still shows so the patient can:

1. **Confirm or change** the pre-selected product
 2. **Select the form factor** if multiple exist (e.g. NAD+ Injectable vs NAD+ Nasal Spray)
 3. **Select the plan** (duration + price, as configured in the pricing panel)
-

Payment — BNPL

Stripe Payment Element handles all payment methods in one integration:

- Credit / debit card
- Apple Pay / Google Pay
- HSA / FSA
- BNPL (Klarna, Afterpay, Affirm) — enabled/disabled per method in Stripe dashboard, no code change needed

No separate BNPL vendor integration required.

Intake Forms — One Per Product, Built in Admin

Each product has its own intake form built in the admin form builder. The intake form assigned to a product is stored in Firestore and rendered dynamically — no code deployment needed to change questions.

Form builder question types:

Type	Input	Example
<code>free_text</code>	Open text field	"Please describe your medical history"
<code>number</code>	Numeric input	"What is your current weight in lbs?"
<code>single_select</code>	Radio buttons	"Have you taken a GLP-1 before?"
<code>multi_select</code>	Checkboxes	"Select all conditions that apply"
<code>boolean</code>	Yes / No toggle	"Are you currently under medical care?"

Conditional logic: Each question can have show/hide rules based on previous answers (e.g. show free text detail field only if boolean = Yes). Rules stored as JSON in Firestore alongside the question.

Firestore structure for a form:

```
json
{
  "formId": "form-glp1",
  "productCode": "NTC-001",
  "formName": "GLP-1 intake",
  "questions": [
    {
      "questionId": "q1",
      "order": 1,
      "type": "single_select",
      "label_phi": "What sex were you assigned at birth?",
      "options": ["Male", "Female"],
      "required": true,
      "showIf": null
    },
    {
      "questionId": "q2",
      "order": 2,
      "type": "boolean",
      "label_phi": "Are you currently under medical care?",
      "required": true,
      "showIf": null
    },
    {
      "questionId": "q3",
      "order": 3,
      "type": "free_text",
      "label_phi": "Please detail your medical care",
      "required": true,
      "showIf": { "questionId": "q2", "value": true }
    }
  ],
  "updatedAt": "timestamp",
  "updatedBy": "admin_uid"
}
```

Answers stored as JSON in patient record:

```
json
```

```
{
  "intakeAnswers_phi": {
    "formId": "form-glp1",
    "completedAt": "timestamp",
    "answers": {
      "q1": "Female",
      "q2": true,
      "q3": "I take Levothyroxine for hypothyroidism"
    }
  }
}
```

Current Default Flow — GLP-1 (flow-glp1-v1)

Progress bar: Step X of 9

Step	Type	Pre-screen items / notes
1	prescreen	state, pregnancy, bmi, glp1_contraindication
2	account_creation	DOB validation: must be 18-70
3	product_select	Pre-selection from URL param. Form factor + plan selection.
4	shipping_address	State must match served states
5	payment	Stripe Payment Element. Card charged immediately. BNPL available.
6	intake_form	form-glp1 assigned
7	id_upload	—
8	consents	hipaa, telehealth, tos
9	confirmation	24hr review promise

Book-a-Consult Path (separate flow)

Separate entry point from website or app. Patient clicks "Book a consult" anywhere.

No intake form, no ID upload, no product selection.

Consult credited to first plan if patient subsequently purchases a treatment.

Admin Flow Builder — Screens Needed (Section 6.4)

Screen	Description
Flow list	All flows, active/inactive status, product assignments
Flow editor	Drag-and-drop step ordering, add/remove steps, configure items per step
Step configurator	Per step: toggle items on/off, set required/optional
Product → flow assignment	Assign a flow to each product
Form builder	Per product: build intake form with question types, conditional logic, ordering
Form preview	Preview the form as a patient would see it

Step 1 — Pre-Screen

Location: Patient app (app.nutreeclinic.com) — first screen patients see **Applies to:** All patients before account creation **No Firestore writes at this step**

Questions asked (in order):

1. **Age** — "How old are you?" (number input or year of birth)
 - < 18 → hard block: "You must be 18 or older to use Nutree Clinic"
 - 70 → hard block: "Please book a consultation — our clinical team will assess your suitability"
 - 18-70 → continue

2. **State** — "What state do you live in?" (dropdown)

- Served state → continue
- Unserved state → waitlist screen: "We're not in [State] yet — leave your email for early access"
- State list pulled from admin config (served states toggle)

3. **Pregnancy / breastfeeding** (shown to all)

- "Are you currently pregnant, trying to get pregnant, or breastfeeding?"
- Yes → hard block: "GLP-1 medications are not suitable during pregnancy or breastfeeding. Please consult your doctor."
- No → continue

4. **GLP-1 contraindication** (shown only if patient selected a weight loss / GLP-1 product, OR before product selection as a universal safety check)

- "Have you or a blood relative ever been diagnosed with Medullary Thyroid Cancer or MEN2 (Multiple Endocrine Neoplasia Syndrome Type 2)?"
- Yes → hard block: "Based on your answer, GLP-1 medications are not clinically appropriate for you. We recommend booking a consultation to explore other options."
→ CTA: Book \$50 consultation
- No → continue

On passing all pre-screen checks: → Show eligibility confirmation screen:

- Headline: "You most likely qualify"
 - Subtext: "Based on your answers, you appear to be a good candidate. A Nutree clinician will review your full intake and confirm."
 - CTA: "Get started"
-

Step 2 — Account Creation

Location: App

Fields:

- First name, Last name
- Email address + email verification (must match — conditional error shown if mismatch)
- Password (min 8 chars, 1 number, 1 special char)
- Phone number (US format)
- Date of birth (cross-check: must match age entered in pre-screen ± 1 year tolerance)

On submit:

- Firebase Auth creates account
- Firestore document created: `patients/{uid}` with `status: onboarding_in_progress`, `onboardingStep: 2`
- State from pre-screen written to Firestore
- SendGrid: welcome email sent with resume link

Firestore fields written:

```
json
{
  "firstName_phi": "string",
  "lastName_phi": "string",
  "email_phi": "string",
  "phone_phi": "string",
  "dateOfBirth_phi": "date",
  "state_phi": "string",
  "status": "onboarding_in_progress",
  "onboardingStep": 2,
  "createdAt": "timestamp"
}
```

Validation:

- Email must match email verification field exactly
 - DOB must confirm age 18–70 (re-validated server-side)
 - Duplicate email → "Account exists, sign in instead"
-

Step 3 — Product + Plan Selection

Location: App

What the patient sees:

- Treatment category tabs: Weight Loss / Longevity / Strength & Performance / Well-being
- Product cards: name, brief description, monthly price, per-week price
- Plan selector per product: monthly / 3-month (save 8%) / 6-month prepaid
- Consultation option always visible: "\$50 — speak to a clinician first"

BMI routing for weight loss products:

- BMI $\geq$ 25 (from pre-screen): all GLP-1 options shown

- BMI 20–24.9: microdosing only shown, others hidden
- BMI not captured (non-weight loss path): weight loss products not shown

Firestore fields written:

```
json
{
  "selectedProduct": "semaglutide",
  "productCode": "NTC-001",
  "planType": "monthly | 3month | 6month",
  "onboardingStep": 3
}
```

Step 4 — Shipping Address

Location: App

Fields: Street, Apt/Suite (optional), City, State (pre-filled from pre-screen, editable), ZIP

Validation:

- State must be in served states list — if changed to unserved state, inline error
- ZIP format check

Firestore fields written:

```
json
{
  "shippingAddress_phi": {
    "street_phi": "string",
    "apt_phi": "string",
    "city_phi": "string",
    "state_phi": "string",
    "zip_phi": "string"
  },
  "onboardingStep": 4
}
```

Step 5 — Payment

Location: App

What the patient sees:

- Order summary: product, plan, price breakdown, per-week price
- Stripe payment element: card, Apple Pay, Google Pay, HSA/FSA
- Promo code field
- Refund policy clearly stated: "If your intake is not approved by our clinician, you will receive a full refund within 24 hours."
- Charge notice: "Your card will be charged now. Your prescription will be sent once your clinician approves your intake."
- "Pay [amount]" button

Logic:

- Stripe charges immediately on submit
- Stripe product IDs are anonymised (no treatment names in Stripe — use product codes e.g. NTC-001)
- On payment success → proceed to intake form
- On payment failure → inline error, retry

Firestore fields written:

```
json
{
  "stripeCustomerId": "string",
  "stripePaymentIntentId": "string",
  "stripeSubscriptionId": "string (if subscription)",
  "productCode": "NTC-001",
  "planWeeks": 4,
  "planName": "6-month",
  "pricePaid": 1194,
  "standardMonthlyPriceAtOrder": 249,
  "paymentStatus": "paid",
  "paidAt": "timestamp",
  "onboardingStep": 5
}
```

Note: Stripe fields are not PHI — they are anonymous payment references. No `_phi` suffix. `pricePaid` (discounted plan price) and `standardMonthlyPriceAtOrder` (standard 4-week price at time of order) are both stored at order time. Together they enable the partial refund formula: $\text{refund} = \text{pricePaid} - (\text{weeksFulfilled} \times \text{standardMonthlyPriceAtOrder} / 4)$. Never read from current config — prices may change after the order was placed.

Step 6 — Intake Form

Location: App **Applies to:** All patients. Weight loss patients also complete the GLP-1 section. **All answers stored as a single JSON document in Firestore**

The intake is divided into named sections. Each section is a page or group of pages within Step 6.

Section A — General Health (all products)

A1. Sex assigned at birth *(required)*

- Radio: Male / Female

A2. Reproductive health *(shown only if A1 = Female)*

- "Are you...?" → Radio: Pregnant or trying to get pregnant / Breastfeeding / None of the above
- "Have you given birth in the past six months?" → Yes / No
- "What is the date of your last menstrual period?" → Date field (MM-DD-YYYY)

A3. Family / personal history — GLP-1 contraindications *(required — checkbox with myself / a relative columns)*

- Medullary thyroid cancer
- MEN 2 (Multiple endocrine neoplasia syndrome type-2)
- None of the above
- ⚠ Note: this is asked again in the intake as a clinical record even though it was asked in the pre-screen. Pre-screen answer is NOT stored as PHI — this intake answer is the official clinical record.

A4. Personal medical history *(required — checkboxes)*

- Pancreatitis / End stage kidney disease / Long QT syndrome / Gastroparesis / Severe liver disease/cirrhosis / Cancer / None of the above

A5. Family + personal history grid *(required — checkbox grid: myself / a relative)*

- Diabetes / Pre-Diabetes / Bowel disease / High blood pressure / High cholesterol / Fatty liver / Kidney disease / Liver disease / Heart disease / Stroke / PCOS / Sleep Apnea / Other chronic/autoimmune/severe disease / None of the above

A6. Current medical care *(required)*

- "Are you currently under Medical Care (including any condition you are managing with drugs)?" → Yes / No
- If Yes → SHOW: "Please detail your Medical Care" free text (e.g. "Yes I have Hypothyroidism and I take Levothyroxine")

A7. Surgeries and procedures *(required)*

- "Have you had any surgeries or medical procedures (including but not limited to Bariatric surgery)?" → Yes / No
- If Yes → SHOW: "Please list procedure, reason, and date below" free text

A8. Eating disorders *(required)*

- "Have you ever experienced an eating disorder such as: vomiting in order to lose weight, binge eating, or severely limiting your food intake for fear of gaining weight?" → Yes / No
- If Yes → SHOW: "Please explain briefly which eating disorders you experienced" free text

A9. Mental health *(required)*

- "Have you ever been diagnosed with a mental health condition?" → Yes / No
- If Yes → SHOW: "If you have you ever been diagnosed with a mental health condition, please explain" free text

A10. Safety screen *(required — shown after payment, triggers automated alert)*

- Title: "We have to ask..."
- "Do you currently have any desire to harm yourself or others?" → Yes / No
- If Yes →
 - SHOW safety card: "We care about your safety. If you're feeling at risk of harming yourself or others, Nutree Clinic can't provide care in this situation. Please seek immediate help: Call 911, or Call or text 988 (U.S. Suicide & Crisis Lifeline, 24/7)"
 - Patient cannot proceed past this screen
 - Firebase Cloud Function triggers: automated urgent alert written to `clinician_alerts/{uid}` in Firestore with `type: safety_flag`, patient account flagged
 - "Next" button disabled — only "I need help now" link shown
- If No → continue normally

A11. Substance use *(required — radio grid: Never / Monthly / Weekly / Daily)*

- Alcohol / Tobacco/Nicotine / Recreational substances (e.g. Cannabis, Stimulants)

A12. Exercise level *(required)*

- Radio: 1 - Sedentary / 2 - Light / 3 - Moderate / 4 - Active
-

Section B — Weight Loss / GLP-1 Specific (weight loss patients only)

Shown only if selected product is in weight loss category

B1. GLP-1 history (required)

- Info box: "GLP-1s medications can include compounded semaglutide, compounded tirzepatide, Ozempic, Wegovy, Mounjaro, and Zepbound."
- "Are you currently on or have you ever taken a GLP-1 medication?" → Radio:
 - I am currently taking a GLP-1 medication
 - I am a former user of GLP-1 medication
 - No, I have never taken a GLP-1 medication
- If current or former user → SHOW:
 - "When was your last GLP-1 dose?" Date field
 - "If you have taken GIP/GLP-1 medications before, please specify which ones and what was the outcome? (oral/injectable, which medication, highest dose...)" free text
- If never → HIDE: pages B2 (last dose/outcomes), B4 (prior side effects), B5 (muscle loss), B6 (medication transition)

B2. Reasons for stopping (shown only if current or former GLP-1 user)

- "Have you ever stopped a GLP-1 weight loss program before reaching your goal? If so, why?" → Multi-select checkboxes:
 - I wasn't seeing results fast enough / I couldn't stick with it / It became too expensive / I experienced nausea and/or vomiting / I experienced constipation and/or diarrhea / Life got in the way (stress, travel, family obligations) / No, I'm usually consistent / Other

B3. Previous weight loss programs (required for all weight loss patients)

- "Tell us which diets, other weight loss programs or medications (e.g. phentermine) you have previously tried." free text

B4. Prior GLP-1 side effects (shown only if current or former GLP-1 user)

- Info box: "By telling us about any side effects you've experienced, your provider can better personalize your treatment and help manage them going forward."
- "Have you experienced any of the following side effects from GLP-1?" → Multi-select:
 - Nausea / Vomiting / Diarrhea / Constipation / Bloating / Lack of energy / Abdominal pain / Fatigue / Dizziness / Headaches / Other

B5. Muscle loss (shown only if current or former GLP-1 user)

- Info box: "Because muscle loss is common with GLP-1, telling us about your experience may help us adjust your care to better support muscle preservation."
- "Have you experienced muscle loss while taking GLP-1?" → Yes / No

B6. Medication transition confirmation *(shown only if currently taking a GLP-1)*

- "If you're prescribed a GLP-1 medication by a Nutree Clinic provider, do you agree to stop taking your current weight loss medication?"
- Radio:
 - "Yes, I agree to stop taking my current weight loss medication and will inform the provider who prescribed me this before doing so" → continue
 - "No, I prefer to continue my current weight loss medication outside of the Nutree Clinic platform" → SHOW safety note, cannot proceed: "For your safety, we cannot prescribe or manage a GLP-1 medication if you are continuing another GLP-1 treatment outside of Nutree Clinic. Using multiple GLP-1 medications at the same time can increase the risk of side effects and is not medically appropriate."
 - ⚠ No refund issued in this scenario — patient committed to transition in Terms of Service before payment (see Legal Note 13.1)

B7. Injection comfort *(required)*

- Info box: "Most FDA-approved medical weight-loss treatments are administered by injection [...] most patients report that the experience is far more comfortable than expected."
- "I have physical or mental factors that would make injecting myself difficult, even with training." → Yes / No
- If No → HIDE oral medication preference page (B8)
- If Yes → SHOW B8

B8. Oral medication preference *(shown only if B7 = Yes)*

- Info box: "Hurray! FDA-approved ORAL GLP-1s are now available! These pills require morning fasting for at least 30 minutes [...] effectiveness depends on a strict routine."
 - "Would you be able to consistently follow a strict daily medication routine?" → Radio:
 - Yes — I can reliably take a medication every morning while fasting, with no food, drinks, medications, or supplements for at least 30 minutes
 - No — this would be impractical with my routine and/or medication schedule
 - I am not sure
-

Section C — Early Side Effect Preferences (weight loss patients only)

These screens are informational + preference capture for clinician. No hard blocks.

C1. Current GI symptoms

- Info box: "A Nutree Clinic licensed provider may be able to help you manage side effects with a personalized treatment plan."
- "Do you ever experience any of these gastrointestinal symptoms?" → Multi-select:
 - Nausea / Vomiting / Diarrhea / Constipation / Abdominal pain or cramping / Bloating or excessive gas / Acid reflux or heartburn / Difficulty swallowing / Loss of appetite

C2. Personalized dosing interest — GI (*shown if any GI symptoms selected in C1*)

- Info box: "Clinical research shows that gradual GLP-1 dose adjustments can help reduce side effects and improve adherence to treatment while maintaining results.*"
- "Would you be interested in your provider considering a personalized dosage plan that can help manage gastrointestinal side effects like nausea, vomiting, constipation, and diarrhea?" → Yes / No

C3. GI disruption severity (*shown if C2 shown*)

- "How disruptive would nausea, vomiting, constipation, and/or diarrhea be to your daily life?" → Very disruptive / Moderately disruptive / Not disruptive at all

C4. Fatigue personalized dosing interest (*shown if fatigue/energy loss selected in B4 or C1*)

- Info box: "Because fatigue can occur with GLP-1 treatment—especially after larger dose increases—personalized dosing may help improve tolerability."
- "Would you be interested in your provider considering a personalized dosage plan that can help manage side effects like fatigue and energy loss?" → Yes / No

C5. Fatigue disruption severity (*shown if C4 shown*)

- "How disruptive would fatigue and energy loss be to your daily life?" → Very disruptive / Moderately disruptive / Not disruptive at all

C6. Muscle health info screen (*shown if B5 = Yes, or always for weight loss patients — confirm*)

- Info box: "Supporting muscle mass helps protect strength, metabolism, and long-term health. Weight loss—especially when it happens quickly—can be associated with decrease in muscle mass [...] Adequate protein intake and resistance-based movement are commonly recommended."
- No question — informational only, Next button

- "Would you be interested in your provider considering a personalized dosage plan that can help manage side effects like muscle loss?" → Yes / No

C8. Muscle loss disruption severity (*shown if C7 shown*)

- "How disruptive would muscle loss be to your daily life?" → Very disruptive / Moderately disruptive / Not disruptive at all

Section D — Goals + Attribution (all products)

D1. Weight loss goals (*weight loss patients only*)

- "What are your weight loss goals (e.g. lose 50 lbs, drop by 3 sizes)?" free text (*required*)

D2. Other wellness goals (*all products*)

- "Are you interested in other wellness goals?" → Multi-select:
 - Retain lean muscle / Increase energy / Longevity / Improve Sleep / Personalized skincare / Hair regrowth / None of the above

D3. How did you hear about us (*all products — last question*)

- Title: "Last question!"
- Radio: Website / Ad / Referring Provider / Client Referral / Community / Other

Intake Conditional Logic — Complete Reference

Rule	Condition	Action
1	Sex = Female	SHOW: last menstrual period, given birth in past 6 months, pregnancy/breastfeeding
2	GLP-1 history = current or former user	SHOW: last dose date, prior medication outcomes
3	GLP-1 history = never	HIDE: pages 18, 20, 21, 22 (last dose, outcomes, prior side effects, muscle loss, medication transition)
4	Harm to self = Yes	SHOW: safety card, disable Next, trigger automated clinician alert
5	Harm to self = No	Continue normally

Rule	Condition	Action
6	Medication transition = "No, I prefer to continue"	SHOW: important safety note, block progress
7	Medication transition = "Yes, I agree to stop"	Continue normally
8	Injection difficulty = No	HIDE: oral medication page
9	Eating disorder = Yes	SHOW: free text explanation
10	Medical care = Yes	SHOW: detail free text
11	Surgeries = Yes	SHOW: list procedure/reason/date
12	Mental health = Yes	SHOW: explain free text
13	Weight or height empty	HIDE: BMI display
14	Email $\neq$ email verification	SHOW: mismatch error, HIDE page break
15	Any GI symptoms selected	SHOW: personalized dosing interest + severity question
16	Fatigue/energy selected	SHOW: fatigue dosing interest + severity
17	Muscle loss = Yes (prior GLP-1)	SHOW: muscle health info card + dosing interest + severity

Step 7 — ID Upload

Location: App

- Upload government-issued ID (driver's license or passport)
- Accepted: JPG, PNG, PDF — max 10MB
- Stored in Google Cloud Storage: `gs://nutree-ids/{uid}/id-{timestamp}.jpg`
- Firestore stores path reference only

Firestore fields written:

```
json
```

```
{
  "idUpload_phi": {
    "storagePath": "nutree-ids/{uid}/id-{timestamp}.jpg",
    "uploadedAt": "timestamp",
    "verified": false
  },
  "onboardingStep": 7
}
```

Step 8 — Consents + E-Signature

Location: App

Three DocuSeal documents signed sequentially:

1. HIPAA Authorization
2. Telehealth Informed Consent
3. Terms of Service

All signed PDFs stored in Google Cloud Storage: `gs://nutree-consents/{uid}/`

On completion → patient status changes to `pending_review`, clinician queue updated, SendGrid confirmation email sent.

Firestore fields written:

```
json
{
  "consents_phi": {
    "hipaaAuth": { "signed": true, "signedAt": "timestamp", "storagePath": "string"
    "telehealthConsent": { "signed": true, "signedAt": "timestamp", "storagePath": "
    "termsOfService": { "signed": true, "signedAt": "timestamp", "storagePath": "str
  },
  "status": "pending_review",
  "submittedAt": "timestamp",
  "onboardingStep": 8
}
```

Step 9 — Post-Intake Confirmation (*not counted in progress bar*)

What the patient sees:

- "You're all set — your clinician is reviewing your intake"

- "You'll hear from us within 24 hours"
 - Status tracker (read-only):
 -  Intake submitted
 -  Clinician review
 - ○ Approved + prescription sent
 - ○ Shipped
 - ○ Delivered
 - "Go to your dashboard" button
-

Onboarding Resume Logic

- Patient logs in → app reads `onboardingStep` from Firestore → redirects to last incomplete step
- All previously entered data pre-filled
- Payment step: if PaymentIntent already exists and is paid, skip payment screen

Patient Status Values

Value	Meaning
<code>onboarding_in_progress</code>	Signed up, not yet submitted intake
<code>pending_review</code>	Intake submitted, awaiting clinician
<code>approved</code>	Clinician approved, Rx being sent
<code>rejected</code>	Clinician rejected, refund triggered
<code>active</code>	Rx sent, patient in active care
<code>waitlisted</code>	State not served
<code>safety_flagged</code>	Harm to self/others answer = Yes

Refund Flow (on clinician rejection)

- Clinician marks intake as rejected in clinician platform
- Firebase Cloud Function triggers Stripe refund via API
- SendGrid email sent to patient: "We were unable to approve your intake. A full refund has been issued and will appear within 5-7 business days."
- Patient account status → `rejected`

- Patient offered: "Book a \$50 consultation to discuss your options"
-

9. Clinical Workflows

9.1 Refill SOP

Status:  Fully specced

Affects: clinician platform (refill queue), patient app (refill status tracker, reminders),
Firebase Cloud Functions (automation), Stripe (payment cycle), LifeFile API (Rx dispatch)

Core Concepts

Payment cycle and **refill cycle** are separate but anchored to the same origin date.

- **Payment cycle** — repeats every plan_length_days from first payment date. Stripe handles this automatically.
- **Refill cycle** — repeats every $\text{prescribed_supply_weeks} \times 7$ days from first Rx sent date. Driven by what the clinician actually prescribed, not a hardcoded interval.
- The clinician inputs supply duration in weeks when sending each prescription. This drives the next refill due date.

Refill due date formula:

```
next_refill_due = last_rx_sent_date + (prescribed_weeks × 7)
reminder_date   = next_refill_due - 10
```

Receipt lag: Pharmacy dispatch takes ~5 days. The refill reminder fires 10 days before end of supply — giving a real ~5-day buffer after pharmacy processes the next Rx.

Clinician Prescription Input (required fields per Rx)

When the clinician sends a prescription via the LifeFile API, they must input:

Field	Firestore field	Description
<code>medication</code>	<code>medicationId</code>	Product level selected (e.g. SEMA-L1) — not PHI, references medications catalogue
<code>dose</code>	<code>dose_phi</code>	Exact dose amount and unit (e.g. 0.35mg) — PHI
<code>volume</code>	<code>volume_phi</code>	Calculated mL from dose (e.g. 0.7mL) — PHI
<code>supplyWeeks</code>	<code>supplyWeeks_phi</code>	Weeks this supply covers — drives next refill due date — PHI
<code>titrationNotes</code>	<code>titrationNotes_phi</code>	Optional free text — PHI
<code>refillApproved</code>	<code>refillApproved</code>	Boolean — not PHI

`supplyWeeks` is the clinician's direct input. If left blank, system defaults to plan's standard supply (4 weeks for monthly, 12 weeks for 3-month+). Max value: 12 weeks.

Refill Rules by Plan Type

5-week / 10-week (Microdosing)

Event	Action
After intake approved	Clinician sends Rx for full plan duration (5 or 10 weeks)
Day $(\text{supply_weeks} \times 7) - 10$	Reminder: "Your supply is ending soon"
End of supply	No auto-renewal. Patient must purchase a new plan.
Check-in required	No — single fulfillment, no refill cycle

1-month (Auto-renewing subscription)

Payment cycle: every 28 days from first payment date (Stripe). Refill cycle: every $\text{supplyWeeks} \times 7$ days from first Rx sent date.

If check-in not completed by renewal date:

- Stripe charges on schedule (no payment delay)
- Rx held — not sent to pharmacy until check-in submitted and clinician approves
- Patient app shows: "Your check-in is required before your next supply can be sent"
- No refund issued — patient was warned 10 days prior
- Must appear in Terms of Service (Appendix A item 3)

3-month prepaid

Payment cycle: single payment. No auto-renewal. Refill cycle: clinician sets supplyWeeks per Rx. Every refill requires check-in + clinician approval for GLP-1.

Event	Action
After intake approved	Clinician sends first Rx — supplyWeeks set by clinician, max 12
Day $\frac{(\text{supplyWeeks} \times 7) - 10}{10}$	Reminder sent every refill cycle
Every refill	Patient submits check-in → clinician reviews → approves → Rx sent
Day 74 (10 days before Day 84)	Final reminder: "Your 3-month plan ends in 10 days"
Day 84	No charge. Patient must purchase next plan.
If check-in not done	No Rx sent. No refund on elapsed plan. Patient can complete late — supply delayed.

6-month prepaid

Payment cycle: single payment. No auto-renewal.
Refill cycle: clinician drives. Max 12 weeks per Rx. Default first fulfillment: 12 weeks.

Event	Action
After intake approved	Clinician sends first Rx. Default: <code>supplyWeeks = 12</code> . Clinician can set lower.
Day $\frac{(\text{supplyWeeks} \times 7) - 10}{10}$	Reminder every refill cycle
Every refill	Check-in submitted → clinician reviews → approves → Rx sent
Day 158 (10 days before Day 168)	Final reminder: "Your 6-month plan ends in 10 days"
Day 168	No charge. Patient must purchase next plan.
If check-in not done	Rx held. No refund. Patient can complete late — supply delayed.

Total refills within a 6-month plan depends on clinician's `supplyWeeks`:

- 12-week supplies → 2 fulfillments
- 4-week supplies → up to 6 fulfillments

12-month prepaid

Same logic as 6-month, across Day 0–336. Max 4×12 -week fulfillments.
Check-in required before every refill. Clinician approves every refill.

Reminder Schedule — All Plans

Trigger	Channel	Message
<code>refill_due - 10</code>	Email + push	"Your refill is coming up. [If check-in required: Complete your check-in to avoid delays.]"
<code>refill_due - 3</code> (check-in required only)	SMS + email	"Your check-in is due in 3 days. Missing it will delay your next supply."
<code>refill_due</code> (check-in still not done)	Email + push	"Your check-in is overdue. Supply held until completed."
Holiday mode (admin toggle)	All channels	All windows extended +7 days. Message includes shipping delay warning.

Clinician Refill Queue

When check-in submitted and approval required, task appears in clinician queue showing:

- Patient name + product code
- Check-in answers (weight, side effects, flags)
- Days until supply runs out (urgency indicator — red if < 5 days)
- Action buttons: Approve Refill / Request More Info / Flag for Review

Clinician action window: 24 hours. If no action after 24h → automated reminder to clinician. If no action after 48h → escalation alert to admin.

Summary Rules Table

9.2 Medication Database & Dosing Protocols

Status:  Fully specced from Nutree_Protocols_and_Pharmacies.xlsx
Serves two purposes: (1) clinician prescription UI, (2) LifeFile API order data

Architecture

The medication database lives in Firestore as a `medications` collection — read-only from the app, admin-editable only. It is separate from `pricing.config.ts` (billing) and from the patient record (what was prescribed).

```
medications/{medicationId} → product, level, pharmacy, vialSpec, doseRange,
concentration
pricing.config.ts           → what patient is charged (NTC-001 etc.)
patients/{uid}/prescriptions/{rxId} → medicationId, exact dose in mg, exact
volume in mL, supplyWeeks
```

When the clinician prescribes, they select a `medicationId`. The app looks up the pharmacy and vial spec and passes it to LifeFile. Stripe billing is driven by the patient's plan in

`pricing.config.ts`), not by the specific level selected.

Standard Protocol Rules

Levels are the protocol. Each level corresponds to a specific vial/concentration from a specific pharmacy. The clinician selects the level, then inputs the exact dose in mg within that level's range. The app calculates mL automatically.

Rule	Detail
Level progression	Levels are sequential — a patient cannot skip a level (e.g. cannot go Level 1 → Level 3)
Dose within level	Clinician inputs exact mg within the level's range — full precision (e.g. 0.35mg, not just "up to 0.5mg")
mL auto-calculation	App calculates <code>mL = desired_mg / concentration</code> in real time as clinician types
Level change	Clinician selects new level when ready — no app suggestion, no automation, clinical judgment only
No level skip	App enforces: next level must be current level + 1. Override requires admin role.
Dose personalisation	Every patient has their own dose history. The level range is a guide; the exact mg is always the clinician's decision.
Protocol display	Clinician sees the full level table as reference when prescribing — no suggestion of "next level"
Dose history	Every Rx sent is logged to the patient chart with: level, exact mg, mL, date, clinician ID

Semaglutide — Compounded

Compounded plans: \$249/month (4 weeks) | Microdosing: \$350/10 weeks (Emerald, BMI 20-24.9 only)

Level	Plan	Pharmacy	Vial spec	Dose (mg/wk)	Dose (mL/wk)	Concentration
Microdosing	10 weeks	Emerald	2 × 1mg (1mL)	0.2mg	0.2mL	1mg/mL
Level 1	4 weeks	Casa Pharma	1 × 1mg (2mL)	up to 0.25mg	up to 0.5mL	0.5mg/mL
Level 2	4 weeks	Casa Pharma	1 × 2mg (2mL)	up to 0.5mg	up to 0.5mL	1mg/mL
Level 3	4 weeks	Casa Pharma	1 × 4mg (2mL)	up to 1mg	up to 0.5mL	2mg/mL
Level 4	4 weeks	Rush	1 × 7.5mg (3mL)	1.5-1.875mg	0.6-0.75mL	2.5mg/mL
Level 5	4 weeks	Rush	1 × 10mg (4mL)	up to 2.5mg	up to 1mL	2.5mg/mL

Dose calculator: $\text{mL} = \text{desired_mg} / \text{concentration}$

Tirzepatide — Compounded

Compounded plans: \$349/month (4 weeks) | Microdosing: \$450/10 weeks (Emerald, BMI 20-24.9 only) Product code: NTC-002 (standard) | NTC-003b (microdosing)

Level	Plan	Pharmacy	Vial spec	Dose (mg/wk)	Dose (mL/wk)	Concentration
Microdosing	10 weeks	Emerald	2 × 10mg (1mL)	2mg	0.2mL	10mg/mL
Level 1	4 weeks	Rush	1 × 8mg (1mL)	2mg	0.25mL	8mg/mL
Level 2	4 weeks	Rush	1 × 12.5mg (1mL)	up to 3.125mg	up to 0.25mL	12.5mg/mL
Level 3	4 weeks	Rush	1 × 25mg (2mL)	up to 6.25mg	up to 0.5mL	12.5mg/mL
Level 4	4 weeks	Rush	1 × 37.5mg (3mL)	up to 9.375mg	up to 0.75mL	12.5mg/mL
Level 5	4 weeks	Rush	1 × 50mg (4mL)	up to 12.5mg	up to 1mL	12.5mg/mL

Dose calculator:

mL =
desired_mg /
concentration

NAD+ Therapy — Injections (Rush Pharmacy)

Plan	Length	Vial spec	Price
Athletic / Injury Recovery	6 weeks	2 × 1000mg (10mL)	\$229
Wellness / Longevity	4 weeks	1 × 1000mg (10mL)	\$199 (\$139 special)
Patches — Loading	TBD	TBD	TBD
Patches — Maintenance	TBD	TBD	TBD

Athletic / Injury Recovery protocol:

Week	Dose	Volume
Week 1	25mg → 50mg → 75mg (ramp up)	0.25 → 0.5 → 0.75mL
Weeks 2–5	100mg × 4 days	1mL × 4
Week 6	80mg × 3 days	0.8mL × 3

Wellness / Longevity protocol:

Week	Dose	Volume
Week 1	25mg → 50mg → 75mg (ramp up)	0.25 → 0.5 → 0.75mL
Weeks 2-4	80mg × 3 days	0.8mL × 3

Sermorelin — Injections (Emerald Pharmacy)

Administration: 5 days/week subcutaneous injection

Plan	Length	Vial spec	Dose	Price
Starter	10 weeks	1 × 3mg (3mL) + 2 × 9mg (9mL)	Titration — see below	\$399
1-month	4 weeks	1 × 9mg (9mL)	0.45mg × 5 days/wk	\$199 (\$175 special)
3-month	12 weeks	3 × 9mg (9mL)	0.45mg × 5 days/wk	\$475 (\$125 first mo, \$175 × 2)
Patches — Loading	TBD	TBD	TBD	TBD
Patches — Maintenance	TBD	TBD	TBD	TBD

Starter titration protocol:

Weeks	Dose	Volume
Weeks 1-2	0.3mg × 5 days/wk	0.3mL × 5
Weeks 3-10	0.45mg × 5 days/wk	0.45mL × 5

Pharmacy Reference

Pharmacy	Code	Products supplied
Casa Pharma	CASA	Semaglutide Levels 1-3
Rush Pharmacy	RUSH	Semaglutide Levels 4-5, all Tirzepatide levels, NAD+
Emerald Pharmacy	EMERALD	Semaglutide Microdosing, Tirzepatide Microdosing, Sermorelin

Firestore `medications` Document Shape

This collection is a **clinical reference catalogue** — like a drug formulary. It contains no patient data. No `_phi` suffix needed here. Fields describe the product, not a patient.

```
json
{
  "medicationId": "SEMA-L1",
  "product": "semaglutide",
  "productCode": "NTC-001",
  "levelNumber": 1,
  "levelLabel": "Level 1",
  "levelOrder": 1,
  "pharmacy": "Casa Pharma",
  "pharmacyCode": "CASA",
  "vialSpec": "1 x 1mg (2mL)",
  "vialMg": 1,
  "vialMl": 2,
  "concentrationMgPerMl": 0.5,
  "doseRangeMgMin": 0,
  "doseRangeMgMax": 0.25,
  "doseRangeMlMin": 0,
  "doseRangeMlMax": 0.5,
  "planLengthWeeks": 4,
  "administrationRoute": "subcutaneous_injection",
  "frequency": "weekly",
  "frequencyDaysPerWeek": null,
  "bmiRestriction": null,
  "canSkipTo": false,
  "active": true,
  "lfProductID": null
}
```

`lfProductID` is the internal LifeFile product ID for this medication level. Must be obtained from LifeFile and populated before any orders can be sent. Null = product not yet configured

for LifeFile ordering.

Key fields for protocol enforcement:

- `levelOrder` — integer used to enforce no-skip rule: next Rx must have `levelOrder = current + 1`
- `canSkipTo` — false for all levels by default; admin can set true to allow exception for a specific patient
- `concentrationMgPerMl` — the single value used by `calcVolume(mg, medicationId)` helper
- `frequencyDaysPerWeek` — null for weekly injections, 5 for Sermorelin (5 days/week)

`calcVolume()` helper (used in clinician platform + patient syringe SVG):

typescript

```
calcVolume(desiredMg: number, medicationId: string): number {  
  const med = medications[medicationId]  
  return desiredMg / med.concentrationMgPerMl  
}  
// e.g. calcVolume(0.35, "SEMA-L2") → 0.35 / 1 = 0.35mL
```

Clinician Prescription Screen — Medication Selector

1. Product pre-selected from patient's plan (e.g. Semaglutide)
2. Level dropdown — shows dose range and vial spec per level
3. Specific dose input — clinician enters exact mg within level's range
4. App auto-calculates mL in real time: `mL = desired_mg / concentration`
5. `supplyWeeks` input — defaults to plan standard, clinician can override
6. LifeFile order preview shown: "Ordering 1 × 1mg (2mL) from Casa Pharma for 4 weeks"
7. Confirm & Send → LifeFile API called

LifeFile API — Order Payload

Flow: Nutree Firebase Cloud Function → Keragon webhook → LifeFile (`POST /order`) **Auth with LifeFile:** BasicAuth credentials stored in Keragon (not in Nutree codebase) **BAA required:** Both Keragon BAA and LifeFile BAA must be signed before first order

⚠ LifeFile requires real patient PHI (name, DOB, gender, address). Nutree sends this to Keragon over HTTPS; Keragon forwards to LifeFile. PHI never stored in Stripe, Vercel, or any non-HIPAA system. Keragon retains data for maximum 7 days per their policy.

json

```
{
  "message": {
    "id": "{lifeFileMessageId}",
    "sentTime": "{ISO datetime}"
  },
  "order": {
    "general": { "referenceId": "{rxId}" },
    "prescriber": {
      "npi": "{clinician.npi_phi}",
      "lastName": "{clinician.lastName_phi}",
      "firstName": "{clinician.firstName_phi}",
      "licenseState": "{state of patient}",
      "licenseNumber": "{clinician license for that state}"
    },
    "patient": {
      "firstName": "{patient.firstName_phi}",
      "lastName": "{patient.lastName_phi}",
      "dateOfBirth": "{patient.dateOfBirth_phi - yyyy-mm-dd}",
      "gender": "{m | f | u - derived from intake sex_phi}",
      "address1": "{shippingAddress_phi.street}",
      "city": "{shippingAddress_phi.city}",
      "state": "{shippingAddress_phi.state}",
      "zip": "{shippingAddress_phi.zip}",
      "phoneMobile": "{patient.phone_phi}",
      "email": "{patient.email_phi}"
    },
    "shipping": {
      "recipientType": "patient",
      "recipientFirstName": "{patient.firstName_phi}",
      "recipientLastName": "{patient.lastName_phi}",
      "recipientPhone": "{patient.phone_phi}",
      "addressLine1": "{shippingAddress_phi.street}",
      "city": "{shippingAddress_phi.city}",
      "state": "{shippingAddress_phi.state}",
      "zipCode": "{shippingAddress_phi.zip}",
      "country": "US",
      "service": "{lifeFileShippingServiceCode - TBD}"
    },
    "billing": { "payorType": "pat" },
    "rxs": [{
      "rxType": "{new | refill}",
      "drugName": "{e.g. Semaglutide}",
      "drugStrength": "{dose_phi}mg / {concentrationMgPerMl}mg per mL",
      "drugForm": "injection",
      "lfProductID": "{medications.lfProductID - TBD from LifeFile}",
      "foreignRxNumber": "{rxId}",
```

```
    "quantity": "{volume_phi}",
    "quantityUnits": "mL",
    "directions": "Inject {volume_phi}mL subcutaneously once weekly",
    "daysSupply": "{supplyWeeks_phi × 7}",
    "dateWritten": "{sentAt - yyyy-mm-dd}"
  }
}
```

Credentials — stored in Keragon, not in Nutree:

- LifeFile BasicAuth username + password → stored in Keragon connector config
- X-Vendor-ID, X-Location-ID, X-API-Network-ID → stored in Keragon connector config
- Nutree only stores the Keragon webhook URL as an environment variable:

`KERAGON_LIFEFILe_WEBHOOK_URL`

Pending from LifeFile before integration can be built:

- `lfProductID` per medication level
- Shipping `service` codes
- Which products require `document.pdfBase64` (controlled substances)
- Webhook/callback URL for shipment status updates (no GET endpoint in current API spec)

Firestore `patients/{uid}/prescriptions/{rxId}` Document Shape

This document IS patient PHI — it records what was prescribed to a specific patient. All clinical fields use `_phi` suffix.

json

```
{
  "rxId": "string",
  "lifeFileMessageId": "string (unique per order – sent as message.id)",
  "lifeFileOrderId": "string (returned by LifeFile on success – store for status up",
  "medicationId": "SEMA-L1",
  "productCode": "NTC-001",
  "levelLabel": "Level 1",
  "pharmacy": "CASA",
  "dose_phi": "0.25mg",
  "volume_phi": "0.5mL",
  "supplyWeeks_phi": 4,
  "titrationNotes_phi": "string (optional)",
  "refillApproved": true,
  "sentAt": "timestamp",
  "sentBy_phi": "clinician_uid",
  "lifFileOrderId": "string",
  "status": "sent | dispensing | shipped | delivered"
}
```

Firestore `patients/{uid}` — Subscription Tracking Fields

These fields track clinical fulfillment linked to a patient's treatment. `_phi` applies.

```
json
{
  "weeksPaid_phi": 12,
  "weeksPrescribed_phi": 8,
  "weeksRemaining_phi": 4,
  "currentMedicationId_phi": "SEMA-L2",
  "currentLevelLabel_phi": "Level 2",
  "lastRxSentAt_phi": "timestamp",
  "nextRefillDue_phi": "timestamp",
  "nextCheckinDue_phi": "timestamp"
}
```

Patient App — Dosing View

Patient sees:

- Current level name and dose (e.g. "Level 2 — 0.5mg / 0.5mL per week")
- Administration route and frequency
- Next injection due date

- Interactive syringe SVG showing fill line at prescribed mL — calculated from `dose_phi / concentrationMgPerMl`. Injection products only.
- Full titration history — all past levels, doses, dates

Pending — Incomplete Specs

Item	Status
NAD+ Patches — Loading and Maintenance protocols	⚠ Spec pending
Sermorelin Patches — Loading and Maintenance protocols	⚠ Spec pending
Wegovy® dosing protocol	⚠ Spec pending
Mounjaro® / Zepbound® dosing protocol	⚠ Spec pending
Semaglutide Microdosing 5-week plan pricing	⚠ TBD
NAD+ \$139 special price	⚠ This is a promotional coupon — move to <code>promotions.config.ts</code> , not a permanent price in medication database
Sermorelin special price confirmation (\$175)	⚠ Confirm before launch

9.3 Side Effect Reporting

- Reported via chat message to clinician or via monthly check-in form
- Flagged in clinician queue with `type: side_effect_report`
- Logged to patient chart automatically
- Clinician responds within 24 hours (same SLA as intake review)

10. Business Rules

Subscriptions

- Full subscription, refill, and fulfillment rules are in Section 9.1 Refill SOP.

- Payments via Stripe. Plans priced in weeks (base = 4 weeks). Admin sets prices.
- Clinician controls supply via `supplyWeeks` input per prescription
- System tracks `weeksPaid` vs `weeksPrescribed` — flags over-prescription
- Pause: 1-4 weeks, reason required, clinician notified, Stripe billing paused
- Cancel: available anytime, no cancellation fee
- Missed check-in: payment taken on schedule, supply held until check-in complete
- No refund on missed check-in or medication transition refusal (see Appendix A)

Refund Calculation Rules

Scenario	Refund type	How calculated	Processed by
Clinician rejects intake	Full refund	Full amount paid	Automatic (Stripe)
Patient ineligible (safety flag, transition refusal)	No refund	—	—
Clinician refuses Rx — 1-month plan, no Rx sent	Full refund	Full month paid	Automatic (Stripe)
Clinician refuses Rx — 1-month plan, Rx already sent	No refund	Medication dispensed	—
Clinician refuses Rx — 3-month plan, no Rx sent	Full refund	Full 3-month paid	Automatic (Stripe)
Clinician refuses Rx — 3-month plan, Rx already sent	No refund	Medication dispensed	—
Clinician refuses Rx — 6-month or 12-month plan	Partial refund	$\frac{\text{pricePaid} - (\text{weeksPrescribed_phi} \times \text{standardMonthlyPriceAtOrder} / 4)}{}$	Manual — admin via Stripe dashboard

Partial refund formula (6-month and 12-month plans only):

```
consumed_cost = weeksPrescribed_phi × (standardMonthlyPriceAtOrder / 4)
refundAmount = pricePaid - consumed_cost
```

Example: patient paid \$1,000 for 6 months (24 weeks), standard monthly = \$250, 3 months (12 weeks) fulfilled:

```
consumed_cost = 12 × ($250 / 4) = 12 × $62.50 = $750
refundAmount = $1,000 - $750 = $250
```

Why consumed at standard monthly rate: The discount was a reward for committing to the full plan. If the patient cannot complete the plan (prescription refused by clinician), they lose the discount on what they already consumed — charged at standard monthly rate. They get back the remainder of what they paid. This is fair to the patient and protects Nutree from subsidising partial use at the discounted rate.

Edge case: If $\text{consumed_cost} > \text{pricePaid}$ (patient consumed more than they paid — possible only if standard rate $\times$ weeks $>$ discounted plan price, which should not happen in practice but must be handled): refund = \$0, no additional charge to patient.

Fields used:

- `pricePaid` — total amount charged at order time (stored on payment document)
- `standardMonthlyPriceAtOrder` — the standard 4-week price at time of order (stored on payment document — never read from current config as prices may change)
- `weeksPrescribed_phi` — weeks already fulfilled (from patient record)

All three values must be stored on the order at time of payment.

State Eligibility

- Patient must provide shipping address in a served state before payment
- Served states configured in admin panel (toggle on/off)
- Clinicians assigned to patients based on state licensure + load

Stripe / PHI Anonymisation

- Product names in Stripe must not contain PHI or treatment names
- Use anonymous product codes mapped internally to treatments

Consultations

- \$50 consultation — permanent, not a promotion
- Credited to first plan
- No call required unless patient requests or clinically necessary

- Book-a-consult flow: Google Calendar → payment → confirmed
-

11. Pending Decisions / Open Items

- ☐ LifeFile API integration spec (to be provided by Chloe)
 - ☐ Full intake form content — weight loss variant questions
 - ☐ Full check-in form content (every 4 weeks)
 - ☐ Confirm NAD+, Oxytocin, B12-MIC, Glutathione prices
 - ☐ Connect nutreeclinic.com domain to Vercel
 - ☐ Sign Google Cloud BAA before storing any PHI
 - ☐ Wire Google Calendar API for book-a-consult flow (no Calendly — confirmed Google Calendar)
 - ☐ Add Atara's new photo to website
 - ☐ Make GitHub repo private once stable
 - ☐ Add marketing pixels (Meta, Google Tag Manager)
 - ☐ HFA financing — pending Abby confirmation
 - ☐ Payroll system — founder only for now, revisit when team grows
 - ☐ Patient-to-clinician auto-assignment logic (P2)
 - ☐ Book-a-consult flow fully configured in admin flow builder
 - ☐ All product intake forms built in admin form builder (GLP-1 form content from screenshots captured in Section 8 — others TBD)
 - ☐ Flow builder and form builder admin screens built (Section 6.4)
 - ☐ Tirzepatide Microdosing full medication database entry (Section 9.2) — vial spec confirmed but protocol details TBD
 - ☐ NAD+ Nasal Spray — full spec (protocol, pharmacy, pricing, product code) TBD
 - ☐ Fullscript integration (Phase 2) — contact api@fullscript.com to register, sign BAA, decide if labs required vs optional at intake
-

12. Decisions Log

Date	Decision
------	----------

Session 1	App is separate from marketing website
-----------	--

Session 1	Payments via Stripe (not Square as originally noted)
-----------	--

Session 1	E-signature via DocuSeal (no Google equivalent)
-----------	---

Date	Decision
Session 1	File storage via Google Cloud Storage (IDs + signed PDFs)
Session 1	Side effect reporting via chat / check-in, not separate screen
Session 1	Check-in every 4 weeks; refill not mandatory if still on medication
Session 1	Post-intake review promise: within 24 hours
Session 1	3 partner pharmacies all use LifeFile API
Session 1	Payroll tracking only (CSV export) — no payroll system yet
Session 1	Patient-to-clinician assignment by state license + load (P2)
Session 1	Community forums, nutrition coaching, insurance billing — skipped
Session 1	BMI pre-screener on marketing website (weight loss only)
Session 1	Dosing schedule tracker + interactive syringe SVG in patient app
Session 1	Refill status tracker shows full cycle in patient app
Session 1	Clinician activity report exportable as CSV for payroll
Session 1	Account created after product selection (Step 3), not before
Session 1	Onboarding progress saved at every step — patient can resume
Session 1	Account creation collects: name, email, password, phone, DOB

Date	Decision
Session 1	Progress bar shown throughout: "Step X of 10"
Session 1	BMI routing: ≥ 25 = full GLP-1, 20-24.9 = microdosing, < 20 = ineligible
Session 1	BMI pre-screener on website — no Firestore write, calculation only
Session 1	Draft patient record created at Step 3 with status onboarding_in_progress
Session 1	All intake form answers stored as JSON in Firestore
Session 1	ID uploaded to Google Cloud Storage, path reference only in Firestore
Session 1	Three consent docs via DocuSeal: HIPAA auth, telehealth consent, ToS
Session 1	Patient status $\rightarrow$ pending_review after Step 10 submission
Session 1	Pre-screen is inside the app, not on the website — Step 1 of 9
Session 1	Progress bar: Step X of 9, starting from pre-screen
Session 1	Book-a-consult is a standalone path — age/pregnancy pre-screen $\rightarrow$ calendar $\rightarrow$ \$50 payment — no full intake
Session 1	Tirzepatide Microdosing confirmed product — NTC-003b, \$450/10 weeks, Emerald
Session 1	NAD+ Nasal Spray confirmed as separate product from NAD+ Injectable
Session 1	Pricing model simplified — admin sets prices directly, clinician controls supply in weeks
Session 1	Calendly replaced by Google Calendar API — confirmed

Date	Decision
Session 1	Onboarding flow is configurable in admin — flexible flow architecture
Session 1	Multiple flows can run in parallel — admin assigns flow to each product
Session 1	Pre-screen: state + pregnancy for all; BMI + GLP-1 contraindication for GLP-1 track only
Session 1	No age question in pre-screen — DOB at account creation covers age validation
Session 1	Product pre-selected from URL param — patient still selects form factor + plan
Session 1	BNPL via Stripe Payment Element — no separate vendor
Session 1	One intake form per product — built in admin form builder
Session 1	Form builder question types: free_text, number, single_select, multi_select, boolean
Session 1	Intake form answers stored as JSON in intakeAnswers_phi
Session 1	label_phi suffix on all question labels in form builder (questions are PHI)
Session 1	Patient login: email+password OR Google SSO, patient chooses
Session 1	Clinician login: Google SSO + 2FA only — no email/password option
Session 1	Admin login: same as clinician — Google SSO + 2FA
Session 1	2FA delegated entirely to Google — Nutree does not manage 2FA codes
Session 1	Patient session timeout: 30 minutes inactivity

Date	Decision
Session 1	Clinician/admin session timeout: 8 hours inactivity
Session 1	RBAC via Firebase custom claims — enforced server-side in Firestore Security Rules
Session 1	Auth events logged to audit_log collection (HIPAA requirement)
Session 1	No localStorage for session tokens — Firebase session persistence used
Session 1	Clinician queue: 4 tabs — Intakes / Check-ins / Messages / Flags
Session 1	Charting notes: structured fields + free text + smart predefined verbiage
Session 1	Clinician sees assigned patients only
Session 1	Patient chart: two-column layout, 8 tabs
Session 1	Prescription send: level dropdown, exact mg input, mL auto-calculated, no-level-skip enforced
Session 1	Activity report exportable as CSV for payroll
Session 1	Schedule driven by Google Calendar API — no separate availability UI
Session 1	Internal comments: all clinicians can see, append-only, not shown to patient
Session 1	Intake rejection is 3-step: flag → patient corrects → confirm reject
Session 1	Patient can edit any answer when intake is reopened for correction
Session 1	Previous intake answers archived in intakeAnswers_history_phi on resubmit

Date	Decision
Session 1	Prescription refusal is separate from intake rejection — triggers refund + cancellation
Session 1	All patient comms (email + SMS) contain no PHI — 8 templates defined
Session 1	Clinician sees confirmation popup before any refund-triggering action
Session 1	Patient dashboard: status tracker + 4 quick-access icons + context card
Session 1	Dashboard is journey-state aware — shows different content pre/post approval
Session 1	Weight logging: manual entry only at launch
Session 1	Subscription changes (pause, cancel, upgrade) all go through clinician messaging
Session 1	Patient app check-in form rendered from admin form builder — same as intake
Session 1	Internal clinician comments not shown to patient
Session 1	Patient message thread is single thread per patient-clinician pair
Session 1	Patient can delete manual weight entries but not check-in weights (clinical record)
Session 1	administrationRoute added to product level in Section 4, Section 5, and Firestore pricing config
Session 1	Routes: subcutaneous_injection, nasal_spray, patch, oral, TBD
Session 1	Syringe SVG shown only for subcutaneous_injection — all other routes show text instructions
Session 1	Admin ops dashboard: 4 metric cards (revenue, patients, Rx volume, flags) + flags panel + activity feed

Date	Decision
Session 1	Served states: single clinic-level toggle per state — not per product
Session 1	Promotions: coupon codes only (Stripe Coupon API) — no automatic discounts
Session 1	Form builder has live preview mode with conditional logic
Session 1	Audit log retained minimum 6 years (HIPAA)
Session 1	LifeFile requires real patient PHI (name, DOB, gender) — anonymised UID not sufficient
Session 1	LifeFile payload fully mapped to POST /order spec
Session 1	Clinician NPI and per-state license numbers required — added to clinician Firestore document
Session 1	IfProductID per medication level needed from LifeFile before integration can be built
Session 1	LifeFile has no GET tracking endpoint — status updates via webhook/callback (TBD with LifeFile)
Session 1	daysSupply = supplyWeeks_phi × 7 for LifeFile (API uses days not weeks)
Session 1	billing.payorType = pat (patient pays via Stripe)
Session 1	Keragon used as HIPAA middleware between Nutree and LifeFile — Nutree never connects to LifeFile directly
Session 1	LifeFile credentials stored in Keragon, not in Nutree codebase
Session 1	Clinician document requires: NPI, DEA (controlled substances), per-state license numbers, full address
Session 1	App blocks prescription send if clinician NPI is null or no matching state license for patient state

Date	Decision
Session 1	Keragon BAA signed — integration ready to build
Session 1	Fullscript lab ordering added as Phase 2 (Appendix B5) — addresses top PCP concern about telehealth GLP-1 platforms
Session 1	Treatment summary PDF (shareable with PCP) — added as Phase 2 future feature
Session 1	GLP-1 discontinuation / tapering pathway — noted as missing, to be specced before first patient reaches end of plan
Session 1	Injection site rotation tracker — noted as Phase 2 quick win
Session 1	Muscle preservation / body composition — noted as Phase 2, aligns with Sermorelin + NAD+ product lines
Session 1	shipping.recipientType = patient (direct to patient)
Session 1	Partial refund calculator in admin Finance section — manual confirmation before Stripe refund

Appendix A — Legal & Compliance Checklist

This appendix is for legal counsel and operations. It lists every clause, disclosure, and SOP that needs to be drafted, reviewed, or updated before launch. Grouped by document.

Status column: ☐ Not started /  In progress / ☒ Done

A1. Terms of Service

#	Item	Notes	Status
1	Medication transition commitment	GLP-1 patients commit to discontinuing current GLP-1 before payment. No refund if they refuse transition in intake. Summary must appear visibly above Pay button, not only in ToS.	☐
2	Intake-based rejection +	Clinician-initiated rejection = full automatic refund within 5–7 business days. Patient-initiated disqualifications	☐

#	Item	Notes	Status
	refund policy	(medication transition refusal, safety flag) = no refund.	
2a	Prescription refusal refund policy	If clinician refuses prescription after intake approval: partial or full refund depending on plan type and weeks already fulfilled. See refund calculation rules below (item 2b). Refund is manually processed by admin — not automatic.	☐
2b	Partial refund calculation rules for prepaid plans	Only applies to 6-month and 12-month plans. Formula: $\text{refund} = \text{pricePaid} - (\text{weeksPrescribed} \times \text{standardMonthlyPriceAtOrder} / 4)$. Consumed weeks are charged at standard monthly rate (discount forfeited on used supply). Example: paid \$1,000 for 6 months, standard monthly \$250, 3 months used $\rightarrow$ consumed = $3 \times \$250 = \$750 \rightarrow$ refund = $\$1,000 - \$750 = \$250$. Admin processes manually via Stripe dashboard.	☐
2c	Refund calculation — 1-month and 3-month plans	1-month plan: full refund of current month if no Rx sent. No refund if Rx already sent (medication in transit or delivered). 3-month plan: full refund if no Rx sent. No partial refund once any Rx sent — medication has been dispensed.	☐
2d	Prices at time of order	Both <code>pricePaid</code> (discounted plan price) and <code>standardMonthlyPriceAtOrder</code> (standard 4-week price) must be stored on the order record at time of payment — never read from current config (prices may change after order). These two fields together enable the partial refund calculation.	☐
2e	Manual refund process	All partial refunds for 6-month and 12-month plans are manually processed by admin via Stripe dashboard. Admin screen shows: weeks paid, weeks fulfilled, calculated refund amount, confirmation button. Admin confirms $\rightarrow$ Stripe refund initiated $\rightarrow$ patient notified via Template 5 or 6 with refund amount.	☐
3	Subscription auto-renewal disclosure	Monthly and prepaid plans auto-renew. Cancel anytime, no fee. Cancellation does not cancel orders already sent to pharmacy. Prepaid plans non-refundable after Rx sent to pharmacy. Florida auto-renewal law requires specific placement and timing of disclosure.	☐

#	Item	Notes	Status
3a	Missed check-in payment policy	Monthly subscribers: Stripe charges on renewal date even if check-in is not completed. Rx held until check-in done. No refund. Patient is warned 10 days prior. This must be clearly disclosed at plan purchase and in ToS.	☐
3b	Refill delay disclosure	Supply may be delayed if check-in is not completed on time or if clinician review takes up to 24 hours. Patient is responsible for completing check-in with sufficient lead time. Holiday delays may extend shipping.	☐
3c	Clinician discretion on supply amount	For multi-month plans, the clinician determines how many weeks of supply to send per fulfillment, up to a maximum of 12 weeks. The full plan amount is charged upfront but medication is dispensed at clinician's discretion.	☐
4	Pause policy	Pausing does not cancel subscription. Billing resumes at end of pause period.	☐
5	No guarantee of prescription	Prescription issued at sole discretion of licensed clinician. Payment does not guarantee a prescription will be issued.	☐
6	Compounded medication disclosure	Compounded semaglutide and tirzepatide are not FDA-approved. Prepared by state-licensed partner pharmacies. Results vary, no outcomes guaranteed.	☐
6a	Check-in delay / no-refund rules	If check-in not completed: payment still taken, medication held until check-in done, no refund. Applies to 1-month (every 3rd month), 6-month and 12-month plans (before each fulfillment). Must be explicit in ToS — patient agrees before payment.	☐
6b	Holiday season delay disclosure		
6c	Patient communication templates	8 templates drafted in Section 6.5. Lawyer to review all 8 for compliance — especially Template 5 (rejection) and Template 6 (prescription refusal). No PHI in any template — verify.	During holiday periods, medication delivery may be delayed. Nutree Clinic is not liable for pharmacy or shipping delays outside its control.

A2. Telehealth Informed Consent

#	Item	Notes	Status
7	Care model disclosure	Care is delivered primarily via asynchronous review of intake forms. Patients may also request a synchronous appointment (video or phone) with their clinician at any time. No call is required unless the patient requests one or the clinician determines it is clinically necessary.	☐
8	No in-person examination	Patients understand they are not receiving an in-person physical examination.	☐
9	Safety flag protocol	If a patient discloses desire to harm themselves or others, Nutree Clinic cannot provide care. Clinician is notified. Applicable state reporting obligations apply. No prescription issued.	☐
10	State-specific telehealth requirements	Florida and each additional served state may have specific informed consent requirements for telehealth. Lawyer to verify per state as new states are added.	☐
11	Prescription discretion	Clinician retains full clinical discretion to prescribe or decline to prescribe.	☐

A3. HIPAA Authorization

#	Item	Notes	Status
12	PHI collected	List all PHI categories: name, DOB, contact info, medical history, intake answers, prescriptions, metrics, ID document, signed consent PDFs.	☐
13	Who has access to PHI	Treating clinician, Nutree Clinic administrative staff, partner pharmacies via LifeFile API.	☐
14	Data retention period	PHI records retained minimum 6 years per HIPAA. Audit logs retained minimum 6 years. Florida medical records law may require longer — confirm with lawyer. After retention period: secure deletion process required.	☐
15	Patient rights	Right to access, amend, request restriction, request deletion of records. How to exercise these rights.	☐

#	Item	Notes	Status
16	Complaint process	How to file a HIPAA complaint with Nutree Clinic and with HHS Office for Civil Rights.	☐
17	Google Cloud BAA	Must be signed before any PHI is stored in Firestore or Google Cloud Storage. Blocks go-live.	☐

A4. Payment Screen Disclosures (shown inline at checkout, not in a separate doc)

#	Item	Notes	Status
18	Charge timing notice	"Your card will be charged now. Your prescription will be sent once your clinician approves your intake." Must be visible above Pay button.	☐
19	Refund policy summary	"If your clinician does not approve your intake, a full refund will be issued within 5-7 business days."	☐
20	Medication transition commitment summary	One-sentence summary of commitment visible above Pay button for GLP-1 products. Full language in ToS.	☐
21	HSA/FSA eligibility notice	Statement that HSA/FSA cards are accepted and that treatments may be eligible — patient responsible for confirming eligibility with their plan.	☐

A5. Standard Operating Procedures (SOPs) — Internal

#	SOP	Owner	Notes	Status
22	Clinician intake review SOP	Clinical	Steps for reviewing and approving/rejecting an intake. Time requirement: within 24 hours. What constitutes a rejection vs a request for more information.	☐
23	Refill SOP	Clinical + Ops	Fully spec'd in Section 9.1. Covers all plan types, check-in reminder schedule, fulfillment decision by clinician, delay rules, no-refund rules. Must be reviewed by lawyer and reflected in ToS.	☐

#	SOP	Owner	Notes	Status
23a	Holiday override SOP	Ops	Admin process for activating early reminder window during holiday season. Who activates it, how far in advance, which dates trigger it annually.	☐
24	Safety flag response SOP	Clinical	What happens when a patient answers Yes to the harm question. Clinician notification, response timeline, documentation requirements, state reporting obligations.	☐
25	Prescription rejection + refund SOP	Ops	Steps to reject an intake, trigger Stripe refund, notify patient via SendGrid. Timeline.	☐
26	Medication transition refusal SOP	Ops	Patient refuses transition in intake. No refund issued. What communication goes to the patient. How account is marked.	☐
27	Subscription pause + cancellation SOP	Ops	Steps to process a pause or cancellation request. Stripe actions. LifeFile actions if order in flight. Patient communications.	☐
28	State expansion SOP	Ops + Legal	Steps required before adding a new served state: clinician licensure verified, state-specific telehealth consent updated, admin toggle enabled.	☐
29	Clinician onboarding SOP	Ops	Steps to onboard a new clinician: credential verification, state license confirmation, Firebase Auth role assignment, calendar setup.	☐
30	HIPAA breach response SOP	Compliance	Steps if a data breach is suspected or confirmed. Notification requirements under HIPAA (60-day rule).	☐
31	Patient complaint handling SOP	Ops	Intake and escalation path for patient complaints. What goes to the clinician vs ops vs legal.	☐

A6. Pending Legal / Compliance Items (Blocking Go-Live)

#	Item	Status
32	Google Cloud BAA signed	☐
33	All three DocuSeal consent documents drafted and lawyer-	☐

#	Item	Status
	reviewed	
34	Terms of Service drafted and lawyer-reviewed	☐
35	Payment terms / refund policy drafted	☐
36	Florida telehealth compliance review completed	☐
37	LegitScript certification maintained / renewed	☐
38	LifeFile API BAA or data agreement in place	LifeFile receives patient PHI (name, DOB, gender, address) for every order. BAA is mandatory before first order.
38a	Keragon BAA signed	Keragon transmits PHI between Nutree and LifeFile. BAA required. Keragon signs BAA with all healthcare customers.
39	LifeFile lfProductID mapping	Get internal LifeFile product IDs for each medication level and populate medications catalogue
40	LifeFile shipping service codes	Get available shipping service codes from LifeFile and configure in admin
41	LifeFile controlled substance check	Confirm which products require document.pdfBase64 (scheduled/controlled substances)
42	LifeFile webhook / callback setup	Confirm mechanism for LifeFile to push shipment status updates to Nutree (no GET endpoint in current API spec)
43	LifeFile credentials provisioning	Obtain: BASE_URL, USERNAME, PASSWORD, VENDOR_ID, LOCATION_ID, NETWORK_ID at activation

This checklist should be reviewed with legal counsel before any patient data is collected or any payment is processed.

Appendix B — Future Features (AI-Powered)

These features are explicitly out of scope for Phase 1 and Phase 2.

They are logged here so they are not forgotten and can be scoped properly when ready.

All features below leverage the Anthropic Claude API already integrated in the app.

B1. AI Dose Suggestion (Clinician Platform)

What it does: When a clinician opens the prescription screen for a refill, the AI analyses the patient's dose history, weight trend, check-in answers, and reported side effects, then suggests the appropriate next dose and level with a brief rationale.

How it works:

- Claude API call with patient context (dose history, weight log, latest check-in, side effects)
- Returns: suggested `medicationId`, suggested `mg` dose, confidence note, rationale in plain English
- Clinician sees suggestion as a pre-filled recommendation — fully editable, never enforced
- Clinician can accept, modify, or ignore — their input is always final
- Suggestion and whether it was accepted/modified/ignored logged to patient chart for audit

Why deferred: Requires sufficient patient history data to be meaningful (minimum 2-3 refill cycles). Clinical validation of the suggestion logic needed before deploying. Liability review required.

Dependencies: Minimum 3 months of patient data in Firestore, Claude API system prompt to be written by Atara (clinical), legal review of AI-assisted clinical decision support.

B2. AI Personalised Meal Plans (Patient App)

What it does: Patient receives a weekly or monthly meal plan generated by Claude, personalised to their treatment, current dose level, reported side effects, wellness goals from intake, and dietary preferences.

How it works:

- Patient fills in a short meal preference form (dietary restrictions, cuisine preferences, cooking time available)
- Claude API call with: product type, current dose level, side effects (e.g. nausea → smaller meals, high protein focus), wellness goals from intake (retain muscle, longevity etc.)
- Returns: structured weekly meal plan with breakfast/lunch/dinner + snacks
- Patient can regenerate, save favourites, mark meals as completed
- Meal plan stored in Firestore per patient — not PHI, but linked to patient record

Why deferred: Content feature — high patient value but zero clinical risk. Can be added post-launch once core clinical workflows are stable. Requires meal plan prompt engineering and UI design.

Dependencies: Patient app built, Claude API wired (already done), meal preference form design, meal plan display UI.

B3. AI Check-in Analysis (Clinician Platform)

What it does: When a check-in is submitted, Claude analyses the answers and surfaces a brief summary for the clinician: key flags, weight trend direction, side effect pattern, and whether the current dose appears well-tolerated — before the clinician opens the full check-in.

How it works:

- Triggered automatically when check-in is submitted to Firestore
- Firebase Cloud Function calls Claude API with: check-in JSON, weight history, previous check-in answers, current dose
- Returns: 3-5 bullet summary shown at top of clinician's refill review screen
- Clinician still reads full check-in — the summary is a time-saving scan, not a replacement

Why deferred: Requires check-in system to be built and running with real data first. Prompt engineering needed with clinical input from Atara.

Dependencies: Check-in form built, clinician refill review screen built, minimum 1 check-in cycle of real data.

B4. AI Drug Interaction Checker

What it does: When the clinician enters a new prescription, Claude cross-checks the prescribed medication against the patient's current medications list (from intake) and flags any known interactions.

How it works:

- Triggered on clinician prescription screen when medication + dose are selected
- Claude API call or DrugBank / OpenFDA API call with: prescribed medication, patient's current medications from intake
- Returns: interaction flags (none / mild / moderate / severe) with plain-English explanation
- Shown as inline warning — does not block prescription, clinician decides

Why deferred: Requires integration with a drug database (DrugBank or OpenFDA) for accuracy — Claude alone is not sufficient for clinical drug interaction checking. Regulatory and liability review needed.

Dependencies: DrugBank or OpenFDA API integration, legal review of AI-assisted interaction checking, clinician prescription screen built.

B5. Fullscript Lab Ordering Integration (Phase 2)

What it does: Clinician orders baseline or follow-up lab tests directly from the Nutree patient chart. Patient receives a Quest Diagnostics booking link (walk in to any Quest location) or an at-home specialty kit. Results are returned to Nutree automatically and stored in the patient record. Clinician reviews results in Nutree without switching platforms.

What Fullscript is: Primarily a supplement dispensing platform (practitioners recommend professional supplements to patients). Lab ordering was added via their Rupa Health acquisition. Used by 100,000+ US practitioners. Integrates via REST API + OAuth.

Suggested baseline panel for GLP-1 patients:

- CMP (Comprehensive Metabolic Panel) — kidney/liver function, electrolytes, glucose
- HbA1c — blood sugar control over 3 months
- TSH (Thyroid Stimulating Hormone) — GLP-1 contraindication screening
- CBC (Complete Blood Count) — general health baseline
- Lipid panel (optional) — baseline before GLP-1 improves lipids
- Insulin / HOMA-IR (optional) — insulin resistance score

How it works (integration architecture):

1. Register Nutree as Fullscript integration partner — contact `api@fullscript.com`. Sign BAA.
2. Clinician connects Fullscript account to Nutree via OAuth — one-time setup per clinician in Nutree settings.
3. On patient approval, Nutree creates a mirrored patient record in Fullscript (`POST /clinic/patients`). Stores `fullscriptPatientId` in Firestore.
4. Clinician selects lab tests from a new Labs tab in Nutree patient chart → Nutree calls Fullscript API (create treatment plan with selected tests) → patient receives email/SMS from Fullscript with Quest booking link or kit.
5. Fullscript fires `lab_order.updated` webhook to Nutree when results ready → Firebase Cloud Function stores results in `patients/{uid}/lab_results_phi/` → clinician sees results in chart Labs tab → patient sees summary in patient app.

Patient payment: Patient pays Fullscript directly for labs (cash-pay only, no insurance). Quest blood draw fee = \$10 flat. Must be disclosed at point of recommendation. Separate from Nutree's Stripe payment.

Additional unlock — supplement recommendations: Clinician can also recommend supplements alongside prescriptions (protein powder, creatine, electrolytes for GLP-1 muscle preservation) → patient gets Fullscript order link. Fullscript offers practitioners a revenue share on supplement sales.

Why deferred to Phase 2: Core clinical workflow (prescriptions, check-ins) must be stable first. Lab ordering adds meaningful clinical credibility and directly addresses PCP concerns about telehealth GLP-1 platforms, but is not required for launch.

Pre-requisites:

- Email api@fullscript.com to register as integration partner
- Sign Fullscript BAA
- Clinician completes Fullscript labs registration (required before ordering — clinician-level step)
- Decide whether labs are required, recommended, or optional for intake approval
- Decide which lab panel is the Nutree standard recommendation

All features in this appendix use the Anthropic Claude Sonnet API already integrated via /api/chat. No new AI vendor needed.