



A Subsea7 Group Company

Corporate Quality Assurance Manual

Offshore & EPCI Operations

Document No:	QA-MAN-2026-EPCI
Revision:	3.0
Effective Date:	July 10, 2026
Department:	Global HSEQ

Mock Data Generated for Prototype Demonstration
Strictly Confidential

1. Introduction and Scope

This Quality Assurance Manual defines the core Quality Management System (QMS) applied by Seaway7 for all Engineering, Procurement, Construction, and Installation (EPCI) operations. The primary objective is to ensure that all subsea, heavy-lifting, and wind farm installation projects are executed with zero defects, strict adherence to international maritime regulations, and total client satisfaction.

Mandatory Compliance Clause: All Tier 1 and Tier 2 suppliers involved in Seaway7 projects are strictly mandated to adhere to the applicable standards referenced in this document. Any deviations require formal dispensation from the Global HSEQ Director.

2. Fundamental Quality Standards

At the core of our operations is a robust, internationally recognized Quality Management System. All supply chain partners must maintain certification to these baseline standards:

- **ISO 9001:2015** - Quality Management Systems (Required for all structural suppliers)
- **ISO/TS 29001** - Petroleum, petrochemical, and natural gas industries — Sector-specific QMS (Applicable to subsea tooling)
- **ISO 14001:2015** - Environmental Management Systems
- **ISO 45001:2018** - Occupational Health and Safety Management Systems

3. Key Offshore & Maritime Standards Matrix

Given the severe operating environment of offshore wind and subsea installations, generic quality standards are insufficient. The following matrix dictates the specific industry standards applicable to procurement and engineering operations:

Authority	Standard Ref.	Application Area & Scope
DNV (Det Norske Veritas)	DNV-ST-0126	Support Structures for Wind Turbines: Governs the design, materials, fabrication, and quality control of monopiles, transition pieces, and jacket foundations.
DNV	DNV-OS-H101	Marine Operations (VMO Standard): Dictates quality and safety requirements for load-out, transport, and offshore installation (lifting) of components.

NORSOK	NORSOK M-501	Surface Preparation and Protective Coating: Crucial for subsea components and splash-zone structures to prevent corrosion in harsh saline environments.
NORSOK	NORSOK N-004	Design of Steel Structures: Required for secondary steel work, boat landings, and offshore lifting appliances.
IMCA (Int. Marine Contractors Assoc.)	IMCA M 140 / M 103	Dynamic Positioning (DP) Operations: Quality assurance and FMEA (Failure Mode and Effects Analysis) requirements for DP2/DP3 heavy-lift and cable-lay vessels.
API (American Petroleum Institute)	API Spec 17J	Unbonded Flexible Pipe: Applicable cross-reference standard used for dynamic subsea power cables and umbilicals.

4. Factory Acceptance Testing (FAT) & Traceability

All critical components procured for EPCI operations must undergo rigorous Factory Acceptance Testing (FAT) before shipment. Suppliers must submit an Inspection and Test Plan (ITP) to Seaway7 Quality Control at least 30 days prior to manufacturing.

4.1 Material Traceability

Complete traceability (Type 3.1 or 3.2 material certificates strictly following EN 10204) is required for all primary steel and load-bearing components. Uncertified materials will be immediately rejected at the mobilization port.

4.2 Non-Destructive Testing (NDT)

Welding and fabrication quality shall be verified via NDT (Radiographic, Ultrasonic, Magnetic Particle, or Dye Penetrant testing) strictly in accordance with DNV-CG-0051. All NDT operators must be certified to ISO 9712 Level II minimum.