Comprehensive List of

# NumPy

Library

Rajendra Prasad JM



https://chlorinexxe.github.io/portfolio

## 1. Array Creation

- np.array(object)
- np.zeros(shape)
- np.ones(shape)
- np.empty(shape)
- np.full(shape,fill\_value)
- np.arrange(start,stop,step)
- np.linspace(start,stop,num)
- np.logspace(start,stop,num)

: Creates an array from an object

: Returns a new array of given shape and type, filled with zeros

: Returns a new array of given shape and type, filled with ones

: Returns a new array of given shape and type, without initializing entries

: Returns a new array of given shape and type, filled with fill\_value

: Returns evenly spaced values within a given interval

: Returns evenly spaced numbers over a specified interval

: Returns numbers spaced evenly on a log scale

# 2. Array Manipulation

• np.reshape()

: Reshapes an array without changing its data

• np.transpose()

: Permutes the dimensions of an array

np.concatenate()

: Joins a sequence of arrays along an existing axis

np.stack()

: Join a Sequence of array along axis

np.split()

: Split array into multiple sub-arrays

np.flip()

: Reverse the order of elements in an array

np.roll()

: Roll array elements along a specified axis

#### 3. Mathematical Functions

- np.sum() : Computes the sum of array elements over a specified axis
- np.sqrt() : Returns the non-negative square-root of an array, element-wise
- np.sin() : Trigonometric sine, element-wise {cos(), tan() can be used}
- np.abs() : Calculate the absolute value element wise
- np.exp() : Calculate the exponential of all elements in the input array
- np.log() : Calculate the natural logarithm
- np.arcsin() : Calculate the Sin inverse, element wise {arccos(), arctan() can be used}
- np.power() : First array elements raised to powers from second array

### 4. Statistical Functions

np.median() : Computes the median along the specified axis

• np.std() : Computes the standard deviation along the specified axis

• np.histogram() : Computes the histogram of a set of data

• np.percentile() : Computes the q-th percentile of the data along the specified axis

• np.mean() : Compute the arithmetic mean along the specified axis

• np.var() : Compute the variance along the specified axis

• np.std() : Compute the standard deviation along the specified axis

• np.corrcoef() : Return Pearson product-moment correlation coefficients

# 5. Linear Algebra

• np.dot() : Dot product of two arrays

• np.linalg.inv() : Computes the multiplicative inverse of a matrix

• np.linalg.eig() : Computes the eigenvalues and right eigenvectors of a square array

• np.linalg.svd() : Singular Value Decomposition

• np.linalg.det() : Compute the Determinant of a square matrix

• np.linalg.solve() : Solve a linear matrix equation or system of linear scalar equations

• np.linalg.norm() : Compute the matrix or Vector norm

• np.matmuls() : Compute the dot product of two arrays

• np.cross() : Returns the Cross product of 2 arrays

• np.inner() : Inner product of 2 arrays

## 6. Random Sampling

• np.random.rand()

np.random.randn()

np.random.randint()

np.random.choice()

• np.random.shuffle()

np.random.permutation()

• np.random.seed()

• np.random.normal()

• np.random.binomial()

np.random.exponential()

• np.radom.poisson()

: Random values in a given shape

: Return a sample from the "standard normal" distribution

: Returns random integers from low to high

: Generates a random sample from a given 1-D array

: Modifies a sequence in-place by shuffling its contents

: Randomly permute a sequence, or return a permuted range

: Seed the generator

: Draw random sample from a normal (Gaussian) Distribution.

: Draw samples from a binomial distribution

: Draw samples from a exponential distribution

: Draw samples from a Poisson distribution

#### 7. Advanced Features

• np.broadcast\_to() : Broadcasts an array to a new shape

• np.delete() : Deletes elements along an axis of an array

• np.insert() : Inserts values into an array at specified indices along an axis

np.append() : Appends values to the end of an array

• np.isclose() : Returns a boolean array where two arrays are element-wise equal within a tolerance

• np.gradient() : Computes the gradient of a multidimensional array

• np.eye() : Creates a identity matrix

# 8. File Input and Output

• np.save() : Saves an array to a binary file in NumPy .npy format

• np.load() : Loads arrays or pickled objects from .npy, .npz, or pickled files

• np.loadtxt() : Load data from a text file

• np.savetxt() : Save array to a text file

• np.fromfile() : Read data from a binary file

• np.memmap() : Memory-mapped files for accessing large arrays stored on disk

• np.frombuffer() : to create arrays from raw bytes

• np.savez\_compressed(): For saving multiple arrays into a single compressed .npz file

## 9. Special Functions

• np.special.(): A module containing various special mathematical functions such as Bessel functions, gamma functions, etc

These are now in scipy.special

Scipy is a Python library used for scientific and technical computing. It builds on top of NumPy, another Python library, and provides a wide range of modules for tasks such as numerical integration, optimization, signal processing, statistics, and more.

"I hope you found this information helpful! Feel free to save this post for future reference. Let's continue to learn and grow together! "

Thank You for Your Support Rajendra Prasad JM

