# COMP2350/COMP6350 Database Systems

# Practical – Week 9

# **MySQL Procedural Programming**

## **Objectives:**

- To create the first stored procedure and understand the building blocks of a stored procedure.
- To formulate some simple stored procedures.
- To understand how to use conditional and iterative control structure in a stored procedure.

### Introduction to MySQL stored procedure

#### 1. Creating the very first stored procedure

- Run MySQL Workbench and then open a connection to the database server.
- Open a New Query tab in WorkBench environment and type in the procedure into the query interface as shown in Figure 1:




Figure 1: The Environment

Next, Execute the stored procedure by pressing CTRL+SHIFT+ENTER or clicking on



This will create a stored procedure and it will be stored in the database as shown in Figure 2:




Figure 2: Creating the very first procedure

#### 2. Calling the stored procedure

To call the stored procedure, execute the statement as shown in Figure 3.




Figure 3: Result of calling the procedure

.

### **Task Specification**

1. Write a stored procedure to displays a welcome message, such as 'Welcome to MySQL Procedural Programming'. Execute the procedure and then call it to display the message. You can use the following template:

```
DELIMITER //
DROP PROCEDURE IF EXISTS ...
//
CREATE PROCEDURE ...
BEGIN
...
END
//
DELIMITER;
CALL ...;
```

2. What output would you expect from the following stored procedure?

```
-- Dropping the procedure if exists
DELIMITER //
DROP PROCEDURE IF EXISTS devideNumbers
-- Declaring the Procedure
DELIMITER //
CREATE PROCEDURE devideNumbers()
BEGIN
DECLARE firstNumber, secondNumber INT; -- Declaring the variables
DECLARE result NUMERIC(6,2) DEFAULT 0;
SET firstNumber = 82;
SET secondNumber =15;
SET result = firstNumber/secondNumber;
SELECT result as 'Output';
END
11
DELIMITER;
-- Calling the procedure
CALL devideNumbers();
```

- 3. Create and call the above procedure (devideNumbers) and verify the output.
- 4. Run the following code and fix the syntax errors that you encounter:

```
DELIMITER //

DROP PROCEDURE IF EXISTS CalculateAverage
//

DELIMITER //
```

```
CREATE PROCEDURE CalculateAverage()

BEGIN

DECLARE lower_limit, upper_limit INT;

DECLARE num_count, total INT 0;

DECLARE range_average Numeric(5,2) DEFAULT 0;

SET lower_limit = 3;

SET upper_limit := 15;

WHILE (lower_limit + num_count) <= upper_limit DO;

SET total = total + lower_limit + num_count;

SET num_count = num_count + 1

range_average = total / num_count;

SELECT range_average 'Range Average';

END

DELIMITER;
```

#### CALL CalculateAverage;

5. Write a stored procedure that takes a number as an input and prints whether it is an odd number or an even number. You may use the following procedure template:

```
CREATE PROCEDURE OddOrEven(IN myNumber INT)
BEGIN
....
END
CALL OddOrEven(123);
```

#### [Hint: (n % d) divides n by d, and returns the integer remainder from the operation]

6. A shop gives a discount according to the code specified on the product tag. Each product has a price and a discount code. The discount code and corresponding discount in percentage are A (20%), B (15%), C (10%) and D (5%). The shop calculates the sale price of a product using this discount code. For example, if a product has a price of 200 dollar and discount code is C then,

```
discount amount = 200*10% = 20;
sale price = price – discount amount = 200-20 = 180;
```

Write a stored procedure that takes the price and the discount code of the product as inputs and prints the sale price of the product.

[HINT: you can use either IF-ELSEIF-ELSE statement or a CASE statement; need to be able to deal with the case of invalid discount codes]

7. Write a stored procedure that takes two numbers as input and print all odd numbers within that range. For example, if the procedure takes two numbers 4 and 11 as input, it prints 5, 7, 9 and 11 as output.