

# YABE

YABE is **Yet Another Binary Encoding** proposal as simple as JSON, but with the addition of a binary blob data value (i.e. Images) and the benefit of marshalling binary data.

**Author:** Christophe Meessen

**Date :** 19 sep 2012

## Value types

*Atomic data values:*

1. *null*;
2. **Boolean** : *true* & *false*;
3. **Integer** : 64 bit integer ;
4. **Floating point** : 64 bit IEEE 754-2008 ;
5. **String** : utf8 encoded character sequence ;
6. **Blob** : array of raw bytes with a mime type string ;

*Composed values:*

1. **Array** : Sequence of any values ;
2. **Object** : Sequence of a pair of value identifier (string) and any value ;

## Value Encoding

Each value is encoded as a tag byte identifying its type, followed by an optional value size and the value itself. When possible the size or the value are stored in the tag.

[tag]([size])([value])

| Value    | Tag          | arguments         | comment                  |
|----------|--------------|-------------------|--------------------------|
| 0..127   | : [0xxxxxxx] |                   | : integer value 0..127   |
| str6     | : [10xxxxxx] | [byte]*           | : utf8 char string       |
| null     | : [11000000] |                   | : null value             |
| int16    | : [11000001] | [int16]           | : 16 bit integer         |
| int32    | : [11000010] | [int32]           | : 32 bit integer         |
| int64    | : [11000011] | [int64]           | : 64 bit integer         |
| flt0     | : [11000100] |                   | : 0. float value         |
| flt16    | : [11000101] | [flt16]           | : 16 bit float           |
| flt32    | : [11000110] | [flt32]           | : 32 bit float           |
| flt64    | : [11000111] | [flt64]           | : 64 bit float           |
| true     | : [11001000] |                   | : boolean true value     |
| false    | : [11001001] |                   | : boolean false value    |
| blob     | : [11001010] | [string] [string] | : mime typed byte array  |
| ends     | : [11001011] |                   | : equivalent to ] or }   |
| none     | : [11001100] |                   | : tag byte to be ignored |
| str16    | : [11001101] | [len16] [byte]*   | : utf8 char string       |
| str32    | : [11001110] | [len32] [byte]*   | : utf8 char string       |
| str64    | : [11001111] | [len64] [byte]*   | : utf8 char string       |
| arrayn   | : [11010xxx] | [value]*          | : 0 to 6 value array     |
| array    | : [11010111] | [value]*          | : equivalent to [        |
| objectn  | : [11011xxx] | [string, value]*  | : 0 to 6 value object    |
| object   | : [11011111] | [string, value]*  | : equivalent to {        |
| -1..-32: | [111xxxxx]   |                   | : integer value -1..-32  |

- The tag is a one byte value ;
- Integer values from -32 to 127 are encoded as is as the tag value ;
- Integer values are encoded as little endian signed integer ;
- Floating point values are encoded in the IEEE 754-2008 format ;
- A strings is a sequence of utf8 encoded chars with the number of bytes as length ;
- A length value are encoded as little endian unsigned integer of 16, 32 or 64 bits ;
- A blob is a pair of strings, the first is a mime type and the second is a sequence or raw bytes ;
- An Array is encoded as a stream of values ;
- An Object is encoded as a stream of string and value pairs where the string is a unique identifier ;
- An Object may not have an empty string as identifier ;
- A array of object stream is ended by the *ends* tag ;
- If an array or an object have less than 7 items, the *arrayn* or *objectn* encoding may be used where the number of items is encoded in the tag ;

## **YABE data Signature**

Stored or transmitted YABE encoded data starts with a five byte signature. The first four bytes are the ASCII code 'Y', 'A', 'B', 'E' in that order, and the fifth byte is the version number of the encoding. This specification describes the encoding version 0.

## **YABE data size**

The encoded data byte length is defined by the context (i.e. file or record size) or is implicit if the data is limited to one value like an array or an object.

## **File extension and mime type**

A file name with extension .yabe and starting with the YABE tag contains YABE encoded data. The mime type is "application/yabe" (to be registered).