



# Exception Handling in Python



# Python

Exceptions

Exception Handling

Try and Except

Nested try Block

Handling Multiple Exceptions in single Except Block

Raising Exception

Finally Block

User Defined Exceptions



# Exception

- When writing a program, we, more often than not, will encounter errors.
- Error caused by not following the proper structure (syntax) of the language is called syntax error or parsing error
- Errors can also occur at runtime and these are called exceptions.
- They occur, for example, when a file we try to open does not exist (`FileNotFoundError`), dividing a number by zero (`ZeroDivisionError`)
- Whenever these type of runtime error occur, Python creates an exception object. If not handled properly, it prints a traceback to that error along with some details about why that error occurred.



Python 3.6.3 (v3.6.3:2c5fed8, Oct 3 2017, 17:26:49) [MSC v.1900 32 bit (Intel)] on win32

Type "copyright", "credits" or "license()" for more information.

```
>>> a = 5
```

```
>>> b = 0
```

```
>>> res = a / b
```

Traceback (most recent call last):

File "<pyshell#2>", line 1, in <module>

res = a / b

ZeroDivisionError: division by zero

```
>>>
```



# Exception Handling

- To handle exceptions, and to call code when an exception occurs, we can use a **try/except** statement.
- The **try** block contains code that might throw an exception.
- If that exception occurs, the code in the **try** block stops being executed, and the code in the **except** block is executed.
- If no error occurs, the code in the **except** block doesn't execute.



```
#Program to perform division and understand exception handling
```

```
a = int ( input('Enter the first number ' ) )  
b = int ( input('Enter the second number ' ) )
```

```
try:  
    res = a / b  
    print('result = ' , res)  
except:  
    print('Exception Handled ')
```

```
print('End of program')
```



# Nested Try Block

```
try:
    num = int ( input('Enter the numerator ' ) )
    den = int ( input('Enter the denominator ' ) )
    try:
        result = num / den;
        print('Result = ' , result)
    except:
        print('Divide by Zero Error')
except:
    print('Invalid Input')

print('End of Program ' )
```



~

.



```
#Program to know the type of exception
```


```
import sys
```

```
a = int ( input('Enter the first number ' ) )  
b = int ( input('Enter the second number ' ) )
```

```
try:  
    res = a / b  
    print('result = ' , res)  
except:  
    print('Exception Handled ' )  
    print("Oops!",sys.exc_info()[0] ,"occured.")
```

```
print('End of program')
```



- 
- A **try** statement can have multiple different **except** blocks to handle different exceptions.



```
import sys
try :
    num = int ( input('Enter the numerator ' ) )
    den = int ( input('Enter the denominator ' ) )
    result = num / den;
    print('Result = ' , result)
except ValueError:
    print('Invalid Input ')
except ZeroDivisionError:
    print('Divide by Zero Error')

print('End of Program ')
```



~  
~  
~  
~  
~  
~  
~  
~  
~  
~  
~  
~  
~  
~  
~



```
#Program to demonstrate multiple except(catch) blocks
```

```
try:
```

```
    a = input('Enter the first number ' )
```

```
    b = input('Enter the second number ' )
```

```
    a = int(a)
```

```
    res = a + b
```

```
    print('result = ' , res)
```

```
except ValueError:
```

```
    print('Invalid Input Error')
```

```
except TypeError:
```


```
    print('Type Error')
```

```
except ZeroDivisionError:
```

```
    print('Divide by Zero Error')
```

```
print('End of program')
```



- 
- Multiple exceptions can also be put into a single **except** block using parentheses, to have the **except** block handle all of them.



```
#Program to demonstrate handling multiple exception types in a single block
```

```
import sys
```

```
try:
```

```
    a = input('Enter the first number ' )
```

```
    b = input('Enter the second number ' )
```

```
    a = int(a)
```

```
    sum = a + b
```

```
    print('sum = ' , sum)
```

```
    quotient = a // b
```

```
    print('quotient = ' , quotient)
```

```
except (ValueError,TypeError):
```

```
    print('Invalid Input Error',sys.exc_info()[0])
```

```
except ZeroDivisionError:
```

```
    print('Divide by Zero Error')
```

```
print('End of program')
```



```
def divide(num,den):  
    res = num / den  
    return res  
  
try :  
    num = int ( input('Enter the numerator ' ) )  
    den = int ( input('Enter the denominator ' ) )  
  
    result = divide(num , den)  
    print('Result = ' , result)  
  
except ValueError:  
    print('Main Block : Invalid Input ' )  
except ZeroDivisionError:  
    print('Main Block : Divide by Zero error')  
  
print('End of Program ' )  
~  
~
```



# Raising Exceptions

exception\_raise.py - D:/sikander/python/exception\_raise.py (3.6.3)

File Edit Format Run Options Window Help

```
try:
    print('Enter the marks ' )
    marks = int( input() )

    if marks < 0 or marks > 100:
        raise ValueError

    #write code to calculate grade

except ValueError:
    print('Input out of range')
```



user@varsity-OptiPlex-320: ~/sikander/python/exception

```
def divide(num,den):  
    try:  
        res = num / den  
        return res  
    except ZeroDivisionError:  
        print('Divide Function : Divide by Zero Error')  
        return 0  
  
try :  
    num = int ( input('Enter the numerator ' ) )  
    den = int ( input('Enter the denominator ' ) )  
  
    result = divide(num , den)  
    print('Result = ' , result)  
  
except ValueError:  
    print('Main Block : Invalid Input ' )  
except ZeroDivisionError:  
    print('Main Block : Divide by Zero error')  
  
print('End of Program ' )
```



# Raising Exception from Except Block

 user@varsity-OptiPlex-320: ~/sikander/python/exception

```
def divide(num,den) :  
    try:  
        res = num / den  
        return res  
    except ZeroDivisionError:  
        print('Divide Function : Divide by Zero Error')  
        raise  
  
try :  
    num = int ( input('Enter the numerator ' ) )  
    den = int ( input('Enter the denominator ' ) )  
  
    result = divide(num , den)  
    print('Result = ' , result)  
  
except ValueError:  
    print('Main Block : Invalid Input ' )  
except ZeroDivisionError:  
    print('Main Block : Divide by Zero error')  
  
print('End of Program ' )
```



# finally

- To ensure some code runs no matter what errors occur, you can use a **finally** statement.
- The **finally** statement is placed at the bottom of a **try/except** statement.
- Code within a **finally** statement always runs after execution of the code in the **try**, and possibly in the **except**, blocks.



```
#Program to demonstrate finally blocks
```

```
try:
```

```
    a = int ( input('Enter the first number ' ) )  
    b = int ( input('Enter the second number ' ) )
```

```
    res = a / b  
    print('result = ' , res)
```

```
except (ValueError,TypeError):
```

```
    print('Invalid Input Error')
```

```
except ZeroDivisionError:
```

```
    print('Divide by Zero Error')
```

```
finally:
```

```
    print('This code will run no matter what')
```

```
print('End of program')
```



'''

===== RESTART: D:/sikander/python/exception\_finally.py =====

Enter the first number 4

Enter the second number 2

result = 2.0

This code will run no matter what

End of program

>>>

===== RESTART: D:/sikander/python/exception\_finally.py =====

Enter the first number 4

Enter the second number a

Invalid Input Error

This code will run no matter what

End of program

>>>

===== RESTART: D:/sikander/python/exception\_finally.py =====

Enter the first number 4

Enter the second number 0

Divide by Zero Error


This code will run no matter what

End of program

>>> |



- Code in a **finally** statement even runs if an uncaught exception occurs in one of the preceding blocks.



```
exception_finally2.py - D:/sikander/python/exception_finally2.py (3.6.3)
File Edit Format Run Options Window Help
try:
    print(1)
    print(10 / 0)
except ZeroDivisionError:
    print(unknown_var)
finally:
    print("This is executed last")
|
```



# Raising Exception

- Raising exception is similar to throwing exception in C++/Java.
- You can raise exceptions by using the **raise** statement



# User Defined Exception

```
class InvalidRange(Exception):  
    pass  
  
try:  
    marks = input('Enter the marks : ')  
    marks = int(marks)  
    if(marks < 0 or marks > 100):  
        raise InvalidRange  
    print('Marks = ', marks)  
  
except ValueError:  
    print('Invalid Input')  
except InvalidRange:  
    print('Input value out of range')
```

