The Memory Hierarchy

CSCI 2021: Machine Architecture and Organization

Antonia Zhai
Department Computer Science and Engineering
University of Minnesota
http://www.cs.umn.edu/~zhai

With Slides from Bryant and O'Hallaron

UNIVERSITY OF MINNESOTA

Abstraction



RAM: Random Access Memory

Is this abstraction accurate? How does the memory really work?

Random-Access Memory (RAM)

Key features

- RAM is packaged as a chip.
- Basic storage unit is a cell (one bit per cell).
- Multiple RAM chips form a memory.

Static RAM (SRAM)

- Each cell stores bit with a six-transistor circuit.
- Retains value indefinitely, as long as it is kept powered.
- Relatively insensitive to disturbances such as electrical noise.
- Faster and more expensive than DRAM.

Dynamic RAM (DRAM)

- Each cell stores bit with a capacitor and transistor.
- Value must be refreshed every 10-100 ms.
- Sensitive to disturbances.
- Slower and cheaper than SRAM.

SRAM vs DRAM Summary

	Tran. per bit	Access time	Persist?	Sensitive?	Cost	Applications
SRAM	6	1X	Yes	No	100x	cache memories
DRAM	1	10X	No	Yes	1X	Main memories, frame buffers

Conventional DRAM Organization

d x w DRAM:

- dw total bits organized as d supercells of size w bits



Reading DRAM Supercell (2,1)

- Step 1(a): Row access strobe (RAS) selects row 2.
- Step 1(b): Row 2 copied from DRAM array to row buffer.



Reading DRAM Supercell (2,1)

- Step 2(a): Column access strobe (CAS) selects column 1.
- Step 2(b): Supercell (2,1) copied from buffer to data lines, and eventually back to the CPU.



Memory Modules



Bus Structure Connecting CPU and Memory

- A bus is a collection of parallel wires that carry address, data, and control signals.
- Buses are typically shared by multiple devices.



Memory Read Transaction (1)

- CPU places address A on the memory bus.



Memory Read Transaction (2)

- Main memory reads A from the memory bus, retreives word x, and places it on the bus.



Memory Read Transaction (3)

- CPU read word x from the bus and copies it into register %eax.



Memory Write Transaction (1)

- CPU places address A on bus. Main memory reads it and waits for the corresponding data word to arrive.



Memory Write Transaction (2)

- CPU places data word y on the bus.



Memory Write Transaction (3)

- Main memory read data word y from the bus and stores it at address A.



Enhanced DRAMs

All enhanced DRAMs are built around the conventional DRAM core.

- Fast page mode DRAM (FPM DRAM)
  - Access contents of row with [RAS, CAS, CAS, CAS, CAS] instead of [(RAS,CAS), (RAS,CAS), (RAS,CAS), (RAS,CAS)].
- Extended data out DRAM (EDO DRAM)
  - Enhanced FPM DRAM with more closely spaced CAS signals.
- Synchronous DRAM (SDRAM)
  - Driven with rising clock edge instead of asynchronous control signals.
- Double data-rate synchronous DRAM (DDR SDRAM) and (DDR2 SDRAM)
  - Enhancement of SDRAM that uses both clock edges as control signals.
  - DDR2 clocks the bus at twice the speed of the memory cells
- Video RAM (VRAM)
  - Like FPM DRAM, but output is produced by shifting row buffer
  - Dual ported (allows concurrent reads and writes)

Nonvolatile Memories

- **DRAM and SRAM are volatile memories**
  - Lose information if powered off.
- **Nonvolatile memories retain value even if powered off**
  - Read-only memory (ROM): programmed during production
  - Programmable ROM (PROM): can be programmed once
  - Eraseable PROM (EPROM): can be bulk erased (UV, X-Ray)
  - Electrically eraseable PROM (EEPROM): electronic erase capability
  - Flash memory: EEPROMs with partial (sector) erase capability
    - Wears out after about 100,000 erasings.
- **Uses for Nonvolatile Memories**
  - Firmware programs stored in a ROM (BIOS, controllers for disks, network cards, graphics accelerators, security subsystems,…)
  - Solid state disks (replace rotating disks in thumb drives, smart phones, mp3 players, tablets, laptops,…)
  - Disk caches

Read Timing for Conventional DRAM



DRAM TUTORIAL
ISCA 2002
Bruce Jacob
David Wang
University of Maryland

Read Timing for Fast Page Mode



DRAM TUTORIAL
ISCA 2002
Bruce Jacob
David Wang
University of Maryland

Read Timing for Extended Data Out



Read Timing for Pipeline Burst EDO



Read Timing for Synchronous DRAM



Our Abstraction



Disk Geometry

- Disks consist of platters, each with two surfaces.
- Each surface consists of concentric rings called tracks.
- Each track consists of sectors separated by gaps.



Disk Geometry (Muliple-Platter View)



- Aligned tracks form a cylinder.

Disk Capacity

- Capacity: maximum number of bits that can be stored.
  - Vendors express capacity in units of gigabytes (GB), where 1 GB = 10^9 Bytes (Lawsuit pending! Claims deceptive advertising).
- Capacity is determined by these technology factors:
  - Recording density (bits/in): number of bits that can be squeezed into a 1 inch segment of a track.
  - Track density (tracks/in): number of tracks that can be squeezed into a 1 inch radial segment.
  - Areal density (bits/in2): product of recording and track density.
- Modern disks partition tracks into disjoint subsets called recording zones
  - Each track in a zone has the same number of sectors, determined by the circumference of innermost track.
  - Each zone has a different number of sectors/track

Computing Disk Capacity

Capacity = (# bytes/sector) x (avg. # sectors/track) x
(# tracks/surface) x (# surfaces/platter) x
(# platters/disk)

Example:

- 512 bytes/sector
- 300 sectors/track (on average)
- 20,000 tracks/surface
- 2 surfaces/platter
- 5 platters/disk

Capacity = 512 x 300 x 20000 x 2 x 5
= 30,720,000,000
= 30.72 GB

Disk Operation (Single-Platter View)



Disk Operation (Multi-Platter View)



Disk Structure - top view of single platter



Surface organized into tracks

Tracks divided into sectors

Disk Access



Head in position above a track

Disk Access



Rotation is counter-clockwise

Disk Access – Read



About to read blue sector

Disk Access – Read



After BLUE read

After reading blue sector

Disk Access – Read



After BLUE read

Red request scheduled next

Disk Access – Seek



After BLUE read



Seek for RED

Seek to red's track

Disk Access – Rotational Latency



After BLUE read | Seek for RED | Rotational latency

Wait for red sector to rotate around

Disk Access – Read



After BLUE read | Seek for RED | Rotational latency | After RED read

Complete read of red

Disk Access – Service Time Components



Disk Access Time Example

- Given:
  - Rotational rate = 7,200 RPM
  - Average seek time = 9 ms.
  - Avg # sectors/track = 400.
- Derived:
  - Tavg rotation = 1/2 x (60 secs/7200 RPM) x 1000 ms/sec = 4 ms.
  - Tavg transfer = 60/7200 RPM x 1/400 secs/track x 1000 ms/sec = 0.02 ms
  - Taccess = 9 ms + 4 ms + 0.02 ms
- Important points:
  - Access time dominated by seek time and rotational latency.
  - First bit in a sector is the most expensive, the rest are free.
  - SRAM access time is about 4 ns/doubleword, DRAM about 60 ns
    - Disk is about 40,000 times slower than SRAM,
    - 2,500 times slower then DRAM.

Logical Disk Blocks

- Modern disks present a simpler abstract view of the complex sector geometry:
  - The set of available sectors is modeled as a sequence of b-sized logical blocks (0, 1, 2, ...)
- Mapping between logical blocks and actual (physical) sectors
  - Maintained by hardware/firmware device called disk controller.
  - Converts requests for logical blocks into (surface,track,sector) triples.
- Allows controller to set aside spare cylinders for each zone.
  - Accounts for the difference in "formatted capacity" and "maximum capacity".

I/O Bus



Reading a Disk Sector (1)



CPU initiates a disk read by writing a command, logical block number, and destination memory address to a port (address) associated with disk controller.

Reading a Disk Sector (2)



Disk controller reads the sector and performs a direct memory access (DMA) transfer into main memory.

Reading a Disk Sector (3)



When the DMA transfer completes, the disk controller notifies the CPU with an *interrupt* (i.e., asserts a special "interrupt" pin on the CPU)

Solid State Disks (SSDs)



- Pages: 512KB to 4KB, Blocks: 32 to 128 pages
- Data read/written in units of pages.
- Page can be written only after its block has been erased
- A block wears out after 100,000 repeated writes.

SSD Performance Characteristics

Sequential read tput	250 MB/s	Sequential write tput	170 MB/s
Random read tput	140 MB/s	Random write tput	14 MB/s
Rand read access	30 us	Random write access	300 us

- Why are random writes so slow?
  - Erasing a block is slow (around 1 ms)
  - Write to a page triggers a copy of all useful pages in the block
    - Find an used block (new block) and erase it
    - Write the page into the new block
    - Copy other pages from old block to the new block

SSD Tradeoffs vs Rotating Disks

- Advantages
  - No moving parts → faster, less power, more rugged
- Disadvantages
  - Have the potential to wear out
    - Mitigated by "wear leveling logic" in flash translation layer
    - E.g. Intel X25 guarantees 1 petabyte (1015 bytes) of random writes before they wear out
  - In 2010, about 100 times more expensive per byte
- Applications
  - MP3 players, smart phones, laptops
  - Beginning to appear in desktops and servers

Storage Trends

SRAM

Metric	1980	1985	1990	1995	2000	2005	2010	*2010:1980*
$/MB	19,200	2,900	320	256	100	75	60	*320*
access (ns)	300	150	35	15	3	2	1.5	*200*

DRAM

Metric	1980	1985	1990	1995	2000	2005	2010	*2010:1980*
$/MB	8,000	880	100	30	1	0.1	0.06	*130,000*
access (ns)	375	200	100	70	60	50	40	*9*
typical size (MB)	0.064	0.256	4	16	64	2,000	8,000	*125,000*

Disk

Metric	1980	1985	1990	1995	2000	2005	2010	*2010:1980*
$/MB	500	100	8	0.30	0.01	0.005	0.0003	*1,600,000*
access (ms)	87	75	28	10	8	*4*	*3*	*29*
typical size (MB)	1	10	160	1,000	20,000	160,000	1,500,000	*1,500,000*

CPU Clock Rates

Inflection point in computer history when designers hit the "Power Wall"

	1980	1990	1995	2000	2003	2005	2010	*2010:1980*
CPU	8080	386	Pentium	P-III	P-4	Core 2	Core i7	---
Clock rate (MHz)	1	20	150	600	3300	2000	2500	2500
Cycle time (ns)	1000	50	6	1.6	0.3	0.50	0.4	2500
Cores	1	1	1	1	1	2	4	4
Effective cycle time (ns)	1000	50	6	1.6	0.3	0.25	0.1	10,000

The CPU-Memory Gap

The gap widens between DRAM, disk, and CPU speeds.



Locality

Locality

- Principle of Locality: Programs tend to use data and instructions with addresses near or equal to those they have used recently

- Temporal locality:
  - Recently referenced items are likely to be referenced again in the near future



- Spatial locality:
  - Items with nearby addresses tend to be referenced close together in time



Locality Example

```
sum = 0;
for (i = 0; i < n; i++)
    sum += a[i];
return sum;
```

- Data references
  - Reference array elements in succession (stride-1 reference pattern).
  - Reference variable `sum` each iteration.
- Instruction references
  - Reference instructions in sequence.
  - Cycle through loop repeatedly.

Spatial locality

Temporal locality

Spatial locality

Temporal locality

Qualitative Estimates of Locality

- Claim: Being able to look at code and get a qualitative sense of its locality is a key skill for a professional programmer.
- Question: Does this function have good locality with respect to array a?

```
int sum_array_rows(int a[M][N])
{
    int i, j, sum = 0;

    for (i = 0; i < M; i++)
        for (j = 0; j < N; j++)
            sum += a[i][j];
    return sum;
}
```

Locality Example

- Question: Does this function have good locality with respect to array a?

```
int sum_array_cols(int a[M][N])
{
    int i, j, sum = 0;

    for (j = 0; j < N; j++)
        for (i = 0; i < M; i++)
            sum += a[i][j];
    return sum;
}
```

Locality Example

- Question: Can you permute the loops so that the function scans the 3-d array `a` with a stride-1 reference pattern (and thus has good spatial locality)?

```
int sum_array_3d(int a[M][N][N])
{
    int i, j, k, sum = 0;

    for (i = 0; i < M; i++)
        for (j = 0; j < N; j++)
            for (k = 0; k < N; k++)
                sum += a[k][i][j];
    return sum;
}
```

Memory Hierarchies

- Some fundamental and enduring properties of hardware and software:
  - Fast storage technologies cost more per byte, have less capacity, and require more power (heat!).
  - The gap between CPU and main memory speed is widening.
  - Well-written programs tend to exhibit good locality.
- These fundamental properties complement each other beautifully.
- They suggest an approach for organizing memory and storage systems known as a memory hierarchy.

Summary

- The speed gap between CPU, memory and mass storage continues to widen.
- Well-written programs exhibit a property called locality.
- Memory hierarchies based on caching close the gap by exploiting locality.