



SQL: Queries, Constraints, Triggers

Chapter 5



The SQL Query Language

- ❖ Developed by IBM (system R) in the 1970s
- ❖ *The* most widely used language for **creating**, **manipulating**, and **querying** relational DBMS.
- ❖ Need for a standard since it is used by many vendors
- ❖ Standards:
 - SQL-86
 - SQL-89 (minor revision)
 - SQL-92 (major revision)
 - SQL-99 (major extensions, current standard)



Example Instances

- ❖ We will use these instances of the Sailors and Reserves relations in our examples.

S1

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
58	rusty	10	35.0


R1

<u>sid</u>	<u>bid</u>	<u>day</u>
22	101	10/10/96
58	103	11/12/96

S2


<u>sid</u>	sname	rating	age
28	yuppy	9	35.0
31	lubber	8	55.5
44	guppy	5	35.0
58	rusty	10	35.0

Basic SQL Query




SELECT	[DISTINCT] <i>target-list</i>
FROM	<i>relation-list</i>
WHERE	<i>qualification</i>

- ❖ *relation-list* A list of relation names
- ❖ *target-list* A list of attributes of relations in *relation-list*
- ❖ *qualification* Comparisons (Attr *op* const or Attr1 *op* Attr2, where *op* is one of $<$, $>$, $=$, \leq , \geq , \neq) combined using AND, OR and NOT.
- ❖ DISTINCT is an optional keyword indicating that the answer should not contain duplicates. Default is that duplicates are not eliminated!



Conceptual Evaluation Strategy

- ❖ Semantics of an SQL query defined in terms of the following conceptual evaluation strategy:
 1. Compute the cross-product of *relation-list*.
 2. Discard resulting tuples if they fail *qualifications*.
 3. Delete attributes that are not in *target-list*.
 4. If **DISTINCT** is specified, eliminate duplicate rows.
- ❖ This strategy is probably the *least efficient way* to compute a query! An **optimizer** will find more efficient strategies to compute *the same answers*.




Example of Conceptual Evaluation

```
SELECT S.sname  
FROM   Sailors S, Reserves R  
WHERE  S.sid=R.sid AND R.bid=103
```

(sid)	sname	rating	age	(sid)	bid	Day
22	dustin	7	45.0	22	101	10/10/96
22	dustin	7	45.0	58	103	11/12/96
31	lubber	8	55.5	22	101	10/10/96
31	lubber	8	55.5	58	103	11/12/96
58	rusty	10	35.0	22	101	10/10/96
58	rusty	10	35.0	58	103	11/12/96

Find sailors who've reserved at least one boat




```
SELECT S.sid  
FROM Sailors S, Reserves R  
WHERE S.sid=R.sid
```

- ❖ Would adding DISTINCT to this query make a difference?
- ❖ What is the effect of replacing *S.sid* by *S.sname* in the SELECT clause? Would adding DISTINCT to this variant of the query make a difference?

Find the names of sailors who have reserved a red boat

```
SELECT S.name  
FROM Sailors S, Reserves R, Boats B  
WHERE S.sid=R.sid AND R.bid = B.bid AND B.color = 'red'
```


Expressions and Strings



```
SELECT S.age, age1=S.age-5, 2*S.age AS age2  
FROM Sailors S  
WHERE S.sname LIKE 'B_%B'
```

- ❖ Illustrates use of arithmetic expressions and string pattern matching: *Find triples (of ages of sailors and two fields defined by expressions) for sailors whose names begin and end with B and contain at least three characters.*
- ❖ **AS** and **=** are two ways to name fields in result.
- ❖ **LIKE** is used for string matching. **`_`** stands for any one character and **`%`** stands for 0 or more arbitrary characters.

Find sid's and names of sailors who've reserved a red or a green boat



- ❖ **UNION**: Can be used to compute the union of any two *union-compatible* sets of tuples (which are themselves the result of SQL queries).
- ❖ If we replace **OR** by **AND** in the first version, what do we get?
- ❖ Also available: **EXCEPT** (What do we get if we replace **UNION** by **EXCEPT**?)


```
SELECT S.sid, S.sname
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid
      AND (B.color='red' OR B.color='green')
```

```
SELECT S.sid, S.sname
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid
      AND B.color='red'

UNION

SELECT S.sid, S.sname
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid
      AND B.color='green'
```

Find sid's and names of sailors who've reserved a red and a green boat



- ❖ **INTERSECT**: Can be used to compute the intersection of any two *union-compatible* sets of tuples.
- ❖ Included in the SQL/92 standard, but some systems don't support it.
- ❖ Contrast symmetry of the **UNION** and **INTERSECT** queries with how much the other versions differ.

```
SELECT S.sid, S.sname
FROM Sailors S, Boats B1, Reserves R1,
     Boats B2, Reserves R2
WHERE S.sid=R1.sid AND R1.bid=B1.bid
     AND S.sid=R2.sid AND R2.bid=B2.bid
     AND B1.color='red' AND B2.color='green'
```


```
SELECT S.sid, S.sname
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid
     AND B.color='red'
```

Key field!

INTERSECT

```
SELECT S.sid, S.sname
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid
     AND B.color='green'
```


Find sid's and names of sailors who've reserved red boats but not green boats



```
SELECT S.sid, S.sname
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid AND B.color='red'
EXCEPT
SELECT S.sid, S.sname
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid AND B.color='green'
```

- ❖ **EXCEPT**: Can be used to compute the difference of any two *union-compatible* sets of tuples
- ❖ Many systems recognize the keyword **MINUS** instead of **EXCEPT**

Nested Queries




Find names of sailors who've reserved boat #103

```
SELECT S.sname  
FROM Sailors S  
WHERE S.sid IN (SELECT R.sid  
                FROM Reserves R  
                WHERE R.bid=103)
```


- ❖ A very powerful feature of SQL: a WHERE clause can itself contain an SQL query! (Actually, so can FROM clauses.)
- ❖ To find sailors who've *not* reserved #103, use NOT IN.
- ❖ To understand semantics of nested queries, think of a nested loops evaluation: *For each Sailors tuple, check the qualification by computing the subquery.*

Nested Queries



Find names of sailors who've not reserved a red boat

```
SELECT S.sname
FROM Sailors S
WHERE S.sid NOT IN (SELECT R.sid
                    FROM Reserves R
                    WHERE R.bid IN (SELECT B.bid
                                    FROM Boats B
                                    WHERE B.color = 'red'))
```




Nested Queries with Correlation

Find names of sailors who've reserved boat #103:

```
SELECT S.sname  
FROM Sailors S  
WHERE EXISTS (SELECT *  
               FROM Reserves R  
               WHERE R.bid=103 AND S.sid=R.sid)
```

- ❖ **EXISTS** is another set comparison operator, like **IN**.
- ❖ If **UNIQUE** is used, and * is replaced by *R.bid*, finds sailors with at most one reservation for boat #103.
- ❖ Illustrates why, in general, subquery must be re-computed for each Sailors tuple.




More on Set-Comparison Operators

- ❖ We've already seen IN, EXISTS and UNIQUE. Can also use NOT IN, NOT EXISTS and NOT UNIQUE.
- ❖ Also available: *op* ANY, *op* ALL, *op* IN >, <, =, ≥, ≤, ≠
- ❖ Find sailors whose rating is greater than that of some sailor called Horatio:

```
SELECT *  
FROM Sailors S  
WHERE S.rating > ANY (SELECT S2.rating  
                      FROM Sailors S2  
                      WHERE S2.sname='Horatio')
```

Rewriting INTERSECT Queries Using IN



Find sid of sailors who've reserved both a red and a green boat:

```
SELECT S.sid
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid AND B.color='red'
      AND S.sid IN (SELECT S2.sid
                     FROM Sailors S2, Boats B2, Reserves R2
                     WHERE S2.sid=R2.sid AND R2.bid=B2.bid
                        AND B2.color='green')
```


- ❖ Similarly, EXCEPT queries re-written using NOT IN.
- ❖ Useful if your system does not support INTERSECT or EXCEPT

Division in SQL

Find sailors who've reserved all boats.


❖ Let's do it the hard way, without EXCEPT:

```
SELECT S.sname
FROM Sailors S
WHERE NOT EXISTS
    ((SELECT B.bid
      FROM Boats B)
  EXCEPT
  (SELECT R.bid
   FROM Reserves R
   WHERE R.sid=S.sid))
```



```
SELECT S.sname
FROM Sailors S
WHERE NOT EXISTS (SELECT B.bid
                  FROM Boats B
                  WHERE NOT EXISTS (SELECT R.bid
                                   FROM Reserves R
                                   WHERE R.bid=B.bid
                                   AND R.sid=S.sid))
```

Aggregate Operators



- ❖ Significant extension of relational algebra.

COUNT (*)
COUNT ([DISTINCT] A)
SUM ([DISTINCT] A)
AVG ([DISTINCT] A)
MAX (A)
MIN (A)

sid	sname	rating	age
28	Bob	10	35
31	Bob	10	20
44	guppy	5	50
58	rusty	10	35

```
SELECT COUNT (*)  
FROM Sailors S
```


```
SELECT AVG (S.age)  
FROM Sailors S  
WHERE S.rating=10
```

```
SELECT AVG ( DISTINCT S.age)  
FROM Sailors S  
WHERE S.rating=10
```

```
SELECT COUNT (DISTINCT S.rating)  
FROM Sailors S  
WHERE S.sname='Bob'
```

```
SELECT MAX (S.age)  
FROM Sailors S
```

Find name and age of the oldest sailor(s)




```
SELECT S.sname, MAX (S.age)
FROM Sailors S
```

```
SELECT S.sname, S.age
FROM Sailors S
WHERE S.age =
      (SELECT MAX (S2.age)
       FROM Sailors S2)
```

```
SELECT S.sname, S.age
FROM Sailors S
WHERE (SELECT MAX (S2.age)
       FROM Sailors S2)
      = S.age
```

- ❖ The first query is illegal! (We'll look into the reason a bit later, when we discuss **GROUP BY**.)
- ❖ The third query is equivalent to the second query, and is allowed in the SQL/92 standard, but is not supported in some systems.

Motivation for Grouping




- ❖ So far, we've applied aggregate operators to all (qualifying) tuples. Sometimes, we want to apply them to each of several *groups* of tuples.
- ❖ Consider: *Find the age of the youngest sailor for each rating level.*
 - Suppose we know that rating values go from 1 to 10; we can write 10 queries that look like this (!):

For $i = 1, 2, \dots, 10$:


```
SELECT MIN (S.age)
FROM Sailors S
WHERE S.rating = i
```
 - In general, we don't know how many rating levels exist, and what the rating values for these levels are!

Queries With GROUP BY and HAVING




SELECT	[DISTINCT] <i>target-list</i>
FROM	<i>relation-list</i>
WHERE	<i>qualification</i>
GROUP BY	<i>grouping-list</i>
HAVING	<i>group-qualification</i>

- ❖ The *target-list* contains (i) attribute names (ii) terms with aggregate operations (e.g., MIN (*S.age*)).
 - The attribute list (i) must be a subset of *grouping-list*.
Intuitively, each answer tuple corresponds to a *group*, and these attributes must have a single value per group. (A *group* is a set of tuples that have the same value for all attributes in *grouping-list*.)



Conceptual Evaluation

1. Compute the cross-product of *relation-list*.
2. Discard resulting tuples if they fail *qualifications*.
3. Delete attributes that are not in *target-list*.
4. The remaining tuples are partitioned into groups by the value of attributes in *grouping-list*.
5. The *group-qualification* is applied to eliminate some groups.
6. One answer tuple is generated per qualifying group.
7. If **DISTINCT** is specified, eliminate duplicate rows.



Find age and rating of the youngest sailor with age ≥ 18 , for each rating with at least 2 such sailors

```
SELECT S.rating, MIN (S.age) AS minage
FROM Sailors S
WHERE S.age >= 18
GROUP BY S.rating
HAVING COUNT (*) > 1
```

Answer relation:


rating	minage
3	25.5
7	35.0
8	25.5

- What if we do not have the condition age > 18
- What if we only need the age


Sailors instance:

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
29	brutus	1	33.0
31	lubber	8	55.5
32	andy	8	25.5
58	rusty	10	35.0
64	horatio	7	35.0
71	zorra	10	16.0
74	horatio	9	35.0
85	art	3	25.5
95	bob	3	63.5
96	frodo	3	25.5


*Find age of the youngest sailor with age ≥ 18 ,
for each rating with at least 2 such sailors.*



rating	age
7	45.0
1	33.0
8	55.5
8	25.5
10	35.0
7	35.0
10	16.0
9	35.0
3	25.5
3	63.5
3	25.5




rating	age
1	33.0
3	25.5
3	63.5
3	25.5
7	45.0
7	35.0
8	55.5
8	25.5
9	35.0
10	35.0




rating	minage
3	25.5
7	35.0
8	25.5


*Find age of the youngest sailor with age ≥ 18 ,
for each rating with at least 2 such sailors and
with every sailor under 60.*



HAVING COUNT (*) > 1 AND EVERY (S.age <=60)




For each red boat, find the number of reservations for this boat



```
SELECT      B.bid, COUNT (*) AS scount
FROM        Boats B, Reserves R
WHERE       R.bid=B.bid AND B.color='red'
GROUP BY    B.bid
```

- ❖ Grouping over a join of two relations.
- ❖ What do we get if we remove *B.color='red'* from the WHERE clause and add a HAVING clause with this condition?

Find age of the youngest sailor with age ≥ 18 , for each rating with at least 2 sailors between 18 and 60.



Sailors instance:


```
SELECT S.rating, MIN (S.age) AS minage
FROM Sailors S
WHERE S.age >= 18 AND S.age <= 60
GROUP BY S.rating
HAVING COUNT (*) > 1
```

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
29	brutus	1	33.0
31	lubber	8	55.5
32	andy	8	25.5
58	rusty	10	35.0
64	horatio	7	35.0
71	zorba	10	16.0
74	horatio	9	35.0
85	art	3	25.5
95	bob	3	63.5
96	frodo	3	25.5

Answer relation:

rating	minage
3	25.5
7	35.0
8	25.5


*Find age of the youngest sailor with age > 18,
for each rating with at least 2 sailors (of any age)*



```
SELECT S.rating, MIN (S.age)
FROM Sailors S
WHERE S.age > 18
GROUP BY S.rating
HAVING 1 < (SELECT COUNT (*)
             FROM Sailors S2
             WHERE S.rating=S2.rating)
```

- ❖ Shows HAVING clause can also contain a subquery.
- ❖ Compare this with the query where we considered only ratings with 2 sailors over 18!
- ❖ What if HAVING clause is replaced by:
 - HAVING COUNT(*) >1

Find those ratings for which the average age is the minimum over all ratings



❖ Aggregate operations cannot be nested! **WRONG:**

```
SELECT S.rating
FROM Sailors S
WHERE S.age = (SELECT MIN (AVG (S2.age)) FROM Sailors S2)
```

❖ Correct solution (in SQL/92):

```
SELECT Temp.rating, Temp.avgage
FROM (SELECT S.rating, AVG (S.age) AS avgage
      FROM Sailors S
      GROUP BY S.rating) AS Temp
WHERE Temp.avgage = (SELECT MIN (Temp.avgage)
                    FROM Temp)
```