CSci 2021, Spring 2015 Homework Assignment II: Solutions

Problem 0: (1 point)

Textbook problem 3.57 (p. 296).

Should have been easy.

Problem 1:

```
int zero = 0;
int cread_alt(int *xp) {
    return *(xp ? xp : &zero);
```

Problem 2:

}

Problem 3:

Register	C Expression
%eax, lines 8-11	mat
%edi, lines 14-37	r
%ebx, lines 10-35	mat[r]
%edx, lines 22-27	mat[r - 1]
%esi, lines 23-30	r - 1
%eax, lines 23-30	c - 1

Problem 4:

Textbook problem 3.68 (p. 306).

```
void good_echo() {
    char buf[2];
    int i;
    while (1) {
        if (!fgets(buf, 2, stdin)) {
            return;
        for (i = 0; buf[i] \&\& buf[i] != ' \n'; i++) {
            if (putchar(buf[i]) == EOF) {
                return;
            }
        }
        if (buf[i] == '\n') {
            putchar('\n');
            return;
    }
}
```

A simpler version that uses getchar and only processes one character at a time is also possible.

Problem 5: (based on textbook problem 3.69)

The following function declaration defines a class of structures for use in constructing binary trees:

```
A. int trace(tree_ptr tp) {
    int v = 0;
    while (tp) {
        v = tp->val;
        tp = tp->right;
    }
    return v;
}
```

B. The function returns the value of the rightmost node in the tree, or 0 if the tree pointer is null.

Problem 6:

A.

- B. 24 (see A.)
- C. 4 (the most needed by any element: p, i, and a all need 4-byte alignment)
- D. 1 (down from 5 unused bytes in the given order) Here's one order that does it:

- E. 8 (the size of the largest element, a)
- F. 4 (the most needed by any element)