Data Sheet

Brilliant LED

"Let's brighten up the Nation"

Benefits of LED Lights

Brilliant LED canopy light product is a rectangular or square-shaped lighting fixture that is designed to be installed in outdoor canopies or covered areas such as gas stations, parking garages, and petrolpump. LED canopy lights are known for their high efficiency, long lifespan, and durability.LED canopy light products come in various sizes and shapes to fit different canopy structures and applications. They are typically made of high-quality materials such as aluminum or polycarbonate, which provide a sturdy and long-lasting construction.

Waterproof Light

Ip66 wet location rated

waterproof IP65 Driver

Recyclable, Flexibility

Long life: 50,000 hours

Aluminium Dia Casting Heavy Body

Osram LED with 130Lm/Per Watt

5 mm High Quality Toughened Glass

- Ideal for:
  - Perimeter Lighting
  - Awnings
  - Manufacturing Plants
  - Parking Garages
  - Canopies
  - Garden & Parks
  - Security Lighting

440V Protection

Under Voltage Protection

10 Kv* Surge Protection

Neon Canopy Light

"Lighting beyond Enternity"

Technical Data Sheet

Applications:

This product family can be effectively used in outdoor ceiling mount locations. Commercial, Industrial, Retail, and healthcare exterior lighting; Parking Garages, Awnings, Canopies, Security Lighting, etc.

Construction:

Die-cast Aluminum Housing
Impact-resistant Toughened Glass
Durable grey power coat
Hands from an included eye bolt
Operating temperature:-20°C - 40°C

Electrical:

Wet location rated-IP66
System rated for long 50,000 hour life
Delivers bright, white light and xcellent uniformity

Optical Parameters:

Internal Driver
LED Used 1W 3030,
0.75mm 3 Core Cable
120 Degree beam Angle

ITEM	WATT	LUMENS	VOLTAGE	POWER FACTOR	CCT	CRI	SURGE	CURRENT	DIMENSIONS			
Neon Canopy Light - 50,000 Hours									L(mm)	B(mm)	H(mm)	W(Kg)
BR-NO-CL-60	60W	7800	110-285V	>90	6500K	>80	4Kv, 10Kv*	1500 mA	370	370	65	2.5
BR-NO-CL-80	80W	10400	110-285V	>90	6500K	>80	4Kv, 10Kv*	1500 mA	370	370	65	2.7
BR-NO-CL-100	100W	13000	110-285V	>90	6500K	>80	4Kv, 10Kv*	1500 mA	370	370	65	2.8
BR-NO-CL-120	120W	15600	110-285V	>90	6500K	>80	4Kv, 10Kv*	1500 mA	370	370	65	2.9

Thanks

Actual products may vary in colour, design, description and colour combination etc. Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication. Speci cations & performance data are constantly changing. Current details should therefore be checked with Brilliant Industries.