

# SMART CONTRACT CODE REVIEW AND SECURITY ANALYSIS REPORT



**Customer**: GeniusAssets **Date**: July 13<sup>th</sup>, 2022



This report may contain confidential information about IT systems and the intellectual property of the Customer, as well as information about potential vulnerabilities and methods of their exploitation.

The report can be disclosed publicly after prior consent by another Party. Any subsequent publication of this report shall be without mandatory consent.

#### Document

Name	Smart Contract Code Review and Security Analysis Report for GeniusAssets			
Approved By	Evgeniy Bezuglyi   SC Audits Department Head at Hacken OU			
Туре	ERC20 token			
Platform	EVM			
Network	Ethereum, Polygon			
Language	Solidity			
Methods	Manual Review, Automated Review, Architecture review			
Website	https://genius-assets.com/			
Timeline	28.06.2022 - 13.07.2022			
Changelog	30.06.2022 - Initial Review 13.07.2022 - Second Review			



## Table of contents

Introduction	4
Scope	4
Severity Definitions	5
Executive Summary	6
Checked Items	7
System Overview	10
Findings	11
Disclaimers	13



### Introduction

Hacken OÜ (Consultant) was contracted by GeniusAssets (Customer) to conduct a Smart Contract Code Review and Security Analysis. This report presents the findings of the security assessment of the Customer's smart contracts.

## Scope

The scope of the project is smart contracts in the repository:

## Initial review scope

Repository:

https://github.com/geniusassets/iux-smart-contract

Commit:

09c364f76d98880cd0198b6be6921c827846d608

Technical Documentation:

Type: README (partial functional requirements provided)

Link

Integration and Unit Tests: No
Deployed Contracts Addresses:No

Contracts:

File: ./contracts/IUX.sol

SHA3: fb4f97fde23d726eda3ad0d85c22ca5739d5a034ea0f58624a25d800b6f22ba4

## Second review scope

Repository:

https://github.com/geniusassets/iux-smart-contract

Commit.

e339386a0e50be0aec346e64b99e4fdfdf07790f

Technical Documentation:

Type: README (partial functional requirements provided)

<u>Link</u>

Integration and Unit Tests: Yes
Deployed Contracts Addresses:No

Contracts:

File: ./contracts/IUX.sol

SHA3: fb4f97fde23d726eda3ad0d85c22ca5739d5a034ea0f58624a25d800b6f22ba4



# **Severity Definitions**

Risk Level	Description		
Critical	Critical vulnerabilities are usually straightforward to exploit and can lead to assets loss or data manipulations.		
High	High-level vulnerabilities are difficult to exploit; however, they also have a significant impact on smart contract execution, e.g., public access to crucial functions.		
Medium	Medium-level vulnerabilities are important to fix; however, they cannot lead to assets loss or data manipulations.		
Low	Low-level vulnerabilities are mostly related to outdated, unused, etc. code snippets that cannot have a significant impact on execution.		



## **Executive Summary**

The score measurement details can be found in the corresponding section of the <a href="methodology">methodology</a>.

## **Documentation quality**

The total Documentation Quality score is 10 out of 10.

## Code quality

The total CodeQuality score is 9 out of 10. Style guide was violated.

## Architecture quality

The architecture quality score is 10 out of 10.


## Security score

As a result of the audit, the code contains 1 low severity issue. The security score is 10 out of 10.

All found issues are displayed in the "Findings" section.

#### Summary

According to the assessment, the Customer's smart contract has the following score: 9.9.





## **Checked Items**

We have audited provided smart contracts for commonly known and more specific vulnerabilities. Here are some of the items that are considered:

Item	Туре	Description	Status
Default Visibility	SWC-100 SWC-108	Functions and state variables visibility should be set explicitly. Visibility levels should be specified consciously.	Passed
Integer Overflow and Underflow	<u>SWC-101</u>	If unchecked math is used, all math operations should be safe from overflows and underflows.	Passed
Outdated Compiler Version	SWC-102	It is recommended to use a recent version of the Solidity compiler.	Passed
Floating Pragma	SWC-103	Contracts should be deployed with the same compiler version and flags that they have been tested thoroughly.	Passed
Unchecked Call Return Value	<u>SWC-104</u>	The return value of a message call should be checked.	Not Relevant
Access Control & Authorization	CWE-284	Ownership takeover should not be possible. All crucial functions should be protected. Users could not affect data that belongs to other users.	Passed
SELFDESTRUCT Instruction	SWC-106	The contract should not be self-destructible while it has funds belonging to users.	Not Relevant
Check-Effect- Interaction	SWC-107	Check-Effect-Interaction pattern should be followed if the code performs ANY external call.	Passed
Assert Violation	<u>SWC-110</u>	Properly functioning code should never reach a failing assert statement.	Passed
Deprecated Solidity Functions	<u>SWC-111</u>	Deprecated built-in functions should never be used.	Passed
Delegatecall to Untrusted Callee	SWC-112	Delegatecalls should only be allowed to trusted addresses.	Not Relevant
DoS (Denial of Service)	SWC-113 SWC-128	Execution of the code should never be blocked by a specific contract state unless it is required.	Passed
Race Conditions	SWC-114	Race Conditions and Transactions Order Dependency should not be possible.	Passed
Authorization	SWC-115	tx.origin should not be used for	Passed



through tx.origin		authorization.	
Block values as a proxy for time	SWC-116	Block numbers should not be used for time calculations.	Not Relevant
Signature Unique Id	SWC-117 SWC-121 SWC-122 EIP-155	Signed messages should always have a unique id. A transaction hash should not be used as a unique id. Chain identifier should always be used. All parameters from the signature should be used in signer recovery	Not Relevant
Shadowing State Variable	SWC-119	State variables should not be shadowed.	Passed
Weak Sources of Randomness	SWC-120	Random values should never be generated from Chain Attributes or be predictable.	Not Relevant
Incorrect Inheritance Order	SWC-125	When inheriting multiple contracts, especially if they have identical functions, a developer should carefully specify inheritance in the correct order.	Passed
Calls Only to Trusted Addresses	EEA-Lev el-2 SWC-126	All external calls should be performed only to trusted addresses.	Passed
Presence of unused variables	<u>SWC-131</u>	The code should not contain unused variables if this is not <u>justified</u> by design.	Passed
EIP standards violation	EIP	EIP standards should not be violated.	Passed
Assets integrity	Custom	Funds are protected and cannot be withdrawn without proper permissions.	Passed
User Balances manipulation	Custom	Contract owners or any other third party should not be able to access funds belonging to users.	Failed
Data Consistency	Custom	Smart contract data should be consistent all over the data flow.	Passed
Flashloan Attack	Custom	When working with exchange rates, they should be received from a trusted source and not be vulnerable to short-term rate changes that can be achieved by using flash loans. Oracles should be used.	Not Relevant
Token Supply manipulation	Custom	Tokens can be minted only according to rules specified in a whitepaper or any other documentation provided by the customer.	Passed
Gas Limit and Loops	Custom	Transaction execution costs should not depend dramatically on the amount of	Passed



		data stored on the contract. There should not be any cases when execution fails due to the block Gas limit.	
Style guide violation	Custom	Style guides and best practices should be followed.	Failed
Requirements Compliance	Custom	The code should be compliant with the requirements provided by the Customer.	Passed
Environment Consistency	Custom	The project should contain a configured development environment with a comprehensive description of how to compile, build and deploy the code.	Passed
Secure Oracles Usage	Custom	The code should have the ability to pause specific data feeds that it relies on. This should be done to protect a contract from compromised oracles.	Not Relevant
Tests Coverage	Custom	The code should be covered with unit tests. Test coverage should be 100%, with both negative and positive cases covered. Usage of contracts by multiple users should be tested.	Passed
Stable Imports	Custom	The code should not reference draft contracts, that may be changed in the future.	Passed



## System Overview

*GeniusAssets* is a token contract that is created based on the ERC20 standard.

• *IUX* — simple burnable ERC-20 token that mints all initial supply to a deployer. Additional minting is not allowed.

It has the following attributes:

Name: GeniuXSymbol: IUXDecimals: 18

o Total supply: 1,000,000,000 tokens.

## Privileged roles

• The owner can burn tokens from an account to a different account, can set the *antisnipe* address and *antisnipe* disable status.

#### Risks

- The total supply of the token could not be verified before the deployment.
- The owner can transfer tokens between addresses without allowance validated.



## **Findings**

#### ■■■■ Critical

No critical severity issues were found.

## High

#### 1. Requirements compliance

The documentation states that the token is pausable, though the contract has no function to pause or unpause it.

File: ./contracts/IUX.sol

Contract: IUX

Function: -

**Recommendation**: Create functions that call internal \_pause and \_unpause functions in Pausable.sol contract.

Status: Fixed (Revised commit: e339386a0e50be0aec346e64b99e4fdfdf07790f)

#### 2. Highly permissive owner access

The owner can forcefully burn tokens from any address and mint those tokens to a different address.

Users may lose their funds without any permission.

File: ./contracts/IUX.sol

Contract: IUX

Function: forceTransfer

**Recommendation**: Do not allow the owner to burn funds without an allowance.

Status: Mitigated (This behavior is described in the documentation).

#### ■■ Medium

No medium severity issues were found.

#### Low

#### 1. Style guide violation

The correct order for the contract's events and functions is not followed.

This may break the consistency and make the code more difficult to understand.

File: ./contracts/IUX.sol



Contract: IUX

Function: -

Recommendation: Inside the contract, follow the correct order.

Use the style guide

Status: Reported (Revised commit:

e339386a0e50be0aec346e64b99e4fdfdf07790f)



## **Disclaimers**

#### Hacken Disclaimer

The smart contracts given for audit have been analyzed by the best industry practices at the date of this report, with cybersecurity vulnerabilities and issues in smart contract source code, the details of which are disclosed in this report (Source Code); the Source Code compilation, deployment, and functionality (performing the intended functions).

The report contains no statements or warranties on the identification of all vulnerabilities and security of the code. The report covers the code submitted to and reviewed, so it may not be relevant after any modifications. Do not consider this report as a final and sufficient assessment regarding the utility and safety of the code, bug-free status, or any other contract statements.

While we have done our best in conducting the analysis and producing this report, it is important to note that you should not rely on this report only — we recommend proceeding with several independent audits and a public bug bounty program to ensure the security of smart contracts.

English is the original language of the report. The Consultant is not responsible for the correctness of the translated versions.

#### Technical Disclaimer

Smart contracts are deployed and executed on a blockchain platform. The platform, its programming language, and other software related to the smart contract can have vulnerabilities that can lead to hacks. Thus, Consultant cannot guarantee the explicit security of the audited smart contracts.