

ISLAMIC UNIVERSITY OF TECHNOLOGY (IUT)
ORGANISATION OF ISLAMIC COOPERATION (OIC)

Department of Computer Science and Engineering (CSE)

SEMESTER FINAL EXAMINATION

SUMMER SEMESTER, 2018-2019

DURATION: 3 Hours

FULL MARKS: 150

CSE 4619: Peripherals and Interfacing

Programmable calculators are not allowed. Do not write anything on the question paper.

There are **8 (eight)** questions. Answer any **6 (six)** of them.

Figures in the right margin indicate marks.

-
- | | | | |
|----|----|---|----|
| 1. | a) | What is an Embedded System? How does it differ from typical Computer Systems? | 10 |
| | b) | Differentiate between <i>Asynchronous</i> , <i>Synchronous</i> and <i>Isochronous</i> data transfer. | 10 |
| | c) | Draw an Embedded Control System Block diagram considering a designer's view. | 5 |
| 2. | a) | Write the basic differential features between 8155 and 8255 Programmable Peripheral Interface (PPI). | 10 |
| | b) | Write short notes on:
i. Daisy-Chain Architecture
ii. Multi-Level Bus Architecture | 10 |
| | c) | List out the implications of being embedded by the embedded systems. | 5 |
| 3. | a) | Draw and explain the timing diagrams of 8255 PPI <i>mode 0</i> and <i>mode 1</i> signaling. | 10 |
| | b) | Explain about the handshake signals of 8155 Programmable Peripheral Interface (PPI). | 10 |
| | c) | In order to connect a Dot-Matrix Display with an 8086 Microprocessor system, how can you interface using a single 8255 PPI? Just draw the interfacing diagram. | 5 |
| 4. | a) | How does 8259 PIC can handle 64 Interrupt levels? Explain with necessary diagram. | 10 |
| | b) | Briefly explain about the operation of Register sets of 8259 PIC. | 10 |
| | c) | Draw the STACK operation states during an Interrupt. | 5 |
| 5. | a) | Draw a block diagram for an 8237 DMA controller. Briefly explain the importance of using HOLD and HOLDA signals. | 10 |
| | b) | Write a comparative study on <i>Polling</i> , <i>Interrupt</i> and <i>DMA I/O</i> interfacing. | 10 |
| | c) | " <i>Memory-Read & I/O Write</i> and <i>I/O Read & Memory-Write</i> signals are used simultaneously for DMA operation" – Explain. | 5 |
| 6. | a) | What is CAN bus and why is it called a broadcast type bus? "CAN bus protocol remove $\frac{n(n-1)}{2}$ connections complexity for an embedded system" – explain how?. | 10 |
| | b) | "In CAN, with the bus length increment the transmission speed for data rate decreases" – True/False? Justify your answer. | 10 |
| | c) | Draw the data frame format of CAN protocol. | 5 |

7. a) "In I²C bus connections, *master bus* can only be transmitter or transmitter-receiver whereas *slave buses* can only be receiver or receiver-transmitter" – Why? 10
- b) Why does in I²C bus the Start-End condition and Data-Transition signaling are opposite to each other? Explain. 10
- c) Draw the data formats of I²C protocol when the Master IC reads and writes to/from Slave IC. 5
8. a) What are UART and USART? Why do we need 8251 UART/USART IC? 10
- b) Write technical specifications on following interfacing techniques: 10
- i. USB
 - ii. Firewire
 - iii. Infiniband
 - iv. Fiber-channel
- c) Differentiate between DVI and HDMI. 5