

# Lighting

CS 355: Interactive Graphics and Image Processing







# Kinds of Lighting

- Direct:
   Light falling on an object directly from a light source
- Indirect: More in CS 455
   Light falling on an object after being reflected off (or going through) other objects
- Ambient: General light bouncing around and scattered

enough to be effectively "everywhere"

# Light Sources

We'll focus on this for now

Point


Area

Spot

and many other models...

#### Basic Geometry of Lighting

- The surface **n**ormal
- The lighting direction (to the light)
- The viewing direction (to the eye/camera)
- The reflected light direction




#### Surface Reflectance

- Most objects don't give off light
  - reflect some of the light that falls on them
  - absorb the rest
- The wavelengths reflected give the object its color
- The effect is multiplicative:
   i.e., "reflects 40% of the green light"
- If we model the light as RGB, we can also model reflectance as RGB
- Reflectance is also sometimes called *albedo*


#### Irradiance


- We sometimes say "the amount of light"
- But it's really how much light per unit area
- This quantity is called the *irradiance*




#### Irradiance

- Two important properties:
  - Irradiance falls of with the square of the distance
  - Irradiance is less when falling on a slanted surface





### Specular vs. Diffuse




Some light is reflected perfectly (specular)


Some light is scattered (diffuse)

#### Diffuse Reflection


- Light scattered in every direction is called the *diffuse* part of the reflected light
- A perfectly diffuse surface is called Lambertian
- Only lighting direction matters
- Viewing direction does not




### A Simple Diffuse Model




Assumes constant lighting direction and strength









Angle of reflection = Angle of incidence (but may be blurred)







 $m_{
m gls}$ 


 $\mathbf{m}_{\mathrm{spec}}$ 

#### Ambient Reflection

- Ambient light is "all around", so directions don't matter
- Just the product of the ambient light and the surface reflectance

$$\mathbf{c}_{\mathrm{amb}} = \mathbf{s}_{\mathrm{amb}} \otimes \mathbf{m}_{\mathrm{amb}}$$

# All Together Now...




This is called the *Phong* model (the *Blinn* model is similar with slightly different specular)

#### BRDFs


- The Phong model is only an approximation
- Not a simple mix of pure diffuse and pure specular
- Reflectance isn't constant across the surface
- Function of both incoming direction and outgoing direction





#### BRDFs


- The Phong model is only an approximation
- Not a simple mix of pure diffuse and pure specular
- Reflectance isn't constant across the surface
- Function of both incoming direction and outgoing direction



Bidirectional Reflectance Distribution Function


#### What About Shadows?

- Point lights cast hard shadows
- Area lights cast softer shadows
  - Umbra = area in full shadow
  - Penumbra = area in partial shadow



### Simple Shadows

- For point lights, shadows are pretty simple
- Do a visibility test from the point of view of the light!
- Can also be used for distance-based falloff



# Coming up...

- More lighting
- Cameras and image acquisition revisited
- Image processing